

FOR MOUNTING, SEE NOTE 5



1. ACTUATOR NOTE: VERIFY ACTUATOR BUSHING IS IN THE FULL CCW POSITION. ROTATE DAMPER CCW TO THE FULLY CLOSED POSITION. MOUNT ACTUATOR OVER DAMPER SHAFT AND SECURE TO SHAFT ENCLOSURE. ENGAGE CLUTCH AND ROTATE DAMPER CW TO THE FULLY OPEN POSITION.
2. SHOP NOTE: USE INSULATED QUICK CONNECTS.
3. CAUTION: ELECTRIC SHOCK MAY RESULT. DISCONNECT UNIT PRIOR TO SERVICING UNIT.
4. THESE CONTROLS HAVE BEEN WIRED TO COMPLY WITH UL-1995.
5. SECURE WITH SCREWS, BUSHINGS, AND O-RINGS SUPPLIED WITH CONTROLLER. CENTER THE BUSHING IN THE ANTI-ROTATION SLOT.

-8909

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AAR SYSTEM COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AAR SYSTEM COMPONENTS IS PROHIBITED.	DO NOT SCALE DRAWING		REMOVE ALL BARBS AND SHARP EDGES	
	DIMENSIONS ARE IN INCHES		TOLERANCES:	
	ANGULAR: MACH $\pm 1^\circ$ BEND: $\pm 2^\circ$		FINISH RELEASED	
	TWO PLACE DECIMAL $\pm .03$ THREE PLACE DECIMAL $\pm .005$		RELEASED ON 06/07/23 RELEASED BY LJS	
TITLE			DWG NO	
WD FAN POWERED			1066648909	
TV-VVTZC-E2			REV	
PROP HOT WATER VALVE			SHEET	
			10 OF 12	