

TOOLS by TPI

ENGINEERED

QUALITY

UNIVERSAL

OFFERING



TOTALINE

Universal HVAC/R
Parts and Supplies

by



Totaline® is a single source for your
universal aftermarket parts and tools

Totaline® Tools by TPI

Table of Content

Electrical Tools:

| | Page |
|---|------|
| AC Safety Volt Check (P920-50-TPI) | 2 |
| Clamp-On Meter (P920-265-TPI) | 3 |
| HVAC Clamp Meter (P920-270-TPI) | 4 |
| HVAC Multimeter (P920-183A-TPI) | 5 |
| HVAC Multimeter Kit (P920-183AC3-TPI) | 6 |
| Test Lead Kit (P920-TLK3-TPI) | 6 |

Temperature Tools:

| | |
|--|---|
| Pocket Thermometer (P920-315C-TPI) | 7 |
| Infrared Thermometer (P920-381A-TPI) | 8 |
| Digital Thermometer (P920-343-TPI) | 9 |

Combustion Tools:

| | Page |
|---|------|
| Combustible Gas Leak Detector (P920-725L-TPI) | 10 |
| Combustion Analyzer with Smart Sensors (P920-717-TPI) | 10 |
| Combustion Analyzer with Smart Sensors and Printer (P920-717A740-TPI) | 10 |

Pressure Tools:

| | |
|--|----|
| Manometer (P920-621-TPI) | 11 |
| Dual Input Differential Manometer Kit (P920-621C3-TPI) | 11 |

AC Safety Volt Check P920-50-TPI

Non-contact detection of 50-1000 VAC, with sound and visual alert.

Check for AC voltage in wires, wall receptacles, fuses, junction boxes, switches, defective grounds, breaker panels, motors, compressors, and much more with the Totaline AC Safety Volt Check tool.

You no longer need to disconnect your system in order to test for voltage; the P920-50-TPI is a non-contact tool. To use you simply touch the tool to a connection point or move along an insulated wire. If AC voltage is present, the tool will sound an audio alert and an LED light in the probe tip will glow bright red.

Test for wire troubleshooting: The illumination will stop at a break in the circuit or wire.

Benefits:


- Help prevent electrical shocks
- Non-contact detection of 50 to 1000 VAC
- Troubleshoot electrical circuits
- No switch required
- Always ready for use (does not require an on / off button)
- Sound and visual alert
- Buzzer will not react to static electricity, only AC voltage
- Lifetime warranty

Specifications:

| | |
|-----------------------|---|
| Operating Range: | 50 to 1000 VAC |
| Accuracy | ±1°C or ±2°F |
| Response Time | 500 m Second |
| °C/°F Select | Yes |
| Operating Temperature | -20°C ~ 55°C (-4°F ~ 131°F) |
| Operating Humidity | 95% (0 to 30°C) 75% (30 to 40°C) 45% (40 to 55°C) |
| Power | 2 1.5 Volt alkaline batteries |
| Agency Approval | CAT IV 1000V |



AC Voltage in wall receptacles



AC Voltage in switches



AC Voltage in junction boxes

Did you know...

The P920-50-TPI will not pick up interference between various wires. You will get true voltage detection regardless of how close the wires are together.



by



Universal HVAC/R
Parts and Supplies

Electrical Tools

Clamp-on tester with Frequency and Capacitance P920-265-TPI



8" x 3"

The P920-265-TPI with slim jaw and body is ideal for cramped work areas and crowded electrical panels.

Applications:

- Test start and run capacitors
- Measure motor run current
- Measure heat anticipator current
- Determine thermocouple voltage
- Test line and control voltages
- Measure heating element resistance
- Measure and adjust variable frequency drives

Features:

- Slim jaw and body design for use in crowded electrical panels
- 4,000 count display
- Capacitance range up to 4,000 microfarads to test run and start capacitors
- 0.1 DC millivolt resolution to accurately measure thermocouples and use optional adapters
- 0.01 AC Amp resolution to measure heat anticipator current
- Frequency measurement capability
- AC/DC volts up to 600V and AC Amps up to 400A
- Diode, resistance, and audible continuity ranges
- Auto / manual ranging
- Data hold
- Auto power off
- CAT III 600V rated
- 3-Year limited warranty

Specifications:

| | |
|------------------------|---|
| Basic DC Accuracy: | 0.5% |
| DC Voltage (maximum): | 600V |
| Resolution (maximum): | 0.1mV |
| AC Voltage (maximum): | 600V |
| Resolution (maximum): | 0.1mV |
| AC Amps (maximum): | 400A |
| Resolution (maximum): | 0.01A |
| Resistance (maximum): | 40M Ω |
| Resolution (maximum): | 0.1 Ω |
| Frequency (maximum): | 400MHz |
| Resolution (maximum): | 0.001KHz |
| Capacitance (maximum): | 4,000 μ F |
| Resolution (maximum): | 0.001nF |
| Diode: | Test Current Max 1.5mA |
| Continuity: | Buzzer sounds at <approx. 35 Ω Response time; 50ms |
| Overall Dimensions: | 8" x 1.5" x 3.0" (203 x 38.1 x 76.2mm) |
| Weight: | .6 lbs (272g) |

Standard Accessories

| | |
|------|------------------------|
| A040 | Standard test lead set |
| A265 | Soft Carrying Pouch |

Optional Accessories

| | |
|-----------|----------------------------------|
| A202 | Line Splitter |
| A771 | Carbon Monoxide Adapter |
| A620 | Pressure Adapter |
| TLS2000RB | Deluxe Test Lead Kit |
| A301 | Single Input Temperature Adapter |
| A312 | Dual Input Temperature Adapter |
| A213 | Microamp Adapter |

Agency Approvals

| | |
|--------------------|--------------|
| CE IEC 61010-1 | CAT III 600V |
| UL 61010-1 (cULus) | CAT III 600V |

Did you know...

The P920-265-TPI Clamp-on Tester is your go-to basic HVAC meter. For enhanced functionality check out the P920-270-TPI Clamp-on Tester with Digital Multimeter.

Electrical Tools

Clamp-on tester with Digital Multimeter P920-270-TPI



10" x 1.3" x 2.5

Perfect for tight, narrow, spaces.

The P920-270 with slim jaw and body is ideal for cramped work areas and crowded electrical panels.

Applications:

- Measure flame safety control current
- Test run and start capacitors and motors
- Measure motor run current and capture peak motor start up amperage
- Measure heat anticipator current
- Determine thermocouple voltage
- Test line and control voltages
- Measure heating element resistance
- Measure air temperature in ducts
- Test for the presence of voltage in circuits without contacting the circuit
- Measure temperature differential using relative mode

Features:

- Measure motor in-rush current and run current
- Measure temperature differential with relative mode
- Non-contact voltage feature immediately determines if power is being supplied to the 24VAC control circuit on the thermostat
- Frequency, Min/Max/Record, data hold, and peak hold
- Up to 40,000 microfarads to test run and start capacitors
- 4,000 count display with 41 segment analog bar graph

Specifications:

| | |
|------------------------|--|
| Basic DC Accuracy: | 0.5% |
| DC Voltage (maximum): | 600V |
| Resolution (maximum): | 0.1mV |
| AC Voltage (maximum): | 600V |
| Resolution (maximum): | 0.1mV |
| DC Amps(maximum): | 400μA |
| Resolution (maximum): | 0.01μA |
| AC Amps(maximum): | 400A |
| Resolution (maximum): | 0.01A |
| Resistance (maximum): | 40Ω |
| Resolution (maximum): | 0.1Ω |
| Frequency (maximum): | 400MHz |
| Resolution (maximum): | 0.001KHz |
| Capacitance (maximum): | 40,000μF |
| Resolution (maximum): | 0.001nF |
| Temperature (maximum) | 1,000°F |
| Resolution (maximum) | 0.1° |
| Diode: | Test Current Max 1.5mA |
| Continuity: | Buzzer sounds at <approx. 35Ω Response time; 50ms |
| Overall Dimensions: | 10" x 1.3" x 2.5" (255 x 32.5 x 65mm) |
| Weight: | .8 lbs (363g) |

Standard Accessories

| | |
|-------|---|
| GK11M | Standard K-Type Thermocouple Probe |
| A085 | UL Listed Silicone Test Lead Set with Alligator Clips (clip-on) |
| A270 | Soft Carrying Pouch |

Optional Accessories

| | |
|-----------|-------------------------|
| A202 | Line Splitter |
| A771 | Carbon Monoxide Adapter |
| A620 | Pressure Adapter |
| TLS2000RB | Deluxe Test Lead Kit |

Agency Approvals

| | |
|--------------------|--------------|
| CE IEC 61010-1 | CAT III 600V |
| UL 61010-1 (cULus) | CAT III 600V |

Did you know...

The P920-270-TPI does a variety of functions including flame sensor, DC Micro amps, and temperature. Features enhanced Multimeter!



by



Universal HVAC/R
Parts and Supplies

Electrical Tools

True RMS DMM with capacitance, low-pass filter, duty cycle, and temperature HVAC Multimeter P920-183A-TPI



Features:

- True RMS DMM
- Duty cycle (% pulse width modulation) for measuring modulating gas valves
- Low pass filter for noisy environments
- Separate fuse (2) and battery compartment
- IR serial interface that can be used to input data to PC with optional A183
- High resolution (0.01) low DC microamp range for measuring flame safety control circuit
- Frequency, capacitance, temperature, data hold, min/max record, relative mode
- AC/DC volts, AC/DC amps, resistance, audible continuity and diode test
- UL 61010-1 CAT II 750Vac / 1000Vdc CAT III 600Vac/dc
- 3 year limited warranty

Specifications:

Range Selection

Auto / Manual

Display Specifications

4000 Count Display

Analog Bar Graph

Backlight

Basic Functions

AC / DC Volts, AC / DC Amps

Resistance, Diode Test

Audible Continuity

Additional Functions

True RMS, Frequency,

Capacitance, Temperature

Duty Cycle (% of pulse width modulation (PWM))

Data Hold

Min / Max Record

Relative Mode •

Active Low Pass Filter Function

PC Output

Sleep Mode / Auto Off

Additional Features

Frequency Check in Volt Mode

Closed Case Calibration

Separate Fuse / Battery Access

Protective Boot

Range & Resolution

| | |
|-----------------------|--------------|
| Basic DC Accuracy | 0.5% |
| DC Voltage (maximum) | 1000V |
| Input Impedance | 10MΩ |
| Resolution (maximum) | 0.01mV |
| AC Voltage (maximum) | 750V |
| Input Impedance | 10MΩ |
| Resolution (maximum) | 0.01mV |
| DC Amps (maximum) | 10A |
| Resolution (maximum) | 0.01μA |
| AC Amps (maximum) | 10A |
| Resolution (maximum) | 0.1μA |
| Resistance (maximum) | 40MΩ |
| Resolution (maximum) | 0.1Ω |
| Frequency (maximum) | 10MHz |
| Resolution (maximum) | 0.01Hz |
| Temperature (maximum) | 2372°F |
| Resolution (maximum) | 0.1°F |
| Capacitance (maximum) | 4000μF |
| Resolution (maximum) | 0.01nF |
| Duty Cycle | 0.1 to 99.9% |

Agency Approval

| | |
|--------------------|--|
| CE IEC 61010-1 | CAT II 750Vac/1000Vdc CAT III 600Vac/dc |
| UL 61010-1 (cULus) | CAT II 750Vac/1000Vdc CAT III 600Vac/dc |

Electrical Tools

HVAC Multimeter kit P920-183AC3-TPI



HVAC DMM/Clamp Meter Kit

Applications:

- Troubleshoot ECMs and VFDs
- Test Flame Sensors
- Check Capacitors
- Measure Temperature Rise

Kit Includes:

- True RMS DMM (P920-183A-TPI)
- Clamp-On Tester (P920-265-TPI)
- General Purpose Probe
- Test Lead Alligator Clips
- Test Lead
- Soft Padded Case

Test Lead Kit P920-TLK3-TPI

Fits all major brands of meters

- A057 back probes ideal to trouble shoot ECMs, Molex™ connectors or Molex type connector.
- A080 UL listed silicone test leads
- A052 modular male banana plug to screw tip test leads like the A080.
- A150 Screw on alligator clips with boots
- 3-year limited warranty



Did you know...

Test lead replacement for all meters! With this Test Lead Kit P920-TLK3-TPI you get Test Leads and Back Probes. No need to purchase separately!



Universal HVAC/R
Parts and Supplies

by



Temperature Tools

Pocket Thermometer P920-315C-TPI

Test Extreme Temperatures Immediately with the Pocket Thermometer



Applications:

- HVAC/R: Ambient air, calibrate
- Thermostats: Vents, compressor heads, registers
- Electrical: Motor temperatures, transformer temperatures

Features:

- Auto field calibration to +/- 2°F
- Tapered stem (3.1mm diameter) to fit into a Pete's Plug
- Reinforced, heavy-duty housing for strength
- Waterproof (IP63)
- Fits in your pocket
- -58°F to 300°F (-50°C to 150°C)
- Rugged design to withstand a 10 foot drop
- Magnetic clip, perfect for air duct applications
- 3 Year Limited Warranty

Specifications:

| | |
|--------------------|---------------------------------|
| Temperature Range | -58°F to 300°F (-50°C to 150°C) |
| Accuracy | +/-2°F (+/-1°C) |
| Resolution | 0.1°F/°C |
| Sample Rate | 1 reading every 1.5 second |
| Stem Length | 2.8" |
| Tip Type | Penetration |
| Water Resistant | Yes |
| Water Proof | N/A |
| °C / °F Selectable | Yes |
| Data Hold | Yes |
| Auto Off | Yes |
| Battery Type | LR44 |

Did you know...

This Pocket Thermometer P920-315C-TPI is FIELD CALLBRATABLE!!!!

Temperature Tools

Infrared Thermometer - P920-381A-TPI

Measure hard-to-reach, sensitive, or large moving target temperatures

IR/K measurements available with the Totaline Infrared Thermometer; select the IR for non-contact measurements or set to K for contact measurements. Easily read the temperatures throughout various applications by holding the trigger and reading through the backlit display. Easy to use! Repeatable, 0.1° resolution readings ensures tests are consistently correct.

- Free E-type thermocouple with sub-mini input jack included



Applications:

HVAC/R

- Compressor heads
- Vents
- Hot and cold areas in insulation
- Leaks around cooler or freezer doors
- Leaks around windows
- Steam traps
- Registers

Electrical

- Cables
- Circuit breakers
- Connections
- Machinery
- Motors
- Transformers

Food

- Grill & surface temperatures
- Holding cabinets
- Serving temperatures
- Storage temperatures

Features:

- Non-Contact -4° to 572° F
- Contact -146 to 2,192°F (optional temperature probe)
- Temperature compensated
- Single button, last reading hold function (°F / °C Switching)

Specifications:

| | |
|--|--|
| Distance to Spot Ratio | 9 : 1 |
| Temperature Range | Non-contact: -4° to 572°F (-20° to 300°C) Contact:* -148° to 2192°F (-100° to 1200°C) |
| IR Accuracy @ 23°C and 0.95 emissivity | ± 5°F (3°C) below 32°F (0°C) 32°F to 572°F (0°C to 300°C) ± 2% of rdg or ± 3.5°F (2°C) whichever is greater |
| Contact Accuracy | +(0.5% of reading + 3.5°F (2°C)) |
| Emissivity | 0.95 |
| Laser Sighting | Output <1mW, Wavelength 645-660nm, Class II Laser |
| °F or °C | Selectable (slide switch in handle) |
| Contact or Non-contact | Selectable (slide switch in handle) |
| Display Hold | Yes |
| Response Time | 500 millisecond |
| Spectral Response | 7 - 14 um |
| Operating Temperature | 32° to 120°F (0° to 150°C) |
| Battery Type | 9 Volt |



Universal HVAC/R
Parts and Supplies

by



Did you know...

The Infrared Thermometer - P920-381A-TPI has added functionality. K Thermocouple to measure air OR Liquid. A Thermocouple is also included with the purchase of this tool.

Temperature Tools



3 Year
Limited
Warranty

Size: 5.75" x 2.75" x 1.5"
41mm x 152mm x 77mm



Tilt Stand For The P920-343-tpi

Dual Input K-Type Thermocouple Thermometer with Field Calibration

The Totaline P920-343-TPI is a reliable, water-resistant thermometer that accepts K-type thermocouples. With two easy steps this tool is also has the capability to be field calibrated.

Applications:

HVAC/R

- Ambient air
- Calibrate thermostats
- Vents
- Compressor heads
- Temperature differential
- Registers

Food Temperatures

- Grill and surface temperatures

Electrical Temperatures

- Cables
- Circuit breakers
- Connections
- Machinery
- Motors
- Transformers

Features:

- Temperature range -58° to 2,462°F (-50° to 1,350°C)
- Auto field calibrate in less than 10 seconds in ice water to achieve +/- 1°F system accuracy within 30°F to 120°F temperature range.
- Easy to read main display: displays OFL to show disengaged or open probe
- Thermocouple type indicator
- Display mode indicator (T1, T2, T1-T2)
- On/Off button with guard to prevent accidental engagement
- Freezes reading on display
- Select input T1 or T2 and display temperature differential (T1-T2)
- Select between Celsius and Fahrenheit display
- Record and display minimum and maximum temperatures
- 3 Year Limited Warranty

Specifications:

| | |
|-----------------------------|--|
| Measurement Range (K-Type): | -58 to 2,462 °F (-50 to 1,350 °C) |
| Accuracy: | -58° to 32°F (-50° to 0°C) = ±3°F (1.6°C) 32° to 1100°F (0° to 600°C) = ±(0.3% of reading, + 1.8°F (1°C)) 1100° to 2462°F (600° to 1350°C) = ±(0.4% of reading, + 1.8°F (1°C)) |
| Resolution: | 0.1° / 1° |
| Connector Type: | Submini, Dual Input |

Did you know...

Digital Thermometer - P920-343-TPI tool is FIELD CALLBRATABLE!!!!

Combustion Tools

Combustible Gas Leak Detector – P920-725L-TPI



Find Combustible Gas Leaks with the Totaline® Combustible Gas Leak Detector

Applications:

- Detects combustible gases including methane, butane, propane, gasoline, diesel, and kerosene
- Totaline Gas Leak Detector finds the source of combustible gas leaks in valves, pipes and fittings
- Tick rate can be nullified to eliminate background gas concentration and pinpoint the leak source

How to Use:

Point the Totaline Combustible Gas Leak Detector sensor towards the suspected leak until the tool begins to increasingly tick. When the tick rate increases, press and release the on/off key top nullify the tick and continue to approach the leak area with the sensor. Continue to nullify the tick until the location of the leak is detected.

Specifications:

| | |
|----------------|---------------------------------|
| Sensitivity | > 40ppm Methane |
| Operating Temp | 32° to 104°F or 0° to 40°C |
| Response Time | Instantaneous |
| Battery | 1.5 volt, AAA Alkaline (2 each) |
| Battery Life | 3 hours continuous use |

Did you know...

Combustible Gas Leak Detector P920-725L-TPI has the same functionality as UEI, Fieldpiece, and Fluke! Competitive Pricing!

Combustion Analyzer with Smart Sensors – P920-717-TPI

Field Replaceable O2 & CO Sensors



The P920-717-TPI enables users to perform sensor replacement without having to perform calibration through pre-calibrated oxygen and carbon monoxide smart sensors.

How to Use:

Remove the old sensor, install the new sensor, and wait 24 hours for sensor stabilization. Once the 717 is turned on calibration, data is automatically transferred to the analyzer.

Features:

- Built-In differential manometer with 0.001" H2O resolution
- Calculates combustion efficiency
- Pump driven for fast response
- Will not shut off if 15 ppm CO is present for increased safety
- Built-in differential thermometer
- Store function to save up to 100 readings
- Push on fittings for fast and easy use
- Large easy to read backlit display
- 11 selectable fuels

Kit Includes:

- Soft carrying case
- Silicone tubing
- Flue probe
- Mini pump protection filter
- K-type thermocouple
- Brass hose barb fitting

Combustion Analyzer with Smart Sensors and Printer – P920-717A740-TPI



Universal HVAC/R
Parts and Supplies

by



This includes everything the
Combustion Analyzer P920-717-TPI does **plus a printer!**

Pressure Tools

Dual Input Differential Manometer – P920-621-TPI



Differential Manometer can be used for various applications such as adjusting appliance regulators, checking regulators, pressure switches, and furnace duct pressure testing.

Features:

- Capability to measure negative and positive pressure
- Measures in 7 different units of measure (mbar, kPa, PSI, mmHg, mmH2O, inH2O)
- Smooth feature: stabilizes display when measuring fluctuating pressures
- Range -120 and 120 inches of water column
- Temperature compensated: allows you to continue to have an accurate reading even when changing to extreme temperatures

Specifications:

| | |
|----------------------------------|--|
| Measurement Range: | ±120" H2O |
| Display: | 5 Digit LCD with backlight |
| Input Type: | Dual Differential (1/4" Barbed) |
| Resolution (max): | 0.001" H2O |
| Accuracy: | -40.2 to 40.2 inH2O: ±(0.2% of F.V.) <-40.2 & >40.2 inH2O: ±(1% of M.V.) |
| Functions: | One Touch Zero, Back-light, Unit Selection, Smoothing, Auto power Off |
| Units of Measure: | 7 Units (mbar, kPa, PSI, mmHg, inHg, mmH2O, inH2O) |
| Battery Type: | 9V alkaline |
| Battery Life: | 80hours (Typical) |
| Auto Power Off: | 40 minutes |
| Standard Accessories (Included): | 9V alkaline battery (A009A), two pieces 30" silicone tube (A613), two 1/8" NPT to 1/8" barbed fittings (A603) |



Dual Input Differential Manometer Kit – P920-621C3-TPI

Kit Includes:

- P920-621C3-TPI Manometer
- 2 x T Fittings
- 2 x Static Tip
- Tubing
- Adapter Tube
- Carrying Case

Did you know...

This P920-621C3-TPI Manometer replaces the majority of manometers out there PLUS there is a high range of higher resolution. Reduce your inventory!

Totaline® Part Number Tool Cross Reference

| Totaline Part Number | Description | TPI Part Number | UEI Part Number | Fluke® Part Number | Fieldpiece Part Number |
|----------------------|--|-----------------|-----------------|--------------------|------------------------|
| P920-183A-TPI | HVAC Multimeter | 183A | DM393 | 116 | LT16A |
| P920-183AC3-TPI | HVAC Multimeter Kit | 183AC3 | N/A | 116/322 | N/A |
| P920-265-TPI | Clamp-On Meter | 265 | DL369 | 322 | SC220 |
| P920-270-TPI | HVAC Clamp Meter | 270 | DL379 | 324 | SC240 |
| P920-315C-TPI | Pocket Thermometer | 315C | PDT550 | N/A | SWT2 |
| P920-343-TPI | Digital Thermometer | 343 | DTK2 | 52-2 | ST4 |
| P920-381A-TPI | Infrared Thermometer | 381A | INF165 | 62 | SIG1 |
| P920-50-TPI | AC Safety Volt Check | 50 | NCV3 | LAC | N/A |
| P920-621-TPI | Dual Input Differential Manometer | 621 | EM201B | N/A | SDMN5 |
| P920-621C3-TPI | Dual Input Differential Manometer Kit | 621C3 | EM201SP Kit | N/A | N/A |
| P920-725L-TPI | Combustible Gas Leak Detector | 725L | CD100 | N/A | N/A |
| P920-TLK3-TPI | Test Lead Kit | TLK3 | ATLBPK | N/A | N/A |
| P920-717A740-TPI | Combustion Analyzer with Printer | 717A740 | C155 Kit | N/A | N/A |
| P920-717-TPI | Combustion Analyzer with Smart Sensors | 717 | C155 | N/A | N/A |



by



**Universal HVAC/R
Parts and Supplies**

Replacement Components • © Carrier Corporation 2017
Printed in the U.S.A. • Edition Date: Rev. D 08/2017 • Lit. No.: 570-578

For promotional information visit www.totaline.com
and for technical information visit www.hvacpartners.com