

58CTA/CTX

PERFORMANCE 80 TWO-STAGE 4-WAY

MULTIPOISE INDUCED-COMBUSTION FURNACE

Input Capacities: 45,000 thru 155,000 Btuh




Turn to the Experts.™

Product Data

Performance
SERIES

ComfortHeat.



A04041

THE PERFORMANCE 80 GAS FURNACE

The 58CTA/CTX Two-Stage, 4-way Multipoise Gas Furnaces offer unmatched comfort in their class with ComfortHeat™ technology in an 80% AFUE gas furnace. You get the benefits of a ComfortHeat™ technology furnace: reduced drafts, reduced sound levels, longer cycles, less temperature swings between cycles, and less temperature differences between rooms. Its exclusive, intelligent microprocessor control adapts to the heating needs of the home by automatically adjusting high and low heat times to maximize comfort. The 58CTA/CTX furnaces are approved for use with natural or propane gas, and the 58CTX is approved for use in Low NOx Air Quality Management Districts.

STANDARD FEATURES

- ComfortHeat™ Technology
Intelligent microprocessor control
- Two-stage heating with single-stage thermostat with patented Adaptive Control Technology
- Very low operating sound through low-stage operation and QuieTech™ system
SmartEvap™—Humidity control when using a Thermidistat/Infinity control
Comfort Fan™ adjustable constant fan speed from the thermostat
- Media Filter Cabinet included
- Microprocessor based control center
LED diagnostics and self test feature
Stores fault codes during power outages
Adjustable heating air temperature rise
Adjustable cooling airflow
- 4-way Multipoise furnace, 13 vent applications
- Compact design - only 33-1/3 in. tall
- Power Heat Igniter™
- Draft Safeguard switch to ensure proper furnace venting
- Insulated blower compartment
- Inner door for tighter sealing
- Heat Pump compatible
- All models are Chimney Friendly when used with accessory vent kit



ISO 9001:2000



**MEETS DOE RESIDENTIAL CONSERVATION
SERVICES PROGRAM STANDARDS.**


Before purchasing this appliance, read important energy cost and efficiency information available from your retailer.

- Twinning in Upflow, Downflow and Horizontal
- Residential installations eligible for consumer financing through the Retail Credit Program


LIMITED WARRANTY

- 20-year warranty on “Super S™” heat exchanger
- 5-year parts warranty on all other components


58CTA/CTX



HEAT EXCHANGER A02169



CONTROL BOARD A02238




INDUCER BLOWER A02170

Model number nomenclature

58CTA	045	100	08
58CTA Two-Stage 4-Way Multipoise 58CTX Low NOx version			Nominal Cooling Size (Airflow at .5 e.s.p.) (400 CFM per 12,000 Btuh) 08 — 800 CFM 12 — 1200 CFM 14 — 1400 CFM 16 — 1600 CFM 20 — 2000 CFM 22 — 2200 CFM
Input Capacity 045 — 44,000 Btuh 110 — 110,000 Btuh 070 — 66,000 Btuh 135 — 132,000 Btuh 090 — 88,000 Btuh 155 — 154,000 Btuh			Series Number

FURNACE COMPONENTS


58CTA/CTX



*Elbow may be turned to a different position, depending on type of installation

NOTE: The 58CTA/CTX Furnaces are factory shipped for use with natural gas. These furnaces can be field-converted for propane gas with a factory-authorized and listed accessory conversion kit.

Carrier accessories




A97432

CONTROLS: THERMOSTATS AND ZONING

Available in programmable and non-programmable models, Carrier thermostats maintain a constant, comfortable temperature level in the home.

For the ultimate in home comfort, Carrier's 2, 4, and 8-zone systems allow temperature control of individual "zones" of the home. This is accomplished through a series of electronic dampers and remote room sensors. The 4-zone system is shown.




C04008

MECHANICAL OR ELECTRONIC AIR CLEANER

Cleans the air of smoke, dirt, and many pollens commonly found. Saves decorating and cleaning expenses by keeping carpets, furniture, and drapes cleaner.

Electronic air cleaner is shown.



A01484

MODEL HUMCCLFP HUMIDIFIER

By adding moisture to winter-dry air, a Carrier humidifier can often improve comfort and keep furniture, rugs, and draperies in better condition. Moisturizing household air also helps to retain normal body heat and provides comfort at lower temperatures.

Accessories	
ELECTRONIC AIR CLEANER (EAC)	Model EACA
MECHANICAL AIR CLEANER	Models EZXCAB, FILCAB
HUMIDIFIER	Model HUM
HEAT RECOVERY VENTILATOR	Model HRV
ENERGY RECOVERY VENTILATOR	Model ERV
THERMOSTAT - NON-PROGRAMMABLE	For use with 1-speed Air Conditioner - deg. F/C, Auto Changeover - TSTATCCNAC01-B For use with 1-speed Air Conditioner - deg. F/C, Auto Changeover - TSTATCCNHP01-B For use with 2-speed Air Conditioner - deg. F/C, Auto Changeover - TSTATCCN2S01-B For use with multi-use / stage configurations - deg. F/C, Auto Changeover/Temperature and Humidity control - TSTATCCPRH01-B†
THERMOSTAT - PROGRAMMABLE	For use with 1-speed Air Conditioner - deg. F/C, Auto Changeover, 7-Day Programmable - TSTATCCPAC01-B For use with 1-speed Air Conditioner - deg. F/C, Auto Changeover, 7-Day Programmable - TSTATCCPHP01-B* For use with 2-speed Air conditioner - deg. F/C, Auto Changeover, 7-Day Programmable - TSTATCCP2S01-B* For use with 1-speed Air Conditioner - deg. F/C, 5-2 Day Programmable - TSTATCCSAC01 For use with multi-stage applications - deg. F/C, Auto Changeover, 7-Day Programmable - TSTATCCPDF01-B† For multi-use / stage configurations - deg. F/C, Auto Changeover, 7-Day Programmable/ Temperature and Humidity Control - TSTATCCPRH01-B†
ZONING CONTROLS	2-Zone kit - ZONEKIT2ZCAR
	2-Zone kit /Temperature and Humidity Control - ZONECC2KIT01-B
	4-Zone kit/Temperature and Humidity Control - ZONECC4KIT01-B
	8-Zone kit/Temperature and Humidity Control - ZONECC8KIT01-B

* Model HP and 2S thermostat must be field converted to air conditioner operation.

† Thermostat Control can be configured for multiple use and staging, it must be configured for each specific application.

Carrier Accessories

58CTA/CTX DESCRIPTION	PART NO.	045-08	045-12	070-08	070-12	070-16	090-14	090-16	090-20	110-12	110-16	110-22	135-16	135-22	155-20
Cartridge Media Filter	FILCCCAR0016	X	X	X	X	X	X			X					
	FILCCCAR0020							X	X		X	X	X		
	FILCCCAR0024													X	X
EZ Flex Media Filter with End Caps	EXPXXUNV0016	X	X	X	X	X	X			X					
	EXPXXUNV0020							X	X		X	X	X		
	EXPXXUNV0024													X	X
Replacement EZ Flex Filter Media	EXPXXFIL0016	X	X	X	X	X	X			X					
	EXPXXFIL0020							X	X		X	X	X		
	EXPXXFIL0024													X	X
External Bottom Return Filter Rack	KBAFR0401B14	X	X	X	X										
	KGAFR0501B17					X	X			X					
	KGAFR0601B21							X	X		X	X	X		
	KGAFR0701B24													X	X
External Side Return Filter Rack	KGAFR0801SRE	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Unframed Filter 1-in.	KGAWF1306UFR	X	X	X	X	X	X	†	†	X	†	†	†	†	†
	KGAWF1406UFR							X	X		X	X	X		
	KGAWF1506UFR													X	X
Flue Extension	KGAFE0112UPH	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Twinning Kit	KGATW0601HSI	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Combustible Floor Base	KGASB0201ALL	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Downflow Vent Guard	KGAVG0101DFG	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Vent Extension Kit	KGAVE0101DNH	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Chimney Adapter Kit	KGACA02014FC	X	X	X	X	X	X	X	X	X	X	X			
Chimney Adapter Kit	KGACA02015FC												X	X	X
Natural-to-Propane Conversion Kit*	KGANP4001ALL	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Propane-to-Natural Conversion Kit	KGAPN3301ALL	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Label Kit	KGALB0101KIT	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Gas Orifice Kit (Qty 50)	KGAHA0150N42	See Installation Instructions for model, altitude, and heat value usages													
	KGAHA0250N43 (factory supplied)														
	KGAHA0350N44														
	KGAHA0450N45														
	KGAHA0550N46														
	KGAHA1550N47														
	KGAHA1650N48														
	KGAHA0650P54														
	KGAHA0750P55														
Air Leakage Kit (Qty10)	KGBAC0110DGK	All													

* Factory-authorized and field installed. Fuel conversion kits are AGA/CGA recognized.

† Suitable for side return.

58CTA/CTX

Physical data

UNIT SIZE			045		070			090		
			08	12	08	12	16	14	16	20
OUTPUT CAPACITY BTUH* (Nonweatherized ICS) †	All 58CTA; 58CTX Upflow	High	35,000	36,000	54,000	54,000	53,000	71,000	71,000	71,000
		Low	23,000	23,000	36,000	36,000	35,000	47,000	47,000	47,000
	All 58CTX Downflow/ Horizontal	High	34,000	34,000	51,000	51,000	51,000	68,000	68,000	68,000
		Low	23,000	23,000	36,000	36,000	35,000	47,000	47,000	47,000
INPUT BTUH*	All 58CTA; 58CTX Upflow	High	44,000	44,000	66,000	66,000	66,000	88,000	88,000	88,000
		Low	29,000	29,000	43,500	43,500	43,500	58,000	58,000	58,000
	All 58CTX Downflow/ Horizontal	High	42,000	42,000	63,000	63,000	63,000	84,000	84,000	84,000
		Low	29,000	29,000	43,500	43,500	43,500	58,000	58,000	58,000
AFUE†* Nonweatherized ICS			80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0
SHIPPING WEIGHT (lb.)			116	119	120	124	138	136	151	156
CERTIFIED TEMP RISE RANGE (°F)		High	30-60	20-50	40-70	30-60	25-55	40-70	30-60	25-55
		Low	20-50	15-45	30-60	30-60	15-45	25-55	25-55	15-45
CERTIFIED EXT STATIC PRESSURE	Heating		0.10	0.10	0.12	0.12	0.12	0.15	0.15	0.15
	Cooling		0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
AIRFLOW CFM‡	Heating High/Low		820/725	1030/860	790/685	885/695	1570/1045	1375/1195	1265/1030	1580/1325
	Cooling		895	1175	955	1240	1605	1385	1755	2005
LIMIT CONTROL			SPST							
HEATING BLOWER CONTROL			Solid-State Time Operation							
BURNERS (Monoport))			2	2	3	3	3	4	4	4
GAS CONNECTION SIZE			1/2-in. NPT							
GAS VALVE (Redundant) Manufacturer			White-Rodgers							
Minimum Inlet Pressure (In. wc)			4.5 (Natural Gas)							
Maximum Inlet Pressure (In. wc)			13.6 (Natural Gas)							
IGNITION DEVICE			Hot Surface							

* Gas input ratings are certified for elevations to 2000 ft. For elevations above 2000 ft, reduce ratings 4 percent for each 1000 ft above sea level. Refer to National Fuel Gas Code Table F4 or furnace Installation Instructions. In Canada, derate the unit 10 percent for elevations 2000 to 4500 ft above sea level.

† Capacity in accordance with U.S. Government DOE test procedures.

‡ Airflow shown is for bottom only return-air supply. For air delivery above 1800 CFM, see Air Delivery Table for other options. A filter is required for each return-air supply.

ICS — Isolated Combustion System

Blower performance data

UNIT SIZE			045		070			090		
			08	12	08	12	16	14	16	20
DIRECT-DRIVE MOTOR Hp (PSC)			1/5	1/3	1/5	1/3	1/2	1/3	1/2	3/4
MOTOR FULL LOAD AMPS			2.8	5.1	2.8	5.1	7.4	5.2	7.4	11.0
RPM (Nominal) – Speeds			1075-4	1075-5	1075-4	1075-5	1075-5	1075-4	1075-5	1075-5
BLOWER WHEEL DIAMETER × WIDTHS (In.)			10 x 6	10 x 6	10 x 6	10 x 6	11 x 8	10 x 8	10 x 10	11 x 11

PSC-Permanent Split Capacitor

Physical data

UNIT SIZE			110			135		155
			12	16	22	16	22	20
OUTPUT CAPACITY BTUH* (Nonweatherized ICS) †	All 58CTA; 58CTX Upflow	High	89,000	89,000	89,000	107,000	107,000	125,000
		Low	59,000	59,000	59,000	70,000	70,000	82,000
	All 58CTX Downflow/ Horizontal	High	85,000	85,000	85,000	102,000	102,000	119,000
		Low	59,000	59,000	59,000	70,000	70,000	82,000
INPUT BTUH*	All 58CTA; 58CTX Upflow	High	110,000	110,000	110,000	132,000	132,000	154,000
		Low	72,500	72,500	72,500	87,000	87,000	101,500
	All 58CTX Downflow/ Horizontal	High	105,000	105,000	105,000	126,000	126,000	147,000
		Low	72,500	72,500	72,500	87,000	87,000	101,500
AFUE†* Nonweatherized ICS			80.0	80.0	80.0	80.0	80.0	80.0
SHIPPING WEIGHT (lb)			144	158	163	163	174	181
CERTIFIED TEMP RISE RANGE (°F)		High	50-80	40-70	30-60	50-80	40-70	45-75
		Low	30-60	25-55	20-50	30-60	25-55	30-60
CERTIFIED EXT STATIC PRESSURE	Heating		0.20	0.20	0.20	0.20	0.20	0.20
	Cooling		0.50	0.50	0.80	0.50	0.50	0.50
AIRFLOW CFM‡	Heating		1335/1180	1290/1045	1555/1295	1525/1320	1865/1640	1790/1565
	Cooling		1355	1695	2200	1710	2110	2230
LIMIT CONTROL			SPST					
HEATING BLOWER CONTROL			Solid-State Time Operation					
BURNERS (Monoport))			5	5	5	6	6	7
GAS CONNECTION SIZE			1/2-in. NPT					
GAS VALVE (Redundant) Manufacturer			White-Rodgers					
Minimum Inlet Pressure (In. wc)			4.5 (Natural Gas)					
Maximum Inlet Pressure (In. wc)			13.6 (Natural Gas)					
IGNITION DEVICE			Hot Surface					

* Gas input ratings are certified for elevations to 2000 ft. For elevations above 2000 ft, reduce ratings 4 percent for each 1000 ft above sea level. Refer to National Fuel Gas Code Table F4 or furnace Installation Instructions. In Canada, derate the unit 10 percent for elevations 2000 to 4500 ft above sea level.

† Capacity in accordance with U.S. Government DOE test procedures.

‡ Airflow shown is for bottom only return-air supply. For air delivery above 1800 CFM, see Air Delivery Table for other options. A filter is required for each return-air supply.


ICS — Isolated Combustion System

58CTA/CTX

Blower performance data

UNIT SIZE	110			135		155
	12	16	20	16	20	20
DIRECT-DRIVE MOTOR Hp (PSC)	1/3	1/2	3/4	1/2	3/4	3/4
MOTOR FULL LOAD AMPS	5.2	7.4	11.0	7.9	11.1	11.1
RPM (Nominal) – Speeds	1075-4	1075-5	1075-5	1075-4	1075-4	1075-5
BLOWER WHEEL DIAMETER × WIDTHS (In.)	10 x 8	10 x 10	11 x 11	10 x 10	11 x 11	11 x 11


PSC-Permanent Split Capacitor



SEE NOTES: 1,2,4,7,8,9

UPFLOW


A02058



SEE NOTES: 1,2,3,4,7,8,9

UPFLOW


A02059



SEE NOTES: 1,2,4,5,7,8,9

DOWNFLOW


A02061



SEE NOTES: 1,2,3,4,5,7,8,9

DOWNFLOW


A02060



SEE NOTES: 1,2,3,4,5,7,8,9

DOWNFLOW

A02063




SEE NOTES: 1,2,4,5,6,7,8,9

DOWNFLOW

A02062


Venting Notes

1. For common vent, vent connector sizing and vent material: United States, latest edition of the National Fuel Gas Code (NFGC), ANSI Z223.1/NFPA 54. In Canada, latest edition of the National Standards of Canada, Natural Gas and Propane Installation Code (NSCNGPIC), CSA B149.1-00.
2. Immediately increase to 5-in. vent connector outside furnace casing when 5-in. vent connector required, refer to Note 1.
3. Side outlet vent for upflow and downflow installations must use Type B vent immediately after exiting the furnace, except when KGAVG0101DFG is used in downflow position.
4. Type B vent where required, refer to Note 1.
5. 4-in. single wall vent must be used inside furnace casing and the KGAVG0101DFG Downflow Vent Guard Kit.
6. Accessory Downflow Vent Guard Kit, KGAVG0101DFG required in downflow installations with bottom vent configuration.
7. Chimney Adapter Kit required for exterior masonry chimney applications. Refer to Chimney Adapter Kit, KGACA02014FC and KGACA02015FC for sizing and complete application details.
8. Secure vent connector to furnace elbow with (2) corrosion-resistant sheet metal screws, space approximately 180° apart.
9. Secure all other single wall vent connector joints with (3) corrosion-resistant screws spaced approximately 120° apart. Secure Type B vent connectors per vent connector manufacturer's recommendations.




SEE NOTES: 1,2,4,5,7,8,9
HORIZONTAL RIGHT

A02068




SEE NOTES: 1,2,4,5,7,8,9
HORIZONTAL RIGHT

A02070




SEE NOTES: 1,2,4,7,8,9
HORIZONTAL RIGHT

A02069




SEE NOTES: 1,2,4,7,8,9
HORIZONTAL LEFT

A02064




SEE NOTES: 1,2,4,5,7,8,9
HORIZONTAL LEFT

A02065



SEE NOTES: 1,2,4,5,7,8,9
HORIZONTAL LEFT

A02066



SEE NOTES: 1,2,4,5,7,8,9
HORIZONTAL LEFT

A02067

AIR DELIVERY—CFM (With Filter)*

UNIT SIZE	RETURN-AIR SUPPLY	SPEED	EXTERNAL STATIC PRESSURE (In. wc)									
			0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
045-08	Bottom or Side(s)	High	1120	1075	1020	960	895	815	720	605	455	340
		Med-High	930	890	850	805	750	680	600	500	345	195
		Med-Low	820	785	750	700	650	585	505	400	235	—
		Low	725	690	655	605	555	495	405	305	—	—
045-12	Bottom or Side(s)	High	1465	1400	1325	1250	1175	1085	980	860	725	—
		Med-High	1295	1260	1210	1155	1090	1015	930	830	700	—
		Medium	1150	1120	1085	1040	985	920	835	740	620	—
		Med-Low	1030	1008	980	945	895	835	765	685	—	—
070-08	Bottom or Side(s)	High	1140	1105	1055	1010	955	885	815	715	545	390
		Med-High	915	885	855	825	785	725	655	530	420	280
		Med-Low	795	770	740	700	655	600	510	420	325	—
		Low	690	665	630	590	550	475	415	340	245	—
070-12	Bottom or Side(s)	High	1440	1400	1355	1300	1240	1170	1090	1000	890	745
		Med-High	1180	1165	1150	1125	1085	1030	970	890	785	645
		Medium	1015	1020	1010	990	965	925	875	800	700	560
		Med-Low	885	885	880	865	845	815	770	700	605	475
070-16	Bottom or Side(s)	High	1840	1790	1730	1670	1605	1530	1450	1370	1275	1170
		Med-High	1610	1575	1535	1485	1435	1370	1305	1230	1145	1055
		Medium	1460	1430	1400	1360	1315	1260	1205	1130	1055	965
		Med-Low	1260	1240	1215	1180	1145	1100	1040	985	915	835
090-14	Bottom or Side(s)	High	1650	1600	1535	1465	1385	1285	1175	1055	895	645
		Med-High	1515	1485	1440	1380	1300	1220	1115	990	830	600
		Med-Low	1385	1360	1320	1260	1195	1120	1025	915	710	565
		Low	1205	1180	1160	1120	1065	1005	925	810	630	510
090-16	Bottom or Side(s)	High	2060	2000	1930	1835	1755	1620	1490	1315	1115	910
		Med-High	1710	1695	1665	1585	1480	1390	1245	1110	955	775
		Medium	1470	1475	1450	1390	1335	1230	1120	1005	855	690
		Med-Low	1260	1265	1245	1225	1165	1090	995	880	750	600
090-20	Bottom Only	High	2380	2295	2205	2105	2005	1900	1775	1650	1510	1335
		Med-High	2185	2115	2045	1960	1875	1770	1655	1535	1400	1240
		Medium	1905	1865	1815	1740	1670	1590	1490	1390	1245	1110
		Med-Low	1595	1565	1530	1485	1430	1355	1275	1160	1055	920
	Both Sides or 1 Side & Bottom	High	2485	2415	2330	2230	2135	2030	1920	1790	1645	1485
		Med-High	2175	2130	2070	2000	1930	1840	1740	1620	1495	1345
		Medium	1845	1815	1770	1720	1655	1580	1500	1395	1270	1090
		Med-Low	1540	1515	1475	1435	1385	1335	1270	1175	1045	915
	1 Side Only	High	2420	2345	2265	2165	2070	1960	1850	1720	1570	1420
		Med-High	2160	2110	2045	1960	1885	1790	1695	1570	1445	1305
		Medium	1850	1815	1765	1710	1635	1560	1480	1380	1250	1110
		Med-Low	1530	1490	1455	1420	1375	1320	1250	1160	1055	905
	1 Side Only	High	1290	1250	1220	1190	1155	1110	1040	950	835	740
		Med-High	1290	1250	1220	1190	1155	1110	1040	950	835	740
		Medium	1290	1250	1220	1190	1155	1110	1040	950	835	740
		Med-Low	1290	1250	1220	1190	1155	1110	1040	950	835	740

* A filter is required for each return-air supply. Airflow performance includes 1 in. washable filter media such as contained in factory-authorized accessory filter rack. To determine airflow performance without this filter, assume an additional .1 available external static pressure.

— Indicates unstable operating conditions.

AIR DELIVERY—CFM (With Filter)* continued

UNIT SIZE	RETURN-AIR SUPPLY	SPEED	EXTERNAL STATIC PRESSURE (In. wc)									
			0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
110-12	Bottom or Side(s)	High	1625	1575	1515	1445	1355	1260	1165	990	785	595
		Med-High	1510	1470	1415	1355	1285	1185	1070	890	725	530
		Med-Low	1360	1335	1295	1250	1180	1100	985	810	670	475
		Low	1195	1180	1155	1115	1065	980	860	740	605	410
110-16	Bottom or Side(s)	High	2055	1990	1910	1815	1695	1575	1425	1230	1090	910
		Med-High	1750	1725	1670	1605	1515	1400	1255	1120	975	785
		Medium	1545	1525	1490	1445	1355	1260	1135	1020	880	750
		Med-Low	1300	1290	1275	1235	1165	1085	1005	895	750	620
110-22	Bottom Only	High	2530	2460	2380	2285	2200	2085	1970	1835	1695	1545
		Med-High	2225	2190	2135	2075	1995	1910	1805	1695	1565	1430
		Medium	1895	1885	1865	1820	1770	1700	1610	1520	1410	1290
		Med-Low	1565	1555	1535	1505	1465	1410	1350	1265	1175	1050
	Both Sides or 1 Side & Bottom	High	—	—	2415	2330	2235	2125	1995	1860	1735	1605
		Med-High	2205	2175	2120	2065	1975	1900	1790	1685	1580	1460
		High	2485	2430	2360	2270	2175	2070	1950	1825	1685	1535
		Med-High	2155	2135	2100	2040	1970	1885	1790	1680	1560	1420
	1 Side Only	Medium	1830	1830	1810	1780	1730	1665	1595	1505	1395	1275
		Med-Low	1520	1505	1490	1470	1430	1385	1330	1250	1165	1055
		Low	1275	1260	1240	1210	1180	1135	1090	1025	930	840
135-16	Bottom or Side(s)	High	2090	2010	1930	1835	1710	1590	1470	1335	1025	835
		Med-High	1790	1755	1705	1640	1550	1465	1360	1210	945	785
		Med-Low	1545	1525	1500	1450	1380	1315	1215	1005	855	670
		Low	1325	1320	1295	1265	1210	1150	995	865	745	540
135-22	Bottom Only	High	2485	2400	2310	2215	2110	2000	1880	1725	1535	1355
		Med-High	2195	2150	2090	2000	1920	1825	1720	1565	1405	1255
		Med-Low	1880	1850	1820	1780	1715	1635	1540	1415	1290	1160
		Low	1640	1635	1615	1585	1530	1465	1370	1255	1150	1040
	Both Sides or 1 Side & Bottom	High	—	—	2385	2305	2195	2085	1960	1825	1670	1465
		Med-High	2180	2145	2060	2010	1945	1865	1765	1660	1515	1325
		Med-Low	1880	1850	1820	1780	1715	1635	1540	1415	1290	1160
		Low	1640	1635	1615	1585	1530	1465	1370	1255	1150	1040
	1 Side Only	High	2320	2250	2155	2055	1970	1855	1725	1600	1450	1280
		Med-High	2125	2065	1995	1910	1815	1710	1610	1490	1340	1175
		Med-Low	1845	1825	1765	1710	1650	1570	1475	1370	1240	1100
		Low	1640	1620	1580	1540	1485	1410	1330	1220	1080	960
155-20	Bottom Only	High	2465	2430	2375	2305	2230	2110	2000	1865	1725	1545
		Med-High	2115	2105	2075	2030	1980	1910	1830	1725	1590	1425
		Med-Low	1800	1790	1770	1735	1695	1640	1570	1465	1345	1225
		Low	1570	1565	1551	1525	1495	1445	1370	1270	1175	1070
	Both Sides or 1 Side & Bottom	High	—	—	2375	2285	2200	2105	1995	1870	1730	1570
		Med-High	2155	2135	2095	2040	1975	1895	1790	1685	1550	1400
155-20	1 Side Only	High	—	—	2260	2180	2085	1975	1865	1740	1605	1455
		Med-High	2140	2095	2040	1975	1890	1810	1705	1595	1480	1325

58CTA/CTX

* A filter is required for each return-air supply. Airflow performance includes 1 in. washable filter media such as contained in factory-authorized accessory filter rack. To determine airflow performance without this filter, assume an additional .1 available external static pressure.

— Indicates unstable operating conditions.

58CTA/C7X



- | 58CTA/CTX
UNIT SIZE | A
(CABINET
WIDTH) | D
(SUPPLY
WIDTH) | E
(BOTTOM
RETURN
WIDTH) | F
(TOP VENT
OUTLET) | VENT
CONNECTION
SIZE
(see notes 1 & 2) | MEDIA CABINET
SIZE (in.) |
|------------------------|-------------------------|------------------------|----------------------------------|---------------------------|---|-----------------------------|
| 045-08 | 14-3/16 | 12-9/16 | 12-11/16 | 9-5/16 | 4 | 16 |
| 045-12 | 14-3/16 | 12-9/16 | 12-11/16 | 9-5/16 | 4 | 16 |
| 070-08 | 14-3/16 | 12-9/16 | 12-11/16 | 9-5/16 | 4 | 16 |
| 070-12 | 14-3/16 | 12-9/16 | 12-11/16 | 9-5/16 | 4 | 16 |
| 070-16 | 17-1/2 | 15-7/8 | 16-1/8 | 11-9/16 | 4 | 16 |
| 090-14 | 17-1/2 | 15-7/8 | 16-1/8 | 11-9/16 | 4 | 16 |
| 090-16 | 21 | 19-3/8 | 19-1/2 | 13-5/16 | 4 | 20 |
| 090-20 | 21 | 19-3/8 | 19-1/2 | 13-5/16 | 4 | 20 |
| 110-12 | 17-1/2 | 15-7/8 | 16-1/8 | 11-9/16 | 4 | 16 |
| 110-16 | 21 | 19-3/8 | 19-1/2 | 13-5/16 | 4 | 20 |
| 110-22 | 21 | 19-3/8 | 19-1/2 | 13-5/16 | 4 | 20 |
| 135-16 | 21 | 19-3/8 | 19-1/2 | 13-5/16 | 4 (note 1) | 20 |
| 135-22 | 24-1/2 | 22-7/8 | 23 | 15-1/16 | 4 (note 1) | 24 |
| 155-20 | 24-1/2 | 22-7/8 | 23 | 15-1/16 | 4 (note 1) | 24 |

- 12

INSTALLATION**MINIMUM INCHES CLEARANCE TO COMBUSTIBLE CONSTRUCTION
DISTANCE MINIMALE EN POUCES AUX CONSTRUCTIONS COMBUSTIBLES**

This forced air furnace is equipped for use with natural gas at altitudes 0-10,000 ft (0-3,050m).

An accessory kit, supplied by the manufacturer, shall be used to convert to propane gas use or may be required for some natural gas applications.

This furnace is for indoor installation in a building constructed on site.

This furnace may be installed on combustible flooring in alcove or closet at minimum clearance as indicated by the diagram from combustible material.

This furnace may be used with a Type B-1 Vent and may be vented in common with other gas fired appliances.

Cette fournaise à air pulsé est équipée pour utilisation avec gaz naturel et altitudes comprises entre 0-3,050m (0-10,000 pi).

Utiliser une trousse de conversion, fournie par le fabricant, pour passer au gaz propane ou pour certaines installations au gaz naturel.

Cette fournaise est prévue pour être installée dans un bâtiment construit sur place.

Cette fournaise peut être installée sur un plancher combustible dans une alcôve ou dans un garde-robe en respectant le minimum d'espace libre des matériaux combustibles, tel qu'indiqué sur le diagramme.


Cette fournaise peut être utilisée avec un conduit d'évacuation de Type B-1 ou connectée au conduit omnnun d'autres appareils à gaz.

This furnace is approved for UPFLOW, DOWNFLOW, and HORIZONTAL installations.

Cette fournaise est approuvée pour l'installation HORIZONTALE et la circulation d'air VERS LE HAUT et VERS LE BAS.

Clearance arrows do not change with furnace orientation.

Les flèches de dégagement ne change pas avec l'orientation de la fournaise.



Clearance in inches
Dégagement (po).

Vent Clearance to combustibles:

For Single Wall vents 6 inches (6 po).

For Type B-1 vent type 1 inch (1 po).

Dégagement de l'évent avec combustibles:

Pour conduit d'évacuation à paroi simple 6 po (6 inches).

Pour conduit d'évacuation de Type B-1 1 po (1 inch).

MINIMUM INCHES CLEARANCE TO COMBUSTIBLE CONSTRUCTION**DOWNFLOW POSITIONS:**

† Installation on non-combustible floors only.

For Installation on combustible flooring only when installed on special base, Part No. KGASB0201ALL, Coil Assembly, Part No. CD5 or CK5, or Coil Casing, Part No. KCAKC.

Ø 18 inches front clearance required for alcove.

★ Indicates supply or return sides when furnace is in the horizontal position. Line contact only permissible between lines formed by intersections of the Top and two Sides of the furnace jacket, and building joists, studs or framing.

**DÉGAGEMENT MINIMUM EN POUCES AVEC ÉLÉMENTS
DE CONSTRUCTION COMBUSTIBLES****POUR LA POSITION COURANT DESCENDANT:**

† Pour l'installation sur plancher non combustible seulement.

Pour l'installation sur un plancher combustible seulement quand on utilise la base spéciale, pièce n° KGASB0201ALL, l'ensemble serpent, pièce n° CD5 ou CK5, ou le carter de serpent, pièce n° KCAKC.

Ø Dans une alcôve, on doit maintenir un dégagement à l'avant de 18 po (450mm).


★ La position indiquée concerne le côté d'entrée ou de retour quand la fournaise est dans la position horizontale.

Le contact n'est permis qu'entre les lignes formées par les intersections du dessus et des deux côtés de la chérisse de la fournaise et les solives, montant sous cadre de charpente.

327590-101 REV. C

Media Cabinet Dimensions


*See Dimensions Table for Unit/Media Cabinet Combinations



A02210

Typical wiring schematic

58CTA/CTX



A95236

Electrical data

58CTA/CTX UNIT SIZE	VOLTS HERTZ- PHASE	OPERATING VOLTAGE RANGE		MAXIMUM UNIT AMPS	MAXIMUM WIRE LENGTH (FT)‡	MAXIMUM FUSE OR CKT BKR AMPS†	MINIMUM WIRE GAGE
		Maximum*	Minimum*				
045-08	115-60-1	127	104	5.3	49	15	14
045-12	115-60-1	127	104	7.1	38	15	14
070-08	115-60-1	127	104	5.2	51	15	14
070-12	115-60-1	127	104	7.3	37	15	14
070-16	115-60-1	127	104	10.1	27	15	14
090-14	115-60-1	127	104	8.2	34	15	14
090-16	115-60-1	127	104	9.9	28	15	14
090-20	115-60-1	127	104	12.9	34	20	12
110-12	115-60-1	127	104	8.2	34	15	14
110-16	115-60-1	127	104	10.1	28	15	14
110-22	115-60-1	127	104	13.7	32	20	12
135-16	115-60-1	127	104	10.2	27	15	14
135-22	115-60-1	127	104	14.5	30	20	12
155-20	115-60-1	127	104	15.0	29	20	12

* Permissible limits of the voltage range at which unit operates satisfactorily.

† Time-delay type is recommended.

‡ Length shown is as measured 1 way along wire path between unit and service panel for maximum 2 percent voltage drop.

Guide Specifications

Gas Furnace 58CTA/CTX

General

SYSTEM DESCRIPTION

Furnish a _____ fixed capacity gas-fired furnace for use with natural gas or propane (factory authorized conversion kit required for propane); furnish cold air return plenum; furnish external medial cabinet for use with accessory media filter or standard filter.

QUALITY ASSURANCE

Unit will be designed, tested and constructed to the current ANSI Z 21.47/CSA 2.3 design standard for gas-fired central furnaces.

Unit will be 3rd party certified by CSA to the current ANSI Z 21.47/CSA 2.3 design standard for gas-fired central furnaces.

Unit will carry the CSA Blue Star® and Blue Flame® labels.

Unit efficiency testing will be performed per the current DOE test procedure as listed in the Federal Register.

Unit will be certified for capacity and efficiency and listed in the latest GAMA Consumer's Directory of Certified Efficiency Ratings.

Unit shall carry the current Federal Trade Commission Energy Guide efficiency label.

DELIVERY, STORAGE AND HANDLING

Unit shall be shipped as single package only and is stored and handled per unit manufacturer's recommendations.

WARRANTY (for inclusion by specifying engineer)

U.S. and Canada only. Warranty certificate available upon request.

Products

EQUIPMENT

Components shall include: slow-opening two stage gas valve to reduce ignition noise, regulate gas flow, with electric switch gas shut-off; flame proving sensor, hot surface igniter, pressure switch assembly, flame rollout switch, blower and inducer assembly, 40va transformer; low-voltage (heating) (heating/cooling) thermostat.

Blower Wheel and Blower Motor

Galvanized blower wheel shall be centrifugal type, statically and dynamically balanced. Blower motor of PSC type shall be permanently lubricated with sealed bearings, of _____ hp, and shall be multiple-speed direct drive. Blower motor shall be soft mounted to the blower scroll to reduce vibration transmission.

Filters

Furnace shall have reusable-type filters. Filter shall be _____ in (x) _____ in. An accessory high efficiency Me-

dia Filter is available as an option. _____ Media Filter.

Casing

Casing shall be of .030 in. thickness minimum, pre-painted galvanized steel.

Two Speed Inducer Motor

Two Speed Inducer motor shall be soft mounted to reduce vibration transmission.

Draft Safeguard Switch

Draft Safeguard Switch (blocked vent safeguard) shall be factory installed to reduce the possibility of vent gas infiltration due to a blocked or restricted vent pipe.

Heat Exchangers

Heat exchangers shall be a 4-Pass 20 gage aluminized steel of fold-and-crimp sectional design when applied operating under negative pressure.

Controls

Control shall include a micro-processor based integrated electronic control board with at least 11 service troubleshooting codes displayed via diagnostic flashing LED light on the control, a self-test feature that checks all major functions of the furnace within one minute, and a replaceable automotive-type circuit protection fuse. Multiple operational settings available including, separate blower speeds for low heat, high heat, low cooling, high cooling and continuous fan. Continuous fan speed may be adjusted from the thermostat. Cooling airflow will be selectable between 350 or 400 CFM per ton of air conditioning. Features will also include temporary reduced airflow in the cooling mode for improved dehumidification when an Infinity Control or Thermidistat® is selected as the thermostat.

OPERATING CHARACTERISTICS

Heating Capacity shall be _____ Btuh input; _____ Btuh output capacity.

Fuel Gas Efficiency shall be 80% AFUE.

Air delivery shall be _____ cfm minimum at 0.50 in. wg external static pressure.

Dimensions shall be: depth _____ in.; width _____ in; height _____ in. (casing only). Height shall be _____ in. with A/C coil and _____ in. overall with plenum.

ELECTRICAL REQUIREMENTS

Electrical supply shall be 115 volts, 60 Hz, single-phase (nominal). Minimum wire size shall be _____ AWG; maximum fuse size or HACR-type designated circuit breaker shall be _____ Amps.

SPECIAL FEATURES

Refer to section of the product data sheet identifying accessories and descriptions for specific features and available enhancements.