




**MULTIPOISE 4-WAY GAS-FIRED
CONDENSING FURNACE**

The Payne 490AAV Furnaces utilize a 4-way multipoise design to allow 1 unit to be installed in upflow, downflow, horizontal left, or horizontal right applications. Using condensing furnace technology, the Payne 490AAV is a high-efficiency gas furnace that achieves 91.5% Annual Fuel Utilization Efficiency (AFUE). The combination of high efficiency and flexibility in a 4-way multipoise design make the 490AAV a must for your product line. Proven, reliable hot surface ignition, a microprocessor control center, and a sealed combustion system will provide years of dependable service and a good value to the consumer.

FEATURES

Multipoise 4-Way Design—Allows a 490AAV model to be installed in an upflow, downflow, or horizontal orientation.

The model 490AAV is available in 10 heat/airflow combinations and, when combined with the 4-way design, allows for 40 different application types. Factory configured for upflow application, this furnace can easily be made ready for downflow or horizontal installation.

Sealed Combustion (Direct Vent) System—Enclosed burner assembly isolates operating noise without the expense of

sound deadening devices. The sealed combustion (direct vent) system brings outdoor air directly into the combustion chamber, cutting cold air infiltration into the structure and reducing heat loss.

3-Pass Primary Heat Exchangers—This design accelerates heat transfer and extracts heat that conventional heat exchangers waste up the flue. The primary heat exchanger is made of aluminized steel for corrosion resistance.

Flow-Through Secondary Heat Exchangers—Each cell is laminated with our patented Everlastic™ Polypropylene for greater resistance to corrosion. This breakthrough in heating technology helps extend the life of the furnace for years of dependable performance. The heat exchanger is positioned in the furnace to extract additional heat from the combustion products regardless of furnace orientation.

Warranty—Limited Lifetime Warranty on the heat exchangers for the lifetime of the original owner in single family residence; 20 years in other residential and commercial applications. Contact your dealer for details. One-year Warranty on microprocessor control, hot surface ignitor, and inducer motor.

Monoport Inshot Burners—Produce precise air-to-gas mixture which gives a clean burn. The large monoport on the inshot or injection-type burners seldom, if ever, needs cleaning.


Microprocessor Control Center—The printed-circuit board and all internal wiring are factory installed. Convenient terminals permit quick connection of a thermostat, a humidifier, an air cleaner, and air conditioning control circuits.

The control has adjustable blower off delay switches. As an added feature, the control has a built-in status indicator and self-test feature. The status indicator flashes to indicate a problem condition and assists the servicer in diagnosis. The component test allows for a complete check of the control circuits in only seconds.

Combustion Air and Ventilation—The 490AAV advanced design allows Schedule 40PVC, PVC-DWV, SDR-21 PVC, SDR-26 PVC (not approved in Canada), ABS-DWV, or ABS-F628 Schedule 40 pipe to bring outdoor air into the furnace for combustion. The extracted heat lowers the temperature of the combustion products to a point typically below 115°F that any of the approved types of pipe can also be used for venting combustion products outside the structure. The combustion-air and vent pipes can terminate through a side wall or through the roof when using 1 of our approved vent termination kits.

Fully-Insulated Casing—Foil-faced insulation in the heat exchanger section cuts the heat loss, and insulation in the blower section reduces noise levels. The casing also has the required openings for left- or right-side connection of gas, electric, drain, and vent connections.

Certifications—The 490AAV units are A.G.A. and C.G.A. design certified for use with natural and propane gases, as well as GAMA efficiency rating certified. The Payne 490AAV meets the oxides of nitrogen (NO_x) emission levels set by South Coast and Bay Area Air Quality Management Districts in California.




- NOTES:** Minimum return-air opening at furnace:
1. For 800 CFM--16-in. round or 14 1/2 x 12-in. rectangle.
 2. For 1200 CFM--20-in. round or 14 1/2 x 19 1/2-in. rectangle.
 3. For 1600 CFM--22-in. round or 14 1/2 x 23 1/4-in. rectangle.
 4. For airflow requirements above 1800 CFM, use both side inlets, a combination of 1 side inlet and the bottom, or the bottom only.

A93023

DIMENSIONS (In.)

UNIT SIZE	A	D	E	SHIP. WEIGHT
024040	17-1/2	15-7/8	16	149
036040	17-1/2	15-7/8	16	152
036060	17-1/2	15-7/8	16	163
048060	17-1/2	15-7/8	16	166
036080	17-1/2	15-7/8	16	172
048080	17-1/2	15-7/8	16	175
060080	21	19-3/8	19-1/2	197
048100	21	19-3/8	19-1/2	193
060100	21	19-3/8	19-1/2	196
060120	24-1/2	22-7/8	23	228

CONCENTRIC VENT








DIMENSIONS (In.)

PART NO.	A*	B	C	D†
KGAVT0501CVT	41-1/8	2	3-1/2	27-1/4
KGAVT0601CVT	46-3/4	3	4-1/2	31-7/8

* Dimension A will change accordingly as dimension D is lengthened or shortened.


† Dimension D may be lengthened to 60 in. maximum. Dimension D may also be shortened by cutting the pipes provided in the kit to 12 in. minimum.

A93294




A93026

RETURN FILTER PLENUM*



A93078

SIDE FILTER RACK*



A80199

*Includes two 20 x 25 x 1 in. washable filters.

*Accepts one 16 x 25 x 1 in. filter.

UNIT SIZE		024040	036040	036060	048060	036080	048080	060080	048100	060100	060120
RATINGS AND PERFORMANCE											
Input Btuh*		40,000	40,000	60,000	60,000	80,000	80,000	80,000	100,000	100,000	120,000
Output Capacity†	Nonweatherized ICS	37,200	37,200	55,800	55,800	74,400	74,400	74,400	93,000	93,000	111,600
AFUE%†	Nonweatherized ICS	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0
Certified Temperature Rise Range °F		30—60	15—45	30—60	20—50	40—70	30—60	20—50	45—75	30—60	40—70
Certified External Static Pressure	Heating	0.10	0.10	0.12	0.12	0.15	0.15	0.15	0.20	0.20	0.20
	Cooling	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
Airflow CFM‡	Heating	740	1205	1260	1300	1160	1285	1785	1315	1690	1720
	Cooling	895	1230	1250	1545	1255	1525	1925/2035	1570	1930/2130	2040/2130
ELECTRICAL											
Unit Volts—Hertz—Phase		115—60—1									
Operating Voltage Range Min—Max††		104—127									
Maximum Unit Amps		6.1	7.3	7.1	9.5	7.6	10.0	14.1	10.2	14.8	14.6
Unit Ampacity†††		8.4	10.0	9.8	12.8	10.4	13.4	18.4	13.5	19.3	19.1
Minimum Wire Size		14	14	14	14	14	14	12	14	12	12
Maximum Wire Length (Ft)**		44	37	38	29	36	28	31	27	30	30
Maximum Fuse Size or Ckt Bkr Amps‡‡		15	15	15	15	15	15	20	15	20	20
Transformer (24v)		40VA									
External Control	Heating	13VA									
Power Available	Cooling	21VA									
Air Conditioning Blower Relay		Standard									
CONTROLS											
Limit Control		SPST									
Heating Blower Control (Off Delay)		Selectable 90, 135, 180, or 225 Sec									
Burners (Monoport)		2	2	3	3	4	4	4	5	5	6
Gas Connection Size		1/2-in. NPT									
GAS CONTROLS											
Gas Valve (Redundant)	Manufacturer	White-Rodgers									
	Min Inlet Pressure (In. wc.)	4.5 (Natural Gas)									
	Max Inlet Pressure (In. wc.)	13.6 (Natural Gas)									
Ignition Device		Hot Surface									
BLOWER DATA											
Direct-Drive Motor HP (PSC)		1/5	1/3	1/3	1/2	1/3	1/2	3/4	1/2	3/4	3/4
Motor Full Load Amps		4.9	5.8	5.8	7.9	5.8	7.9	11.1	7.9	11.1	11.1
RPM (Nominal)—Speeds		1075—3	1075—4								
Blower Wheel Diameter x Width (In.)		10 x 6	10 x 7	10 x 7	11 x 8	10 x 7	11 x 8	11 x 10	11 x 8	11 x 10	11 x 10
Filter Size (In.)—Permanent Washable		(1) 16 x 25 x 1						(1) 20 x 25 x 1		(2)16 x 25 x 1	
FACTORY-AUTHORIZED AND LISTED, DEALER-INSTALLED OPTIONS											
Twinning Kit***		N/A			KGATW0301HSI	N/A	KGATW0301HSI				
Side Filter Rack (Without Filter)***						KGAFR0206ALL					
Return Filter Plenum (With Washable Filters)***		KGARP0201ALL									
Downflow Base (For Combustible Floors With or Without A/C Coil)		KGASB0201ALL									
Vent Termination Kit (Bracket Only for 2-Pipes)						2-in.—KGAVT0101BRA	3-in.—KGAVT0201BRA				
Concentric Vent Termination Kit (Single Exit)						2-in.—KGAVT0501CVT	3-in.—KGAVT0601CVT				
Side-Wall Vent Termination Cover						2-in.—KGAVT0301COV	3-in.—KGAVT0401COV				
Gas Conversion Kit—Natural-to-Propane		KGANP2001ALL									
Gas Conversion Kit—Propane-to-Natural		KGAPN1601ALL									

* Gas input ratings are certified for elevations to 2000 ft. For elevations above 2000 ft, reduce ratings 4 percent for each 1000 ft above sea level. In Canada, derate the unit 10 percent for elevations 2000 to 4500 ft above sea level.

†Capacity and AFUE in accordance with U.S. Government DOE test procedures.

‡ Air delivery above 1800 CFM requires that both sides, a combination of 1 side and bottom, or bottom only of the furnace be used for return air. Where 2 sets of data are listed, the first set is for bottom only return-air supply. The second set is for both sides, or 1 side and bottom return-air supply. A filter is required for each return-air supply.

** Length shown is measured 1 way along wire path between unit and service panel for maximum 2 percent voltage drop.

†† Permissible voltage limits for proper furnace operation.

‡‡ Time-delay fuse is recommended.

*** Upflow application ONLY. See kit Installation Instructions for details.

††† Unit ampacity =125 percent of largest operating component's full load amps plus, 100 percent of all other potential operating component's (EAC, humidifier, etc.) full load amps.

N/A—Not applicable

ICS—Isolated Combustion System

PSC—Permanent Split Capacitor



MEETS DOE RESIDENTIAL CONSERVATION SERVICES PROGRAM STANDARDS.

Before purchasing this appliance, read important energy cost and efficiency information available from your retailer.

MAXIMUM ALLOWABLE PIPE LENGTH (FT)

ALTITUDE ABOVE SEA LEVEL (FT)	UNIT SIZE	TERMINATION TYPE	PIPE DIA (IN.)*	NUMBER OF 90° ELBOWS					
				1	2	3	4	5	6
0 to 2000	024040 036040	2 Pipe or 2-In. Concentric	1	5	NA	NA	NA	NA	NA
			1-1/2	70	70	65	60	60	55
			2	70	70	70	70	70	70
	036060 048060	2 Pipe or 2-In. Concentric	1-1/2	20	15	10	5	NA	NA
			2	70	70	70	70	70	70
	036080 048080 060080	2 Pipe or 2-In. Concentric	1-1/2	10	NA	NA	NA	NA	NA
			2	55	50	35	30	30	20
			2-1/2	70	70	70	70	70	70
	048100 060100	2 Pipe or 3-In. Concentric	2	5	NA	NA	NA	NA	NA
			2-1/2	40	30	20	20	10	NA
			3	70	70	70	70	70	70
	060120	2 Pipe or 3-In. Concentric	2-1/2 one disk	10	NA	NA	NA	NA	NA
			3 one disk	35	30	15	NA	NA	NA
			3† one disk	35	35	35	30	30	30
			3† no disk	70	70	70	70	70	70
2001 to 3000	024040 036040	2 Pipe or 2-In. Concentric	1-1/2	67	62	57	52	52	47
			2	70	70	70	70	70	70
	036060 048060	2 Pipe or 2-In. Concentric	1-1/2	17	12	7	NA	NA	NA
			2	70	67	66	61	61	61
	036080 048080 060080	2 Pipe or 2-In. Concentric	2	49	44	30	25	25	15
			2-1/2	70	70	70	70	70	70
	048100 060100	2 Pipe or 3-In. Concentric	2-1/2	35	26	16	16	6	NA
			3	70	70	70	70	66	61
	060120	2 Pipe or 3-In. Concentric	3 one disk	31	26	12	NA	NA	NA
			3† one disk	31	30	30	25	25	24
			3† no disk	63	62	62	61	61	61
3001 to 4000	024040 036040	2 Pipe or 2-In. Concentric	1-1/2	64	59	54	49	48	43
			2	70	70	70	70	70	70
	036060 048060	2 Pipe or 2-In. Concentric	1-1/2	16	11	6	NA	NA	NA
			2	68	63	62	57	57	56
	036080 048080 060080	2 Pipe or 2-In. Concentric	2	46	41	28	23	22	13
			2-1/2	70	70	70	70	70	70
	048100 060100	2 Pipe or 3-In. Concentric	2-1/2	33	24	15	14	5	NA
			3	70	70	70	66	61	56
	060120	2 Pipe or 3-In. Concentric	3 one disk	29	24	10	NA	NA	NA
			3† one disk	29	28	28	23	22	21
			3† no disk	59	59	58	57	57	56
4001 to 5000†	024040 036040	2 Pipe or 2-In. Concentric	1-1/2	60	55	50	45	44	39
			2	70	70	70	70	70	70
	036060 048060	2 Pipe or 2-In. Concentric	1-1/2	15	10	5	NA	NA	NA
			2	64	59	58	53	52	52
	036080 048080 060080	2 Pipe or 2-in Concentric	2	44	39	26	21	20	11
			2-1/2	70	70	70	70	70	70
	048100 060100	2 Pipe or 3-In. Concentric	2-1/2	31	22	13	12	NA	NA
			3	70	70	67	62	57	52
	060120	2 Pipe or 3-In. Concentric	3† one disk	27	26	26	21	20	19
			3† no disk	56	55	54	53	52	52
5001 to 6000†	024040 036040	2 Pipe or 2-In. Concentric	1-1/2	57	52	47	42	40	35
			2	70	70	70	70	70	70
	036060 048060	2 Pipe or 2-In. Concentric	1-1/2	14	9	NA	NA	NA	NA
			2	60	55	54	49	48	47
	036080 048080 060080	2 Pipe or 2-In. Concentric	2	41	36	23	18	17	8
			2-1/2	70	70	70	70	70	70
	048100 060100	2 Pipe or 3-in Concentric	2-1/2	29	21	12	11	NA	NA
			3	70	67	62	57	52	47
	060120	2 Pipe or 3-In. Concentric	3† one disk	26	24	23	18	17	16
			3† no disk	53	52	50	49	48	47

See notes on page 6.

ALTITUDE ABOVE SEA LEVEL (FT)	UNIT SIZE	TERMINATION TYPE	PIPE DIA (IN.)*	NUMBER OF 90° ELBOWS					
				1	2	3	4	5	6
6001 to 7000‡	024040 036040	2 Pipe or 2-In. Concentric	1-1/2	53	48	43	38	37	32
			2	70	70	68	67	66	64
	036060 048060	2 Pipe or 2-In. Concentric	1-1/2	13	8	NA	NA	NA	NA
			2	57	52	50	45	44	43
	036080 048080 060080	2 Pipe or 2-In. Concentric	2	38	33	21	16	15	6
			2-1/2	70	70	68	67	66	64
	048100 060100	2 Pipe or 3-In. Concentric	2-1/2	27	19	10	9	NA	NA
			3	68	63	58	53	48	43
7001 to 8000‡	024040 036040	2 Pipe or 2-In. Concentric	1-1/2	49	44	39	34	33	28
			2	66	65	63	62	60	59
	036060 048060	2 Pipe or 2-In. Concentric	1-1/2	12	7	NA	NA	NA	NA
			2	53	48	46	41	40	38
	036080 048080 060080	2 Pipe or 2-In. Concentric	2	36	31	19	14	12	NA
			2-1/2	66	65	63	62	60	59
	048100 060100	2 Pipe or 3-In. Concentric	2-1/2	25	17	8	7	NA	NA
			3	63	58	53	48	43	38
8001 to 9000‡	024040 036040	2 Pipe or 2-In. Concentric	1-1/2	46	41	36	31	29	24
			2	62	60	58	56	55	53
	036060 048060	2 Pipe or 2-In. Concentric	1-1/2	11	6	NA	NA	NA	NA
			2	49	44	42	37	35	34
	036080 048080 060080	2 Pipe or 2-In. Concentric	2	33	28	17	12	10	NA
			2-1/2	62	60	58	56	55	53
	048100 060100	2 Pipe or 3-In. Concentric	2-1/2	23	15	7	5	NA	NA
			3	59	54	49	44	39	34
9001 to 10,000‡	024040 036040	2 Pipe or 2-In. Concentric	1-1/2	42	37	32	27	25	20
			2	57	55	53	51	49	47
	036060 048060	2 Pipe or 2-In. Concentric	2	45	40	38	33	31	29
			2	30	25	14	9	7	NA
	036080 048080 060080	2 Pipe or 2-In. Concentric	2-1/2	57	55	53	51	49	47
			2-1/2	21	13	5	NA	NA	NA
	048100 060100	2 Pipe or 3-In. Concentric	3	54	49	44	39	34	29
			3† one disk	18	16	14	9	7	5
	060120	2 Pipe or 3-In. Concentric	3† no disk	39	37	35	33	31	29

* Disk usage—Unless otherwise specified, use perforated disk assembly (factory supplied in loose parts bag). If stated, unsnap 1/2 perforated disk assembly and use shouldered disk half or no disk assembly.

† Wide radius elbow.

‡ Vent sizing for Canadian installations above 4500 ft (1370m) above sea level are subject to acceptance by the local authorities having jurisdiction.

NOTES:

1. Do not use pipe size greater than those specified in table or incomplete combustion, flame disturbance, or flame sense lockout may occur.
2. Size both the combustion-air and vent pipe independently, then use the larger diameter for both pipes.
3. Assume two 45° elbows equal one 90° elbow. Long radius elbows are desirable and may be required in some cases.
4. Elbows and pipe sections within the furnace casing and at the vent termination should not be included in vent length or elbow count.
5. The minimum pipe length is 5 ft for all applications.

IN WINTER DESIGN TEMPERATURE AMBIENT*

UNIT SIZE	WINTER DESIGN TEMP °F	MAXIMUM PIPE DIA (IN.)	INSULATION THICKNESS (IN.)†				
			0	3/8	1/2	3/4	1
024040 and 036040	20	1-1/2	31	56	63	70	70
	0	1-1/2	16	34	39	47	54
	20	1-1/2	9	23	27	34	39
024060 and 036060	20	2	45	70	70	70	70
	0	2	25	51	58	70	70
	20	2	16	36	42	51	60
036080, 048080, and 060080	20	2-1/2	55	70	70	70	70
	0	2-1/2	31	61	69	70	70
	20	2-1/2	20	43	49	61	70
048100 and 060100	20	3	61	70	70	70	70
	0	3	33	65	70	70	70
	20	3	20	45	52	65	70
060120	20	3	70	70	70	70	70
	0	3	40	70	70	70	70
	20	3	26	55	64	70	70

* Pipe length (ft) specified for maximum vent pipe lengths located in unconditioned spaces. Vent pipes located in unconditioned space cannot exceed the total allowable pipe length as specified in maximum allowable pipe length table.

† Insulation thickness based on R value of 3.5 per in.

This unit complies with CAN/CGA 2.3 M86, CAN/CSA C22.2 No. 0-M91, CSA C22.2 No.3-1988 standards.

This appliance is equipped only for altitudes 0 - 2,000 ft (0-610 m) for use with natural gas and propane. A conversion kit, supplied by the manufacturer, shall be used to convert to the alternate fuel or elevation.

This direct-vent, forced-air furnace is for indoor installation in a building constructed on site. For installation in alcove or closet at minimum clearances from combustible material as shown below, minimum front clearance for service is 30 inches (762 mm).

This furnace is for use with schedule-40 PVC, PVC-DWV, or ABS-DWV pipe, and must not be vented in common with other gas-fired appliances. Construction through which vent/air intake pipes may be installed is maximum 24 inches (600 mm), minimum 3/4 inches (19 mm) thickness (including roofing materials).

Special venting system required. In Canada use certified venting system specified by furnace manufacturer. See Installation Instructions provided with furnace. Flue gas temperature 131°F (55°C) vent pressure positive.

MINIMUM CLEARANCE TO COMBUSTIBLE MATERIAL

INCHES	TOP	BOTTOM	SIDES	BACK	FRONT	VENT	
	1	0	0	0	3	0	
	1	++	0	0	3	0	
	1	0+	1*	0	3	0	
	UPFLOW						
	DOWNFLOW						
	HORIZONTAL						

++ For installation on combustible floors only when installed on special base No. KGASB0201ALL.

* Clearance shown is for air inlet and air outlet end.

Horizontal position: Line contact is permissible only between lines formed by intersections of top and two sides of furnace jacket, and building joists, studs, or framing.

+ 120,000 BTU Input Furnaces require 1 inch bottom clearance to combustible materials.

UNIT SIZE	RETURN-AIR SUPPLY	SPEED	EXTERNAL STATIC PRESSURE (In. wc)									
			0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8		
024040	1 side or bottom	High	1075	1040	995	945	895	840	760	670		
		Med-High	850	825	780	740	685	635	560	480		
		Med-Low	740	700	650	620	565	515	455	385		
036040	1 side or bottom	High	1500	1445	1370	1300	1230	1145	1030	910		
		Med-High	1370	1310	1255	1195	1130	1040	950	840		
		Med-Low	1205	1160	1125	1070	1020	940	855	760		
		Low	1035	1005	970	930	885	825	745	675		
036060	1 side or bottom	High	1505	1445	1385	1320	1250	1170	1090	1005		
		Med-High	1415	1360	1295	1235	1170	1100	1010	920		
		Med-Low	1270	1230	1170	1120	1050	985	905	810		
		Low	1080	1045	1005	965	915	855	785	705		
048060	1 side or bottom	High	1700	1695	1640	1580	1545	1450	1380	1310		
		Med-High	1500	1465	1435	1385	1355	1300	1250	1185		
		Med-Low	1325	1295	1265	1230	1190	1150	1105	1050		
		Low	1205	1170	1145	1110	1080	1035	990	950		
036080	1 side or bottom	High	1525	1465	1400	1335	1255	1175	1070	960		
		Med-High	1385	1330	1280	1220	1155	1075	985	880		
		Med-Low	1165	1150	1115	1060	1005	940	865	780		
		Low	1000	985	950	905	860	790	725	655		
048080	1 side or bottom	High	1750	1685	1635	1575	1525	1445	1380	1310		
		Med-High	1495	1455	1405	1355	1305	1250	1185	1120		
		Med-Low	1310	1260	1225	1170	1125	1095	1040	980		
		Low	1135	1105	1075	1040	995	995	910	860		
060080	bottom only	High	2200	2175	2085	2025	1925	1820	1735	1635		
		Med-High	2100	2025	1945	1865	1785	1700	1620	1540		
		Med-Low	1815	1760	1720	1670	1620	1550	1480	1405		
		Low	1560	1555	1515	1460	1435	1390	1340	1270		
060080	both sides or 1 side and bottom	High	2360	2280	2210	2130	2035	1960	1875	1790		
		Med-High	1965	1925	1870	1830	1760	1710	1670	1575		
048100	1 side or bottom	High	1740	1705	1660	1615	1570	1500	1425	1355		
		Med-High	1500	1470	1445	1410	1375	1330	1280	1210		
		Med-Low	1340	1315	1300	1270	1235	1200	1140	1095		
		Low	1195	1175	1165	1130	1100	1070	1030	975		
060100	bottom only	High	2250	2175	2090	2020	1930	1855	1760	1670		
		Med-High	2020	1950	1900	1840	1790	1710	1640	1545		
		Med-Low	1725	1690	1660	1630	1575	1520	1460	1370		
		Low	1490	1480	1460	1440	1380	1340	1295	1230		
060100	both sides or 1 side and bottom	High	2360	2315	2265	2200	2130	2055	1965	1890		
		Med-High	1960	1940	1930	1900	1850	1800	1740	1660		
		060120	bottom only	High	2350	2250	2160	2070	2000	1885	1790	1635
				Med-High	2100	2015	1955	1875	1810	1710	1650	1540
Med-Low	1770			1720	1675	1620	1575	1515	1450	1365		
Low	1545			1520	1465	1415	1365	1325	1265	1185		
060120	both sides or 1 side and bottom	High	2435	2360	2285	2220	2130	2050	1965	1875		
		Med-High	2040	2000	1950	1905	1835	1790	1725	1650		

*Air delivery above 1800 CFM requires that both sides, a combination of 1 side and bottom, or bottom only of the furnace be used for return air.

A filter is required for each return-air supply.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

UNIT MUST BE INSTALLED IN ACCORDANCE
WITH INSTALLATION INSTRUCTIONS

Cancels: PDS 490A.40.1P



Heating & Cooling