

VRF Indoor Unit 45VMF048A--3—4-Way Cassette



Submittal Data

Job Name _____ Location _____
Tag _____



STANDARD FEATURES

- Delivers air in all four directions
- Knock out for OA opening
- Louver control (fixed or swing)
- Seven fan speeds
- Built-in condensate lift mechanism
- Built in EEV (Electronic Expansion Valve) for installation ease


INDOOR UNIT MODEL		45VMF048A--3
PERFORMANCE		
Total Cooling Capacity	Btu/h	48,000
Total Heating Capacity	Btu/h	54,000
Airflow Rates	CFM	1207/1146/1085/ 1024/962/901/840
Sound Pressure Levels	dBA	55/54.8/54.2/54/ 52.8/51.6/50
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Indoor Fan Motor Rated Motor (Output)	W	125
Minimum Circuit Amps (MCA)	A	2.20
Maximum Overcurrent Protection	A	15.0
Motor Type		DC

PHYSICAL DATA		
Pipe Connection Size - Liquid	in.	3/8 (OD)
Pipe Connection Size - Suction	in.	5/8 (OD)
Pipe Connection Size - Drain	in.	1 (OD)
Refrigerant		R-454B
Unit Width	in.	33-1/16
Unit Height	in.	11-5/16
Unit Depth	in.	33-1/16
Unit Net Weight	lbs.	61.7
Panel Width	in.	37-3/8
Panel Height	in.	3
Panel Depth	in.	37-3/8
Panel Net Weight	lbs.	12.8

ACCESSORIES

- ☐ Wireless Remote Controller 45VM900001
- ☐ Wired Remote Controller - Non-Prog. 45VM900002
- ☐ Grille 45VM0001---

DIMENSIONAL DRAWING INDOOR UNIT 4-WAY CASSETTE 45VMF048---3



Dimensions are shown in mm (in)

A	B	C	D	E	F
288 (11-5/16)	190 (7-1/2)	103 (4-1/16)	56.5 (2-1/4)	$\Phi 15.9$ (5/8)	$\Phi 9.52$ (3/8)

