

Ducted Heat Pump Ductless System

Indoor Model: 40MBQB24D--3



Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



Performance
SERIES

STANDARD FEATURES

- Built-in condensate pump
- Modes: Cool, Heat, Dry, Fan, Auto
- Timer
- One touch memory
- Follow me
- 46°F Heating Mode (Heating Setback)

CONTROL FEATURES

- Wireless remote control (standard)
- Wired remote control (standard)

System	Size	24	
	Indoor Model	40MBQB24D--3	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	0.62
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Standard	
Operating Range	Cooling Indoor DB Min -Max	°F(°C)	63~90 (17~32)
	Heating Indoor DB Min -Max	°F(°C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)
	Pipe Connection Size - Suction	in (mm)	5/8 (16)

Indoor Coil	Face Area	Sq. Ft.	2.00
	No. Rows		4
	Fins per inch		16
	Circuits		6
Indoor	Unit Width	in (mm)	36.22 (920)
	Unit Height	in (mm)	10.63 (270)
	Unit Depth	in (mm)	25 (635)
	Net Weight	lbs (kg)	57.32 (26)
	Number of Fan Speeds		3
	Airflow (lowest to highest)	CFM	590/650/810
	Sound Pressure (lowest to highest)	dB(A)	43/45/48
	Max Static Pressure	In.WG.	0.4


Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.

Compatibility Table

Indoor Unit	40MBQB24D--3
Outdoor Unit	38MAQB24R--3
	38MAQB24---3
	38MGQF36---3
	38MGQF48---3

Construction View

Indoor Model: 40MBQB24D--3



Unit Width	in (mm)	36.22 (920)
Unit Height	in (mm)	10.63 (270)
Unit Depth	in (mm)	25 (635)
Net Weight	lbs (kg)	57.32 (26)

