



bryant**Bryant**
Air ConditioningIndianapolis, IN
City of Industry, CA**MID-EFFICIENCY
DOWNFLOW/HORIZONTAL
INDUCED-COMBUSTION FURNACE****Model 373L**Sizes 035
thru 110

A90160

DOWNFLOW

A90171

HORIZONTAL

This is our special induced-combustion furnace manufactured to meet the requirements of builders and budget minded consumers. Lower cost with the same quality and efficiency you expect.

FEATURES

EFFICIENCY—The 373L Induced-Combustion Gas Furnace provides the efficiency customers want with 80% AFUE.

HOT SURFACE IGNITION—No pilot to waste gas with this field proven ignition system.

ALUMINIZED HEAT EXCHANGER—The patented four-pass heat exchanger is made of aluminized steel and backed by a 10-year Limited Warranty.

INTELLIGENT CONTROL BOARD—The 373L Furnace has an intelligent control board that monitors the operation of the furnace. This control board also has a self-test feature that enables the servicing technician to verify operation of the board itself, the inducer, the hot-surface ignitor, both high- and low-speed blower operation, and the humidifier.


40-INCH HEIGHT—The 373L is assembled in a cabinet only 40 inches tall. This simplifies installation in alcoves, attics, basements (ideal for short basement), closets, and utility rooms, especially with a taller high-efficiency cooling coil.

MULTI-POISED DOWNFLOW OR HORIZONTAL—Our furnace can be used in a downflow, horizontal-left, or horizontal-right configuration.

CABINET—An embossed galvanized steel with a clear coating that surpasses our 200-hour high humidity test. It provides superior rust and humidity protection.

PATENTED DRAFT SAFEGUARD—Our induced-combustion furnace has a patented draft safeguard switch. The safeguard switch will stop furnace operation if the vent system becomes blocked or is not operating properly. An exclusive with our furnaces.

EASY INSTALLATION—The Model 373L has many features that make installation easier: left or right gas and electrical connections, blower speed selector, matching coil sizes, accessory low-voltage connections, and many more.




A88324

DIMENSIONS (In Inches)

Size	A	D	E	Vent Conn*	Ship. Wt
024035	14-3/16	12-9/16	12-11/16	4	118
036035	14-3/16	12-9/16	12-11/16	4	121
024055	14-3/16	12-9/16	12-11/16	4	135
036055	14-3/16	12-9/16	12-11/16	4	139
036075	17-1/2	15-7/8	16	4	146
048075	17-1/2	15-7/8	16	4	146
048090	17-1/2	15-7/8	16	4	163
060090	21	19-3/8	19-1/2	4	171
060110	24-1/2	22-7/8	23	5	182


*Refer to the furnace installation instructions for proper venting procedures.

ACCESSORY DOWNFLOW SUBBASE



A88207

Disassembled



A88206

Assembled

DIMENSIONAL DATA

Furnace Width	Plenum Opening*		Framed Floor Hole		Hole No. for Width Adjustment
	A	B	C	D	
14-3/16	11-13/16	19	13-7/16	20-3/8	4
17-1/2	15-1/8	19	16-3/4	20-3/8	3
21	18-5/8	19	20-1/4	20-3/8	2
24-1/2	22-1/8	19	23-3/4	20-3/8	1

*The plenum should be constructed 1/4-inch smaller in width and depth than the plenum dimensions shown above.

SPECIFICATIONS

SIZE	024035	036035	024055	036055	036075	048075	048090	060090	060110
RATINGS AND PERFORMANCE									
Input Btuh*	46,000	46,000	69,000	69,000	92,000	92,000	115,000	115,000	138,000
Capacity† Nonweatherized (ICS)‡	37,000	37,000	56,000	56,000	75,000	75,000	94,000	94,000	112,000
AFUE%† Nonweatherized (ICS)‡	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2
California Seasonal Efficiencies (CSE)	75.2	73.0	76.6	74.9	76.0	75.5	76.5	75.0	75.6
Certified Temperature Rise Range °F	35—65	15—45	55—85	30—60	50—80	40—70	50—80	40—70	50—80
Certified External Static Pressure Heat/Cool	0.10/0.50	0.10/0.50	0.12/0.50	0.12/0.50	0.15/0.50	0.15/0.50	0.20/0.50	0.20/0.50	0.20/0.50
Airflow CFM	Heating	720	1170	660	1200	1155	1350	1400	1735
	Cooling	895	1215	930	1300	1395	1580	1595	2055
ELECTRICAL									
Unit Volts—Hertz—Phase	115—60—1								
Operating Voltage Range Min—Max	104—127								
Maximum Unit Ampacity	6.6	8.1	6.7	8.4	9.2	10.2	10.0	13.1	14.3
Maximum Wire Length Feet	53	44	53	43	40	35	36	44	40
Minimum Wire Size	14							12	
Maximum Fuse Size	15							20	
Transformer (24-V)	40VA								
External Control Heating	12VA								
Power Available Cooling	35VA								
Air-Conditioning Blower Relay	Standard								
CONTROLS									
Limit Control	SPST								
Heating Blower Control	Solid-State Time Operation								
Burners (Monoport)	2	2	3	3	4	4	5	5	6
Gas Connection Size	1/2-inch NPT								
GAS CONTROLS									
Gas Valve (Redundant)	White-Rodgers								
Min Inlet Pressure	4.5 inches wc (Natural Gas)								
Max Inlet Pressure	13.6 inches wc								
Main Burner Ignitor	Hot-Surface								
BLOWER DATA									
Direct-Drive Motor HP—Type	1/5—PSC	1/3—PSC	1/5—PSC	1/3—PSC	1/3—PSC	1/2—PSC	1/2—PSC	3/4—PSC	3/4—PSC
Motor Full Load Amps	3.4	5.8	3.4	5.8	5.8	7.9	7.9	11.1	11.1
RPM (Nominal)—Speeds	1075—4	1075—4	1075—4	1075—4	1075—4	1075—4	1075—4	1075—4	1075—4
Blower Wheel Dia x Width	10 x 6	10 x 6	10 x 6	10 x 6	10 x 7	10 x 8	10 x 8	11 x 10	11 x 10
Filter Size—Permanent Washable	(2) 16 x 20 x 1								
FACTORY-AUTHORIZED DEALER-INSTALLED ACCESSORIES									
Accessory Downflow Subbase	313512-701								
Gas Conversion Kit—Natural-to-Propane	310318-701								
Gas Conversion Kit—Propane-to-Natural	310325-701								
Duct-Flange Kit	305809-701								

*Gas inputs shown are for elevations up to 2000 feet. For elevations above 2000 feet, input should be reduced at the rate of 4% for each 1000 feet above sea level. Refer to National Fuel Gas Code Table F4.


†Capacity in accordance with U.S. Government DOE test procedures. California Seasonal Efficiencies based on California-specified procedures.

‡Isolated Combustion System (ICS)




MEETS DOE RESIDENTIAL CONSERVATION SERVICES PROGRAM STANDARDS.

Before purchasing this appliance, read important energy cost and efficiency information available from your retailer.



A82172

**Duct Flanges
(Accessory)**



A82173

**Filter Retainers
(Field Supplied)**

AIR DELIVERY—Cfm (With Filters)

Furnace Size	Blower Motor HP	Speed	External Static Pressure Inches wc							
			0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8
024035	1/5 PSC	High	1100	1050	1000	950	895	840	760	650
		Med-High	860	820	790	760	710	655	580	480
		Med-Low	720	685	650	615	560	505	440	360
		Low	615	585	555	510	460	400	340	250
036035	1/3 PSC	High	—	1400	1355	1300	1215	1130	1050	960
		Med-High	—	1295	1255	1190	1115	1045	975	890
		Med-Low	1170	1150	1115	1060	1005	950	880	800
		Low	1020	1010	980	945	895	850	785	715
024055	1/5 PSC	High	—	—	1010	975	930	885	825	745
		Med-High	—	815	800	765	725	685	620	550
		Med-Low	—	660	645	620	590	545	480	415
		Low	590	570	545	510	470	405	360	295
036055	1/3 PSC	High	—	1490	1425	1365	1300	1240	1175	1100
		Med-High	—	1345	1300	1255	1200	1140	1075	1000
		Med-Low	1200	1180	1140	1100	1060	1015	960	895
		Low	1020	1000	985	950	915	880	835	780
036075	1/3 PSC	High	—	1575	1515	1455	1395	1325	1230	1120
		Med-High	—	1380	1340	1285	1230	1165	1095	1005
		Med-Low	1165	1145	1130	1090	1055	1005	940	870
		Low	965	955	940	910	885	840	785	705
048075	1/2 PSC	High	1855	1765	1710	1665	1580	1570	1410	1310
		Med-High	1595	1570	1530	1485	1410	1355	1280	1200
		Med-Low	1355	1345	1305	1270	1220	1170	1110	1025
		Low	1170	1170	1140	1110	1075	1025	965	890
048090	1/2 PSC	High	1930	1850	1770	1685	1595	1505	1405	1305
		Med-High	1685	1630	1580	1525	1445	1370	1285	1195
		Med-Low	1425	1400	1370	1325	1280	1225	1155	1070
		Low	1250	1240	1210	1170	1150	1095	1035	950
060090	3/4 PSC	High	2235	2185	2110	2030	1950	1835	1700	1540
		Med-High	1995	1970	1915	1845	1765	1680	1545	1415
		Med-Low	1735	1735	1675	1625	1565	1480	1370	1265
		Low	1510	1500	1485	1455	1400	1320	1230	1130
060110	3/4 PSC	High	—	2250	2190	2130	2055	1960	1875	1760
		Med-High	—	2000	1960	1910	1850	1785	1710	1615
		Med-Low	1700	1690	1670	1650	1610	1560	1490	1435
		Low	1480	1480	1480	1460	1430	1380	1320	1255

—Indicates unstable operating conditions.

MINIMUM CLEARANCES (In Inches From Combustible Materials)

Sizes	035 and 055	075 thru 110
DOWNFLOW		
Sides—Single-Wall Vent	1	0
Type B-1 Double-Wall Vent	0	0
Back	0	0
Top	1	1
Front—Single-Wall Vent	6	6
Type B-1 Double-Wall Vent	3	3
Vent—Single-Wall	6	6
Type B-1 Double-Wall	1	1

NOTES:

1. Provide 30-inch front clearance for servicing. An open door in front of the furnace can meet this requirement.
2. A minimum clearance of 3 inches must be provided in front of the furnace for combustion air and proper operation.

Sizes	035 and 055	075 thru 110
HORIZONTAL (In Alcove/Attic)		
Sides*	1	0
Back	0	0
Top—Single-Wall	1	1
Type B-1 Double-Wall	1	1
Front	18	18
Vent—Single-Wall	6	6
Type B-1 Double-Wall	1	1
HORIZONTAL (In Closet)		
Sides*	1	1
Back	3	3
Top—Single-Wall	2	2
Type B-1 Double-Wall	2	2
Front—Single-Wall Vent	6	6
Type B-1 Double-Wall Vent	3	3
Vent—Single-Wall	6	6
Type B-1 Double-Wall	1	1

*Indicates supply or return sides when furnace is in the horizontal position.



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

UNIT MUST BE INSTALLED IN ACCORDANCE
WITH INSTALLATION INSTRUCTIONS