

24ANB6

Infinity® Air Conditioner with Puron® Refrigerant
1–1/2 to 5 Nominal Tons (Size 18–60)



Product Data



Carrier's Air Conditioners with Puron® refrigerant provide a collection of features unmatched by any other family of equipment. The 24ANB6 has been designed utilizing Carrier's Puron refrigerant. The environmentally sound refrigerant allows you to make a responsible decision in the protection of the earth's ozone layer.

This product has been designed and manufactured to meet Energy Star® criteria for energy efficiency when matched with appropriate coil components. Refer to the combination ratings in the Product Data for system combinations that meet Energy Star® guidelines.

NOTE: Ratings contained in this document are subject to change at any time. Always refer to the AHRI directory (www.ahridirectory.org) for the most up-to-date ratings information.

INDUSTRY LEADING FEATURES / BENEFITS

Efficiency

- 14 - 16 SEER / 11.0- 13.5 EER
- Microtube Technology™ refrigeration system
- Indoor air quality accessories available

Sound

- Sound level as low as 66 dBA
- Compressor sound blanket standard

Comfort

- System supports Infinity Control or standard thermostat controls

Reliability

- Puron® refrigerant - environmentally sound, won't deplete the ozone layer and low lifetime service cost.
- Scroll compressor
- Internal pressure relief valve
- Internal thermal overload
- Filter drier
- High and low pressure switches
- Balanced refrigeration system for maximum reliability

Durability

WeatherArmor™ protection package:

- Solid, durable sheet metal construction
- Louvered coil guard
- Baked-on, complete outer coverage, powder paint

Applications

- Long-line - up to 250 feet (76.20 m) total equivalent length, up to 200 feet (60.96 m) condenser above evaporator, or up to 80 ft. (24.38 m) evaporator above condenser (See Longline Guide for more information.)
- Low ambient (down to -20°F/-28.9°C)) with accessory kit

MODEL NUMBER NOMENCLATURE

1	2	3	4	5	6	7	8	9	10	11	12	13
N	N	A	A	A/N	N	N	N	A/N	A/N	A/N	N	N
2	4	A	N	B	6	2	4	A	0	0	3	0
Product Series	Product Family	Tier	Major Series	SEER	Cooling Capacity	Variations	Open	Open	Voltage	Minor Series		
24=AC	A=RES AC	N=Infinity Series	B=Puron	6=16 SEER (Nominal)		A=Standard	0=Not Defined	0=Not Defined	3=208/230-1	0, 1, 2...		



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.



This product has been designed and manufactured to meet Energy Star criteria for energy efficiency when matched with appropriate coil components. However, proper refrigerant charge and proper air flow are critical to achieve rated capacity and efficiency. Installation of this product should follow all manufacturing refrigerant charging and air flow instructions. **Failure to confirm proper charge and air flow may reduce energy efficiency and shorten equipment life.**



STANDARD FEATURES

Feature	18	24	30	36	42	48	60
Puron Refrigerant	X	X	X	X	X	X	X
Maximum SEER *	16.0	16.0	16.5	16.5	16.0	16.0	16.0
Scroll Compressor	X	X	X	X	X	X	X
Field Installed Filter Drier	X	X	X	X	X	X	X
Front Seating Service Valves	X	X	X	X	X	X	X
Internal Pressure Relief Valve	X	X	X	X	X	X	X
Internal Thermal Overload	X	X	X	X	X	X	X
Long Line capability	X	X	X	X	X	X	X
Low Ambient capability with Kit	X	X	X	X	X	X	X
High Pressure Switch	X	X	X	X	X	X	X
Low Pressure Switch	X	X	X	X	X	X	X
Compressor Sound Blanket	X	X	X	X	X	X	X
Louvered Coil Guard	X	X	X	X	X	X	X

*Based on tested combinations

X = Standard

PHYSICAL DATA

UNIT SIZE SERIES	18-30	24-30	30-30	36-30	42-30	48-30	60-30
Operating Weight lb (Kg)	184 (83)	186 (84)	193 (88)	209 (95)	261 (118)	303 (137)	334 (151)
Shipping Weight lb (Kg)	217 (98)	219 (99)	227 (103)	250 (113)	303 (137)	346 (157)	380 (172)
Compressor Type	Scroll						
REFRIGERANT	R-410A						
Control	TXV (R-410A Hard Shutoff)						
Charge lb (Kg)	5.25 (2.38)	6.00 (2.72)	6.81 (3.09)	7.00 (3.18)	8.62 (3.91)	13.00 (5.9)	14.50 (6.58)
COND FAN	Propeller Type, Direct Drive						
Air Discharge	Vertical						
Air Qty (CFM)	2233	2614	2614	3223	3810	4046	4046
Motor HP	1/12	1/10	1/10	1/12	1/5	1/4	1/4
Motor RPM	800	800	800	800	800	800	800
COND COIL							
Face Area (Sq ft)	15.07	15.07	17.22	17.58	25.12	25.12	30.14
Fins per In.	25	25	25	25	25	20	20
Rows	1	1	1	1	1	2	2
Circuits	3	4	4	4	6	7	8
VALVE CONNECT. (In. ID)							
Vapor	3/4	3/4	3/4	7/8	7/8	7/8	7/8
Liquid	3/8	3/8	3/8	3/8	3/8	3/8	3/8
REFRIGERANT TUBES (In. OD)							
Rated Vapor*	3/4			7/8			1-1/8
Max Liquid Line	3/8"						

*Units are rated with 25 ft (7.6 m) of lineset length. See Vapor Line Sizing and Cooling Capacity Loss table when using other sizes and lengths of lineset.

NOTE: See unit Installation Instruction for proper installation.

REFRIGERANT PIPING LENGTH LIMITATIONS

Liquid Line Sizing and Maximum Total Equivalent Lengths† for Cooling Only Systems with Puron® Refrigerant:

The maximum allowable length of a residential split system depends on the liquid line diameter and vertical separation between indoor and outdoor units.

See Table below for liquid line sizing and maximum lengths :

Maximum Total Equivalent Length Outdoor Unit BELOW Indoor Unit

Size	Liquid Line Connection	Liquid Line Diam. w/ TXV	AC with Puron Refrigerant Maximum Total Equivalent Length†: Outdoor unit BELOW Indoor Vertical Separation ft (m)								
			0-5 (0-1.5)	6-10 (1.8-3.0)	11-20 (3.4-6.1)	21-30 (6.4-9.1)	31-40 (9.4-12.2)	41-50 (12.5-15.2)	51-60 (15.5-18.3)	61-70 (18.6-21.3)	71-80 (21.6-24.4)
018 AC with Puron	3/8	1/4	150	150	125	100	100	75	--	--	--
		5/16	250*	250*	250*	250*	250*	250*	250*	225*	150
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
024 AC with Puron	3/8	1/4	75	75	75	50	50	--	--	--	--
		5/16	250*	250*	250*	250*	250*	225*	175	125	100
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
030 AC with Puron	3/8	1/4	30	--	--	--	--	--	--	--	--
		5/16	175	225*	200	175	125	100	75	--	--
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
036 AC with Puron	3/8	5/16	175	150	150	100	100	100	75	--	--
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
042 AC with Puron	3/8	5/16	125	100	100	75	75	50	--	--	--
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	150
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	150
048 AC with Puron	3/8	3/8	250*	250*	250*	250*	250*	250*	230	160	--
060 AC with Puron	3/8	3/8	250*	250*	250*	225*	190	150	110	--	--

* Maximum actual length not to exceed 200 ft (61 m)

† Total equivalent length accounts for losses due to elbows or fitting. See the Residential Piping and Long Line Guideline for details.

-- = outside acceptable range

Maximum Total Equivalent Length Outdoor Unit ABOVE Indoor Unit

Size	Liquid Line Connection	Liquid Line Diam. w/ TXV	AC with Puron Refrigerant Maximum Total Equivalent Length†: Outdoor unit ABOVE Indoor Vertical Separation ft (m)							
			25 (7.6)	26-50 (7.9-15.2)	51-75 (15.5-22.9)	76-100 (23.2-30.5)	101-125 (30.8-38.1)	126-150 (38.4-45.7)	151-175 (46.0-53.3)	176-200 (53.6-61.0)
018 AC with Puron	3/8	1/4	175	250*	250*	250*	250*	250*	250*	250*
		5/16	250*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
024 AC with Puron	3/8	1/4	100	125	175	200	225*	250*	250*	250*
		5/16	250*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
030 AC with Puron	3/8	1/4	30	--	--	--	--	--	--	--
		5/16	250*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
036 AC with Puron	3/8	5/16	225*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
042 AC with Puron	3/8	5/16	175	200	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
048 AC with Puron	3/8	3/8	250*	250*	250*	250*	250*	250*	250*	250*
060 AC with Puron	3/8	3/8	250*	250*	250*	250*	250*	250*	250*	250*

* Maximum actual length not to exceed 200 ft (61 m)

† Total equivalent length accounts for losses due to elbows or fitting. See the Residential Piping and Long Line Guideline for details.

-- = outside acceptable range

24ANB6

REFRIGERANT CHARGE ADJUSTMENTS

Liquid Line Size	Puron Charge oz/ft (g/m)
3/8	0.60 (17.74) (Factory charge for lineset = 9 oz / 266.16 g)
5/16	0.40 (11.83)
1/4	0.27 (7.98)

Units are factory charged for 15 ft (4.6 m) of 3/8" liquid line. The factory charge for 3/8" lineset 9 oz. When using other length or diameter liquid lines, charge adjustments are required per the chart above.

Charging Formula:

$[(\text{Lineset oz/ft} \times \text{total length}) - (\text{factory charge for lineset})] = \text{charge adjustment}$

Example 1: System has 15 ft of line set using existing 1/4" liquid line. What charge adjustment is required?

Formula: $(.27 \text{ oz/ft} \times 15\text{ft}) - (9 \text{ oz}) = (-4.95) \text{ oz.}$

Net result is to remove 4.95 oz of refrigerant from the system

Example 2: System has 45 ft of existing 5/16" liquid line. What is the charge adjustment?

Formula: $(.40 \text{ oz/ft.} \times 45\text{ft}) - (9 \text{ oz.}) = 9 \text{ oz.}$

Net result is to add 9 oz of refrigerant to the system

LONG LINE APPLICATIONS

An application is considered Long Line, when the refrigerant level in the system requires the use of accessories to maintain acceptable refrigerant management for systems reliability. See Accessory Usage Guideline table for required accessories. Defining a system as long line depends on the liquid line diameter, actual length of the tubing, and vertical separation between the indoor and outdoor units.

For Air Conditioner systems, the chart below shows when an application is considered Long Line.

AC WITH PURON® REFRIGERANT LONG LINE DESCRIPTION ft (m)

Beyond these lengths, long line accessories are required

Liquid Line Size	Units On Same Level	Outdoor Below Indoor	Outdoor Above Indoor
1/4	No accessories needed within allowed lengths	No accessories needed within allowed lengths	175 (53.3)
5/16	120 (36.6)	50 (15.2) vertical or 120 (36.6) total	120 (36.6)
3/8	80 (24.4)	35 (10.7) vertical or 80 (24.4) total	80 (24.4)

Note: See Long Line Guideline for details

VAPOR LINE SIZING AND COOLING CAPACITY LOSS

Acceptable vapor line diameters provide adequate oil return to the compressor while avoiding excessive capacity loss. The suction line diameters shown in the chart below are acceptable for AC systems with Puron refrigerant:

Vapor Line Sizing and Cooling Capacity Losses — Puron® Refrigerant 1-Stage Air Conditioner Applications

Unit Nominal Size (Btuh)	Maximum Liquid Line Diameters (In. OD)	Vapor Line Diameters (In. OD)	Cooling Capacity Loss (%)								
			Total Equivalent Line Length ft. (m)								
			26–50 (7.9–15.2)	51–80 (15.5–24.4)	81–100 (24.7–30.5)	101–125 (30.8–38.1)	126–150 (38.4–45.7)	151–175 (46.0–53.3)	176–200 (53.6–61.0)	201–225 (61.3–68.6)	226–250 (68.9–76.2)
018 1 Stage AC with Puron	3/8	1/2	1	2	3	5	6	7	8	9	11
		5/8	0	1	1	1	2	2	2	3	3
		3/4	0	0	0	0	1	1	1	1	1
024 1 Stage AC with Puron	3/8	5/8	0	1	2	2	3	3	4	5	5
		3/4	0	0	1	1	1	1	1	2	2
		7/8	0	0	0	0	0	1	1	1	1
030 1 Stage AC with Puron	3/8	5/8	1	2	3	3	4	5	6	7	8
		3/4	0	0	1	1	1	2	2	2	3
		7/8	0	0	0	0	1	1	1	1	1
036 1 Stage AC with Puron	3/8	5/8	1	2	4	5	6	8	9	10	12
		3/4	0	1	1	2	2	3	3	4	4
		7/8	0	0	0	1	1	1	1	2	2
042 1 Stage AC with Puron	3/8	3/4	0	1	2	2	3	4	4	5	6
		7/8	0	0	1	1	1	2	2	2	3
		1 1/8	0	0	0	0	0	0	0	0	0
048 1 Stage AC with Puron	3/8	3/4	0	1	2	3	4	5	5	6	7
		7/8	0	0	1	1	2	2	2	3	3
		1 1/8	0	0	0	0	0	0	0	1	1
060 1 Stage AC with Puron	3/8	3/4	1	2	4	5	6	7	9	10	11
		7/8	0	1	2	2	3	4	4	5	5
		1 1/8	0	0	0	1	1	1	1	1	1

Applications in this area may be long line and may have height restrictions. See the *Residential Piping and Long Line Guideline*.

ACCESSORY USAGE GUIDELINE

ACCESSORY	REQUIRED FOR LOW-AMBIENT COOLING APPLICATIONS (Below 55°F / 12.8°C)	REQUIRED FOR LONG LINE APPLICATIONS* (Over 80 ft. / 24.38 m)
Compressor Start Assist Capacitor and Relay	Yes	Yes
Crankcase Heater	Yes	Yes
Evaporator Freeze Thermostat	Yes (For non-Infinity systems only)	No
Liquid Line Solenoid Valve	No	See Long-Line Application Guideline
Low-ambient Pressure Switch	Yes (For non-Infinity system only)	No
Support Feet	Recommended	No
Thermal Expansion Valve (TXV) Hard Shutoff	Yes	Yes
Winter Start Control	Yes (For non-Infinity systems only)	No

* For tubing line sets between 80 and 200 ft. (24.38 and 60.96 m) and/or 20 ft. (6.09 m) vertical differential, refer to Residential Split-System Longline Application Guideline.

Accessory Description and Usage (Listed Alphabetically)

1. Compressor Start Assist - Capacitor and Relay

Start capacitor and relay gives a "hard" boost to compressor motor at each start up.

Usage Guideline:

Required for reciprocating compressors in the following applications:

- Long line
- Low ambient cooling
- Hard shut off expansion valve on indoor coil
- Liquid line solenoid on indoor coil

Required for single-phase scroll compressors in the following applications:

- Long line
- Low ambient cooling

Suggested for all compressors in areas with a history of low voltage problems.

2. Compressor Start Assist — PTC Type

Solid state electrical device which gives a "soft" boost to the compressor at each start-up.

Usage Guideline:

Suggested in installations with marginal power supply.

3. Crankcase Heater

An electric resistance heater which mounts to the base of the compressor to keep the lubricant warm during off cycles. Improves compressor lubrication on restart and minimizes the chance of liquid slugging.

Usage Guideline:

- Required in low ambient cooling applications.
- Required in long line applications.
- Suggested in all commercial applications.

4. Cycle Protector

The cycle protector is designed to prevent compressor short cycling. This control provides an approximate 5-minute delay after power to the compressor has been interrupted for any reason, including power outage, protector control trip, thermostat jiggling, or normal cycling.

5. Evaporator Freeze Thermostat

An SPST temperature-actuated switch that stops unit operation when evaporator reaches freeze-up conditions.

Usage Guideline:

Required when low ambient kit has been added.

6. Low-Ambient Pressure Switch Kit

A long life pressure switch which is mounted to outdoor unit service valve. It is designed to cycle the outdoor fan motor in order to maintain head pressure within normal operating limits (approximately 100 psig to 225 psig). The control will maintain working head pressure at low-ambient temperatures down to 0°F (-18°C) when properly installed.

Usage Guideline:

A Low-Ambient Pressure Switch or MotorMaster® Low-Ambient Controller must be used when cooling operation is used at outdoor temperatures below 55°F (12.8°C).

7. Outdoor Air Temperature Sensor

Designed for use with Carrier Thermostats listed in this publication. This device enables the thermostat to display the outdoor temperature. This device also is required to enable special thermostat features such as auxiliary heat lock out.

Usage Guideline:

Suggested for all Carrier thermostats listed in this publication.

8. Support Feet

Four stick-on plastic feet that raise the unit 4 in. (101.6 mm) above the mounting pad. This allows sand, dirt, and other debris to be flushed from the unit base, minimizing corrosion.

Usage Guideline:

Suggested in the following applications:

- Coastal installations.
- Windy areas or where debris is normally circulating.
- Rooftop installations.
- For improved sound ratings.

9. Thermostatic Expansion Valve (TXV)

A modulating flow-control valve which meters refrigerant liquid flow rate into the evaporator in response to the superheat of the refrigerant gas leaving the evaporator.

Kit includes valve, adapter tubes, and external equalizer tube. Hard shut off types are available.

NOTE: When using a hard shut off TXV with single phase reciprocating compressors, a Compressor Start Assist Capacitor and Relay is required.

Usage Guideline:

- Required to achieve AHRI ratings in certain equipment combinations. Refer to combination ratings.
- Hard shut off TXV or LLS required in air conditioner long line applications.
- Required for use on all zoning systems.

Accessory Description and Usage (Listed Alphabetically) (Continued)

10. Time-Delay Relay

An SPST delay relay which briefly continues operation of indoor blower motor to provide additional cooling after the compressor cycles off.

NOTE: Most indoor unit controls include this feature. For those that do not, use the guideline below.

Usage Guideline:

For improved efficiency ratings for certain combinations of indoor and outdoor units. Refer to AHRI Unitary Directory.

12. Winter Start Control

This control is designed to alleviate nuisance opening of the low-pressure switch by bypassing it for the first 3 minutes of operation.

ACCESSORIES

KIT NUMBER	KIT NAME	18–30	24–30	30–30	36–30	42–30	48–30	60–30
KAACH1701AAA	CRANKCASE HTR	X	X	X	X			
KAACH1601AAA	CRANKCASE HTR					X		
STANDARD	CRANKCASE HTR						S	S
KAFT0101AAA	FREEZE THERMOSTAT	X	X	X	X	X	X	X
KSAS2701AAA	HARD START (CAP/RELAY)	X	X	X	X	X	X	X
KSALA0301410	LOW–AMBIENT PRESSURE SWITCH	X	X	X	X	X	X	X
KAACS0201PTC	PTC START ASSIST	X	X	X	X	X	X	X
KAALS0201LLS	SOLENOID VALVE	X	X	X	X	X	X	X
KSASF0101AAA	SUPPORT FEET	X	X	X	X	X	X	X
KAATD0101TDR	TIME DELAY	X	X	X	X	X	X	X
KSATX0201PUR	TXV (HSO)	X	X	X				
KSATX0301PUR	TXV (HSO)				X			
KSATX0401PUR	TXV (HSO)					X		
KSATX0501PUR	TXV (HSO)						X	X
KAAWS0101AAA	WINTER START	X	X	X	X	X	X	X

X = Accessory, S = Standard

ACCESSORY CONTROLS

PART NUMBER	DESCRIPTION
SYSTXCCUID01–B	Infinity Control Deluxe 7–Day Programmable (Wall–mounted system control.)
SYSTXCCUIZ01–B	Infinity Control Deluxe Zoning 7–Day Programmable (Wall–mounted control for a multi–zone system.)
SYSTXCC4ZC01	Infinity 4–Zone Damper Control Module (Wall–mounted control for a four–zone system.)
SYSTXCCSMS01	Infinity Smart Sensor (Optional wall control used to monitor temperature and/or fan control in an individual zone.)
SYSTXCCRRS01	Infinity Remote Room Sensor (Monitors temperature in an individual zone.)
SYSTXCCRCT01 or SYSTXCCRWF01	Infinity System Access Module (Hardware for wireless access and control via internet.)
SYSTXCCNIM01	Infinity Network Interface Module (Connects Heat Recovery and Energy Recovery Ventilators on non–zoning applications.)
SYSTXXXBPU01	Decorative Back Plate for Infinity Control (Decorative wall plate.)

ELECTRICAL DATA

UNIT SIZE – SERIES	V/PH	OPER VOLTS*		COMPR		FAN	MCA	MIN WIRE SIZE†	MIN WIRE SIZE†	MAX LENGTH ft (m)‡	MAX LENGTH ft (m)‡	MAX FUSE** or CKT BRK AMPS
		MAX	MIN	LRA	RLA	FLA		60° C	75° C	60° C	75° C	
18–30	208/230/1	253	197	48.0	9.0	0.43	11.7	14	14	66 (20.12)	62 (18.90)	20
24–30				58.3	13.5	0.60	17.5	14	14	44 (13.41)	42 (12.80)	25
30–30				64.0	12.8	0.60	16.6	14	14	46 (14.02)	44 (13.41)	25
36–30				77.0	14.1	0.60	18.2	14	14	44 (13.41)	42 (12.80)	30
42–30				112.0	17.9	1.00	23.4	12	12	52 (15.85)	50 (15.24)	40
48–30				109.0	19.9	1.20	26.1	10	10	77 (23.47)	73 (22.25)	40
60–30				135.0	21.4	1.20	28.0	10	10	71 (21.64)	68 (20.73)	40

* Permissible limits of the voltage range at which the unit will operate satisfactorily

† If wire is applied at ambient greater than 30°C, consult table 310–16 of the NEC (NFPA 70). The ampacity of non-metallic-sheathed cable (NM), trade name ROMEX, shall be that of 60°C conditions, per the NEC (NFPA 70) Article 336–26. If other than uncoated (no-plated), 60 or 75°C insulation, copper wire (solid wire for 10 AWG or smaller, stranded wire for larger than 10 AWG) is used, consult applicable tables of the NEC (NFPA 70).

‡ Length shown is as measured one way along wire path between unit and service panel for voltage drop not to exceed 2%.

** Time–Delay fuse.

FLA – Full Load Amps

LRA – Locked Rotor Amps

MCA – Minimum Circuit Amps

RLA – Rated Load Amps

NOTE: Control circuit is 24–V on all units and requires external power source. Copper wire must be used from service disconnect to unit.

All motors/compressors contain internal overload protection.

Complies with 2007 requirements of ASHRAE Standards 90.1

24ANB6

A-WEIGHTED SOUND POWER (dBA)

UNIT SIZE – SERIES	STANDARD RATING	TYPICAL OCTAVE BAND SPECTRUM (without tone adjustment)						
		125	250	500	1000	2000	4000	8000
18–30	66	52.0	56.5	60.5	61.5	59.0	53.5	44.5
24–30	67	51.5	58.0	61.5	62.5	59.5	54.0	47.5
30–30	68	56.5	60.0	63.0	62.5	59.5	54.5	46.0
36–30	69	55.5	61.0	62.0	62.5	61.0	57.0	49.0
42–30	68	53.0	60.5	62.0	63.0	60.5	58.0	51.0
48–30	70	55.0	61.0	63.5	63.0	60.5	57.0	52.0
60–30	70	55.0	61.5	63.0	63.0	59.5	57.0	51.5

NOTE: Tested in accordance with AHRI Standard 270–08 (not listed in AHRI).

CHARGING SUBCOOLING (TXV-TYPE EXPANSION DEVICE)


UNIT SIZE – SERIES	REQUIRED SUBCOOLING °F (°C)
18–30	9 (5.0)
24–30	11 (6.1)
30–30	10 (5.6)
36–30	11 (6.1)
42–30	11 (6.1)
48–30	12 (6.7)
60–30	12 (6.7)

DIMENSIONS - ENGLISH

UNIT	SERIES	ELECTRICAL CHARACTERISTICS			A	B	C	D	E	F	G	K	L	M	N	P	OPERATING WEIGHT (lbs)	SHIPPING WEIGHT (lbs)	SHIPPING DIMENSIONS (L x W x H)		
24ANB618	0	X	0	0	31 3/16"	29 9/16"	3 3/4"	3/4"	6 9/16"	24 11/16"	9 1/8"	2 13/16"	1/2"	15 1/4"	15"	14"	184	217	32 5/16"	X 35 1/2"	X 35 15/16"
24ANB624	0	X	0	0	31 3/16"	29 9/16"	3 3/4"	3/4"	6 9/16"	24 11/16"	9 1/8"	2 13/16"	1/2"	15 1/4"	15 1/4"	14"	186	219	32 5/16"	X 35 1/2"	X 35 15/16"
24ANB630	0	X	0	0	31 3/16"	32 15/16"	3 3/4"	3/4"	6 9/16"	24 11/16"	9 1/8"	2 13/16"	1/2"	15 3/4"	15 1/2"	16 1/2"	193	227	32 5/16"	X 35 1/2"	X 39 3/8"
24ANB636	0	X	0	0	35"	30 7/16"	3 7/8"	7/8"	6 9/16"	28 7/16"	9 1/8"	2 15/16"	5/8"	17 1/4"	17 1/8"	14 3/4"	209	250	36 1/8"	X 39 1/4"	X 35 15/16"
24ANB642	0	X	0	0	35"	40 5/8"	3 7/8"	7/8"	6 9/16"	28 7/16"	9 1/8"	2 15/16"	5/8"	17 1/2"	16 3/4"	18 1/4"	261	303	36 1/8"	X 39 1/4"	X 46 1/8"
24ANB648	0	X	0	0	35"	40 5/8"	3 7/8"	7/8"	6 9/16"	28 7/16"	9 1/8"	2 15/16"	5/8"	17 1/2"	17 1/4"	18 3/4"	303	346	36 1/8"	X 39 1/4"	X 46 1/8"
24ANB660	0	X	0	0	35"	47 7/16"	3 7/8"	7/8"	6 9/16"	28 7/16"	9 1/8"	2 15/16"	5/8"	17 3/4"	16"	21 1/2"	334	380	36 1/8"	X 39 1/4"	X 51 13/16"

X = YES
0 = NO

208-230-160	230-160	208/230-3-60	460-3-60
-------------	---------	--------------	----------




UNIT SIZE	MINIMUM MOUNTING PAD DIMENSIONS
-	26" X 26"
18, 24, 30	31 1/2" X 31 1/2"
36, 37, 42, 43, 48, 60	35" X 35"

DIMENSIONS - SI

UNIT	SERIES	ELECTRICAL CHARACTERISTICS			A	B	C	D	E	F	G	K	L	M	N	P	OPERATING WEIGHT (Kgs)	SHIPPING WEIGHT (Kgs)	SHIPPING DIMENSIONS (L x W x H)	
24ANB618	0	X	0	0	792.5	750.6	95.6	19.1	166.1	626.3	231.3	70.9	12.7	387.4	381.0	355.6	83	98	821.2 X 901.2 X 913.2	
24ANB624	0	X	0	0	792.5	750.6	95.6	19.1	166.1	626.3	231.3	70.9	12.7	387.4	387.4	355.6	84	99	821.2 X 901.2 X 913.2	
24ANB630	0	X	0	0	792.5	836.9	95.6	19.1	166.1	626.3	231.3	70.9	12.7	400.1	393.7	419.1	88	103	821.2 X 901.2 X 999.5	
24ANB636	0	X	0	0	889.0	773.6	97.9	22.2	166.1	722.8	231.3	74.5	16.3	438.2	435.0	374.7	95	113	917.7 X 997.7 X 913.2	
24ANB642	0	X	0	0	889.0	1032.6	97.9	22.2	166.1	722.8	231.3	74.5	16.3	444.5	425.5	463.6	118	137	917.7 X 997.7 X 1172.2	
24ANB648	0	X	0	0	889.0	1032.6	97.9	22.2	166.1	722.8	231.3	74.5	16.3	444.5	438.2	476.3	137	157	917.7 X 997.7 X 1172.2	
24ANB660	0	X	0	0	889.0	1205.4	97.9	22.2	166.1	722.8	231.3	74.5	16.3	450.9	406.4	546.1	151	172	917.7 X 997.7 X 1315.7	

X = YES
O = NO


208-230-160	230-160	208/230-3-60	460-3-60
-------------	---------	--------------	----------



UNIT SIZE	MINIMUM MOUNTING PAD DIMENSIONS
-	660.4 X 660.4
18, 24, 30	800.1 X 800.1
36, 37, 42, 43, 48, 60	889.0 X 889.0

24ANB6

CLEARANCES



Note: Numbers in () = mm

IMPORTANT: When installing multiple units in an alcove, roof well, or partially enclosed area, ensure there is adequate ventilation to prevent re-circulation of discharge air.

COMBINATION RATINGS

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB618A**30	*CNPV*1917A**	18,000	TXV		14.50		12.00	
	FB4CNF018	18,000	TDR			16.00	13.00	
	FB4CNF024	18,000	TDR			16.00	13.00	
	FB4CNF030	18,000	TDR			15.00	12.50	
	FE4ANF002	18,000	TDR&TXV	16.50			13.50	
	FF1ENP018	18,000	TDR&TXV	14.00			11.50	
	FF1ENP019	18,000	TDR&TXV	15.50			13.00	
	FF1ENP024	18,000	TDR&TXV	14.50			12.00	
	FF1ENP025	18,000	TDR&TXV	16.00			13.50	
	FF1ENP031	18,000	TDR&TXV	16.00			13.00	
	FF1ENP037	18,000	TDR&TXV	16.00			13.00	
	FV4CNF002	18,000	TDR&TXV	16.50			13.50	
	FX4DN(B,F)031	18,000	TDR&TXV	16.00			13.00	
	FX4DNF019	18,000	TDR&TXV	16.50			13.50	
	FX4DNF025	18,000	TDR&TXV	16.00			13.50	
	FY5BNF018	18,000	TDR			15.00	12.50	
	FY5BNF024	18,000	TDR			15.00	12.50	
	CAP**1814A**	18,000	TXV		14.00		11.50	
	CAP**1814A**	17,800	TDR&TXV	15.50			13.00	58CV(A,X)070–12
	CAP**1814A**	18,000	TDR&TXV	16.00			13.00	58PH*045–08
	CAP**2414A**	18,000	TXV		14.50		12.00	
	CAP**2414A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CAP**2414A**	18,000	TDR&TXV	16.00			13.00	58PH*045–08
	CAP**2417A**	18,000	TXV		14.50		12.00	
	CAP**2417A**	18,000	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CAP**2417A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CAP**2417A**	18,000	TDR&TXV	16.50			13.50	58MEB040–12
	CAP**2417A**	18,000	TDR&TXV	16.50			13.50	58MEC060–12
	CAP**2417A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CAP**2417A**	18,000	TDR&TXV	16.00			13.00	58PH*045–08
	CAP**2417A**	18,000	TDR&TXV	16.00			13.00	OVMAAB036098
	CAP**2417A**	18,000	TDR&TXV	16.00			13.00	OVLAAB036098
	CAP**3621A**	18,000	TXV		14.50		12.00	
	CAP**3621A**	18,000	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CNPH*2417A**	18,000	TXV		14.50		12.00	
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.00	58MVB040–14
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.00	58PH*045–08
	CNPH*2417A**	18,000	TDR&TXV	16.50			13.50	58MEB040–12
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.50	58MEC060–12
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.00	58HDV040– – 12
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.00	58HDV060– – 12
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.00	OVMAAB036098
	CNPH*2417A**	18,000	TDR&TXV	16.00			13.00	OVLAAB036098
	CNPV*1814A**	18,000	TXV		14.50		12.00	
	CNPV*1814A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CNPV*1814A**	18,000	TDR&TXV	16.00			13.00	58PH*045–08
	CNPV*1917A**	18,000	TDR&TXV	16.00			13.50	58MV(B,C)060–14
	CNPV*1917A**	18,000	TDR&TXV	16.00			13.50	58CV(A,X)090–16
	CNPV*1917A**	18,000	TDR&TXV	17.00			13.50	58MEB040–12
	CNPV*1917A**	18,000	TDR&TXV	16.50			13.50	58MEC060–12
	CNPV*1917A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)070–12

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB618A**30	CNPV*1917A**	18,000	TDR&TXV	16.00			13.50	58PH*045–08
	CNPV*1917A**	18,000	TDR&TXV	16.00			13.00	OVMAAB036098
	CNPV*1917A**	18,000	TDR&TXV	16.00			13.00	OVLAAB036098
	CNPV*1917A**	18,600	TDR&TXV	16.00			13.00	58HDV040– – 12
	CNPV*1917A**	18,600	TDR&TXV	16.00			13.00	58HDV060– – 12
	CNPV*2414A**	18,000	TXV		14.50		12.00	
	CNPV*2414A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)070– 12
	CNPV*2414A**	18,000	TDR&TXV	16.00			13.00	58PH*045–08
	CNPV*2417A**	18,000	TXV		14.50		12.00	
	CNPV*2417A**	18,000	TDR&TXV	16.00			13.00	58MV(B,C)060– 14
	CNPV*2417A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)090– 16
	CNPV*2417A**	18,000	TDR&TXV	16.50			13.50	58MEB040– 12
	CNPV*2417A**	18,000	TDR&TXV	16.00			13.50	58MEC060– 12
	CNPV*2417A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)070– 12
	CNPV*2417A**	18,000	TDR&TXV	16.00			13.00	58PH*045–08
	CNPV*2417A**	18,000	TDR&TXV	16.00			13.00	OVMAAB036098
	CNPV*2417A**	18,000	TDR&TXV	16.00			13.00	OVLAAB036098
	CNPV*2417A**	18,000	TDR&TXV	15.50			13.00	58HDV040– – 12
	CNPV*2417A**	18,000	TDR&TXV	15.50			13.00	58HDV060– – 12
	CNPV*3621A**	18,000	TXV		14.50		12.00	
	CNPV*3621A**	18,000	TDR&TXV	16.00			13.00	58MV(B,C)080– 14
	CSPH*2412A**	18,000	TXV		14.50		12.00	
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.00	58MVB040– 14
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.00	58MV(B,C)060– 14
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.00	58MV(B,C)080– 14
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)070– 12
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.00	58CV(A,X)090– 16
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.00	58PH*045–08
	CSPH*2412A**	18,000	TDR&TXV	16.50			13.50	58MEB040– 12
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.50	58MEC060– 12
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.00	58HDV040– – 12
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.00	58HDV060– – 12
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.00	OVMAAB036098
	CSPH*2412A**	18,000	TDR&TXV	16.00			13.00	OVLAAB036098
24ANB624A**30	*CNPV*3117A**	23,800	TXV			14.50	12.00	
	FE5ANB004	24,200	TDR&TXV	16.00			13.50	
	FF1ENP024	23,000	TDR&TXV	13.50			11.50	
	FF1ENP025	23,400	TDR&TXV	15.00			12.50	
	FF1ENP030	23,000	TDR&TXV	13.50			11.50	
	FF1ENP031	23,400	TDR&TXV	15.00			12.50	
	FF1ENP036	23,200	TDR&TXV	13.50			11.00	
	FF1ENP037	23,600	TDR&TXV	15.50			12.50	
	FV4CN(B,F)003	23,400	TDR&TXV	16.00			13.00	
	FV4CNF002	23,400	TDR&TXV	16.00			13.00	
	FX4DN(B,F)031	23,800	TDR&TXV	15.50			12.50	
	FX4DN(B,F)037	24,000	TDR&TXV	16.00			13.00	
	FX4DNF025	23,600	TDR&TXV	16.00			13.00	
	FY5BNF024	23,400	TDR		15.00		12.00	
	FY5BNF030	23,600	TDR		15.00		12.00	
	CAP**2414A**	23,200	TXV			14.00	11.50	
	CAP**2414A**	23,000	TDR&TXV	15.50			12.50	58CV(A,X)070– 12

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB624A**30	FB4CNF024	23,000	TDR		15.00		12.00	
	FB4CNF030	23,600	TDR		16.00		13.00	
	FB4CNF036	23,000	TDR		13.50		11.20	
	FE4AN(B,F)003	23,400	TDR&TXV	16.00			13.00	
	FE4ANF002	23,400	TDR&TXV	16.00			13.00	
	CAP**2414A**	23,200	TDR&TXV	15.50			12.50	58PH*045–08
	CAP**2417A**	23,200	TXV			14.00	11.50	
	CAP**2417A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CAP**2417A**	23,000	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CAP**2417A**	23,600	TDR&TXV	16.00			13.00	58MEB040–12
	CAP**2417A**	23,600	TDR&TXV	16.00			13.00	58MEC060–12
	CAP**2417A**	23,400	TDR&TXV	16.00			13.00	58MEC080–12
	CAP**2417A**	23,000	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CAP**2417A**	23,200	TDR&TXV	15.50			12.50	58PH*045–08
	CAP**2417A**	23,200	TDR&TXV	15.50			12.50	OVMAAB036098
	CAP**2417A**	23,200	TDR&TXV	15.50			12.50	OVLAAB036098
	CAP**2417A**	23,200	TDR&TXV	16.00			13.00	OVMAAB042112
	CAP**3014A**	23,400	TXV			14.00	11.50	
	CAP**3014A**	23,000	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CAP**3014A**	23,400	TDR&TXV	15.50			12.50	58PH*045–08
	CAP**3017A**	23,400	TXV			14.00	11.50	
	CAP**3017A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CAP**3017A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CAP**3017A**	23,800	TDR&TXV	16.00			13.00	58MEB040–12
	CAP**3017A**	23,800	TDR&TXV	16.00			13.00	58MEC060–12
	CAP**3017A**	23,600	TDR&TXV	16.00			13.00	58MEC080–12
	CAP**3017A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CAP**3017A**	23,400	TDR&TXV	16.00			13.00	58PH*045–08
	CAP**3017A**	23,400	TDR&TXV	15.50			13.00	OVMAAB036098
	CAP**3017A**	23,400	TDR&TXV	16.00			13.00	OVLAAB036098
	CAP**3017A**	23,200	TDR&TXV	16.00			13.00	OVMAAB042112
	CAP**3614A**	23,400	TXV			14.00	11.50	
	CAP**3614A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CAP**3614A**	23,400	TDR&TXV	16.00			13.00	58PH*045–08
	CAP**3617A**	23,400	TXV			14.00	11.50	
	CAP**3617A**	23,600	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CAP**3617A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CAP**3617A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CAP**3617A**	23,600	TDR&TXV	16.00			13.00	58PH*045–08
	CAP**3617A**	23,800	TDR&TXV	16.00			13.00	58MEB040–12
	CAP**3617A**	24,000	TDR&TXV	16.00			13.00	58MEC060–12
	CAP**3617A**	23,800	TDR&TXV	16.00			13.00	58MEC080–12
	CAP**3619A**	23,400	TXV			14.00	11.50	
	CAP**3619A**	23,800	TDR&TXV	16.00			13.00	58MEB040–12
	CAP**3619A**	24,000	TDR&TXV	16.00			13.00	58MEC060–12
	CAP**3621A**	23,400	TXV			14.00	11.50	
	CAP**3621A**	23,600	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CAP**3621A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CAP**3621A**	23,000	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CAP**3621A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CAP**3621A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CAP**3621A**	23,400	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CAP**3621A**	24,000	TDR&TXV	16.00			13.00	58MEB040–12

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB624A**30	CAP**3621A**	24,000	TDR&TXV	16.00			13.00	58MEC060–12
	CAP**3621A**	23,800	TDR&TXV	16.00			13.00	58MEC080–12
	CNPF*2418A**	23,200	TXV			14.00	11.50	
	CNPF*3618A**	23,400	TXV			14.00	11.50	
	CNPH*2417A**	23,200	TXV			14.00	11.50	
	CNPH*2417A**	23,000	TDR&TXV	15.50			12.50	58MVB040–14
	CNPH*2417A**	23,200	TDR&TXV	15.50			12.50	58MV(B,C)060–14
	CNPH*2417A**	23,000	TDR&TXV	15.50			12.50	58MV(B,C)080–14
	CNPH*2417A**	22,800	TDR&TXV	15.50			12.50	58MV(B,C)080–20
	CNPH*2417A**	23,000	TDR&TXV	15.50			12.50	58MV(B,C)100–20
	CNPH*2417A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*2417A**	23,000	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CNPH*2417A**	23,000	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*2417A**	23,000	TDR&TXV	15.50			12.50	58CV(A,X)110–20
	CNPH*2417A**	23,000	TDR&TXV	15.50			12.50	58CV(A,X)135–22
	CNPH*2417A**	23,000	TDR&TXV	15.50			12.50	58CV(A,X)155–22
	CNPH*2417A**	23,200	TDR&TXV	15.50			12.50	58PH*045–08
	CNPH*2417A**	23,400	TDR&TXV	16.00			13.00	58MEB040–12
	CNPH*2417A**	23,400	TDR&TXV	16.00			13.00	58MEC060–12
	CNPH*2417A**	23,200	TDR&TXV	16.00			13.00	58MEC080–12
	CNPH*2417A**	23,200	TDR&TXV	15.00			12.00	58HDV040– –12
	CNPH*2417A**	23,200	TDR&TXV	15.00			12.00	58HDV060– –12
	CNPH*2417A**	23,600	TDR&TXV	15.00			12.50	58HDV080– –20
	CNPH*2417A**	23,400	TDR&TXV	15.50			12.50	58HDV100– –20
	CNPH*2417A**	23,200	TDR&TXV	15.50			12.50	OVMAAB036098
	CNPH*2417A**	23,200	TDR&TXV	15.50			12.50	OVLAAB036098
	CNPH*2417A**	23,200	TDR&TXV	15.50			12.50	OVMAAB042112
	CNPH*3017A**	23,400	TXV			14.00	11.50	
	CNPH*3017A**	23,200	TDR&TXV	16.00			13.00	58MVB040–14
	CNPH*3017A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPH*3017A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CNPH*3017A**	23,000	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPH*3017A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CNPH*3017A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*3017A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CNPH*3017A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*3017A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPH*3017A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*3017A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*3017A**	23,400	TDR&TXV	16.00			13.00	58PH*045–08
	CNPH*3017A**	23,800	TDR&TXV	16.00			13.00	58MEB040–12
	CNPH*3017A**	23,800	TDR&TXV	16.00			13.00	58MEC060–12
	CNPH*3017A**	23,600	TDR&TXV	16.00			13.00	58MEC080–12
	CNPH*3017A**	23,400	TDR&TXV	15.50			12.50	58HDV040– –12
	CNPH*3017A**	23,800	TDR&TXV	15.50			12.50	58HDV060– –12
	CNPH*3017A**	24,000	TDR&TXV	16.00			13.00	58HDV100– –20
	CNPH*3017A**	23,600	TDR&TXV	16.00			13.00	58HDV080– –20
	CNPH*3017A**	23,400	TDR&TXV	15.50			13.00	OVMAAB036098
	CNPH*3017A**	23,400	TDR&TXV	16.00			13.00	OVLAAB036098
	CNPH*3017A**	23,400	TDR&TXV	16.00			13.00	OVMAAB042112
	CNPH*3117A**	23,800	TXV			14.50	12.00	
	CNPH*3117A**	23,600	TDR&TXV	16.00			13.00	58MVB040–14
	CNPH*3117A**	24,000	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPH*3117A**	23,600	TDR&TXV	16.00			13.00	58MV(B,C)080–14

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB624A**30	CNPH*3117A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPH*3117A**	23,600	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CNPH*3117A**	23,800	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*3117A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CNPH*3117A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*3117A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPH*3117A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*3117A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*3117A**	24,000	TDR&TXV	16.00			13.00	58PH*045–08
	CNPH*3117A**	24,000	TDR&TXV	16.00			13.00	58MEB040–12
	CNPH*3117A**	24,000	TDR&TXV	16.00			13.00	58MEC060–12
	CNPH*3117A**	24,000	TDR&TXV	16.00			13.00	58MEC080–12
	CNPH*3117A**	24,000	TDR&TXV	16.00			13.00	58HDV040– –12
	CNPH*3117A**	24,000	TDR&TXV	16.00			13.00	58HDV060– –12
	CNPH*3117A**	24,400	TDR&TXV	16.00			13.00	58HDV100– –20
	CNPH*3117A**	24,000	TDR&TXV	16.00			13.00	58HDV080– –20
	CNPH*3117A**	23,800	TDR&TXV	16.00			13.00	OVMAAB036098
	CNPH*3117A**	23,800	TDR&TXV	16.00			13.00	OVLAAB036098
	CNPH*3117A**	23,800	TDR&TXV	16.00			13.00	OVMAAB042112
	CNPH*3617A**	23,400	TXV			14.00	11.50	
	CNPH*3617A**	23,200	TDR&TXV	16.00			13.00	58MVB040–14
	CNPH*3617A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPH*3617A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CNPH*3617A**	23,000	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPH*3617A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CNPH*3617A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*3617A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CNPH*3617A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*3617A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPH*3617A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*3617A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*3617A**	23,400	TDR&TXV	16.00			13.00	58PH*045–08
	CNPH*3617A**	23,800	TDR&TXV	16.00			13.00	58MEB040–12
	CNPH*3617A**	23,800	TDR&TXV	16.00			13.00	58MEC060–12
	CNPH*3617A**	23,600	TDR&TXV	16.00			13.00	58MEC080–12
	CNPV*1917A**	23,400	TXV			14.00	11.50	
	CNPV*1917A**	23,600	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPV*1917A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CNPV*1917A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPV*1917A**	23,400	TDR&TXV	16.00			13.00	58PH*045–08
	CNPV*1917A**	23,800	TDR&TXV	16.00			13.00	58MEB040–12
	CNPV*1917A**	23,800	TDR&TXV	16.00			13.00	58MEC060–12
	CNPV*2414A**	23,200	TXV			14.00	11.50	
	CNPV*2414A**	23,000	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CNPV*2414A**	23,200	TDR&TXV	15.50			12.50	58PH*045–08
	CNPV*2417A**	23,200	TXV			14.00	11.50	
	CNPV*2417A**	23,200	TDR&TXV	15.50			12.50	58MV(B,C)060–14
	CNPV*2417A**	23,000	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPV*2417A**	23,400	TDR&TXV	16.00			13.00	58MEB040–12
	CNPV*2417A**	23,400	TDR&TXV	16.00			13.00	58MEC060–12
	CNPV*2417A**	23,200	TDR&TXV	16.00			13.00	58MEC080–12
	CNPV*2417A**	23,000	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CNPV*2417A**	23,200	TDR&TXV	15.50			12.50	58PH*045–08
	CNPV*2417A**	23,200	TDR&TXV	15.50			12.50	OVMAAB036098

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB624A**30	CNPV*2417A**	23,400	TDR&TXV	15.50			12.50	OVLAAB036098
	CNPV*2417A**	23,200	TDR&TXV	15.50			12.50	OVMAAB042112
	CNPV*2417A**	23,200	TDR&TXV	15.00			12.50	58HDV040 – – 12
	CNPV*2417A**	23,200	TDR&TXV	15.00			12.50	58HDV060 – – 12
	CNPV*3014A**	23,400	TXV			14.00	11.50	
	CNPV*3014A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)070 – 12
	CNPV*3014A**	23,400	TDR&TXV	15.50			12.50	58PH*045 – 08
	CNPV*3017A**	23,400	TXV			14.00	11.50	
	CNPV*3017A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)060 – 14
	CNPV*3017A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)090 – 16
	CNPV*3017A**	23,800	TDR&TXV	16.00			13.00	58MEB040 – 12
	CNPV*3017A**	23,800	TDR&TXV	16.00			13.00	58MEC060 – 12
	CNPV*3017A**	23,600	TDR&TXV	16.00			13.00	58MEC080 – 12
	CNPV*3017A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)070 – 12
	CNPV*3017A**	23,400	TDR&TXV	16.00			13.00	58PH*045 – 08
	CNPV*3017A**	23,400	TDR&TXV	15.50			13.00	OVMAAB036098
	CNPV*3017A**	23,400	TDR&TXV	16.00			13.00	OVLAAB036098
	CNPV*3017A**	23,400	TDR&TXV	16.00			13.00	OVMAAB042112
	CNPV*3017A**	23,400	TDR&TXV	15.50			12.50	58HDV040 – – 12
	CNPV*3017A**	23,800	TDR&TXV	15.50			12.50	58HDV060 – – 12
	CNPV*3117A**	24,000	TDR&TXV	16.00			13.00	58MV(B,C)060 – 14
	CNPV*3117A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)090 – 16
	CNPV*3117A**	24,000	TDR&TXV	16.00			13.00	58MEB040 – 12
	CNPV*3117A**	24,000	TDR&TXV	16.00			13.00	58MEC060 – 12
	CNPV*3117A**	24,000	TDR&TXV	16.00			13.00	58MEC080 – 12
	CNPV*3117A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)070 – 12
	CNPV*3117A**	24,000	TDR&TXV	16.00			13.00	58PH*045 – 08
	CNPV*3117A**	23,800	TDR&TXV	16.00			13.00	OVMAAB036098
	CNPV*3117A**	23,800	TDR&TXV	16.00			13.00	OVLAAB036098
	CNPV*3117A**	23,800	TDR&TXV	16.00			13.00	OVMAAB042112
	CNPV*3117A**	24,000	TDR&TXV	16.00			13.00	58HDV040 – – 12
	CNPV*3117A**	24,000	TDR&TXV	16.00			13.00	58HDV060 – – 12
	CNPV*3617A**	23,400	TXV			14.00	11.50	
	CNPV*3617A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)060 – 14
	CNPV*3617A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)070 – 12
	CNPV*3617A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)090 – 16
	CNPV*3617A**	23,400	TDR&TXV	16.00			13.00	58PH*045 – 08
	CNPV*3617A**	23,800	TDR&TXV	16.00			13.00	58MEB040 – 12
	CNPV*3617A**	23,800	TDR&TXV	16.00			13.00	58MEC060 – 12
	CNPV*3617A**	23,600	TDR&TXV	16.00			13.00	58MEC080 – 12
	CNPV*3621A**	23,400	TXV			14.00	11.50	
	CNPV*3621A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)060 – 14
	CNPV*3621A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)080 – 14
	CNPV*3621A**	23,000	TDR&TXV	16.00			13.00	58MV(B,C)080 – 20
	CNPV*3621A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)100 – 20
	CNPV*3621A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)090 – 16
	CNPV*3621A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)110 – 20
	CNPV*3621A**	23,800	TDR&TXV	16.00			13.00	58MEB040 – 12
	CNPV*3621A**	23,800	TDR&TXV	16.00			13.00	58MEC060 – 12
	CNPV*3621A**	23,600	TDR&TXV	16.00			13.00	58MEC080 – 12
	CSPH*2412A**	23,400	TXV			14.00	11.50	
	CSPH*2412A**	23,200	TDR&TXV	15.50			12.50	58MVB040 – 14
	CSPH*2412A**	23,600	TDR&TXV	16.00			13.00	58MV(B,C)060 – 14
	CSPH*2412A**	23,200	TDR&TXV	16.00			12.50	58MV(B,C)080 – 14

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB624A**30	CSPH*2412A**	23,000	TDR&TXV	16.00			12.50	58MV(B,C)080–20
	CSPH*2412A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CSPH*2412A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CSPH*2412A**	23,200	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CSPH*2412A**	23,400	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CSPH*2412A**	23,200	TDR&TXV	15.50			12.50	58CV(A,X)110–20
	CSPH*2412A**	23,400	TDR&TXV	16.00			12.50	58CV(A,X)135–22
	CSPH*2412A**	23,400	TDR&TXV	16.00			12.50	58CV(A,X)155–22
	CSPH*2412A**	23,400	TDR&TXV	15.50			12.50	58PH*045–08
	CSPH*2412A**	23,600	TDR&TXV	16.00			13.00	58MEB040–12
	CSPH*2412A**	23,600	TDR&TXV	16.00			13.00	58MEC060–12
	CSPH*2412A**	23,400	TDR&TXV	16.00			13.00	58MEC080–12
	CSPH*2412A**	23,400	TDR&TXV	15.20			12.50	58HDV040– –12
	CSPH*2412A**	23,400	TDR&TXV	15.20			12.50	58HDV060– –12
	CSPH*2412A**	23,800	TDR&TXV	15.50			12.50	58HDV080– –20
	CSPH*2412A**	23,600	TDR&TXV	15.50			12.50	58HDV100– –20
	CSPH*2412A**	23,400	TDR&TXV	15.50			12.50	OVMAAB036098
	CSPH*2412A**	23,400	TDR&TXV	15.50			12.50	OVLAAB036098
	CSPH*2412A**	23,400	TDR&TXV	15.50			12.50	OVMAAB042112
	CSPH*3012A**	23,400	TXV			14.00	11.50	
	CSPH*3012A**	23,200	TDR&TXV	16.00			13.00	58MVB040–14
	CSPH*3012A**	23,600	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CSPH*3012A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CSPH*3012A**	23,000	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CSPH*3012A**	23,200	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CSPH*3012A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CSPH*3012A**	23,200	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CSPH*3012A**	23,400	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CSPH*3012A**	23,400	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CSPH*3012A**	23,400	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*3012A**	23,400	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*3012A**	23,400	TDR&TXV	16.00			13.00	58PH*045–08
	CSPH*3012A**	23,800	TDR&TXV	16.00			13.00	58MEB040–12
	CSPH*3012A**	23,800	TDR&TXV	16.00			13.00	58MEC060–12
	CSPH*3012A**	23,600	TDR&TXV	16.00			13.00	58MEC080–12
	CSPH*3012A**	23,600	TDR&TXV	15.50			12.50	58HDV040– –12
	CSPH*3012A**	23,800	TDR&TXV	15.50			12.50	58HDV060– –12
	CSPH*3012A**	24,000	TDR&TXV	16.00			13.00	58HDV080– –20
	CSPH*3012A**	24,000	TDR&TXV	16.00			13.00	58HDV100– –20
	CSPH*3012A**	23,600	TDR&TXV	15.50			13.00	OVMAAB036098
	CSPH*3012A**	23,600	TDR&TXV	15.50			13.00	OVLAAB036098
	CSPH*3012A**	23,400	TDR&TXV	16.00			13.00	OVMAAB042112
	CSPH*3612A**	23,800	TXV			14.50	12.00	
	CSPH*3612A**	23,600	TDR&TXV	16.00			13.00	58MVB040–14
	CSPH*3612A**	24,000	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CSPH*3612A**	23,600	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CSPH*3612A**	23,400	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CSPH*3612A**	23,600	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CSPH*3612A**	23,800	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CSPH*3612A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CSPH*3612A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CSPH*3612A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CSPH*3612A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*3612A**	23,600	TDR&TXV	16.00			13.00	58CV(A,X)155–22

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB624A**30	CSPH*3612A**	23,800	TDR&TXV	16.00			13.00	58PH*045–08
	CSPH*3612A**	24,000	TDR&TXV	16.00			13.00	58MEB040–12
	CSPH*3612A**	24,000	TDR&TXV	16.00			13.00	58MEC060–12
	CSPH*3612A**	24,000	TDR&TXV	16.00			13.00	58MEC080–12
24ANB630A**30	*CNPV*3117A**	28,400	TXV			14.50	12.00	
	FB4CNF030	28,000	TDR		15.00		12.50	
	FB4CNF036	28,000	TDR		15.00		12.50	
	FB4CNF042	28,400	TDR		14.50		12.00	
	FE4AN(B,F)003	28,000	TDR&TXV	16.00			13.00	
	FE4AN(B,F)005	28,600	TDR&TXV	16.50			13.00	
	FE4ANF002	28,000	TDR&TXV	16.00			13.00	
	FE5ANB004	29,000	TDR&TXV	16.50			13.00	
	FF1ENP030	27,600	TDR&TXV	14.00			12.00	
	FF1ENP031	28,000	TDR&TXV	15.20			12.50	
	FF1ENP036	28,000	TDR&TXV	14.00			12.00	
	FF1ENP037	28,200	TDR&TXV	15.00			12.50	
	FV4CN(B,F)003	28,000	TDR&TXV	16.00			13.00	
	FV4CN(B,F)005	28,600	TDR&TXV	16.50			13.50	
	FV4CNF002	28,000	TDR&TXV	16.00			13.00	
	FX4DN(B,F)031	28,400	TDR&TXV	15.50			13.00	
	FX4DN(B,F)037	28,800	TDR&TXV	16.00			13.00	
	FX4DN(B,F)043	28,600	TDR&TXV	15.00			12.50	
	FY5BNF030	28,200	TDR		14.50		12.50	
	FY5BNF036	28,000	TDR		14.50		12.00	
	CAP**3014A**	27,800	TXV			14.00	12.00	
	CAP**3014A**	27,600	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CAP**3017A**	27,800	TXV			14.00	12.00	
	CAP**3017A**	27,800	TDR&TXV	15.50			13.00	58MV(B,C)060–14
	CAP**3017A**	27,600	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CAP**3017A**	27,800	TDR&TXV	15.20			12.50	58PH*070–16
	CAP**3017A**	28,000	TDR&TXV	16.00			13.00	58MEB040–12
	CAP**3017A**	28,000	TDR&TXV	16.00			13.00	58MEC060–12
	CAP**3017A**	28,000	TDR&TXV	16.00			13.00	58MEC080–12
	CAP**3017A**	28,200	TDR&TXV	15.50			13.00	58MEC080–16
	CAP**3017A**	27,600	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CAP**3017A**	27,800	TDR&TXV	15.00			12.50	OVMAAB036098
	CAP**3017A**	27,600	TDR&TXV	15.20			12.50	OVLAAB036098
	CAP**3017A**	27,800	TDR&TXV	15.50			12.50	OVMAAB042112
	CAP**3017A**	27,800	TDR&TXV	15.50			12.50	58MV(B,C)060–14
	CAP**3614A**	27,800	TXV			14.00	12.00	
	CAP**3614A**	27,600	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CAP**3617A**	27,800	TXV			14.00	12.00	
	CAP**3617A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CAP**3617A**	27,800	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CAP**3617A**	28,000	TDR&TXV	15.20			12.50	58PH*070–16
	CAP**3617A**	28,200	TDR&TXV	16.00			13.00	58MEB040–12
	CAP**3617A**	28,200	TDR&TXV	16.00			13.00	58MEC060–12
	CAP**3617A**	28,000	TDR&TXV	16.00			13.00	58MEC080–12
	CAP**3617A**	28,200	TDR&TXV	16.00			13.00	58MEC080–16
	CAP**3617A**	27,800	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CAP**3617A**	27,800	TDR&TXV	15.00			12.50	OVMAAB036098
	CAP**3617A**	27,800	TDR&TXV	15.20			12.50	OVLAAB036098
	CAP**3617A**	28,000	TDR&TXV	15.50			12.50	OVMAAB042112

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB630A**30	CAP**3619A**	27,800	TXV			14.00	11.50	
	CAP**3619A**	27,800	TDR&TXV	15.00			12.50	58HDV040 – 12
	CAP**3619A**	28,000	TDR&TXV	15.20			12.50	58HDV060 – 12
	CAP**3621A**	27,800	TXV			14.00	12.00	
	CAP**3621A**	27,600	TDR&TXV	16.00			13.00	58MV(B,C)080 – 14
	CAP**3621A**	27,800	TDR&TXV	16.00			13.00	58MV(B,C)080 – 20
	CAP**3621A**	27,600	TDR&TXV	15.50			13.00	58MV(B,C)100 – 20
	CAP**3621A**	27,800	TDR&TXV	16.00			13.00	58CV(A,X)110 – 20
	CAP**3621A**	28,200	TDR&TXV	16.00			13.00	58PH*090 – 16
	CAP**3621A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)060 – 14
	CAP**3621A**	27,800	TDR&TXV	16.00			13.00	58CV(A,X)090 – 16
	CAP**3621A**	28,000	TDR&TXV	15.50			12.50	58PH*070 – 16
	CAP**3621A**	28,200	TDR&TXV	16.00			13.00	58MEB040 – 12
	CAP**3621A**	28,200	TDR&TXV	16.00			13.00	58MEC060 – 12
	CAP**3621A**	28,200	TDR&TXV	16.00			13.00	58MEC080 – 12
	CAP**3621A**	28,400	TDR&TXV	16.00			13.00	58MEC080 – 16
	CAP**3621A**	28,000	TDR&TXV	15.50			12.50	OVLAAB048112
	CAP**4221A**	28,000	TXV			14.00	11.50	
	CAP**4221A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)060 – 14
	CAP**4221A**	27,800	TDR&TXV	16.00			13.00	58MV(B,C)080 – 14
	CAP**4221A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)080 – 20
	CAP**4221A**	27,800	TDR&TXV	16.00			13.00	58MV(B,C)100 – 20
	CAP**4221A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)090 – 16
	CAP**4221A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)110 – 20
	CAP**4221A**	28,200	TDR&TXV	15.50			12.50	58PH*070 – 16
	CAP**4221A**	28,400	TDR&TXV	16.00			13.00	58PH*090 – 16
	CAP**4221A**	28,400	TDR&TXV	16.00			13.00	58MEB040 – 12
	CAP**4221A**	28,400	TDR&TXV	16.00			13.00	58MEC060 – 12
	CAP**4221A**	28,400	TDR&TXV	16.00			13.00	58MEC080 – 12
	CAP**4221A**	28,600	TDR&TXV	16.00			13.00	58MEC080 – 16
	CAP**4224A**	28,000	TXV			14.00	11.50	
	CAP**4224A**	27,800	TDR&TXV	16.00			13.00	58MVB040 – 14
	CAP**4224A**	27,800	TDR&TXV	16.00			13.00	58MV(B,C)080 – 14
	CAP**4224A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)080 – 20
	CAP**4224A**	27,800	TDR&TXV	16.00			13.00	58MV(B,C)100 – 20
	CAP**4224A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)120 – 20
	CAP**4224A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)110 – 20
	CAP**4224A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)135 – 22
	CAP**4224A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)155 – 22
	CAP**4224A**	28,400	TDR&TXV	16.00			13.00	58PH*090 – 16
	CNPF*3618A**	27,800	TXV			14.00	11.50	
	CNPH*3017A**	27,800	TXV			14.00	12.00	
	CNPH*3017A**	27,600	TDR&TXV	15.50			12.50	58MVB040 – 14
	CNPH*3017A**	27,800	TDR&TXV	15.50			13.00	58MV(B,C)060 – 14
	CNPH*3017A**	27,600	TDR&TXV	15.50			12.50	58MV(B,C)080 – 14
	CNPH*3017A**	27,600	TDR&TXV	15.50			12.50	58MV(B,C)080 – 20
	CNPH*3017A**	27,400	TDR&TXV	15.50			12.50	58MV(B,C)100 – 20
	CNPH*3017A**	27,800	TDR&TXV	16.00			13.00	58MV(B,C)120 – 20
	CNPH*3017A**	27,600	TDR&TXV	15.50			12.50	58CV(A,X)070 – 12
	CNPH*3017A**	27,800	TDR&TXV	15.50			13.00	58CV(A,X)090 – 16
	CNPH*3017A**	27,800	TDR&TXV	15.50			13.00	58CV(A,X)110 – 20
	CNPH*3017A**	27,800	TDR&TXV	16.00			13.00	58CV(A,X)135 – 22
	CNPH*3017A**	27,800	TDR&TXV	16.00			13.00	58CV(A,X)155 – 22
	CNPH*3017A**	27,800	TDR&TXV	15.00			12.50	58PH*070 – 16

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB630A**30	CNPH*3017A**	27,800	TDR&TXV	15.50			12.50	58PH*090–16
	CNPH*3017A**	28,000	TDR&TXV	16.00			13.00	58MEB040–12
	CNPH*3017A**	28,000	TDR&TXV	15.50			13.00	58MEC060–12
	CNPH*3017A**	28,000	TDR&TXV	16.00			13.00	58MEC080–12
	CNPH*3017A**	28,200	TDR&TXV	15.50			13.00	58MEC080–16
	CNPH*3017A**	27,800	TDR&TXV	15.00			12.00	58HDV040– –12
	CNPH*3017A**	27,800	TDR&TXV	15.00			12.00	58HDV060– –12
	CNPH*3017A**	28,200	TDR&TXV	15.50			12.50	58HDV080– –20
	CNPH*3017A**	28,000	TDR&TXV	15.50			12.50	58HDV100– –20
	CNPH*3017A**	27,800	TDR&TXV	15.00			12.50	OVMAAB036098
	CNPH*3017A**	27,800	TDR&TXV	15.00			12.50	OVLAAB036098
	CNPH*3017A**	27,800	TDR&TXV	15.50			12.50	OVMAAB042112
	CNPH*3017A**	28,000	TDR&TXV	15.20			12.50	OVLAAB048112
	CNPH*3117A**	28,400	TXV			14.50	12.00	
	CNPH*3117A**	28,200	TDR&TXV	16.00			13.00	58MVB040–14
	CNPH*3117A**	28,400	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPH*3117A**	28,200	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CNPH*3117A**	28,200	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPH*3117A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CNPH*3117A**	28,400	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*3117A**	28,200	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CNPH*3117A**	28,200	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*3117A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPH*3117A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*3117A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*3117A**	28,400	TDR&TXV	15.50			13.00	58PH*070–16
	CNPH*3117A**	28,600	TDR&TXV	16.00			13.00	58PH*090–16
	CNPH*3117A**	28,600	TDR&TXV	16.00			13.00	58MEB040–12
	CNPH*3117A**	28,800	TDR&TXV	16.00			13.00	58MEC060–12
	CNPH*3117A**	28,600	TDR&TXV	16.00			13.00	58MEC080–12
	CNPH*3117A**	28,800	TDR&TXV	16.00			13.00	58MEC080–16
	CNPH*3117A**	28,400	TDR&TXV	15.00			12.50	58HDV040– –12
	CNPH*3117A**	28,600	TDR&TXV	15.50			12.50	58HDV060– –12
	CNPH*3117A**	28,800	TDR&TXV	16.00			13.00	58HDV080– –20
	CNPH*3117A**	28,600	TDR&TXV	16.00			13.00	58HDV100– –20
	CNPH*3117A**	28,400	TDR&TXV	15.50			12.50	OVMAAB036098
	CNPH*3117A**	28,400	TDR&TXV	15.50			13.00	OVLAAB036098
	CNPH*3117A**	28,400	TDR&TXV	16.00			13.00	OVMAAB042112
	CNPH*3117A**	28,600	TDR&TXV	16.00			13.00	OVLAAB048112
	CNPH*3617A**	27,800	TXV			14.00	12.00	
	CNPH*3617A**	27,600	TDR&TXV	15.50			12.50	58MVB040–14
	CNPH*3617A**	27,800	TDR&TXV	15.50			13.00	58MV(B,C)060–14
	CNPH*3617A**	27,600	TDR&TXV	15.50			12.50	58MV(B,C)080–14
	CNPH*3617A**	27,600	TDR&TXV	15.50			12.50	58MV(B,C)080–20
	CNPH*3617A**	27,400	TDR&TXV	15.50			12.50	58MV(B,C)100–20
	CNPH*3617A**	27,800	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*3617A**	27,600	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CNPH*3617A**	27,800	TDR&TXV	15.50			13.00	58CV(A,X)090–16
	CNPH*3617A**	27,800	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CNPH*3617A**	27,800	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*3617A**	27,800	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*3617A**	27,800	TDR&TXV	15.20			12.50	58PH*070–16
	CNPH*3617A**	27,800	TDR&TXV	15.50			12.50	58PH*090–16
	CNPH*3617A**	28,000	TDR&TXV	16.00			13.00	58MEB040–12

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB630A**30	CNPH*3617A**	28,000	TDR&TXV	15.50			13.00	58MEC060–12
	CNPH*3617A**	28,000	TDR&TXV	16.00			13.00	58MEC080–12
	CNPH*3617A**	28,200	TDR&TXV	15.50			13.00	58MEC080–16
	CNPH*3617A**	27,800	TDR&TXV	15.00			12.00	58HDV040– –12
	CNPH*3617A**	27,800	TDR&TXV	15.00			12.00	58HDV060– –12
	CNPH*3617A**	28,200	TDR&TXV	15.50			12.50	58HDV080– –20
	CNPH*3617A**	28,000	TDR&TXV	15.50			12.50	58HDV100– –20
	CNPH*3617A**	27,800	TDR&TXV	15.00			12.50	OVMAAB036098
	CNPH*3617A**	27,800	TDR&TXV	15.00			12.50	OVLAAB036098
	CNPH*3617A**	27,800	TDR&TXV	15.50			12.50	OVMAAB042112
	CNPH*3617A**	28,000	TDR&TXV	15.20			12.50	OVLAAB048112
	CNPH*4221A**	28,200	TXV			14.00	11.50	
	CNPH*4221A**	27,800	TDR&TXV	15.50			13.00	58MVB040–14
	CNPH*4221A**	28,200	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPH*4221A**	27,800	TDR&TXV	15.50			13.00	58MV(B,C)080–14
	CNPH*4221A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPH*4221A**	27,800	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CNPH*4221A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*4221A**	28,000	TDR&TXV	15.50			13.00	58CV(A,X)070–12
	CNPH*4221A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*4221A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPH*4221A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*4221A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*4221A**	28,200	TDR&TXV	15.50			12.50	58PH*070–16
	CNPH*4221A**	28,200	TDR&TXV	16.00			13.00	58PH*090–16
	CNPH*4221A**	28,400	TDR&TXV	16.00			13.00	58MEB040–12
	CNPH*4221A**	28,400	TDR&TXV	16.00			13.00	58MEC060–12
	CNPH*4221A**	28,200	TDR&TXV	16.00			13.00	58MEC080–12
	CNPH*4221A**	28,400	TDR&TXV	16.00			13.00	58MEC080–16
	CNPV*3014A**	27,800	TXV			14.00	12.00	
	CNPV*3014A**	27,600	TDR&TXV	15.20			12.50	58CV(A,X)070–12
	CNPV*3017A**	27,800	TXV			14.00	12.00	
	CNPV*3017A**	27,800	TDR&TXV	15.50			13.00	58MV(B,C)060–14
	CNPV*3017A**	27,800	TDR&TXV	15.50			13.00	58CV(A,X)090–16
	CNPV*3017A**	27,800	TDR&TXV	15.00			12.50	58PH*070–16
	CNPV*3017A**	28,000	TDR&TXV	16.00			13.00	58MEB040–12
	CNPV*3017A**	28,000	TDR&TXV	15.50			13.00	58MEC060–12
	CNPV*3017A**	28,000	TDR&TXV	16.00			13.00	58MEC080–12
	CNPV*3017A**	28,200	TDR&TXV	15.50			13.00	58MEC080–16
	CNPV*3017A**	27,600	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CNPV*3017A**	27,800	TDR&TXV	15.00			12.50	OVMAAB036098
	CNPV*3017A**	27,800	TDR&TXV	15.00			12.50	OVLAAB036098
	CNPV*3017A**	27,800	TDR&TXV	15.50			12.50	OVMAAB042112
	CNPV*3017A**	27,800	TDR&TXV	15.00			12.50	58HDV040– –12
	CNPV*3017A**	27,800	TDR&TXV	15.00			12.50	58HDV060– –12
	CNPV*3117A**	28,400	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPV*3117A**	28,200	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPV*3117A**	28,400	TDR&TXV	15.50			13.00	58PH*070–16
	CNPV*3117A**	28,600	TDR&TXV	16.00			13.00	58MEB040–12
	CNPV*3117A**	28,800	TDR&TXV	16.00			13.00	58MEC060–12
	CNPV*3117A**	28,600	TDR&TXV	16.00			13.00	58MEC080–12
	CNPV*3117A**	28,800	TDR&TXV	16.00			13.00	58MEC080–16
	CNPV*3117A**	28,200	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CNPV*3117A**	28,400	TDR&TXV	15.50			13.00	OVMAAB036098

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB630A**30	CNPV*3117A**	28,400	TDR&TXV	15.50			13.00	OVLAAB036098
	CNPV*3117A**	28,400	TDR&TXV	16.00			13.00	OVMAAB042112
	CNPV*3117A**	28,400	TDR&TXV	15.00			12.50	58HDV040 – – 12
	CNPV*3117A**	28,600	TDR&TXV	15.20			12.50	58HDV060 – – 12
	CNPV*3617A**	27,800	TXV			14.00	12.00	
	CNPV*3617A**	27,800	TDR&TXV	15.50			13.00	58MV(B,C)060 – 14
	CNPV*3617A**	27,800	TDR&TXV	15.50			13.00	58CV(A,X)090 – 16
	CNPV*3617A**	27,800	TDR&TXV	15.00			12.50	58PH*070 – 16
	CNPV*3617A**	28,000	TDR&TXV	16.00			13.00	58MEB040 – 12
	CNPV*3617A**	28,000	TDR&TXV	15.50			13.00	58MEC060 – 12
	CNPV*3617A**	28,000	TDR&TXV	16.00			13.00	58MEC080 – 12
	CNPV*3617A**	28,200	TDR&TXV	15.50			13.00	58MEC080 – 16
	CNPV*3617A**	27,600	TDR&TXV	15.50			12.50	58CV(A,X)070 – 12
	CNPV*3617A**	27,800	TDR&TXV	15.00			12.50	OVMAAB036098
	CNPV*3617A**	27,800	TDR&TXV	15.00			12.50	OVLAAB036098
	CNPV*3617A**	27,800	TDR&TXV	15.50			12.50	OVMAAB042112
	CNPV*3617A**	27,800	TDR&TXV	15.00			12.50	58HDV040 – – 12
	CNPV*3617A**	27,800	TDR&TXV	15.00			12.50	58HDV060 – – 12
	CNPV*3621A**	27,800	TXV			14.00	12.00	
	CNPV*3621A**	27,600	TDR&TXV	15.50			12.50	58MV(B,C)080 – 14
	CNPV*3621A**	27,600	TDR&TXV	15.50			12.50	58MV(B,C)080 – 20
	CNPV*3621A**	27,400	TDR&TXV	15.50			12.50	58MV(B,C)100 – 20
	CNPV*3621A**	27,800	TDR&TXV	15.50			13.00	58CV(A,X)110 – 20
	CNPV*3621A**	27,800	TDR&TXV	15.50			12.50	58PH*090 – 16
	CNPV*3621A**	27,800	TDR&TXV	15.50			13.00	58MV(B,C)060 – 14
	CNPV*3621A**	27,800	TDR&TXV	16.00			13.00	58CV(A,X)090 – 16
	CNPV*3621A**	27,800	TDR&TXV	15.00			12.50	58PH*070 – 16
	CNPV*3621A**	28,000	TDR&TXV	16.00			13.00	58MEB040 – 12
	CNPV*3621A**	28,000	TDR&TXV	15.50			13.00	58MEC060 – 12
	CNPV*3621A**	28,000	TDR&TXV	16.00			13.00	58MEC080 – 12
	CNPV*3621A**	28,200	TDR&TXV	15.50			13.00	58MEC080 – 16
	CNPV*3621A**	28,000	TDR&TXV	15.20			12.50	OVLAAB048112
	CNPV*3621A**	27,800	TDR&TXV	15.00			12.50	58HDV040 – – 12
	CNPV*3621A**	27,800	TDR&TXV	15.00			12.50	58HDV060 – – 12
	CNPV*3621A**	28,200	TDR&TXV	15.50			12.50	58HDV080 – – 20
	CNPV*3717A**	28,800	TXV			14.50	12.00	
	CNPV*3717A**	28,800	TDR&TXV	16.00			13.00	58MV(B,C)060 – 14
	CNPV*3717A**	28,600	TDR&TXV	16.00			13.00	58CV(A,X)090 – 16
	CNPV*3717A**	28,800	TDR&TXV	16.00			13.00	58PH*070 – 16
	CNPV*3717A**	29,000	TDR&TXV	16.00			13.50	58MEB040 – 12
	CNPV*3717A**	29,000	TDR&TXV	16.00			13.50	58MEC060 – 12
	CNPV*3717A**	29,000	TDR&TXV	16.00			13.50	58MEC080 – 12
	CNPV*3717A**	29,200	TDR&TXV	16.00			13.00	58MEC080 – 16
	CNPV*3717A**	28,600	TDR&TXV	15.50			13.00	OVMAAB036098
	CNPV*3717A**	28,600	TDR&TXV	16.00			13.00	OVLAAB036098
	CNPV*3717A**	28,800	TDR&TXV	16.00			13.00	OVMAAB042112
	CNPV*3717A**	28,600	TDR&TXV	15.50			13.00	58HDV040 – – 12
	CNPV*3717A**	29,000	TDR&TXV	15.50			13.00	58HDV060 – – 12
	CNPV*4217A**	28,400	TXV			14.00	12.00	
	CNPV*4217A**	28,200	TDR&TXV	16.00			13.00	58MV(B,C)060 – 14
	CNPV*4217A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)070 – 12
	CNPV*4217A**	28,200	TDR&TXV	16.00			13.00	58CV(A,X)090 – 16
	CNPV*4217A**	28,400	TDR&TXV	15.50			13.00	58PH*070 – 16
	CNPV*4217A**	28,600	TDR&TXV	16.00			13.00	58MEB040 – 12

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB630A**30	CNPV*4217A**	28,600	TDR&TXV	16.00			13.00	58MEC060–12
	CNPV*4217A**	28,400	TDR&TXV	16.00			13.00	58MEC080–12
	CNPV*4217A**	28,600	TDR&TXV	16.00			13.00	58MEC080–16
	CNPV*4221A**	28,200	TXV			14.00	11.50	
	CNPV*4221A**	28,200	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPV*4221A**	27,800	TDR&TXV	15.50			13.00	58MV(B,C)080–14
	CNPV*4221A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPV*4221A**	27,800	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CNPV*4221A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPV*4221A**	28,000	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPV*4221A**	28,200	TDR&TXV	15.50			12.50	58PH*070–16
	CNPV*4221A**	28,200	TDR&TXV	16.00			13.00	58PH*090–16
	CNPV*4221A**	28,400	TDR&TXV	16.00			13.00	58MEB040–12
	CNPV*4221A**	28,400	TDR&TXV	16.00			13.00	58MEC060–12
	CNPV*4221A**	28,200	TDR&TXV	16.00			13.00	58MEC080–12
	CNPV*4221A**	28,400	TDR&TXV	16.00			13.00	58MEC080–16
	CSPH*3012A**	28,000	TXV			14.00	11.50	
	CSPH*3012A**	27,800	TDR&TXV	15.50			12.50	58MVB040–14
	CSPH*3012A**	28,000	TDR&TXV	15.50			13.00	58MV(B,C)060–14
	CSPH*3012A**	27,600	TDR&TXV	15.50			12.50	58MV(B,C)080–14
	CSPH*3012A**	27,800	TDR&TXV	15.50			12.50	58MV(B,C)080–20
	CSPH*3012A**	27,600	TDR&TXV	15.50			12.50	58MV(B,C)100–20
	CSPH*3012A**	27,800	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CSPH*3012A**	27,800	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CSPH*3012A**	27,800	TDR&TXV	15.50			13.00	58CV(A,X)090–16
	CSPH*3012A**	27,800	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CSPH*3012A**	27,800	TDR&TXV	15.50			13.00	58CV(A,X)135–22
	CSPH*3012A**	27,800	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*3012A**	27,800	TDR&TXV	15.20			12.50	58PH*070–16
	CSPH*3012A**	27,800	TDR&TXV	15.50			12.50	58PH*090–16
	CSPH*3012A**	28,000	TDR&TXV	16.00			13.00	58MEB040–12
	CSPH*3012A**	28,000	TDR&TXV	15.50			13.00	58MEC060–12
	CSPH*3012A**	28,000	TDR&TXV	16.00			13.00	58MEC080–12
	CSPH*3012A**	28,200	TDR&TXV	15.50			13.00	58MEC080–16
	CSPH*3012A**	27,800	TDR&TXV	15.00			12.50	58HDV040–12
	CSPH*3012A**	27,800	TDR&TXV	15.00			12.50	58HDV060–12
	CSPH*3012A**	28,200	TDR&TXV	15.50			12.50	58HDV080–20
	CSPH*3012A**	28,000	TDR&TXV	15.50			12.50	58HDV100–20
	CSPH*3012A**	27,800	TDR&TXV	15.00			12.50	OVMAAB036098
	CSPH*3012A**	27,800	TDR&TXV	15.00			12.50	OVLAAB036098
	CSPH*3012A**	28,000	TDR&TXV	15.50			12.50	OVMAAB042112
	CSPH*3012A**	28,000	TDR&TXV	15.20			12.50	OVLAAB048112
	CSPH*3612A**	28,400	TXV			14.00	12.00	
	CSPH*3612A**	28,200	TDR&TXV	16.00			13.00	58MVB040–14
	CSPH*3612A**	28,400	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CSPH*3612A**	28,200	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CSPH*3612A**	28,200	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CSPH*3612A**	28,000	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CSPH*3612A**	28,200	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CSPH*3612A**	28,200	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CSPH*3612A**	28,200	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CSPH*3612A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CSPH*3612A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*3612A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)155–22

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB630A**30	CSPH*3612A**	28,400	TDR&TXV	15.50			13.00	58PH*070–16
	CSPH*3612A**	28,600	TDR&TXV	16.00			13.00	58PH*090–16
	CSPH*3612A**	28,600	TDR&TXV	16.00			13.00	58MEB040–12
	CSPH*3612A**	28,600	TDR&TXV	16.00			13.00	58MEC060–12
	CSPH*3612A**	28,600	TDR&TXV	16.00			13.00	58MEC080–12
	CSPH*3612A**	28,800	TDR&TXV	16.00			13.00	58MEC080–16
	CSPH*3612A**	28,400	TDR&TXV	15.00			12.50	58HDV040– –12
	CSPH*3612A**	28,600	TDR&TXV	15.50			12.50	58HDV060– –12
	CSPH*3612A**	28,800	TDR&TXV	16.00			13.00	58HDV080– –20
	CSPH*3612A**	28,600	TDR&TXV	16.00			13.00	58HDV100– –20
	CSPH*3612A**	28,400	TDR&TXV	15.50			12.50	OVMAAB036098
	CSPH*3612A**	28,200	TDR&TXV	15.50			13.00	OVLAAB036098
	CSPH*3612A**	28,400	TDR&TXV	16.00			13.00	OVMAAB042112
	CSPH*3612A**	28,600	TDR&TXV	15.50			12.50	OVLAAB048112
	CSPH*4212A**	28,600	TXV			14.00	12.00	
	CSPH*4212A**	28,400	TDR&TXV	16.00			13.00	58MVB040–14
	CSPH*4212A**	28,600	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CSPH*4212A**	28,200	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CSPH*4212A**	28,400	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CSPH*4212A**	28,200	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CSPH*4212A**	28,400	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CSPH*4212A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CSPH*4212A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CSPH*4212A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CSPH*4212A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*4212A**	28,400	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*4212A**	28,600	TDR&TXV	16.00			13.00	58PH*070–16
	CSPH*4212A**	28,800	TDR&TXV	16.00			13.00	58PH*090–16
	CSPH*4212A**	28,800	TDR&TXV	16.00			13.00	58MEB040–12
	CSPH*4212A**	28,800	TDR&TXV	16.00			13.00	58MEC060–12
	CSPH*4212A**	28,800	TDR&TXV	16.00			13.00	58MEC080–12
	CSPH*4212A**	29,000	TDR&TXV	16.00			13.00	58MEC080–16
24ANB636A**30	*CNPV*3717A**	34,400	TXV			14.50	12.00	
	FB4CNF036	33,000	TDR		14.50		12.00	
	FB4CNF042	34,200	TDR		15.50		12.50	
	FB4CNF048	34,200	TDR		15.00		12.50	
	FE4AN(B,F)003	33,200	TDR&TXV	16.00			13.00	
	FE4AN(B,F)005	34,200	TDR&TXV	16.00			13.00	
	FE4ANB006	34,600	TDR&TXV	16.50			13.50	
	FE4ANF002	33,000	TDR&TXV	15.00			12.00	
	FE5ANB004	34,600	TDR&TXV	16.50			13.50	
	FF1ENP036	33,000	TDR&TXV	13.50			11.00	
	FF1ENP037	33,200	TDR&TXV	14.00			11.50	
	FV4CN(B,F)003	33,200	TDR&TXV	16.00			13.00	
	FV4CN(B,F)005	34,200	TDR&TXV	16.00			13.00	
	FV4CNB006	34,600	TDR&TXV	16.50			13.50	
	FV4CNF002	33,000	TDR&TXV	15.00			12.00	
	FX4DN(B,F)037	34,200	TDR&TXV	16.00			13.00	
	FX4DN(B,F)043	34,200	TDR&TXV	16.00			13.00	
	FX4DN(B,F)049	34,800	TDR&TXV	16.00			13.00	
	FY5BNF036	33,400	TDR		14.50		12.00	
	FY5BNF042	33,800	TDR		14.50		12.00	
CAP**3614A**	32,800	TXV			14.00	11.50		

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB636A**30	CAP**3614A**	32,800	TDR&TXV	15.00			12.00	58CV(A,X)070–12
	CAP**3614A**	32,600	TDR&TXV	14.00			11.50	58PH*045–08
	CAP**3617A**	33,000	TXV			14.00	11.50	
	CAP**3617A**	33,000	TDR&TXV	15.20			12.50	58MV(B,C)060–14
	CAP**3617A**	33,000	TDR&TXV	15.50			12.50	58CV(A,X)090–16
	CAP**3617A**	33,000	TDR&TXV	15.00			12.00	58PH*070–16
	CAP**3617A**	33,200	TDR&TXV	15.50			12.50	58MEB040–12
	CAP**3617A**	33,200	TDR&TXV	15.20			12.50	58MEC060–12
	CAP**3617A**	33,000	TDR&TXV	15.20			12.50	58MEC080–12
	CAP**3617A**	33,200	TDR&TXV	15.20			12.50	58MEC080–16
	CAP**3617A**	32,800	TDR&TXV	15.00			12.00	58CV(A,X)070–12
	CAP**3617A**	32,800	TDR&TXV	14.50			12.00	58PH*045–08
	CAP**3617A**	32,800	TDR&TXV	14.50			12.00	OVMAAB036098
	CAP**3617A**	32,800	TDR&TXV	14.50			12.00	OVLAAB036098
	CAP**3617A**	33,000	TDR&TXV	15.00			12.50	OVMAAB042112
	CAP**3619A**	33,000	TXV			14.00	11.50	
	CAP**3619A**	32,800	TDR&TXV	14.00			11.50	58HDV040– – 12
	CAP**3619A**	33,000	TDR&TXV	14.50			12.00	58HDV060– – 12
	CAP**3621A**	33,000	TXV			14.00	11.50	
	CAP**3621A**	33,000	TDR&TXV	15.20			12.00	58MV(B,C)080–14
	CAP**3621A**	33,000	TDR&TXV	15.20			12.50	58MV(B,C)080–20
	CAP**3621A**	33,000	TDR&TXV	15.50			12.50	58MV(B,C)100–20
	CAP**3621A**	33,000	TDR&TXV	15.50			12.50	58CV(A,X)110–20
	CAP**3621A**	33,200	TDR&TXV	15.50			12.50	58PH*090–16
	CAP**3621A**	33,400	TDR&TXV	15.50			12.50	58PH*110–20
	CAP**3621A**	33,200	TDR&TXV	16.00			13.00	58MEC100–20
	CAP**3621A**	33,200	TDR&TXV	15.50			12.50	58MV(B,C)060–14
	CAP**3621A**	33,000	TDR&TXV	15.50			12.50	58CV(A,X)090–16
	CAP**3621A**	33,000	TDR&TXV	15.00			12.00	58PH*070–16
	CAP**3621A**	33,200	TDR&TXV	15.50			12.50	58MEB040–12
	CAP**3621A**	33,400	TDR&TXV	15.50			12.50	58MEC060–12
	CAP**3621A**	33,200	TDR&TXV	15.50			12.50	58MEC080–12
	CAP**3621A**	33,200	TDR&TXV	15.20			12.50	58MEC080–16
	CAP**3621A**	33,200	TDR&TXV	15.00			12.50	OVLAAB048112
	CAP**4221A**	33,400	TXV			14.00	11.50	
	CAP**4221A**	33,200	TDR&TXV	15.20			12.50	58MV(B,C)080–14
	CAP**4221A**	33,200	TDR&TXV	15.50			12.50	58MV(B,C)080–20
	CAP**4221A**	33,200	TDR&TXV	15.50			12.50	58MV(B,C)100–20
	CAP**4221A**	33,200	TDR&TXV	15.50			12.50	58CV(A,X)110–20
	CAP**4221A**	33,400	TDR&TXV	16.00			13.00	58PH*090–16
	CAP**4221A**	33,600	TDR&TXV	16.00			13.00	58PH*110–20
	CAP**4221A**	33,400	TDR&TXV	16.00			13.00	58MEC100–20
	CAP**4221A**	33,400	TDR&TXV	15.50			12.50	58MV(B,C)060–14
	CAP**4221A**	33,200	TDR&TXV	15.50			12.50	58CV(A,X)090–16
	CAP**4221A**	33,200	TDR&TXV	15.00			12.00	58PH*070–16
	CAP**4221A**	33,400	TDR&TXV	15.50			12.50	58MEB040–12
	CAP**4221A**	33,600	TDR&TXV	15.50			12.50	58MEC060–12
	CAP**4221A**	33,400	TDR&TXV	15.50			12.50	58MEC080–12
	CAP**4221A**	33,400	TDR&TXV	15.50			12.50	58MEC080–16
	CAP**4221A**	33,400	TDR&TXV	15.00			12.50	OVLAAB048112
	CAP**4224A**	33,400	TXV			14.00	11.50	
	CAP**4224A**	33,000	TDR&TXV	15.20			12.50	58MVB040–14
	CAP**4224A**	33,200	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CAP**4224A**	33,200	TDR&TXV	16.00			13.00	58CV(A,X)135–22

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB636A**30	CAP**4224A**	33,400	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CAP**4224A**	33,600	TDR&TXV	15.50			12.50	58HDV100– –20
	CAP**4224A**	33,200	TDR&TXV	15.20			12.50	58MV(B,C)080–14
	CAP**4224A**	33,200	TDR&TXV	15.50			12.50	58MV(B,C)080–20
	CAP**4224A**	33,200	TDR&TXV	15.50			12.50	58MV(B,C)100–20
	CAP**4224A**	33,200	TDR&TXV	15.50			12.50	58CV(A,X)110–20
	CAP**4224A**	33,600	TDR&TXV	16.00			13.00	58PH*090–16
	CAP**4224A**	33,600	TDR&TXV	16.00			13.00	58PH*110–20
	CAP**4224A**	33,400	TDR&TXV	16.00			13.00	58MEC100–20
	CAP**4817A**	34,000	TXV			14.00	11.50	
	CAP**4817A**	34,000	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CAP**4817A**	33,600	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CAP**4817A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CAP**4817A**	33,800	TDR&TXV	14.50			12.00	58PH*045–08
	CAP**4817A**	33,800	TDR&TXV	15.20			12.00	58PH*070–16
	CAP**4817A**	34,000	TDR&TXV	16.00			13.00	58MEB040–12
	CAP**4817A**	34,200	TDR&TXV	16.00			13.00	58MEC060–12
	CAP**4817A**	34,000	TDR&TXV	16.00			13.00	58MEC080–12
	CAP**4817A**	34,200	TDR&TXV	16.00			13.00	58MEC080–16
	CAP**4821A**	33,800	TXV			14.00	11.50	
	CAP**4821A**	33,800	TDR&TXV	15.50			12.50	58MV(B,C)060–14
	CAP**4821A**	33,600	TDR&TXV	15.50			12.50	58MV(B,C)080–14
	CAP**4821A**	33,600	TDR&TXV	15.50			12.50	58MV(B,C)080–20
	CAP**4821A**	33,600	TDR&TXV	15.50			12.50	58MV(B,C)100–20
	CAP**4821A**	33,600	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CAP**4821A**	33,600	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CAP**4821A**	33,600	TDR&TXV	15.00			12.00	58PH*070–16
	CAP**4821A**	34,000	TDR&TXV	16.00			13.00	58PH*090–16
	CAP**4821A**	34,000	TDR&TXV	16.00			13.00	58PH*110–20
	CAP**4821A**	33,800	TDR&TXV	16.00			13.00	58MEB040–12
	CAP**4821A**	34,000	TDR&TXV	16.00			13.00	58MEC060–12
	CAP**4821A**	33,800	TDR&TXV	16.00			13.00	58MEC080–12
	CAP**4821A**	34,000	TDR&TXV	15.50			13.00	58MEC080–16
	CAP**4821A**	33,800	TDR&TXV	16.00			13.00	58MEC100–20
	CAP**4823A**	33,800	TXV			14.00	11.50	
	CAP**4823A**	33,800	TDR&TXV	15.00			12.00	58HDV060– –12
	CAP**4823A**	34,200	TDR&TXV	15.20			12.50	58HDV080– –20
	CAP**4824A**	33,800	TXV			14.00	11.50	
	CAP**4824A**	33,400	TDR&TXV	15.50			12.50	58MVB040–14
	CAP**4824A**	33,600	TDR&TXV	15.50			12.50	58MV(B,C)080–14
	CAP**4824A**	33,600	TDR&TXV	15.50			12.50	58MV(B,C)080–20
	CAP**4824A**	33,800	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CAP**4824A**	33,600	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CAP**4824A**	33,600	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CAP**4824A**	33,600	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CAP**4824A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CAP**4824A**	34,000	TDR&TXV	16.00			13.00	58PH*090–16
	CAP**4824A**	34,200	TDR&TXV	16.00			13.00	58PH*110–20
	CAP**4824A**	33,800	TDR&TXV	16.00			13.00	58MEC100–20
	CNPF*3618A**	33,000	TXV			14.00	11.00	
	CNPF*4818A**	33,800	TXV			14.00	11.50	
	CNPH*3617A**	33,000	TXV			14.00	11.50	
	CNPH*3617A**	32,600	TDR&TXV	15.00			12.00	58MVB040–14
	CNPH*3617A**	33,000	TDR&TXV	15.00			12.00	58MV(B,C)060–14

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB636A**30	CNPH*3617A**	32,800	TDR&TXV	15.00			12.00	58MV(B,C)080–14
	CNPH*3617A**	32,800	TDR&TXV	15.00			12.00	58MV(B,C)080–20
	CNPH*3617A**	33,000	TDR&TXV	15.00			12.00	58MV(B,C)100–20
	CNPH*3617A**	32,800	TDR&TXV	15.20			12.50	58MV(B,C)120–20
	CNPH*3617A**	32,800	TDR&TXV	15.00			12.00	58CV(A,X)070–12
	CNPH*3617A**	32,800	TDR&TXV	15.20			12.50	58CV(A,X)090–16
	CNPH*3617A**	32,800	TDR&TXV	15.20			12.50	58CV(A,X)110–20
	CNPH*3617A**	32,800	TDR&TXV	15.20			12.50	58CV(A,X)135–22
	CNPH*3617A**	33,000	TDR&TXV	15.50			12.50	58CV(A,X)155–22
	CNPH*3617A**	32,800	TDR&TXV	14.50			11.50	58PH*045–08
	CNPH*3617A**	32,800	TDR&TXV	14.50			12.00	58PH*070–16
	CNPH*3617A**	33,000	TDR&TXV	15.20			12.50	58PH*090–16
	CNPH*3617A**	33,000	TDR&TXV	15.50			12.50	58PH*110–20
	CNPH*3617A**	33,000	TDR&TXV	15.20			12.50	58MEB040–12
	CNPH*3617A**	33,000	TDR&TXV	15.00			12.00	58MEC060–12
	CNPH*3617A**	33,000	TDR&TXV	15.20			12.50	58MEC080–12
	CNPH*3617A**	33,000	TDR&TXV	15.00			12.00	58MEC080–16
	CNPH*3617A**	32,800	TDR&TXV	15.50			12.50	58MEC100–20
	CNPH*3617A**	32,600	TDR&TXV	14.00			11.50	58HDV040– –12
	CNPH*3617A**	32,800	TDR&TXV	14.50			11.50	58HDV060– –12
	CNPH*3617A**	33,200	TDR&TXV	14.50			12.00	58HDV080– –20
	CNPH*3617A**	33,000	TDR&TXV	15.00			12.00	58HDV100– –20
	CNPH*3617A**	32,800	TDR&TXV	14.50			12.00	OVMAAB036098
	CNPH*3617A**	32,600	TDR&TXV	14.50			12.00	OVLAAB036098
	CNPH*3617A**	32,800	TDR&TXV	15.00			12.00	OVMAAB042112
	CNPH*3617A**	33,000	TDR&TXV	14.50			12.00	OVLAAB048112
	CNPH*3617A**	33,600	TDR&TXV	15.00			12.00	OVLAAB060154
	CNPH*4221A**	33,400	TXV			14.00	11.50	
	CNPH*4221A**	33,000	TDR&TXV	15.00			12.00	58MVB040–14
	CNPH*4221A**	33,400	TDR&TXV	15.20			12.50	58MV(B,C)060–14
	CNPH*4221A**	33,200	TDR&TXV	15.00			12.00	58MV(B,C)080–14
	CNPH*4221A**	33,200	TDR&TXV	15.20			12.50	58MV(B,C)080–20
	CNPH*4221A**	33,200	TDR&TXV	15.50			12.50	58MV(B,C)100–20
	CNPH*4221A**	33,200	TDR&TXV	15.50			12.50	58MV(B,C)120–20
	CNPH*4221A**	33,000	TDR&TXV	15.20			12.00	58CV(A,X)070–12
	CNPH*4221A**	33,200	TDR&TXV	15.50			12.50	58CV(A,X)090–16
	CNPH*4221A**	33,200	TDR&TXV	15.50			12.50	58CV(A,X)110–20
	CNPH*4221A**	33,200	TDR&TXV	15.50			12.50	58CV(A,X)135–22
	CNPH*4221A**	33,400	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*4221A**	33,200	TDR&TXV	14.50			12.00	58PH*045–08
	CNPH*4221A**	33,200	TDR&TXV	15.00			12.00	58PH*070–16
	CNPH*4221A**	33,400	TDR&TXV	15.50			12.50	58PH*090–16
	CNPH*4221A**	33,600	TDR&TXV	16.00			13.00	58PH*110–20
	CNPH*4221A**	33,400	TDR&TXV	15.50			12.50	58MEB040–12
	CNPH*4221A**	33,400	TDR&TXV	15.50			12.50	58MEC060–12
	CNPH*4221A**	33,400	TDR&TXV	15.50			12.50	58MEC080–12
	CNPH*4221A**	33,400	TDR&TXV	15.50			12.50	58MEC080–16
	CNPH*4221A**	33,200	TDR&TXV	16.00			13.00	58MEC100–20
	CNPH*4221A**	33,000	TDR&TXV	14.00			11.50	58HDV040– –12
	CNPH*4221A**	33,400	TDR&TXV	14.50			12.00	58HDV060– –12
	CNPH*4221A**	33,800	TDR&TXV	15.00			12.00	58HDV080– –20
	CNPH*4221A**	33,600	TDR&TXV	15.20			12.00	58HDV100– –20
	CNPH*4221A**	33,000	TDR&TXV	14.50			12.00	OVMAAB036098
	CNPH*4221A**	33,000	TDR&TXV	14.50			12.00	OVLAAB036098

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB636A**30	CNPH*4221A**	33,200	TDR&TXV	15.00			12.50	OVMAAB042112
	CNPH*4221A**	33,400	TDR&TXV	15.00			12.00	OVLAAB048112
	CNPH*4221A**	34,000	TDR&TXV	15.50			12.50	OVLAAB060154
	CNPH*4321A**	34,400	TXV			14.00	11.50	
	CNPH*4321A**	34,000	TDR&TXV	15.50			12.50	58MVB040–14
	CNPH*4321A**	34,200	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPH*4321A**	34,000	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CNPH*4321A**	34,000	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPH*4321A**	34,200	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CNPH*4321A**	34,000	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*4321A**	34,000	TDR&TXV	16.00			13.00	58CV(A,X)070–12
	CNPH*4321A**	34,000	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*4321A**	34,200	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPH*4321A**	34,200	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*4321A**	34,200	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*4321A**	34,200	TDR&TXV	15.00			12.00	58PH*045–08
	CNPH*4321A**	34,200	TDR&TXV	15.50			12.50	58PH*070–16
	CNPH*4321A**	34,400	TDR&TXV	16.00			13.00	58PH*090–16
	CNPH*4321A**	34,600	TDR&TXV	16.00			13.00	58PH*110–20
	CNPH*4321A**	34,400	TDR&TXV	16.00			13.00	58MEB040–12
	CNPH*4321A**	34,600	TDR&TXV	16.00			13.00	58MEC060–12
	CNPH*4321A**	34,400	TDR&TXV	16.00			13.00	58MEC080–12
	CNPH*4321A**	34,400	TDR&TXV	16.00			13.00	58MEC080–16
	CNPH*4321A**	34,400	TDR&TXV	16.00			13.00	58MEC100–20
	CNPH*4321A**	34,000	TDR&TXV	14.50			12.00	58HDV040–12
	CNPH*4321A**	34,400	TDR&TXV	15.20			12.00	58HDV060–12
	CNPH*4321A**	34,800	TDR&TXV	15.50			12.50	58HDV080–20
	CNPH*4321A**	34,600	TDR&TXV	16.00			13.00	58HDV100–20
	CNPH*4321A**	34,000	TDR&TXV	15.20			12.50	OVMAAB036098
	CNPH*4321A**	33,800	TDR&TXV	15.20			12.50	OVLAAB036098
	CNPH*4321A**	34,200	TDR&TXV	16.00			13.00	OVMAAB042112
	CNPH*4321A**	34,200	TDR&TXV	15.50			12.50	OVLAAB048112
	CNPH*4321A**	35,000	TDR&TXV	16.00			13.00	OVLAAB060154
	CNPH*4821A**	34,000	TXV			14.00	11.50	
	CNPH*4821A**	33,600	TDR&TXV	15.50			12.50	58MVB040–14
	CNPH*4821A**	33,800	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPH*4821A**	33,800	TDR&TXV	15.50			12.50	58MV(B,C)080–14
	CNPH*4821A**	33,600	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPH*4821A**	33,800	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CNPH*4821A**	33,800	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*4821A**	33,600	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CNPH*4821A**	33,600	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*4821A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPH*4821A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*4821A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*4821A**	33,800	TDR&TXV	15.00			12.00	58PH*045–08
	CNPH*4821A**	33,800	TDR&TXV	15.20			12.50	58PH*070–16
	CNPH*4821A**	34,000	TDR&TXV	16.00			13.00	58PH*090–16
	CNPH*4821A**	34,200	TDR&TXV	16.00			13.00	58PH*110–20
	CNPH*4821A**	34,000	TDR&TXV	16.00			13.00	58MEB040–12
	CNPH*4821A**	34,200	TDR&TXV	16.00			13.00	58MEC060–12
	CNPH*4821A**	34,000	TDR&TXV	16.00			13.00	58MEC080–12
	CNPH*4821A**	34,200	TDR&TXV	16.00			13.00	58MEC080–16
	CNPH*4821A**	34,000	TDR&TXV	16.00			13.00	58MEC100–20

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB636A**30	CNPH*6024A**	34,200	TXV			14.50	12.00	
	CNPH*6024A**	34,400	TDR&TXV	16.00			13.00	58PH*090–16
	CNPV*3617A**	33,000	TXV			14.00	11.50	
	CNPV*3617A**	33,000	TDR&TXV	15.00			12.00	58MV(B,C)060–14
	CNPV*3617A**	32,800	TDR&TXV	15.20			12.00	58CV(A,X)090–16
	CNPV*3617A**	32,800	TDR&TXV	14.50			12.00	58PH*070–16
	CNPV*3617A**	33,000	TDR&TXV	15.20			12.00	58MEB040–12
	CNPV*3617A**	33,000	TDR&TXV	15.00			12.00	58MEC060–12
	CNPV*3617A**	33,000	TDR&TXV	15.20			12.00	58MEC080–12
	CNPV*3617A**	33,000	TDR&TXV	15.00			12.00	58MEC080–16
	CNPV*3617A**	32,800	TDR&TXV	15.00			12.00	58CV(A,X)070–12
	CNPV*3617A**	32,800	TDR&TXV	14.50			11.50	58PH*045–08
	CNPV*3617A**	32,800	TDR&TXV	14.50			12.00	OVMAAB036098
	CNPV*3617A**	32,600	TDR&TXV	14.50			12.00	OVLAAB036098
	CNPV*3617A**	32,800	TDR&TXV	15.00			12.00	OVMAAB042112
	CNPV*3617A**	32,600	TDR&TXV	14.00			11.50	58HDV040– – 12
	CNPV*3617A**	32,800	TDR&TXV	14.50			12.00	58HDV060– – 12
	CNPV*3621A**	33,000	TXV			14.00	11.50	
	CNPV*3621A**	32,800	TDR&TXV	15.00			12.00	58MV(B,C)080–14
	CNPV*3621A**	32,800	TDR&TXV	15.00			12.00	58MV(B,C)080–20
	CNPV*3621A**	33,000	TDR&TXV	15.00			12.00	58MV(B,C)100–20
	CNPV*3621A**	33,000	TDR&TXV	15.20			12.50	58CV(A,X)110–20
	CNPV*3621A**	33,000	TDR&TXV	15.50			12.50	58PH*090–16
	CNPV*3621A**	33,200	TDR&TXV	15.50			12.50	58PH*110–20
	CNPV*3621A**	32,800	TDR&TXV	15.50			12.50	58MEC100–20
	CNPV*3621A**	33,000	TDR&TXV	15.00			12.00	58MV(B,C)060–14
	CNPV*3621A**	32,800	TDR&TXV	15.20			12.50	58CV(A,X)090–16
	CNPV*3621A**	32,800	TDR&TXV	14.50			12.00	58PH*070–16
	CNPV*3621A**	33,000	TDR&TXV	15.20			12.50	58MEB040–12
	CNPV*3621A**	33,000	TDR&TXV	15.20			12.00	58MEC060–12
	CNPV*3621A**	33,000	TDR&TXV	15.20			12.50	58MEC080–12
	CNPV*3621A**	33,000	TDR&TXV	15.00			12.00	58MEC080–16
	CNPV*3621A**	33,000	TDR&TXV	14.50			12.00	OVLAAB048112
	CNPV*3621A**	32,600	TDR&TXV	14.00			11.50	58HDV040– – 12
	CNPV*3621A**	33,000	TDR&TXV	14.50			12.00	58HDV060– – 12
	CNPV*3621A**	33,400	TDR&TXV	15.00			12.00	58HDV080– – 20
	CNPV*3717A**	34,200	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPV*3717A**	34,000	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPV*3717A**	34,200	TDR&TXV	15.50			12.50	58PH*070–16
	CNPV*3717A**	34,400	TDR&TXV	16.00			13.00	58MEB040–12
	CNPV*3717A**	34,400	TDR&TXV	16.00			13.00	58MEC060–12
	CNPV*3717A**	34,200	TDR&TXV	16.00			13.00	58MEC080–12
	CNPV*3717A**	34,400	TDR&TXV	16.00			13.00	58MEC080–16
	CNPV*3717A**	34,000	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CNPV*3717A**	34,000	TDR&TXV	15.00			12.00	58PH*045–08
	CNPV*3717A**	34,000	TDR&TXV	15.20			12.50	OVMAAB036098
	CNPV*3717A**	33,800	TDR&TXV	15.00			12.50	OVLAAB036098
	CNPV*3717A**	34,000	TDR&TXV	15.50			12.50	OVMAAB042112
	CNPV*3717A**	34,000	TDR&TXV	14.50			12.00	58HDV040– – 12
	CNPV*3717A**	34,200	TDR&TXV	15.00			12.50	58HDV060– – 12
	CNPV*4217A**	33,800	TXV			14.00	11.50	
	CNPV*4217A**	33,600	TDR&TXV	15.50			12.50	58MV(B,C)060–14
	CNPV*4217A**	33,400	TDR&TXV	15.50			12.50	58CV(A,X)090–16
	CNPV*4217A**	33,400	TDR&TXV	15.00			12.00	58PH*070–16

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB636A**30	CNPV*4217A**	33,600	TDR&TXV	15.50			12.50	58MEB040–12
	CNPV*4217A**	33,800	TDR&TXV	15.50			12.50	58MEC060–12
	CNPV*4217A**	33,600	TDR&TXV	15.50			12.50	58MEC080–12
	CNPV*4217A**	33,800	TDR&TXV	15.50			12.50	58MEC080–16
	CNPV*4217A**	33,400	TDR&TXV	15.20			12.50	58CV(A,X)070–12
	CNPV*4217A**	33,400	TDR&TXV	14.50			11.50	58PH*045–08
	CNPV*4217A**	33,400	TDR&TXV	15.00			12.00	OVMAAB036098
	CNPV*4217A**	33,200	TDR&TXV	15.00			12.00	OVLAAB036098
	CNPV*4217A**	33,400	TDR&TXV	15.50			12.50	OVMAAB042112
	CNPV*4217A**	33,200	TDR&TXV	14.50			12.00	58HDV040– – 12
	CNPV*4217A**	33,600	TDR&TXV	15.00			12.00	58HDV060– – 12
	CNPV*4221A**	33,400	TXV			14.00	11.50	
	CNPV*4221A**	33,200	TDR&TXV	15.00			12.00	58MV(B,C)080–14
	CNPV*4221A**	33,200	TDR&TXV	15.20			12.50	58MV(B,C)080–20
	CNPV*4221A**	33,200	TDR&TXV	15.50			12.50	58MV(B,C)100–20
	CNPV*4221A**	33,200	TDR&TXV	15.50			12.50	58CV(A,X)110–20
	CNPV*4221A**	33,400	TDR&TXV	15.50			12.50	58PH*090–16
	CNPV*4221A**	33,600	TDR&TXV	16.00			13.00	58PH*110–20
	CNPV*4221A**	33,200	TDR&TXV	16.00			13.00	58MEC100–20
	CNPV*4221A**	33,400	TDR&TXV	15.20			12.50	58MV(B,C)060–14
	CNPV*4221A**	33,200	TDR&TXV	15.50			12.50	58CV(A,X)090–16
	CNPV*4221A**	33,200	TDR&TXV	15.00			12.00	58PH*070–16
	CNPV*4221A**	33,400	TDR&TXV	15.50			12.50	58MEB040–12
	CNPV*4221A**	33,400	TDR&TXV	15.50			12.50	58MEC060–12
	CNPV*4221A**	33,400	TDR&TXV	15.50			12.50	58MEC080–12
	CNPV*4221A**	33,400	TDR&TXV	15.50			12.50	58MEC080–16
	CNPV*4221A**	33,400	TDR&TXV	15.00			12.00	OVLAAB048112
	CNPV*4221A**	33,000	TDR&TXV	14.50			12.00	58HDV040– – 12
	CNPV*4221A**	33,400	TDR&TXV	14.50			12.00	58HDV060– – 12
	CNPV*4221A**	33,800	TDR&TXV	15.00			12.00	58HDV080– – 20
	CNPV*4324A**	34,400	TXV			14.50	12.00	
	CNPV*4324A**	34,000	TDR&TXV	16.00			13.00	58MVB040–14
	CNPV*4324A**	34,200	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPV*4324A**	34,200	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPV*4324A**	34,200	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPV*4324A**	34,600	TDR&TXV	16.00			13.00	58HDV100– – 20
	CNPV*4324A**	34,200	TDR&TXV	16.00			13.00	58MV(B,C)080–14
	CNPV*4324A**	34,000	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPV*4324A**	34,200	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CNPV*4324A**	34,200	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPV*4324A**	34,600	TDR&TXV	16.00			13.00	58PH*090–16
	CNPV*4324A**	34,800	TDR&TXV	16.00			13.00	58PH*110–20
	CNPV*4324A**	34,400	TDR&TXV	16.00			13.00	58MEC100–20
	CNPV*4324A**	34,800	TDR&TXV	16.00			13.00	58HDV080– – 20
	CNPV*4324A**	34,800	TDR&TXV	16.00			13.00	58HDV080– – 20
	CNPV*4324A**	34,600	TDR&TXV	16.00			13.00	58HDV100– – 20
	CNPV*4821A**	34,000	TXV			14.00	11.50	
	CNPV*4821A**	33,800	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CNPV*4821A**	33,800	TDR&TXV	15.50			12.50	58MV(B,C)080–14
	CNPV*4821A**	33,600	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPV*4821A**	33,800	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CNPV*4821A**	33,600	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPV*4821A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPV*4821A**	33,800	TDR&TXV	15.20			12.50	58PH*070–16

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB636A**30	CNPV*4821A**	34,000	TDR&TXV	16.00			13.00	58PH*090–16
	CNPV*4821A**	34,200	TDR&TXV	16.00			13.00	58PH*110–20
	CNPV*4821A**	34,000	TDR&TXV	16.00			13.00	58MEB040–12
	CNPV*4821A**	34,200	TDR&TXV	16.00			13.00	58MEC060–12
	CNPV*4821A**	34,000	TDR&TXV	16.00			13.00	58MEC080–12
	CNPV*4821A**	34,200	TDR&TXV	16.00			13.00	58MEC080–16
	CNPV*4821A**	34,000	TDR&TXV	16.00			13.00	58MEC100–20
	CNPV*4824A**	34,000	TXV			14.00	11.50	
	CNPV*4824A**	33,600	TDR&TXV	15.50			12.50	58MVB040–14
	CNPV*4824A**	33,800	TDR&TXV	15.50			12.50	58MV(B,C)080–14
	CNPV*4824A**	33,600	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CNPV*4824A**	33,800	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CNPV*4824A**	33,800	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPV*4824A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPV*4824A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPV*4824A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPV*4824A**	34,000	TDR&TXV	16.00			13.00	58PH*090–16
	CNPV*4824A**	34,200	TDR&TXV	16.00			13.00	58PH*110–20
	CNPV*4824A**	34,000	TDR&TXV	16.00			13.00	58MEC100–20
	CSPH*3612A**	33,800	TXV			14.00	11.50	
	CSPH*3612A**	33,400	TDR&TXV	15.20			12.50	58MVB040–14
	CSPH*3612A**	33,800	TDR&TXV	15.50			12.50	58MV(B,C)060–14
	CSPH*3612A**	33,600	TDR&TXV	15.20			12.50	58MV(B,C)080–14
	CSPH*3612A**	33,600	TDR&TXV	15.50			12.50	58MV(B,C)080–20
	CSPH*3612A**	33,800	TDR&TXV	15.50			12.50	58MV(B,C)100–20
	CSPH*3612A**	33,600	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CSPH*3612A**	33,400	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CSPH*3612A**	33,600	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CSPH*3612A**	33,600	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CSPH*3612A**	33,600	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*3612A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*3612A**	33,600	TDR&TXV	14.50			12.00	58PH*045–08
	CSPH*3612A**	33,600	TDR&TXV	15.00			12.00	58PH*070–16
	CSPH*3612A**	33,800	TDR&TXV	16.00			13.00	58PH*090–16
	CSPH*3612A**	34,000	TDR&TXV	16.00			13.00	58PH*110–20
	CSPH*3612A**	33,800	TDR&TXV	16.00			13.00	58MEB040–12
	CSPH*3612A**	33,800	TDR&TXV	15.50			12.50	58MEC060–12
	CSPH*3612A**	33,800	TDR&TXV	16.00			13.00	58MEC080–12
	CSPH*3612A**	33,800	TDR&TXV	15.50			12.50	58MEC080–16
	CSPH*3612A**	33,800	TDR&TXV	16.00			13.00	58MEC100–20
	CSPH*3612A**	33,400	TDR&TXV	14.50			12.00	58HDV040– –12
	CSPH*3612A**	33,800	TDR&TXV	15.00			12.00	58HDV060– –12
	CSPH*3612A**	34,200	TDR&TXV	15.20			12.50	58HDV080– –20
	CSPH*3612A**	34,000	TDR&TXV	15.50			12.50	58HDV100– –20
	CSPH*3612A**	33,400	TDR&TXV	15.00			12.00	OVMAAB036098
	CSPH*3612A**	33,400	TDR&TXV	15.00			12.00	OVLAAB036098
	CSPH*3612A**	33,600	TDR&TXV	15.50			12.50	OVMAAB042112
	CSPH*3612A**	33,800	TDR&TXV	15.20			12.50	OVLAAB048112
	CSPH*3612A**	34,400	TDR&TXV	15.50			12.50	OVLAAB060154
	CSPH*4212A**	34,000	TXV			14.00	11.50	
	CSPH*4212A**	33,600	TDR&TXV	15.50			12.50	58MVB040–14
	CSPH*4212A**	34,000	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CSPH*4212A**	33,800	TDR&TXV	15.50			12.50	58MV(B,C)080–14
	CSPH*4212A**	33,800	TDR&TXV	15.50			12.50	58MV(B,C)080–20

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB636A**30	CSPH*4212A**	34,000	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CSPH*4212A**	33,800	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CSPH*4212A**	33,600	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CSPH*4212A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CSPH*4212A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CSPH*4212A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*4212A**	34,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*4212A**	33,800	TDR&TXV	15.00			12.00	58PH*045–08
	CSPH*4212A**	33,800	TDR&TXV	15.20			12.50	58PH*070–16
	CSPH*4212A**	34,000	TDR&TXV	16.00			13.00	58PH*090–16
	CSPH*4212A**	34,200	TDR&TXV	16.00			13.00	58PH*110–20
	CSPH*4212A**	34,000	TDR&TXV	16.00			13.00	58MEB040–12
	CSPH*4212A**	34,200	TDR&TXV	16.00			13.00	58MEC060–12
	CSPH*4212A**	34,000	TDR&TXV	16.00			13.00	58MEC080–12
	CSPH*4212A**	34,200	TDR&TXV	16.00			13.00	58MEC080–16
	CSPH*4212A**	34,000	TDR&TXV	16.00			13.00	58MEC100–20
	CSPH*4212A**	33,600	TDR&TXV	14.50			12.00	58HDV040– –12
	CSPH*4212A**	34,000	TDR&TXV	15.00			12.00	58HDV060– –12
	CSPH*4212A**	34,400	TDR&TXV	15.50			12.50	58HDV080– –20
	CSPH*4212A**	34,200	TDR&TXV	16.00			13.00	58HDV100– –20
	CSPH*4212A**	33,600	TDR&TXV	15.00			12.00	OVMAAB036098
	CSPH*4212A**	33,600	TDR&TXV	15.00			12.00	OVLAAB036098
	CSPH*4212A**	33,800	TDR&TXV	15.50			12.50	OVMAAB042112
	CSPH*4212A**	34,000	TDR&TXV	15.50			12.50	OVLAAB048112
	CSPH*4212A**	34,600	TDR&TXV	16.00			13.00	OVLAAB060154
	CSPH*4812A**	34,200	TXV			14.00	11.50	
	CSPH*4812A**	33,800	TDR&TXV	15.50			12.50	58MVB040–14
	CSPH*4812A**	34,000	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CSPH*4812A**	34,000	TDR&TXV	15.50			12.50	58MV(B,C)080–14
	CSPH*4812A**	33,800	TDR&TXV	16.00			13.00	58MV(B,C)080–20
	CSPH*4812A**	34,000	TDR&TXV	16.00			13.00	58MV(B,C)100–20
	CSPH*4812A**	34,000	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CSPH*4812A**	33,800	TDR&TXV	15.50			12.50	58CV(A,X)070–12
	CSPH*4812A**	33,800	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CSPH*4812A**	34,000	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CSPH*4812A**	34,000	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*4812A**	34,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*4812A**	34,000	TDR&TXV	15.00			12.00	58PH*045–08
	CSPH*4812A**	34,000	TDR&TXV	15.20			12.50	58PH*070–16
	CSPH*4812A**	34,200	TDR&TXV	16.00			13.00	58PH*090–16
	CSPH*4812A**	34,400	TDR&TXV	16.00			13.00	58PH*110–20
	CSPH*4812A**	34,200	TDR&TXV	16.00			13.00	58MEB040–12
	CSPH*4812A**	34,200	TDR&TXV	16.00			13.00	58MEC060–12
	CSPH*4812A**	34,200	TDR&TXV	16.00			13.00	58MEC080–12
	CSPH*4812A**	34,200	TDR&TXV	16.00			13.00	58MEC080–16
	CSPH*4812A**	34,000	TDR&TXV	16.00			13.00	58MEC100–20
24ANB642A**30	*CNPV*4324A**	42,000	TXV			14.50	12.00	
	FB4CNF042	41,500	TDR		15.00		12.50	
	FB4CNF048	41,500	TDR		15.00		13.00	
	FB4CNF060	42,000	TDR&TXV	15.50	15.50		13.00	
	FE4AN(B,F)003	40,000	TDR&TXV	15.50			13.00	
	FE4AN(B,F)005	41,500	TDR&TXV	16.00			13.00	
	FE4ANB006	42,000	TDR&TXV	16.00			13.00	

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB642A**30	FE5ANB004	42,000	TDR&TXV	16.00			13.00	
	FV4CN(B,F)003	40,000	TDR&TXV	15.50			13.00	
	FV4CN(B,F)005	41,500	TDR&TXV	16.00			13.00	
	FV4CNB006	42,000	TDR&TXV	16.00			13.00	
	FX4DN(B,F)043	41,500	TDR&TXV	15.00			12.50	
	FX4DN(B,F)049	42,000	TDR&TXV	16.00			13.00	
	FX4DN(B,F)061	42,000	TDR&TXV	16.00			13.50	
	FY5BNF042	41,000	TDR		14.50		12.50	
	FY5BNF048	42,000	TDR		14.50		12.50	
	CAP**4221A**	40,500	TXV			14.00	11.50	
	CAP**4221A**	40,000	TDR&TXV	14.50			12.50	58MV(B,C)080–14
	CAP**4221A**	40,000	TDR&TXV	15.00			12.50	58MV(B,C)080–20
	CAP**4221A**	40,000	TDR&TXV	15.00			12.50	58MV(B,C)100–20
	CAP**4221A**	40,000	TDR&TXV	15.20			13.00	58CV(A,X)110–20
	CAP**4221A**	40,500	TDR&TXV	15.20			13.00	58PH*090–16
	CAP**4221A**	40,500	TDR&TXV	15.50			13.00	58PH*110–20
	CAP**4221A**	40,500	TDR&TXV	15.50			13.00	58MEC100–20
	CAP**4221A**	40,000	TDR&TXV	15.20			12.50	58CV(A,X)090–16
	CAP**4221A**	40,000	TDR&TXV	14.50			12.00	58PH*070–16
	CAP**4221A**	40,500	TDR&TXV	15.00			12.50	58MEB040–12
	CAP**4221A**	40,500	TDR&TXV	15.00			12.50	58MEC060–12
	CAP**4221A**	40,500	TDR&TXV	15.00			12.50	58MEC080–12
	CAP**4221A**	40,000	TDR&TXV	15.00			12.50	58MEC080–16
	CAP**4221A**	40,500	TDR&TXV	15.00			12.50	58MV(B,C)060–14
	CAP**4221A**	40,000	TDR&TXV	14.50			12.00	OVLAAB048112
	CAP**4224A**	40,500	TXV			14.00	11.50	
	CAP**4224A**	40,000	TDR&TXV	15.00			12.50	58MVB040–14
	CAP**4224A**	40,000	TDR&TXV	15.20			13.00	58MV(B,C)120–20
	CAP**4224A**	40,500	TDR&TXV	15.50			13.00	58CV(A,X)135–22
	CAP**4224A**	40,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CAP**4224A**	40,500	TDR&TXV	15.50			13.00	58PH*135–20
	CAP**4224A**	40,500	TDR&TXV	15.50			13.00	58MEC120–20
	CAP**4224A**	40,500	TDR&TXV	15.00			12.50	58HDV100– –20
	CAP**4224A**	40,000	TDR&TXV	15.00			12.50	58MV(B,C)080–14
	CAP**4224A**	40,000	TDR&TXV	15.00			12.50	58MV(B,C)080–20
	CAP**4224A**	40,000	TDR&TXV	15.00			12.50	58MV(B,C)100–20
	CAP**4224A**	40,000	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CAP**4224A**	40,500	TDR&TXV	15.50			13.00	58PH*090–16
	CAP**4224A**	40,500	TDR&TXV	15.50			13.00	58PH*110–20
	CAP**4224A**	40,500	TDR&TXV	15.50			13.00	58MEC100–20
	CAP**4817A**	41,500	TXV			14.00	12.00	
	CAP**4817A**	41,000	TDR&TXV	15.20			12.50	58MV(B,C)060–14
	CAP**4817A**	41,000	TDR&TXV	15.50			13.00	58CV(A,X)090–16
	CAP**4817A**	41,000	TDR&TXV	14.50			12.00	58PH*070–16
	CAP**4817A**	41,500	TDR&TXV	15.20			13.00	58MEB040–12
	CAP**4817A**	41,500	TDR&TXV	15.20			12.50	58MEC060–12
	CAP**4817A**	41,500	TDR&TXV	15.50			13.00	58MEC080–12
	CAP**4817A**	41,000	TDR&TXV	15.50			13.00	58MEC080–16
	CAP**4817A**	41,000	TDR&TXV	15.00			12.50	58CV(A,X)070–12
	CAP**4817A**	41,000	TDR&TXV	15.00			12.50	OVMAAB042112
	CAP**4821A**	41,000	TXV			14.00	12.00	
	CAP**4821A**	40,500	TDR&TXV	15.00			12.50	58MV(B,C)080–14
	CAP**4821A**	40,500	TDR&TXV	15.00			12.50	58MV(B,C)080–20
	CAP**4821A**	40,500	TDR&TXV	15.00			12.50	58MV(B,C)100–20

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB642A**30	CAP**4821A**	41,000	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CAP**4821A**	41,000	TDR&TXV	15.50			13.00	58PH*090–16
	CAP**4821A**	41,000	TDR&TXV	16.00			13.00	58PH*110–20
	CAP**4821A**	41,000	TDR&TXV	15.50			13.00	58MEC100–20
	CAP**4821A**	41,000	TDR&TXV	15.00			12.50	58MV(B,C)060–14
	CAP**4821A**	40,500	TDR&TXV	15.50			13.00	58CV(A,X)090–16
	CAP**4821A**	40,500	TDR&TXV	14.50			12.00	58PH*070–16
	CAP**4821A**	41,000	TDR&TXV	15.20			12.50	58MEB040–12
	CAP**4821A**	41,000	TDR&TXV	15.00			12.50	58MEC060–12
	CAP**4821A**	41,000	TDR&TXV	15.20			12.50	58MEC080–12
	CAP**4821A**	41,000	TDR&TXV	15.20			12.50	58MEC080–16
	CAP**4821A**	41,000	TDR&TXV	14.50			12.50	OVLAAB048112
	CAP**4823A**	41,000	TXV			14.00	12.00	
	CAP**4823A**	41,000	TDR&TXV	15.00			12.50	58HDV080– –20
	CAP**4824A**	41,000	TXV			14.00	12.00	
	CAP**4824A**	40,500	TDR&TXV	15.00			12.50	58MVB040–14
	CAP**4824A**	40,500	TDR&TXV	15.50			13.00	58MV(B,C)120–20
	CAP**4824A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CAP**4824A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CAP**4824A**	41,000	TDR&TXV	15.50			13.00	58PH*135–20
	CAP**4824A**	41,000	TDR&TXV	16.00			13.00	58MEC120–20
	CAP**4824A**	41,000	TDR&TXV	15.50			12.50	58HDV100– –20
	CAP**4824A**	40,500	TDR&TXV	15.00			12.50	58MV(B,C)080–14
	CAP**4824A**	40,500	TDR&TXV	15.20			12.50	58MV(B,C)080–20
	CAP**4824A**	40,500	TDR&TXV	15.20			12.50	58MV(B,C)100–20
	CAP**4824A**	41,000	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CAP**4824A**	41,000	TDR&TXV	15.50			13.00	58PH*090–16
	CAP**4824A**	41,000	TDR&TXV	16.00			13.00	58PH*110–20
	CAP**4824A**	41,000	TDR&TXV	16.00			13.00	58MEC100–20
	CAP**6021A**	42,000	TXV			14.50	12.00	
	CAP**6021A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)060–14
	CAP**6021A**	41,000	TDR&TXV	15.00			12.50	58MV(B,C)080–14
	CAP**6021A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–20
	CAP**6021A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CAP**6021A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CAP**6021A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CAP**6021A**	41,500	TDR&TXV	15.00			12.50	58PH*070–16
	CAP**6021A**	41,500	TDR&TXV	16.00			13.00	58PH*090–16
	CAP**6021A**	41,500	TDR&TXV	16.00			13.00	58PH*110–20
	CAP**6021A**	42,000	TDR&TXV	15.50			13.00	58MEB040–12
	CAP**6021A**	41,500	TDR&TXV	15.50			13.00	58MEC060–12
	CAP**6021A**	41,500	TDR&TXV	15.50			13.00	58MEC080–12
	CAP**6021A**	41,500	TDR&TXV	15.50			13.00	58MEC080–16
	CAP**6021A**	41,500	TDR&TXV	16.00			13.00	58MEC100–20
	CAP**6024A**	42,000	TXV			14.50	12.00	
	CAP**6024A**	41,000	TDR&TXV	15.20			13.00	58MVB040–14
	CAP**6024A**	41,500	TDR&TXV	15.20			12.50	58MV(B,C)080–14
	CAP**6024A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–20
	CAP**6024A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CAP**6024A**	41,500	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CAP**6024A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CAP**6024A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CAP**6024A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CAP**6024A**	41,500	TDR&TXV	16.00			13.00	58PH*090–16

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB642A**30	CAP**6024A**	41,500	TDR&TXV	16.00			13.00	58PH*110–20
	CAP**6024A**	41,500	TDR&TXV	16.00			13.00	58PH*135–20
	CAP**6024A**	42,000	TDR&TXV	16.00			13.00	58MEC100–20
	CAP**6024A**	42,000	TDR&TXV	16.00			13.00	58MEC120–20
	CAP**6025A**	42,000	TXV			14.50	12.00	
	CAP**6025A**	42,000	TDR&TXV	15.00			13.00	58HDV080 – –20
	CAP**6025A**	41,500	TDR&TXV	15.50			13.00	58HDV100 – –20
	CNPF*4818A**	41,000	TXV			14.00	12.00	
	CNPH*4221A**	40,500	TXV			14.00	12.00	
	CNPH*4221A**	40,000	TDR&TXV	14.50			12.50	58MVB040–14
	CNPH*4221A**	40,500	TDR&TXV	15.00			12.50	58MV(B,C)060–14
	CNPH*4221A**	40,000	TDR&TXV	14.50			12.00	58MV(B,C)080–14
	CNPH*4221A**	40,000	TDR&TXV	14.50			12.50	58MV(B,C)080–20
	CNPH*4221A**	40,000	TDR&TXV	15.00			12.50	58MV(B,C)100–20
	CNPH*4221A**	40,000	TDR&TXV	15.00			12.50	58MV(B,C)120–20
	CNPH*4221A**	40,000	TDR&TXV	14.50			12.50	58CV(A,X)070–12
	CNPH*4221A**	40,000	TDR&TXV	15.00			12.50	58CV(A,X)090–16
	CNPH*4221A**	40,000	TDR&TXV	15.00			12.50	58CV(A,X)110–20
	CNPH*4221A**	40,500	TDR&TXV	15.50			13.00	58CV(A,X)135–22
	CNPH*4221A**	40,500	TDR&TXV	15.50			13.00	58CV(A,X)155–22
	CNPH*4221A**	40,000	TDR&TXV	14.50			12.00	58PH*070–16
	CNPH*4221A**	40,500	TDR&TXV	15.00			12.50	58PH*090–16
	CNPH*4221A**	40,500	TDR&TXV	15.50			13.00	58PH*110–20
	CNPH*4221A**	40,000	TDR&TXV	15.00			12.50	58PH*135–20
	CNPH*4221A**	40,500	TDR&TXV	15.00			12.50	58MEB040–12
	CNPH*4221A**	40,500	TDR&TXV	15.00			12.50	58MEC060–12
	CNPH*4221A**	40,500	TDR&TXV	15.00			12.50	58MEC080–12
	CNPH*4221A**	40,000	TDR&TXV	15.00			12.50	58MEC080–16
	CNPH*4221A**	40,500	TDR&TXV	15.50			13.00	58MEC100–20
	CNPH*4221A**	40,500	TDR&TXV	15.50			13.00	58MEC120–20
	CNPH*4221A**	40,000	TDR&TXV	14.00			12.00	58HDV060 – –12
	CNPH*4221A**	40,500	TDR&TXV	14.50			12.00	58HDV080 – –20
	CNPH*4221A**	40,500	TDR&TXV	15.00			12.50	58HDV100 – –20
	CNPH*4221A**	40,000	TDR&TXV	14.50			12.50	OVMAAB042112
	CNPH*4221A**	40,500	TDR&TXV	14.50			12.00	OVLAAB048112
	CNPH*4221A**	41,000	TDR&TXV	15.00			12.50	OVLAAB060154
	CNPH*4321A**	42,000	TXV			14.50	12.00	
	CNPH*4321A**	41,000	TDR&TXV	15.00			12.50	58MVB040–14
	CNPH*4321A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)060–14
	CNPH*4321A**	41,500	TDR&TXV	15.00			12.50	58MV(B,C)080–14
	CNPH*4321A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–20
	CNPH*4321A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CNPH*4321A**	41,500	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*4321A**	41,000	TDR&TXV	15.00			12.50	58CV(A,X)070–12
	CNPH*4321A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*4321A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPH*4321A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*4321A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*4321A**	41,500	TDR&TXV	15.00			12.50	58PH*070–16
	CNPH*4321A**	41,500	TDR&TXV	16.00			13.00	58PH*090–16
	CNPH*4321A**	41,500	TDR&TXV	16.00			13.00	58PH*110–20
	CNPH*4321A**	41,500	TDR&TXV	16.00			13.00	58PH*135–20
	CNPH*4321A**	42,000	TDR&TXV	15.50			13.00	58MEB040–12
	CNPH*4321A**	41,500	TDR&TXV	15.50			13.00	58MEC060–12

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB642A**30	CNPH*4321A**	41,500	TDR&TXV	15.50			13.00	58MEC080–12
	CNPH*4321A**	41,500	TDR&TXV	15.50			13.00	58MEC080–16
	CNPH*4321A**	41,500	TDR&TXV	16.00			13.00	58MEC100–20
	CNPH*4321A**	42,000	TDR&TXV	16.00			13.00	58MEC120–20
	CNPH*4321A**	41,500	TDR&TXV	14.50			12.00	58HDV060– –12
	CNPH*4321A**	42,000	TDR&TXV	15.20			12.50	58HDV080– –20
	CNPH*4321A**	41,500	TDR&TXV	15.50			13.00	58HDV100– –20
	CNPH*4321A**	41,500	TDR&TXV	15.50			13.00	OVMAAB042112
	CNPH*4321A**	41,500	TDR&TXV	15.00			12.50	OVLAAB048112
	CNPH*4321A**	42,000	TDR&TXV	15.50			13.00	OVLAAB060154
	CNPH*4821A**	41,000	TXV			14.00	12.00	
	CNPH*4821A**	40,500	TDR&TXV	15.00			12.50	58MVB040–14
	CNPH*4821A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)060–14
	CNPH*4821A**	41,000	TDR&TXV	15.00			12.50	58MV(B,C)080–14
	CNPH*4821A**	41,000	TDR&TXV	15.20			12.50	58MV(B,C)080–20
	CNPH*4821A**	40,500	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CNPH*4821A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)120–20
	CNPH*4821A**	40,500	TDR&TXV	15.00			12.50	58CV(A,X)070–12
	CNPH*4821A**	41,000	TDR&TXV	15.50			13.00	58CV(A,X)090–16
	CNPH*4821A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPH*4821A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*4821A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*4821A**	41,000	TDR&TXV	14.50			12.00	58PH*070–16
	CNPH*4821A**	41,000	TDR&TXV	15.50			13.00	58PH*090–16
	CNPH*4821A**	41,000	TDR&TXV	16.00			13.00	58PH*110–20
	CNPH*4821A**	41,000	TDR&TXV	16.00			13.00	58PH*135–20
	CNPH*4821A**	41,000	TDR&TXV	15.20			13.00	58MEB040–12
	CNPH*4821A**	41,000	TDR&TXV	15.00			12.50	58MEC060–12
	CNPH*4821A**	41,000	TDR&TXV	15.50			13.00	58MEC080–12
	CNPH*4821A**	41,000	TDR&TXV	15.50			13.00	58MEC080–16
	CNPH*4821A**	41,000	TDR&TXV	16.00			13.00	58MEC100–20
	CNPH*4821A**	41,500	TDR&TXV	16.00			13.00	58MEC120–20
	CNPH*4821A**	41,000	TDR&TXV	14.50			12.00	58HDV060– –12
	CNPH*4821A**	41,500	TDR&TXV	15.00			12.50	58HDV080– –20
	CNPH*4821A**	41,000	TDR&TXV	15.50			12.50	58HDV100– –20
	CNPH*4821A**	41,000	TDR&TXV	15.00			12.50	OVMAAB042112
	CNPH*4821A**	41,000	TDR&TXV	15.00			12.50	OVLAAB048112
	CNPH*4821A**	42,000	TDR&TXV	15.50			13.00	OVLAAB060154
	CNPH*6024A**	41,500	TXV			14.50	12.00	
	CNPH*6024A**	41,000	TDR&TXV	15.50			13.00	58MVB040–14
	CNPH*6024A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)060–14
	CNPH*6024A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–14
	CNPH*6024A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–20
	CNPH*6024A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CNPH*6024A**	41,500	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPH*6024A**	41,000	TDR&TXV	15.20			13.00	58CV(A,X)070–12
	CNPH*6024A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CNPH*6024A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPH*6024A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*6024A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*6024A**	41,500	TDR&TXV	14.50			12.50	58PH*070–16
	CNPH*6024A**	41,500	TDR&TXV	16.00			13.00	58PH*090–16
	CNPH*6024A**	42,000	TDR&TXV	16.00			13.00	58PH*110–20
	CNPH*6024A**	42,000	TDR&TXV	16.00			13.00	58PH*135–20

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB642A**30	CNPH*6024A**	42,000	TDR&TXV	15.50			13.00	58MEB040–12
	CNPH*6024A**	42,000	TDR&TXV	15.50			13.00	58MEC060–12
	CNPH*6024A**	42,000	TDR&TXV	15.50			13.00	58MEC080–12
	CNPH*6024A**	41,500	TDR&TXV	15.50			13.00	58MEC080–16
	CNPH*6024A**	42,000	TDR&TXV	16.00			13.00	58MEC100–20
	CNPH*6024A**	42,000	TDR&TXV	16.00			13.00	58MEC120–20
	CNPV*4217A**	41,000	TXV			14.00	12.00	
	CNPV*4217A**	40,500	TDR&TXV	15.00			12.50	58MV(B,C)060–14
	CNPV*4217A**	40,500	TDR&TXV	15.20			12.50	58CV(A,X)090–16
	CNPV*4217A**	40,500	TDR&TXV	14.50			12.00	58PH*070–16
	CNPV*4217A**	40,500	TDR&TXV	15.00			12.50	58MEB040–12
	CNPV*4217A**	40,500	TDR&TXV	15.00			12.50	58MEC060–12
	CNPV*4217A**	40,500	TDR&TXV	15.00			12.50	58MEC080–12
	CNPV*4217A**	40,500	TDR&TXV	15.00			12.50	58MEC080–16
	CNPV*4217A**	40,500	TDR&TXV	14.50			12.50	58CV(A,X)070–12
	CNPV*4217A**	40,500	TDR&TXV	14.50			12.50	OVMAAB042112
	CNPV*4217A**	40,500	TDR&TXV	14.50			12.00	58HDV060– – 12
	CNPV*4221A**	40,500	TXV			14.00	12.00	
	CNPV*4221A**	40,000	TDR&TXV	14.50			12.00	58MV(B,C)080–14
	CNPV*4221A**	40,000	TDR&TXV	14.50			12.50	58MV(B,C)080–20
	CNPV*4221A**	40,000	TDR&TXV	15.00			12.50	58MV(B,C)100–20
	CNPV*4221A**	40,000	TDR&TXV	15.00			12.50	58CV(A,X)110–20
	CNPV*4221A**	40,500	TDR&TXV	15.20			12.50	58PH*090–16
	CNPV*4221A**	40,500	TDR&TXV	15.50			13.00	58PH*110–20
	CNPV*4221A**	40,500	TDR&TXV	15.50			13.00	58MEC100–20
	CNPV*4221A**	40,500	TDR&TXV	15.00			12.50	58MV(B,C)060–14
	CNPV*4221A**	40,000	TDR&TXV	15.00			12.50	58CV(A,X)090–16
	CNPV*4221A**	40,000	TDR&TXV	14.50			12.00	58PH*070–16
	CNPV*4221A**	40,500	TDR&TXV	15.00			12.50	58MEB040–12
	CNPV*4221A**	40,500	TDR&TXV	15.00			12.50	58MEC060–12
	CNPV*4221A**	40,500	TDR&TXV	15.00			12.50	58MEC080–12
	CNPV*4221A**	40,000	TDR&TXV	15.00			12.50	58MEC080–16
	CNPV*4221A**	40,500	TDR&TXV	14.50			12.00	OVLAAB048112
	CNPV*4221A**	40,000	TDR&TXV	14.50			12.00	58HDV060– – 12
	CNPV*4221A**	40,500	TDR&TXV	15.00			12.50	58HDV080– – 20
	CNPV*4324A**	41,000	TDR&TXV	15.50			13.00	58MVB040–14
	CNPV*4324A**	41,500	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPV*4324A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPV*4324A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPV*4324A**	42,000	TDR&TXV	16.00			13.00	58PH*135–20
	CNPV*4324A**	42,000	TDR&TXV	16.00			13.00	58MEC120–20
	CNPV*4324A**	41,500	TDR&TXV	16.00			13.00	58HDV100– – 20
	CNPV*4324A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–14
	CNPV*4324A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–20
	CNPV*4324A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CNPV*4324A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPV*4324A**	41,500	TDR&TXV	16.00			13.00	58PH*090–16
	CNPV*4324A**	42,000	TDR&TXV	16.00			13.00	58PH*110–20
	CNPV*4324A**	42,000	TDR&TXV	16.00			13.00	58MEC100–20
	CNPV*4324A**	42,000	TDR&TXV	15.50			13.00	58HDV080– – 20
	CNPV*4324A**	41,500	TDR&TXV	16.00			13.00	58HDV100– – 20
	CNPV*4821A**	41,000	TXV			14.00	12.00	
	CNPV*4821A**	41,000	TDR&TXV	15.00			12.50	58MV(B,C)080–14
	CNPV*4821A**	41,000	TDR&TXV	15.20			12.50	58MV(B,C)080–20

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB642A**30	CNPV*4821A**	40,500	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CNPV*4821A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPV*4821A**	41,000	TDR&TXV	15.50			13.00	58PH*090–16
	CNPV*4821A**	41,000	TDR&TXV	16.00			13.00	58PH*110–20
	CNPV*4821A**	41,000	TDR&TXV	16.00			13.00	58MEC100–20
	CNPV*4821A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)060–14
	CNPV*4821A**	41,000	TDR&TXV	15.50			13.00	58CV(A,X)090–16
	CNPV*4821A**	41,000	TDR&TXV	14.50			12.00	58PH*070–16
	CNPV*4821A**	41,000	TDR&TXV	15.20			13.00	58MEB040–12
	CNPV*4821A**	41,000	TDR&TXV	15.20			12.50	58MEC060–12
	CNPV*4821A**	41,000	TDR&TXV	15.50			13.00	58MEC080–12
	CNPV*4821A**	41,000	TDR&TXV	15.50			13.00	58MEC080–16
	CNPV*4821A**	41,000	TDR&TXV	15.00			12.50	OVLAAB048112
	CNPV*4821A**	41,000	TDR&TXV	14.50			12.00	58HDV060– –12
	CNPV*4821A**	41,500	TDR&TXV	15.00			13.00	58HDV080– –20
	CNPV*4824A**	41,000	TXV			14.00	12.00	
	CNPV*4824A**	40,500	TDR&TXV	15.00			12.50	58MVB040–14
	CNPV*4824A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)120–20
	CNPV*4824A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPV*4824A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPV*4824A**	41,000	TDR&TXV	16.00			13.00	58PH*135–20
	CNPV*4824A**	41,500	TDR&TXV	16.00			13.00	58MEC120–20
	CNPV*4824A**	41,000	TDR&TXV	15.50			12.50	58HDV100– –20
	CNPV*4824A**	41,000	TDR&TXV	15.00			12.50	58MV(B,C)080–14
	CNPV*4824A**	41,000	TDR&TXV	15.20			12.50	58MV(B,C)080–20
	CNPV*4824A**	40,500	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CNPV*4824A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPV*4824A**	41,000	TDR&TXV	15.50			13.00	58PH*090–16
	CNPV*4824A**	41,000	TDR&TXV	16.00			13.00	58PH*110–20
	CNPV*4824A**	41,000	TDR&TXV	16.00			13.00	58MEC100–20
	CNPV*4824A**	41,500	TDR&TXV	15.00			13.00	58HDV080– –20
	CNPV*4824A**	41,000	TDR&TXV	15.50			13.00	58HDV100– –20
	CNPV*6024A**	41,500	TXV			14.50	12.00	
	CNPV*6024A**	41,000	TDR&TXV	15.50			13.00	58MVB040–14
	CNPV*6024A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–14
	CNPV*6024A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–20
	CNPV*6024A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)100–20
	CNPV*6024A**	41,500	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPV*6024A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CNPV*6024A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPV*6024A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPV*6024A**	41,500	TDR&TXV	16.00			13.00	58PH*090–16
	CNPV*6024A**	42,000	TDR&TXV	16.00			13.00	58PH*110–20
	CNPV*6024A**	42,000	TDR&TXV	16.00			13.00	58PH*135–20
	CNPV*6024A**	42,000	TDR&TXV	16.00			13.00	58MEC100–20
	CNPV*6024A**	42,000	TDR&TXV	16.00			13.00	58MEC120–20
	CSPH*4212A**	41,500	TXV			14.00	12.00	
	CSPH*4212A**	40,500	TDR&TXV	15.00			12.50	58MVB040–14
	CSPH*4212A**	41,000	TDR&TXV	15.20			12.50	58MV(B,C)060–14
	CSPH*4212A**	41,000	TDR&TXV	15.00			12.50	58MV(B,C)080–14
	CSPH*4212A**	41,000	TDR&TXV	15.00			12.50	58MV(B,C)080–20
	CSPH*4212A**	40,500	TDR&TXV	15.20			12.50	58MV(B,C)100–20
	CSPH*4212A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)120–20
	CSPH*4212A**	41,000	TDR&TXV	15.00			12.50	58CV(A,X)070–12

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB642A**30	CSPH*4212A**	41,000	TDR&TXV	15.50			13.00	58CV(A,X)090–16
	CSPH*4212A**	41,000	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CSPH*4212A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*4212A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*4212A**	41,000	TDR&TXV	14.50			12.00	58PH*070–16
	CSPH*4212A**	41,000	TDR&TXV	15.50			13.00	58PH*090–16
	CSPH*4212A**	41,000	TDR&TXV	16.00			13.00	58PH*110–20
	CSPH*4212A**	41,000	TDR&TXV	15.50			13.00	58PH*135–20
	CSPH*4212A**	41,500	TDR&TXV	15.20			13.00	58MEB040–12
	CSPH*4212A**	41,500	TDR&TXV	15.00			12.50	58MEC060–12
	CSPH*4212A**	41,500	TDR&TXV	15.50			13.00	58MEC080–12
	CSPH*4212A**	41,000	TDR&TXV	15.50			13.00	58MEC080–16
	CSPH*4212A**	41,000	TDR&TXV	16.00			13.00	58MEC100–20
	CSPH*4212A**	41,500	TDR&TXV	16.00			13.00	58MEC120–20
	CSPH*4212A**	41,000	TDR&TXV	14.50			12.00	58HDV060– –12
	CSPH*4212A**	41,500	TDR&TXV	15.00			12.50	58HDV080– –20
	CSPH*4212A**	41,000	TDR&TXV	15.50			13.00	58HDV100– –20
	CSPH*4212A**	41,000	TDR&TXV	15.00			12.50	OVMAAB042112
	CSPH*4212A**	41,000	TDR&TXV	15.00			12.50	OVLAAB048112
	CSPH*4212A**	42,000	TDR&TXV	15.00			13.00	OVLAAB060154
	CSPH*4812A**	41,500	TXV			14.50	12.00	
	CSPH*4812A**	41,000	TDR&TXV	15.00			12.50	58MVB040–14
	CSPH*4812A**	41,500	TDR&TXV	15.20			13.00	58MV(B,C)060–14
	CSPH*4812A**	41,000	TDR&TXV	15.00			12.50	58MV(B,C)080–14
	CSPH*4812A**	41,000	TDR&TXV	15.00			12.50	58MV(B,C)080–20
	CSPH*4812A**	41,000	TDR&TXV	15.20			13.00	58MV(B,C)100–20
	CSPH*4812A**	41,000	TDR&TXV	15.50			13.00	58MV(B,C)120–20
	CSPH*4812A**	41,000	TDR&TXV	15.00			12.50	58CV(A,X)070–12
	CSPH*4812A**	41,000	TDR&TXV	15.50			13.00	58CV(A,X)090–16
	CSPH*4812A**	41,000	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CSPH*4812A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*4812A**	41,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*4812A**	41,000	TDR&TXV	14.50			12.50	58PH*070–16
	CSPH*4812A**	41,500	TDR&TXV	16.00			13.00	58PH*090–16
	CSPH*4812A**	41,500	TDR&TXV	16.00			13.00	58PH*110–20
	CSPH*4812A**	41,500	TDR&TXV	16.00			13.00	58PH*135–20
	CSPH*4812A**	41,500	TDR&TXV	15.50			13.00	58MEB040–12
	CSPH*4812A**	41,500	TDR&TXV	15.20			13.00	58MEC060–12
	CSPH*4812A**	41,500	TDR&TXV	15.50			13.00	58MEC080–12
	CSPH*4812A**	41,000	TDR&TXV	15.50			13.00	58MEC080–16
	CSPH*4812A**	41,500	TDR&TXV	16.00			13.00	58MEC100–20
	CSPH*4812A**	41,500	TDR&TXV	16.00			13.00	58MEC120–20
	CSPH*4812A**	41,000	TDR&TXV	14.50			12.00	58HDV060– –12
	CSPH*4812A**	41,500	TDR&TXV	15.00			12.50	58HDV080– –20
	CSPH*4812A**	41,500	TDR&TXV	15.50			13.00	58HDV100– –20
	CSPH*4812A**	41,000	TDR&TXV	15.00			12.50	OVMAAB042112
	CSPH*4812A**	41,500	TDR&TXV	15.00			12.50	OVLAAB048112
	CSPH*4812A**	42,000	TDR&TXV	15.50			13.00	OVLAAB060154
	CSPH*6012A**	42,000	TXV			14.50	12.00	
	CSPH*6012A**	41,500	TDR&TXV	15.50			13.00	58MVB040–14
	CSPH*6012A**	42,000	TDR&TXV	16.00			13.00	58MV(B,C)060–14
	CSPH*6012A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–14
	CSPH*6012A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)080–20
	CSPH*6012A**	41,500	TDR&TXV	15.50			13.00	58MV(B,C)100–20

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB642A**30	CSPH*6012A**	41,500	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CSPH*6012A**	41,500	TDR&TXV	15.50			13.00	58CV(A,X)070–12
	CSPH*6012A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)090–16
	CSPH*6012A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)110–20
	CSPH*6012A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*6012A**	41,500	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*6012A**	41,500	TDR&TXV	15.00			12.50	58PH*070–16
	CSPH*6012A**	42,000	TDR&TXV	16.00			13.00	58PH*090–16
	CSPH*6012A**	42,000	TDR&TXV	16.00			13.00	58PH*110–20
	CSPH*6012A**	42,000	TDR&TXV	16.00			13.00	58PH*135–20
	CSPH*6012A**	42,000	TDR&TXV	15.50			13.00	58MEB040–12
	CSPH*6012A**	42,000	TDR&TXV	15.50			13.00	58MEC060–12
	CSPH*6012A**	42,000	TDR&TXV	16.00			13.00	58MEC080–12
	CSPH*6012A**	42,000	TDR&TXV	16.00			13.00	58MEC080–16
	CSPH*6012A**	42,000	TDR&TXV	16.00			13.00	58MEC100–20
	CSPH*6012A**	42,000	TDR&TXV	16.00			13.00	58MEC120–20
24ANB648A**30	*CNPV*6124A**	46,500	TXV			14.50	12.50	
	FB4CNF048	45,000	TDR		14.50		12.50	
	FB4CNF060	46,000	TDR&TXV	15.00			13.00	
	FE4AN(B,F)005	46,000	TDR&TXV	16.00			13.50	
	FE4ANB006	46,500	TDR&TXV	16.00			13.50	
	FV4CN(B,F)005	46,000	TDR&TXV	16.00			13.50	
	FV4CNB006	46,500	TDR&TXV	16.00			13.50	
	FX4DN(B,F)049	46,500	TDR&TXV	16.00			13.00	
	FX4DN(B,F)061	47,000	TDR&TXV	16.00			13.50	
	FY5BNB060	46,000	TDR&TXV	14.50			12.00	
	FY5BNF048	46,000	TDR		14.50		12.50	
	CAP**4817A**	45,000	TXV			14.00	12.00	
	CAP**4817A**	45,000	TDR&TXV	14.50			12.50	58CV(A,X)090–16
	CAP**4817A**	45,000	TDR&TXV	14.50			12.50	58MEC080–16
	CAP**4821A**	45,000	TXV			14.00	12.00	
	CAP**4821A**	44,500	TDR&TXV	14.50			12.50	58MV(B,C)080–20
	CAP**4821A**	44,500	TDR&TXV	14.50			12.50	58MV(B,C)100–20
	CAP**4821A**	44,500	TDR&TXV	14.50			12.50	58CV(A,X)110–20
	CAP**4821A**	45,000	TDR&TXV	15.00			12.50	58PH*090–16
	CAP**4821A**	45,000	TDR&TXV	15.20			13.00	58PH*110–20
	CAP**4821A**	45,000	TDR&TXV	15.20			13.00	58MEC100–20
	CAP**4821A**	44,500	TDR&TXV	14.50			12.50	58MV(B,C)100–20
	CAP**4821A**	44,500	TDR&TXV	14.50			12.50	58CV(A,X)090–16
	CAP**4821A**	45,000	TDR&TXV	14.50			12.50	58MEC080–16
	CAP**4821A**	44,500	TDR&TXV	14.00			12.00	OVLAAB048112
	CAP**4823A**	45,000	TXV			14.00	12.00	
	CAP**4823A**	45,000	TDR&TXV	14.50			12.50	58HDV080–20
	CAP**4824A**	45,000	TXV			14.00	12.00	
	CAP**4824A**	44,500	TDR&TXV	15.00			12.50	58MV(B,C)120–20
	CAP**4824A**	45,000	TDR&TXV	15.20			13.00	58CV(A,X)135–22
	CAP**4824A**	45,000	TDR&TXV	15.20			13.00	58CV(A,X)155–22
	CAP**4824A**	45,000	TDR&TXV	15.20			13.00	58PH*135–20
	CAP**4824A**	45,000	TDR&TXV	15.20			13.00	58MEC120–20
	CAP**4824A**	45,000	TDR&TXV	14.50			12.50	58HDV100–20
	CAP**4824A**	44,500	TDR&TXV	14.50			12.50	58MV(B,C)080–20
	CAP**4824A**	44,500	TDR&TXV	14.50			12.50	58MV(B,C)100–20
CAP**4824A**	44,500	TDR&TXV	15.00			12.50	58CV(A,X)110–20	

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB648A**30	CAP**4824A**	45,000	TDR&TXV	15.00			12.50	58PH*090–16
	CAP**4824A**	45,000	TDR&TXV	15.20			13.00	58PH*110–20
	CAP**4824A**	45,000	TDR&TXV	15.20			13.00	58MEC100–20
	CAP**4824A**	45,000	TDR&TXV	14.50			12.50	58HDV080– –20
	CAP**6021A**	46,000	TXV			14.00	12.50	
	CAP**6021A**	45,000	TDR&TXV	15.20			13.00	58MV(B,C)080–20
	CAP**6021A**	45,500	TDR&TXV	15.00			12.50	58MV(B,C)100–20
	CAP**6021A**	45,500	TDR&TXV	15.20			13.00	58CV(A,X)110–20
	CAP**6021A**	46,000	TDR&TXV	15.20			13.00	58PH*090–16
	CAP**6021A**	45,500	TDR&TXV	16.00			13.00	58PH*110–20
	CAP**6021A**	46,000	TDR&TXV	15.50			13.00	58MEC100–20
	CAP**6021A**	45,500	TDR&TXV	15.20			13.00	58CV(A,X)090–16
	CAP**6021A**	46,000	TDR&TXV	15.20			13.00	58MEC080–16
	CAP**6021A**	45,500	TDR&TXV	14.50			12.50	OVLAAB048112
	CAP**6024A**	46,000	TXV			14.00	12.50	
	CAP**6024A**	45,500	TDR&TXV	15.20			13.00	58MV(B,C)120–20
	CAP**6024A**	45,500	TDR&TXV	15.50			13.00	58CV(A,X)135–22
	CAP**6024A**	46,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CAP**6024A**	46,000	TDR&TXV	15.50			13.00	58PH*135–20
	CAP**6024A**	46,000	TDR&TXV	16.00			13.00	58MEC120–20
	CAP**6024A**	45,500	TDR&TXV	15.20			13.00	58HDV100– –20
	CAP**6024A**	45,000	TDR&TXV	15.20			13.00	58MV(B,C)080–20
	CAP**6024A**	45,500	TDR&TXV	15.20			13.00	58MV(B,C)100–20
	CAP**6024A**	45,500	TDR&TXV	15.20			13.00	58CV(A,X)110–20
	CAP**6024A**	46,000	TDR&TXV	15.20			13.00	58PH*090–16
	CAP**6024A**	46,000	TDR&TXV	16.00			13.00	58PH*110–20
	CAP**6024A**	46,000	TDR&TXV	15.50			13.00	58MEC100–20
	CAP**6024A**	46,000	TDR&TXV	15.00			13.00	58HDV080– –20
	CAP**6025A**	46,000	TXV			14.00	12.50	
	CAP**6025A**	45,500	TDR&TXV	15.20			13.00	58HDV100– –20
	CAP**6025A**	46,000	TXV			14.00	12.50	
	CAP**6025A**	46,000	TDR&TXV	15.20			13.00	58HDV080– –20
	CAP**6025A**	45,500	TDR&TXV	15.20			13.00	58HDV100– –20
	CNPH*4821A**	45,500	TXV			14.00	12.00	
	CNPH*4821A**	44,500	TDR&TXV	14.50			12.50	58MV(B,C)080–20
	CNPH*4821A**	45,000	TDR&TXV	14.50			12.50	58MV(B,C)100–20
	CNPH*4821A**	45,000	TDR&TXV	15.00			13.00	58MV(B,C)120–20
	CNPH*4821A**	45,000	TDR&TXV	15.00			12.50	58CV(A,X)090–16
	CNPH*4821A**	45,000	TDR&TXV	15.20			13.00	58CV(A,X)110–20
	CNPH*4821A**	45,000	TDR&TXV	15.20			13.00	58CV(A,X)135–22
	CNPH*4821A**	45,000	TDR&TXV	15.50			13.00	58CV(A,X)155–22
	CNPH*4821A**	45,000	TDR&TXV	15.20			13.00	58PH*090–16
	CNPH*4821A**	45,000	TDR&TXV	15.20			13.00	58PH*110–20
	CNPH*4821A**	45,000	TDR&TXV	15.20			13.00	58PH*135–20
	CNPH*4821A**	45,000	TDR&TXV	14.50			12.50	58MEC080–16
	CNPH*4821A**	45,000	TDR&TXV	15.20			13.00	58MEC100–20
	CNPH*4821A**	45,500	TDR&TXV	15.50			13.00	58MEC120–20
	CNPH*4821A**	45,000	TDR&TXV	14.50			12.50	58HDV080– –20
	CNPH*4821A**	45,000	TDR&TXV	14.50			12.50	58HDV100– –20
	CNPH*4821A**	45,000	TDR&TXV	14.00			12.00	OVLAAB048112
	CNPH*4821A**	46,000	TDR&TXV	14.50			12.50	OVLAAB060154
	CNPH*6024A**	46,000	TXV			14.00	12.50	
	CNPH*6024A**	45,000	TDR&TXV	15.20			13.00	58MV(B,C)080–20
	CNPH*6024A**	45,500	TDR&TXV	15.20			13.00	58MV(B,C)100–20

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB648A**30	CNPH*6024A**	45,500	TDR&TXV	15.20			13.00	58MV(B,C)120–20
	CNPH*6024A**	45,500	TDR&TXV	15.20			13.00	58CV(A,X)090–16
	CNPH*6024A**	45,500	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CNPH*6024A**	45,500	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*6024A**	46,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*6024A**	46,000	TDR&TXV	15.50			13.00	58PH*090–16
	CNPH*6024A**	46,000	TDR&TXV	16.00			13.00	58PH*110–20
	CNPH*6024A**	46,000	TDR&TXV	15.50			13.00	58PH*135–20
	CNPH*6024A**	46,000	TDR&TXV	15.20			13.00	58MEC080–16
	CNPH*6024A**	46,000	TDR&TXV	15.50			13.00	58MEC100–20
	CNPH*6024A**	46,000	TDR&TXV	16.00			13.00	58MEC120–20
	CNPH*6024A**	46,000	TDR&TXV	15.00			13.00	58HDV080– –20
	CNPH*6024A**	46,000	TDR&TXV	15.20			13.00	58HDV100– –20
	CNPH*6024A**	45,500	TDR&TXV	14.50			12.50	OVLAAB048112
	CNPH*6024A**	46,500	TDR&TXV	15.20			13.00	OVLAAB060154
	CNPH*6124A**	46,500	TXV			14.50	12.50	
	CNPH*6124A**	45,500	TDR&TXV	15.20			13.00	58MV(B,C)080–20
	CNPH*6124A**	45,500	TDR&TXV	15.20			13.00	58MV(B,C)100–20
	CNPH*6124A**	45,500	TDR&TXV	15.20			13.00	58MV(B,C)120–20
	CNPH*6124A**	45,500	TDR&TXV	15.20			13.00	58CV(A,X)090–16
	CNPH*6124A**	45,500	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CNPH*6124A**	46,000	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPH*6124A**	46,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPH*6124A**	46,000	TDR&TXV	15.50			13.00	58PH*090–16
	CNPH*6124A**	46,000	TDR&TXV	16.00			13.00	58PH*110–20
	CNPH*6124A**	46,000	TDR&TXV	15.50			13.00	58PH*135–20
	CNPH*6124A**	46,000	TDR&TXV	15.20			13.00	58MEC080–16
	CNPH*6124A**	46,000	TDR&TXV	16.00			13.00	58MEC100–20
	CNPH*6124A**	46,000	TDR&TXV	16.00			13.00	58MEC120–20
	CNPH*6124A**	46,000	TDR&TXV	15.20			13.00	58HDV080– –20
	CNPH*6124A**	46,000	TDR&TXV	15.20			13.00	58HDV100– –20
	CNPH*6124A**	45,500	TDR&TXV	14.50			12.50	OVLAAB048112
	CNPH*6124A**	46,500	TDR&TXV	15.20			13.00	OVLAAB060154
	CNPV*4821A**	45,500	TXV			14.00	12.00	
	CNPV*4821A**	44,500	TDR&TXV	14.50			12.50	58MV(B,C)080–20
	CNPV*4821A**	45,000	TDR&TXV	14.50			12.50	58MV(B,C)100–20
	CNPV*4821A**	45,000	TDR&TXV	15.20			13.00	58CV(A,X)110–20
	CNPV*4821A**	45,000	TDR&TXV	15.20			13.00	58PH*090–16
	CNPV*4821A**	45,000	TDR&TXV	15.20			13.00	58PH*110–20
	CNPV*4821A**	45,000	TDR&TXV	15.20			13.00	58MEC100–20
	CNPV*4821A**	45,000	TDR&TXV	15.00			12.50	58CV(A,X)090–16
	CNPV*4821A**	45,000	TDR&TXV	14.50			12.50	58MEC080–16
	CNPV*4821A**	45,000	TDR&TXV	14.00			12.00	OVLAAB048112
	CNPV*4821A**	45,000	TDR&TXV	14.50			12.50	58HDV080– –20
	CNPV*4824A**	45,500	TXV			14.00	12.00	
	CNPV*4824A**	45,000	TDR&TXV	15.00			13.00	58MV(B,C)120–20
	CNPV*4824A**	45,000	TDR&TXV	15.20			13.00	58CV(A,X)135–22
	CNPV*4824A**	45,000	TDR&TXV	15.50			13.00	58CV(A,X)155–22
	CNPV*4824A**	45,000	TDR&TXV	15.20			13.00	58PH*135–20
	CNPV*4824A**	45,500	TDR&TXV	15.20			13.00	58MEC120–20
	CNPV*4824A**	45,000	TDR&TXV	14.50			12.50	58HDV100– –20
	CNPV*4824A**	44,500	TDR&TXV	14.50			12.50	58MV(B,C)080–20
	CNPV*4824A**	45,000	TDR&TXV	14.50			12.50	58MV(B,C)100–20
	CNPV*4824A**	45,000	TDR&TXV	15.20			13.00	58CV(A,X)110–20

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB648A**30	CNPV*4824A**	45,000	TDR&TXV	15.20			13.00	58PH*090–16
	CNPV*4824A**	45,000	TDR&TXV	15.20			13.00	58PH*110–20
	CNPV*4824A**	45,000	TDR&TXV	15.20			13.00	58MEC100–20
	CNPV*4824A**	45,000	TDR&TXV	14.50			12.50	58HDV080– –20
	CNPV*4824A**	45,000	TDR&TXV	14.50			12.50	58HDV080– –20
	CNPV*4824A**	45,000	TDR&TXV	14.50			12.50	58HDV100– –20
	CNPV*6024A**	46,000	TXV			14.00	12.50	
	CNPV*6024A**	45,500	TDR&TXV	15.20			13.00	58MV(B,C)120–20
	CNPV*6024A**	45,500	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPV*6024A**	46,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPV*6024A**	46,000	TDR&TXV	15.50			13.00	58PH*135–20
	CNPV*6024A**	46,000	TDR&TXV	16.00			13.00	58MEC120–20
	CNPV*6024A**	46,000	TDR&TXV	15.20			13.00	58HDV100– –20
	CNPV*6024A**	45,000	TDR&TXV	15.20			13.00	58MV(B,C)080–20
	CNPV*6024A**	45,500	TDR&TXV	15.00			13.00	58MV(B,C)100–20
	CNPV*6024A**	45,500	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CNPV*6024A**	46,000	TDR&TXV	15.20			13.00	58PH*090–16
	CNPV*6024A**	46,000	TDR&TXV	16.00			13.50	58PH*110–20
	CNPV*6024A**	46,000	TDR&TXV	15.50			13.00	58MEC100–20
	CNPV*6024A**	46,000	TDR&TXV	15.00			13.00	58HDV080– –20
	CNPV*6024A**	46,000	TDR&TXV	15.00			13.00	58HDV080– –20
	CNPV*6024A**	46,000	TDR&TXV	15.20			13.00	58HDV100– –20
	CNPV*6124A**	46,000	TDR&TXV	16.00			13.00	58MV(B,C)120–20
	CNPV*6124A**	46,000	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPV*6124A**	46,500	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPV*6124A**	46,500	TDR&TXV	16.00			13.00	58PH*135–20
	CNPV*6124A**	46,500	TDR&TXV	16.00			13.00	58MEC120–20
	CNPV*6124A**	46,500	TDR&TXV	15.50			13.00	58HDV100– –20
	CNPV*6124A**	46,000	TDR&TXV	15.50			13.00	58MV(B,C)080–20
	CNPV*6124A**	46,000	TDR&TXV	15.20			13.00	58MV(B,C)100–20
	CNPV*6124A**	46,000	TDR&TXV	16.00			13.50	58CV(A,X)110–20
	CNPV*6124A**	46,500	TDR&TXV	16.00			13.00	58PH*090–16
	CNPV*6124A**	46,500	TDR&TXV	16.00			13.50	58PH*110–20
	CNPV*6124A**	46,500	TDR&TXV	16.00			13.50	58MEC100–20
	CNPV*6124A**	46,500	TDR&TXV	15.20			13.00	58HDV080– –20
	CNPV*6124A**	46,500	TDR&TXV	15.20			13.00	58HDV080– –20
	CNPV*6124A**	46,500	TDR&TXV	15.50			13.00	58HDV100– –20
	CSPH*4812A**	46,000	TXV			14.00	12.00	
	CSPH*4812A**	45,000	TDR&TXV	14.50			12.50	58MV(B,C)080–20
	CSPH*4812A**	45,000	TDR&TXV	14.50			12.50	58MV(B,C)100–20
	CSPH*4812A**	45,000	TDR&TXV	15.20			13.00	58MV(B,C)120–20
	CSPH*4812A**	45,000	TDR&TXV	15.00			13.00	58CV(A,X)090–16
	CSPH*4812A**	45,000	TDR&TXV	15.20			13.00	58CV(A,X)110–20
	CSPH*4812A**	45,500	TDR&TXV	15.20			13.00	58CV(A,X)135–22
	CSPH*4812A**	45,500	TDR&TXV	15.50			13.00	58CV(A,X)155–22
	CSPH*4812A**	45,500	TDR&TXV	15.20			13.00	58PH*090–16
	CSPH*4812A**	45,500	TDR&TXV	15.50			13.00	58PH*110–20
	CSPH*4812A**	45,500	TDR&TXV	15.20			13.00	58PH*135–20
	CSPH*4812A**	45,500	TDR&TXV	14.50			12.50	58MEC080–16
	CSPH*4812A**	45,500	TDR&TXV	15.20			13.00	58MEC100–20
	CSPH*4812A**	45,500	TDR&TXV	15.50			13.00	58MEC120–20
	CSPH*4812A**	45,500	TDR&TXV	14.50			12.50	58HDV080– –20
	CSPH*4812A**	45,500	TDR&TXV	14.50			12.50	58HDV100– –20
	CSPH*4812A**	45,000	TDR&TXV	14.00			12.00	OVLAAB048112

See notes on page 45

24ANB6

COMBINATION RATINGS CONTINUED

24ANB6

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB648A**30	CSPH*4812A**	46,000	TDR&TXV	14.50			12.50	OVLAAB060154
	CSPH*6012A**	46,500	TXV			14.50	12.50	
	CSPH*6012A**	45,500	TDR&TXV	15.20			13.00	58MV(B,C)080–20
	CSPH*6012A**	46,000	TDR&TXV	15.20			13.00	58MV(B,C)100–20
	CSPH*6012A**	46,000	TDR&TXV	15.50			13.00	58MV(B,C)120–20
	CSPH*6012A**	45,500	TDR&TXV	15.50			13.00	58CV(A,X)090–16
	CSPH*6012A**	46,000	TDR&TXV	15.50			13.00	58CV(A,X)110–20
	CSPH*6012A**	46,000	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CSPH*6012A**	46,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*6012A**	46,000	TDR&TXV	15.50			13.00	58PH*090–16
	CSPH*6012A**	46,000	TDR&TXV	16.00			13.00	58PH*110–20
	CSPH*6012A**	46,000	TDR&TXV	16.00			13.00	58PH*135–20
	CSPH*6012A**	46,000	TDR&TXV	15.20			13.00	58MEC080–16
	CSPH*6012A**	46,000	TDR&TXV	16.00			13.00	58MEC100–20
	CSPH*6012A**	46,500	TDR&TXV	16.00			13.00	58MEC120–20
	CSPH*6012A**	46,000	TDR&TXV	15.20			13.00	58HDV080– –20
	CSPH*6012A**	46,000	TDR&TXV	15.20			13.00	58HDV100– –20
	CSPH*6012A**	46,000	TDR&TXV	14.50			12.50	OVLAAB048112
	CSPH*6012A**	47,000	TDR&TXV	15.50			13.00	OVLAAB060154
24ANB660A**30	*CNPV*6124A**	55,000	TXV			14.50	12.50	
	FB4CNF060	54,000	TDR&TXV	14.50			12.50	
	FE4ANB006	54,500	TDR&TXV	16.00			13.50	
	FV4CNB006	54,500	TDR&TXV	16.00			13.50	
	FX4DN(B,F)061	55,000	TDR&TXV	15.50			13.00	
	FY5BNB060	54,000	TDR&TXV	13.50			12.00	
	CAP**6021A**	53,500	TXV			14.50	12.50	
	CAP**6021A**	53,500	TDR&TXV	15.00			12.50	58CV(A,X)110–20
	CAP**6021A**	53,500	TDR&TXV	15.50			13.00	58PH*110–20
	CAP**6021A**	53,500	TDR&TXV	15.20			13.00	58MEC100–20
	CAP**6024A**	54,500	TXV			14.50	12.50	
	CAP**6024A**	53,500	TDR&TXV	15.50			13.00	58CV(A,X)135–22
	CAP**6024A**	54,000	TDR&TXV	15.50			13.00	58CV(A,X)155–22
	CAP**6024A**	53,500	TDR&TXV	15.20			13.00	58PH*135–20
	CAP**6024A**	53,500	TDR&TXV	15.50			13.00	58MEC120–20
	CAP**6024A**	53,500	TDR&TXV	15.00			13.00	58CV(A,X)110–20
	CAP**6024A**	53,500	TDR&TXV	15.50			13.00	58PH*110–20
	CAP**6024A**	53,500	TDR&TXV	15.20			13.00	58MEC100–20
	CAP**6024A**	53,500	TDR&TXV	13.70			11.70	OVLAAB060154
	CAP**6025A**	54,500	TXV			14.50	12.50	
	CAP**6025A**	53,500	TDR&TXV	13.70			11.70	OVLAAB060154
	CNPH*6024A**	54,500	TXV			14.50	12.50	
	CNPH*6024A**	53,500	TDR&TXV	15.20			13.00	58CV(A,X)110–20
	CNPH*6024A**	53,500	TDR&TXV	15.50			13.00	58CV(A,X)135–22
	CNPH*6024A**	54,000	TDR&TXV	15.50			13.00	58CV(A,X)155–22
	CNPH*6024A**	54,000	TDR&TXV	15.50			13.00	58PH*110–20
	CNPH*6024A**	53,500	TDR&TXV	15.20			13.00	58PH*135–20
	CNPH*6024A**	53,000	TDR&TXV	15.00			12.50	58MEC080–16
	CNPH*6024A**	53,500	TDR&TXV	15.20			13.00	58MEC100–20
	CNPH*6024A**	53,500	TDR&TXV	15.50			13.00	58MEC120–20
	CNPH*6024A**	53,500	TDR&TXV	15.50			13.00	58MEC120–20
	CNPH*6024A**	53,500	TDR&TXV	13.70			11.70	OVLAAB060154
	CNPH*6024A**	53,500	TDR&TXV	14.00			12.00	58HDV080– –20
	CNPH*6024A**	53,500	TDR&TXV	14.50			12.50	58HDV100– –20

See notes on page 45

COMBINATION RATINGS CONTINUED

UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		TOTAL CAP. BTUH	FACTORY SUPPLIED ENHANCE- MENT	SEER			EER	
STANDARD RATING	TDR†			TXV				
24ANB660A**30	CNPH*6124A**	54,000	TXV			14.50	12.50	
	CNPH*6124A**	54,000	TDR&TXV	15.00			13.00	58CV(A,X)110–20
	CNPH*6124A**	54,000	TDR&TXV	15.50			13.00	58CV(A,X)135–22
	CNPH*6124A**	54,000	TDR&TXV	15.50			13.00	58CV(A,X)155–22
	CNPH*6124A**	54,000	TDR&TXV	15.50			13.00	58PH*110–20
	CNPH*6124A**	53,500	TDR&TXV	15.20			13.00	58PH*135–20
	CNPH*6124A**	53,500	TDR&TXV	15.20			13.00	58MEC100–20
	CNPH*6124A**	54,000	TDR&TXV	15.50			13.00	58MEC120–20
	CNPH*6124A**	54,000	TDR&TXV	13.70			11.70	OVLAAB060154
	CNPH*6124A**	54,000	TDR&TXV	14.00			12.00	58HDV080 – –20
	CNPH*6124A**	54,000	TDR&TXV	14.50			12.50	58HDV100 – –20
	CNPV*6024A**	54,500	TXV			14.50	12.50	
	CNPV*6024A**	53,500	TDR&TXV	15.50			13.00	58CV(A,X)135–22
	CNPV*6024A**	54,000	TDR&TXV	15.50			13.00	58CV(A,X)155–22
	CNPV*6024A**	53,500	TDR&TXV	15.20			13.00	58PH*135–20
	CNPV*6024A**	53,500	TDR&TXV	15.50			13.00	58MEC120–20
	CNPV*6024A**	53,500	TDR&TXV	15.20			12.50	58CV(A,X)110–20
	CNPV*6024A**	54,000	TDR&TXV	15.50			13.00	58PH*110–20
	CNPV*6024A**	53,500	TDR&TXV	13.70			11.70	OVLAAB060154
	CNPV*6024A**	53,500	TDR&TXV	14.00			12.00	58HDV080 – –20
	CNPV*6024A**	53,500	TDR&TXV	14.50			12.50	58HDV100 – –20
	CNPV*6124A**	54,000	TDR&TXV	15.20			13.00	58MV(B,C)120–20
	CNPV*6124A**	54,500	TDR&TXV	16.00			13.00	58CV(A,X)135–22
	CNPV*6124A**	54,500	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CNPV*6124A**	54,500	TDR&TXV	15.50			13.00	58PH*135–20
	CNPV*6124A**	54,500	TDR&TXV	16.00			13.00	58MEC120–20
	CNPV*6124A**	54,500	TDR&TXV	15.20			13.00	58CV(A,X)110–20
	CNPV*6124A**	54,500	TDR&TXV	15.50			13.00	58PH*110–20
	CNPV*6124A**	54,000	TDR&TXV	15.50			13.00	58MEC100–20
	CNPV*6124A**	54,500	TDR&TXV	14.00			12.00	OVLAAB060154
	CNPV*6124A**	54,500	TDR&TXV	14.50			12.50	58HDV080 – –20
	CNPV*6124A**	54,500	TDR&TXV	14.50			12.50	58HDV100 – –20
	CSPH*6012A**	54,500	TXV			14.50	12.50	
	CSPH*6012A**	53,500	TDR&TXV	15.00			13.00	58MV(B,C)120–20
	CSPH*6012A**	54,000	TDR&TXV	15.20			13.00	58CV(A,X)110–20
	CSPH*6012A**	54,000	TDR&TXV	15.50			13.00	58CV(A,X)135–22
	CSPH*6012A**	54,000	TDR&TXV	16.00			13.00	58CV(A,X)155–22
	CSPH*6012A**	54,000	TDR&TXV	15.50			13.00	58PH*110–20
	CSPH*6012A**	54,000	TDR&TXV	15.50			13.00	58PH*135–20
	CSPH*6012A**	53,500	TDR&TXV	15.20			13.00	58MEC080–16
	CSPH*6012A**	54,000	TDR&TXV	15.50			13.00	58MEC100–20
	CSPH*6012A**	54,000	TDR&TXV	16.00			13.00	58MEC120–20
	CSPH*6012A**	54,000	TDR&TXV	14.00			12.00	OVLAAB060154

* Tested combination

† In most cases, only 1 method should be used to achieve TDR function. Using more than 1 method in a system may cause degradation in performance. Use either the accessory Time–Delay Relay KAATD0101TDR or a furnace equipped with TDR. Most Carrier furnaces are equipped with TDR.

EER — Energy Efficiency Ratio

SEER — Seasonal Energy Efficiency Ratio

TDR — Time–Delay Relay

TXV — Thermostatic Expansion Valve

NOTES:

1. Ratings are net values reflecting the effects of circulating fan motor heat. Supplemental electric heat is not included.
2. Tested outdoor/indoor combinations have been tested in accordance with DOE test procedures for central air conditioners. Ratings for other combinations are determined under DOE computer simulation procedures.
3. Determine actual CFM values obtainable for your system by referring to fan performance data in fan coil or furnace coil literature.
4. Do not apply with capillary tube coils as performance and reliability are significantly affected.

NOTE: Ratings contained in this document are subject to change at any time. Always refer to the AHRI directory (www.ahridirectory.org) for the most up–to–date ratings information

24ANB6

DETAILED COOLING CAPACITIES#

EVAPORATOR AIR				CONDENSER ENTERING AIR TEMPERATURES °F (°C)									
		75 (23.9)		85 (29.4)		95 (35)		105 (40.6)		115 (46.1)		125 (51.7)	
CFM	EWB °F (°C)	Capacity MBTuh		Total Sys. KW**	Capacity MBTuh		Total Sys. KW**	Capacity MBTuh		Total Sys. KW**	Capacity MBTuh		Total Sys. KW**
		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†	
525	72 (22.2)	21.63	10.95	1.12	20.61	10.57	1.26	19.54	10.18	1.41	18.41	9.76	1.58
	67 (19.4)	19.55	13.28	1.12	18.63	12.90	1.26	17.65	12.51	1.41	16.62	12.09	1.57
	63 (17.2)††	18.05	12.76	1.12	17.20	12.38	1.26	16.30	11.98	1.40	15.33	11.57	1.56
	62 (16.7)	17.71	15.58	1.12	16.88	15.21	1.25	16.01	14.81	1.40	15.10	14.39	1.56
	57 (13.9)	17.06	17.06	1.12	16.42	16.42	1.25	15.73	15.73	1.40	14.99	14.99	1.56
	72 (22.2)	22.11	11.53	1.14	21.03	11.14	1.29	19.90	10.74	1.44	18.72	10.32	1.61
600	67 (19.4)	19.99	14.19	1.14	19.02	13.81	1.28	18.00	13.40	1.43	16.92	12.98	1.60
	63 (17.2)††	18.48	13.61	1.14	17.58	13.22	1.28	16.63	12.82	1.43	15.63	12.39	1.59
	62 (16.7)	18.18	16.82	1.14	17.33	16.42	1.28	16.46	16.46	1.43	15.67	15.67	1.59
	57 (13.9)	17.88	17.88	1.14	17.18	17.18	1.28	16.44	16.44	1.43	15.64	15.64	1.59
	72 (22.2)	22.46	12.08	1.17	21.34	11.68	1.32	20.17	11.27	1.47	18.95	10.85	1.64
	67 (19.4)	20.34	15.07	1.17	19.32	14.67	1.31	18.26	14.26	1.46	17.15	13.83	1.63
675	63 (17.2)††	18.80	14.42	1.17	17.86	14.03	1.31	16.88	13.62	1.46	15.84	13.18	1.62
	62 (16.7)	18.61	18.52	1.17	17.85	17.85	1.31	17.05	17.05	1.46	16.21	16.21	1.62
	57 (13.9)	18.57	18.57	1.17	17.82	17.82	1.31	17.03	17.03	1.46	16.18	16.18	1.62
	72 (22.2)	22.46	12.08	1.17	21.34	11.68	1.32	20.17	11.27	1.47	18.95	10.85	1.64
	67 (19.4)	20.34	15.07	1.17	19.32	14.67	1.31	18.26	14.26	1.46	17.15	13.83	1.63
	63 (17.2)††	18.80	14.42	1.17	17.86	14.03	1.31	16.88	13.62	1.46	15.84	13.18	1.62

COOLING INDOOR				CAPACITY				POWER		FURNACE MODEL			
MODEL													
*CNPV*1917A**		1.00	1.00										
CAP**1814A**		1.00	1.04										
CAP**2414A**		1.00	1.00										
CAP**2417A**		1.00	1.00										
CAP**3621A**		1.00	1.00										
CNPV*2417A**		1.00	1.00										
CNPV*1814A**		1.00	1.00										
CNPV*2414A**		1.00	1.00										
CNPV*2417A**		1.00	1.00										
CNPV*3621A**		1.00	1.00										
CSPH*2412A**		1.00	1.00										
FB4CNF018		1.00	0.92										
FB4CNF024		1.00	0.92										
FB4CNF030		1.00	0.96										
FE4ANF002		1.00	0.89										
FF1ENP018		1.00	1.04										
FF1ENP019		1.00	0.92										
FF1ENP024		1.00	1.00										
FF1ENP025		1.00	0.89										
FF1ENP031		1.00	0.92										
FF1ENP037		1.00	0.92										
FV4CNF002		1.00	0.89										
FX4DN(B,F)031		1.00	0.92										
FX4DNF019		1.00	0.89										
FX4DNF025		1.00	0.89										
FY5BNF018		1.00	0.96										
FY5BNF024		1.00	0.96										
CAP**1814A**		0.99	0.91										
CAP**2414A**		1.00	0.92										
CAP**2417A**		1.00	0.92										
CNPV*2417A**		1.00	0.92										
CNPV*1814A**		1.00	0.92										
CNPV*1917A**		1.00	0.92										
CNPV*2414A**		1.00	0.92										

See notes on pg. 61

DETAILED COOLING CAPACITIES# CONTINUED

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																					
		75 (23.9)				85 (29.4)				95 (35)				105 (40.6)				115 (46.1)				125 (51.7)	
CFM	EWB ° F (° C)	Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**	
		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total
700	72 (22.2)	28.62	14.37	1.54	27.23	13.51	1.73	25.76	12.66	1.94	24.22	11.82	2.16	22.61	10.99	2.41	20.92	10.17	2.69				
	67 (19.4)	26.01	17.59	1.54	24.72	16.64	1.73	23.39	15.71	1.93	21.99	14.77	2.15	20.51	13.85	2.40	18.97	12.93	2.68				
	63 (17.2)††	24.07	16.91	1.55	22.89	15.98	1.73	21.64	15.06	1.92	20.33	14.14	2.14	18.96	13.23	2.39	17.51	12.32	2.67				
	62 (16.7)	23.66	20.76	1.55	22.51	19.72	1.73	21.32	18.69	1.92	20.11	20.07	2.14	18.99	18.99	2.39	17.81	17.81	2.67				
	57 (13.9)	23.01	23.01	1.55	22.09	22.09	1.73	21.11	21.11	1.92	20.07	20.07	2.14	18.96	18.96	2.39	17.78	17.78	2.67				
800	72 (22.2)	29.14	15.12	1.58	27.70	14.25	1.77	26.17	13.37	1.98	24.57	12.50	2.20	22.90	11.64	2.45	21.16	10.79	2.73				
	67 (19.4)	26.54	18.82	1.58	25.20	17.83	1.77	23.80	16.84	1.97	22.34	15.87	2.19	20.81	14.90	2.43	19.21	13.94	2.72				
	63 (17.2)††	24.59	18.05	1.58	23.34	17.08	1.76	22.05	16.12	1.96	20.69	15.16	2.18	19.26	14.21	2.43	17.77	13.26	2.71				
	62 (16.7)	24.26	22.42	1.58	23.11	23.01	1.76	22.04	22.04	1.96	20.92	20.92	2.18	19.73	19.73	2.43	18.47	18.47	2.71				
	57 (13.9)	24.05	24.05	1.58	23.05	23.05	1.76	22.00	22.00	1.96	20.89	20.89	2.18	19.71	19.71	2.43	18.45	18.45	2.71				
900	72 (22.2)	29.51	15.85	1.62	28.04	14.95	1.81	26.46	14.05	2.02	24.81	13.15	2.24	23.10	12.27	2.49	21.31	11.39	2.77				
	67 (19.4)	26.93	20.00	1.62	25.54	18.97	1.80	24.10	17.94	2.01	22.60	16.92	2.23	21.03	15.91	2.47	19.40	14.90	2.75				
	63 (17.2)††	24.97	19.15	1.62	23.69	18.14	1.80	22.35	17.14	2.00	20.95	16.14	2.22	19.49	15.15	2.47	17.97	14.15	2.75				
	62 (16.7)	24.96	24.96	1.62	23.89	23.89	1.80	22.77	22.77	2.00	21.59	21.59	2.22	20.34	20.34	2.47	19.00	19.00	2.75				
	57 (13.9)	24.92	24.92	1.62	23.86	23.86	1.80	22.74	22.74	2.00	21.56	21.56	2.22	20.31	20.31	2.47	18.98	18.98	2.75				
COOLING INDOOR MODEL		CAPACITY		POWER	FURNACE MODEL		COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL		COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL						
*CNPV*3117A**		1.00		1.00				FF1ENP031	0.98	0.94			CNPV*2417A**	0.97	0.89		58CV(A)X090-16						
CAP**2414A**		0.97		1.02				FF1ENP036	0.97	1.06			CNPV*3017A**	0.97	0.90		58CV(A)X090-16						
CAP**2417A**		0.97		1.02				FF1ENP037	0.99	0.95			CNPV*3117A**	0.99	0.92		58CV(A)X090-16						
CAP**3014A**		0.98		1.03				FV4CN(B,F)003	0.98	0.91			CNPV*3617A**	0.97	0.90		58CV(A)X090-16						
CAP**3017A**		0.98		1.03				FV4CNF002	0.98	0.91			CNPV*1917A**	0.97	0.90		58CV(A)X090-16						
CAP**3614A**		0.98		1.03				FX4DN(B,F)031	1.00	0.96			CNPV*2417A**	0.97	0.89		58CV(A)X090-16						
CAP**3617A**		0.98		1.03				FX4DN(B,F)037	1.01	0.93			CNPV*3017A**	0.97	0.90		58CV(A)X090-16						
CAP**3619A**		0.98		1.03				FX4DNF025	0.99	0.92			CNPV*3117A**	0.99	0.92		58CV(A)X090-16						
CAP**3621A**		0.98		1.03				FY5BNF024	0.98	0.98			CNPV*3617A**	0.97	0.90		58CV(A)X090-16						
CNPV*2418A**		0.97		1.02				FY5BNF030	0.99	0.99			CNPV*3621A**	0.97	0.90		58CV(A)X090-16						
CNPV*3618A**		0.98		1.03				CAP**2414A**	0.97	0.93			CSPH*2412A**	0.98	0.91		58CV(A)X090-16						
CNPV*2417A**		0.97		1.02				CAP**2417A**	0.97	0.93			CSPH*3012A**	0.98	0.91		58CV(A)X090-16						
CNPV*3017A**		0.98		1.03				CAP**3014A**	0.97	0.89			CSPH*3612A**	0.99	0.92		58CV(A)X090-16						
CNPV*3117A**		1.00		1.00				CAP**3017A**	0.97	0.90			CAP**3621A**	0.98	0.91		58CV(A)X110-20						
CNPV*3617A**		0.98		1.03				CAP**3614A**	0.97	0.90			CNPV*2417A**	0.97	0.93		58CV(A)X110-20						
CNPV*1917A**		0.98		1.03				CAP**3617A**	0.97	0.90			CNPV*3017A**	0.97	0.90		58CV(A)X110-20						
CNPV*2414A**		0.97		1.02				CNPV*2417A**	0.97	0.93			CNPV*3017A**	0.97	0.90		58CV(A)X110-20						
CNPV*2417A**		0.97		1.02				CNPV*3017A**	0.97	0.90			CNPV*3617A**	0.97	0.90		58CV(A)X110-20						
CNPV*3014A**		0.98		1.03				CNPV*3117A**	0.99	0.92			CNPV*3621A**	0.97	0.90		58CV(A)X110-20						
CNPV*3017A**		0.98		1.03				CNPV*3617A**	0.97	0.90			CSPH*2412A**	0.97	0.94		58CV(A)X110-20						
CNPV*3617A**		0.98		1.03				CNPV*1917A**	0.97	0.90			CSPH*3012A**	0.98	0.91		58CV(A)X110-20						
CNPV*3621A**		0.98		1.03				CNPV*2414A**	0.97	0.93			CSPH*3612A**	0.99	0.92		58CV(A)X110-20						
CSPH*2412A**		0.98		1.03				CNPV*2417A**	0.97	0.93			CNPV*2417A**	0.97	0.93		58CV(A)X135-22						
CSPH*3012A**		0.98		1.03				CNPV*3014A**	0.97	0.90			CNPV*3017A**	0.97	0.90		58CV(A)X135-22						
CSPH*3612A**		1.00		1.00				CNPV*3017A**	0.97	0.90			CNPV*3117A**	0.99	0.92		58CV(A)X135-22						
FB4CNF024		0.97		0.97				CNPV*3117A**	0.99	0.92			CNPV*3617A**	0.97	0.90		58CV(A)X135-22						
FB4CNF030		0.99		0.92				CNPV*3617A**	0.97	0.90			CSPH*2412A**	0.98	0.94		58CV(A)X135-22						
FB4CNF036		0.97		1.04				CSPH*2412A**	0.97	0.94			CSPH*3012A**	0.98	0.91		58CV(A)X135-22						
FE4AN(B,F)003		0.98		0.91				CSPH*3012A**	0.97	0.90			CSPH*3612A**	0.99	0.92		58CV(A)X135-22						
FE4ANF002		0.98		0.91				CSPH*3612A**	0.99	0.92			CNPV*2417A**	0.97	0.93		58CV(A)X155-22						
FE5ANB004		1.02		0.90				CAP**2417A**	0.97	0.89			CNPV*3017A**	0.97	0.90		58CV(A)X155-22						
FF1ENP024		0.97		1.01				CAP**3017A**	0.97	0.90			CNPV*3117A**	0.99	0.92		58CV(A)X155-22						
FF1ENP025		0.98		0.94				CAP**3617A**	0.97	0.90			CNPV*3617A**	0.97	0.90		58CV(A)X155-22						
FF1ENP030		0.97		1.01				CAP**3621A**	0.97	0.90			CSPH*2412A**	0.98	0.94		58CV(A)X155-22						

24ANB6

24ANB6

COOLING INDOOR MODEL	CAPACITY	POWER	FURNACE MODEL
CSPH*2412A**	0.97	0.93	58MV(B,C)080-20
CSPH*3012A**	0.97	0.89	58MV(B,C)080-20
CSPH*3612A**	0.98	0.91	58MV(B,C)080-20
CAP**3621A**	0.97	0.90	58MV(B,C)100-20
CNPH*2417A**	0.97	0.93	58MV(B,C)100-20
CNPH*3017A**	0.97	0.90	58MV(B,C)100-20
CNPH*3117A**	0.99	0.92	58MV(B,C)100-20
CNPH*3617A**	0.97	0.90	58MV(B,C)100-20
CNPV*3621A**	0.97	0.90	58MV(B,C)100-20
CSPH*2412A**	0.97	0.90	58MV(B,C)100-20
CSPH*3012A**	0.97	0.90	58MV(B,C)100-20
CSPH*3612A**	0.99	0.92	58MV(B,C)100-20
CNPH*2417A**	0.97	0.90	58MV(B,C)120-20
CNPH*3017A**	0.98	0.91	58MV(B,C)120-20
CNPH*3117A**	1.00	0.92	58MV(B,C)120-20
CNPH*3617A**	0.98	0.91	58MV(B,C)120-20
CSPH*2412A**	0.98	0.91	58MV(B,C)120-20
CSPH*3012A**	0.98	0.91	58MV(B,C)120-20
CSPH*3612A**	1.00	0.92	58MV(B,C)120-20
CNPH*2417A**	0.97	0.93	58MV(B,C)040-14
CNPH*3017A**	0.97	0.90	58MV(B,C)040-14
CNPH*3117A**	0.99	0.92	58MV(B,C)040-14
CNPH*3617A**	0.97	0.90	58MV(B,C)040-14
CSPH*2412A**	0.97	0.94	58MV(B,C)040-14
CSPH*3012A**	0.97	0.90	58MV(B,C)040-14
CAP**2414A**	0.97	0.94	58PH*045-08
CAP**2417A**	0.97	0.94	58PH*045-08
CAP**3014A**	0.98	0.94	58PH*045-08
CAP**3017A**	0.98	0.91	58PH*045-08
CAP**3617A**	0.99	0.92	58PH*045-08
CNPH*2417A**	0.97	0.94	58PH*045-08
CNPH*3017A**	0.98	0.91	58PH*045-08
CNPH*3117A**	1.01	0.93	58PH*045-08
CNPH*3617A**	0.98	0.91	58PH*045-08
CNPV*1917A**	0.98	0.91	58PH*045-08
CNPV*2414A**	0.97	0.94	58PH*045-08
CNPV*2417A**	0.97	0.94	58PH*045-08
CNPV*3014A**	0.98	0.94	58PH*045-08
CNPV*3017A**	0.98	0.91	58PH*045-08
CNPV*3117A**	1.01	0.93	58PH*045-08
CNPV*3617A**	0.98	0.91	58PH*045-08
CSPH*2412A**	0.98	0.91	58PH*045-08
CSPH*3612A**	1.00	0.92	58PH*045-08
CAP**2417A**	0.97	0.94	OVLAA036098
CAP**3017A**	0.98	0.91	OVLAA036098
CNPH*2417A**	0.97	0.94	OVLAA036098
CNPH*3017A**	0.98	0.91	OVLAA036098
CNPV*2417A**	0.98	0.94	OVLAA036098
CNPV*3017A**	0.98	0.91	OVLAA036098
CNPV*3117A**	1.00	0.92	OVLAA036098
CSPH*2412A**	0.98	0.94	OVLAA036098

DETAILED COOLING CAPACITIES# CONTINUED

24ANB624A**30 Outdoor Section With CNPV*3117A**+TDR Indoor Section

COOLING INDOOR MODEL	CAPACITY	POWER	FURNACE MODEL
CSPH*3012A**	0.99	0.92	OVILAB036098
CAP**2417A**	0.97	0.94	OVMAAB036098
CAP**3017A**	0.98	0.91	OVMAAB036098
CNPH*2417A**	0.97	0.94	OVMAAB036098
CNPH*3017A**	0.98	0.91	OVMAAB036098
CNPH*3117A**	1.00	0.92	OVMAAB036098
CNPV*2417A**	0.97	0.94	OVMAAB036098
CNPV*3017A**	0.98	0.91	OVMAAB036098
CNPV*3117A**	1.00	0.92	OVMAAB036098
CSPH*2412A**	0.98	0.94	OVMAAB036098
CSPH*3012A**	0.99	0.92	OVMAAB036098
CAP**2417A**	0.97	0.90	OVMAAB042112
CAP**3017A**	0.97	0.90	OVMAAB042112
CNPH*2417A**	0.97	0.94	OVMAAB042112
CNPH*3017A**	0.98	0.91	OVMAAB042112
CNPH*3117A**	1.00	0.92	OVMAAB042112
CNPV*2417A**	0.97	0.94	OVMAAB042112
CNPV*3017A**	0.98	0.91	OVMAAB042112
CNPV*3117A**	1.00	0.92	OVMAAB042112
CSPH*2412A**	0.98	0.94	OVMAAB042112
CSPH*3012A**	0.98	0.91	OVMAAB042112

See notes on pg. 61

DETAILED COOLING CAPACITIES# CONTINUED

EVAPORATOR AIR				CONDENSER ENTERING AIR TEMPERATURES ° F (° C)															
CFM	EWB ° F (° C)	75 (23.9)		85 (29.4)		95 (35)				105 (40.6)				115 (46.1)				125 (51.7)	
		Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**				
900	72 (22.2)	34.12	17.11	1.85	32.53	16.70	2.08	30.88	16.26	2.34	29.15	15.80	2.64	27.28	15.28	2.99	25.26	14.70	3.40
	67 (19.4)	31.02	21.15	1.86	29.57	20.76	2.09	28.06	20.35	2.35	26.46	19.90	2.65	24.74	19.40	3.00	22.87	18.83	3.40
	63 (17.2)††	28.79	20.32	1.87	27.44	19.83	2.09	26.03	19.51	2.35	24.52	19.04	2.65	22.89	18.52	3.00	21.12	17.93	3.40
	62 (16.7)	28.37	25.13	1.87	27.08	25.13	2.09	24.55	24.55	2.35	23.21	23.21	2.65	23.21	23.21	3.00	21.75	21.75	3.40
	57 (13.9)	27.93	27.93	1.87	26.86	26.86	2.09	25.73	25.73	2.35	24.51	24.51	2.65	23.18	23.18	3.00	21.72	21.72	3.40
	72 (22.2)	34.56	17.82	1.89	32.92	17.41	2.11	31.23	16.97	2.38	29.45	16.51	2.68	27.53	15.99	3.03	25.46	15.41	3.44
1000	67 (19.4)	31.45	22.30	1.90	29.95	21.91	2.12	28.40	21.50	2.38	26.76	21.05	2.68	25.00	20.54	3.03	23.09	19.97	3.44
	63 (17.2)††	29.21	21.39	1.90	27.81	21.00	2.13	26.36	20.57	2.39	24.81	20.10	2.69	23.15	19.58	3.04	21.35	18.98	3.44
	62 (16.7)	28.93	28.68	1.90	27.74	27.74	2.13	26.55	26.55	2.39	25.27	25.27	2.69	23.88	23.88	3.03	22.35	22.35	3.44
	57 (13.9)	28.84	28.84	1.90	27.70	27.70	2.13	26.52	26.52	2.39	25.23	25.23	2.69	23.85	23.85	3.03	22.32	22.32	3.44
	72 (22.2)	34.98	18.68	1.93	33.28	18.26	2.16	31.54	17.83	2.42	29.70	17.36	2.73	27.74	16.84	3.08	25.63	16.26	3.49
	67 (19.4)	31.86	23.68	1.94	30.31	23.29	2.17	28.73	22.88	2.43	27.04	22.43	2.73	25.25	21.91	3.08	23.32	21.32	3.49
1125	63 (17.2)††	29.61	22.67	1.94	28.18	22.28	2.17	26.68	21.85	2.43	25.10	21.38	2.73	23.41	20.84	3.08	21.59	20.22	3.49
	62 (16.7)	29.84	29.84	1.94	28.63	28.63	2.17	27.38	27.38	2.43	26.02	26.02	2.73	24.56	24.56	3.08	22.96	22.96	3.49
	57 (13.9)	29.80	29.80	1.94	28.59	28.59	2.17	27.34	27.34	2.43	25.99	25.99	2.73	24.53	24.53	3.08	22.93	22.93	3.49
COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL		COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL		COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL			
*CNPV*3117A**		1.00	1.00			FX4DN(B,F)037		1.01	0.94			CAP**4221A**		0.99	0.91	58CV(A)110--20			
CAP**3014A**		0.98	0.98			FX4DN(B,F)043		1.01	0.97			CAP**4224A**		0.99	0.91	58CV(A)110--20			
CAP**3017A**		0.98	0.98			FY5BNF030		0.99	0.95			CNPV*3017A**		0.98	0.90	58CV(A)110--20			
CAP**3614A**		0.98	0.98			FY5BNF036		0.99	0.99			CNPV*3117A**		1.00	0.92	58CV(A)110--20			
CAP**3617A**		0.98	0.98			CAP**3014A**		0.97	0.93			CNPV*3617A**		0.98	0.90	58CV(A)110--20			
CAP**3619A**		0.98	1.02			CAP**3017A**		0.97	0.93			CNPV*4221A**		0.99	0.91	58CV(A)110--20			
CAP**3621A**		0.98	0.98			CAP**3614A**		0.97	0.93			CNPV*3621A**		0.98	0.90	58CV(A)110--20			
CAP**4221A**		0.99	1.03			CAP**3617A**		0.98	0.94			CNPV*4221A**		0.99	0.91	58CV(A)110--20			
CAP**4224A**		0.99	1.03			CNPV*3017A**		0.97	0.93			CSPH*3012A**		0.98	0.90	58CV(A)110--20			
CNPF*3618A**		0.98	1.02			CNPV*3117A**		0.99	0.92			CSPH*3612A**		1.00	0.92	58CV(A)110--20			
CNPH*3017A**		0.98	0.98			CNPV*3617A**		0.97	0.93			CSPH*4212A**		0.99	0.91	58CV(A)110--20			
CNPH*3117A**		1.00	1.00			CNPV*4221A**		0.99	0.91			CAP**4224A**		0.99	0.91	58CV(A)135--22			
CNPH*3617A**		0.98	0.98			CNPV*3014A**		0.97	0.93			CNPV*3017A**		0.98	0.90	58CV(A)135--22			
CNPH*4221A**		0.99	1.04			CNPV*3017A**		0.97	0.93			CNPV*3117A**		1.00	0.92	58CV(A)135--22			
CNPV*3014A**		0.98	0.98			CNPV*3117A**		0.99	0.92			CNPV*3617A**		0.98	0.90	58CV(A)135--22			
CNPV*3017A**		0.98	0.98			CNPV*3617A**		0.97	0.93			CNPV*4221A**		0.99	0.91	58CV(A)135--22			
CNPV*3617A**		0.98	0.98			CNPV*4217A**		0.99	0.91			CSPH*3012A**		0.98	0.90	58CV(A)135--22			
CNPV*3621A**		0.98	0.98			CSPH*3012A**		0.98	0.94			CSPH*3612A**		1.00	0.92	58CV(A)135--22			
CNPV*3717A**		1.01	1.01			CSPH*3612A**		0.99	0.92			CSPH*4212A**		1.00	0.92	58CV(A)135--22			
CNPV*4217A**		1.00	1.00			CSPH*4212A**		1.00	0.92			CAP**4224A**		0.99	0.91	58CV(A)155--22			
CNPV*4221A**		0.99	1.04			CAP**3017A**		0.97	0.90			CNPV*3017A**		0.98	0.90	58CV(A)155--22			
CSPH*3012A**		0.99	1.03			CAP**3617A**		0.98	0.90			CNPV*3117A**		1.00	0.92	58CV(A)155--22			
CSPH*3612A**		1.00	1.00			CAP**3621A**		0.98	0.90			CNPV*3617A**		0.98	0.90	58CV(A)155--22			
CSPH*4212A**		1.01	1.01			CAP**4221A**		0.99	0.91			CNPV*4221A**		0.99	0.91	58CV(A)155--22			
FB4CNF030		0.99	0.95			CNPV*3017A**		0.98	0.90			CSPH*3012A**		0.98	0.90	58CV(A)155--22			
FB4CNF036		0.99	0.95			CNPV*3117A**		0.99	0.92			CSPH*3612A**		1.00	0.92	58CV(A)155--22			
FB4CNF042		1.00	1.00			CNPV*3617A**		0.98	0.90			CSPH*4212A**		1.00	0.92	58CV(A)155--22			
FE4AN(B,F)003		0.99	0.91			CNPV*4221A**		0.99	0.91			CAP**3619A**		0.98	0.94	58HDV040--12			
FE4AN(B,F)005		1.01	0.93			CNPV*3017A**		0.98	0.90			CAP**3621A**		0.98	0.94	58HDV040--12			
FE4ANF002		0.99	0.91			CNPV*3117A**		0.99	0.92			CNPV*3017A**		0.98	0.96	58HDV040--12			
FE5ANB004		1.02	0.94			CNPV*3617A**		0.98	0.90			CNPV*3617A**		0.98	0.98	58HDV040--12			
FF-TENP030		0.97	0.97			CNPV*3621A**		0.98	0.90			CNPV*3017A**		0.98	0.94	58HDV040--12			
FF-TENP031		0.99	0.95			CNPV*3717A**		1.01	0.93			CNPV*3117A**		1.00	0.96	58HDV040--12			
FF-TENP036		0.99	0.99			CNPV*4217A**		0.99	0.92			CNPV*3617A**		0.98	0.94	58HDV040--12			
FF-TENP037		0.99	0.95			CNPV*4221A**		0.99	0.91			CNPV*3621A**		0.98	0.94	58HDV040--12			
FV4CN(B,F)003		0.99	0.91			CSPH*3012A**		0.98	0.90			CNPV*3717A**		1.01	0.93	58HDV040--12			
FV4CN(B,F)005		1.01	0.90			CSPH*3612A**		0.99	0.92			CSPH*3012A**		0.98	0.94	58HDV040--12			
FV4CNF002		0.99	0.91			CSPH*4212A**		1.00	0.92			CSPH*3612A**		1.00	0.96	58HDV040--12			
FX4DN(B,F)031		1.00	0.92			CAP**3621A**		0.98	0.90			CAP**3619A**		0.99	0.95	58HDV060--12			

24ANB630A**30 Outdoor Section With CNPV*3117A** + TDR Indoor Section

24ANB6

DETAILED COOLING CAPACITIES# CONTINUED

24ANB630A**30 Outdoor Section With CNPV*3117A**+TDR Indoor Section

COOLING INDOOR MODEL	CAPACITY	POWER	FURNACE MODEL
CNPV*4217A**	1.00	0.92	58PH*070-16
CNPV*4221A**	0.99	0.95	58PH*070-16
CSPH*3012A**	0.98	0.94	58PH*070-16
CSPH*3612A**	1.00	0.92	58PH*070-16
CSPH*4212A**	1.01	0.93	58PH*070-16
CAP**3621A**	0.99	0.92	58PH*090-16
CAP**4221A**	1.00	0.92	58PH*090-16
CAP**4224A**	1.00	0.92	58PH*090-16
CNPH*3017A**	0.98	0.94	58PH*090-16
CNPH*3117A**	1.01	0.93	58PH*090-16
CNPH*3617A**	0.98	0.94	58PH*090-16
CNPH*4221A**	0.99	0.92	58PH*090-16
CNPV*3621A**	0.98	0.94	58PH*090-16
CSPH*3012A**	0.99	0.92	58PH*090-16
CSPH*4221A**	0.99	0.92	58PH*090-16
CSPH*3612A**	1.01	0.93	58PH*090-16
CSPH*4212A**	1.01	0.94	58PH*090-16
CAP**3017A**	0.97	0.93	OVLAAB036098
CAP**3617A**	0.98	0.94	OVLAAB036098
CNPH*3017A**	0.98	0.94	OVLAAB036098
CNPH*3117A**	1.00	0.92	OVLAAB036098
CNPH*3617A**	0.98	0.94	OVLAAB036098
CNPV*3017A**	0.98	0.94	OVLAAB036098
CNPV*3117A**	1.00	0.92	OVLAAB036098
CNPV*3617A**	0.98	0.94	OVLAAB036098
CNPV*3717A**	1.01	0.93	OVLAAB036098
CSPH*3612A**	0.99	0.92	OVLAAB036098
CAP**3621A**	0.99	0.95	OVLAAB048112
CNPH*3017A**	0.99	0.95	OVLAAB048112
CNPH*3117A**	1.01	0.93	OVLAAB048112
CNPH*3617A**	0.99	0.95	OVLAAB048112
CNPV*3621A**	0.99	0.95	OVLAAB048112
CSPH*3012A**	0.99	0.95	OVLAAB048112
CSPH*3612A**	1.01	0.97	OVLAAB048112
CAP**3017A**	0.98	0.94	OVMAAB036098
CAP**3617A**	0.98	0.94	OVMAAB036098
CNPH*3017A**	0.98	0.94	OVMAAB036098
CNPH*3117A**	1.00	0.96	OVMAAB036098
CNPH*3617A**	0.98	0.94	OVMAAB036098
CNPV*3017A**	0.98	0.94	OVMAAB036098
CNPV*3117A**	1.00	0.92	OVMAAB036098
CNPV*3617A**	0.98	0.94	OVMAAB036098
CNPV*3717A**	1.01	0.93	OVMAAB036098
CSPH*3012A**	0.98	0.94	OVMAAB036098
CSPH*3612A**	1.00	0.96	OVMAAB036098
CAP**3017A**	0.98	0.94	OVMAAB042112
CAP**3617A**	0.99	0.95	OVMAAB042112
CNPH*3017A**	0.98	0.94	OVMAAB042112
CNPH*3117A**	1.00	0.92	OVMAAB042112
CNPH*3617A**	0.98	0.94	OVMAAB042112
CNPV*3017A**	0.98	0.94	OVMAAB042112
CNPV*3117A**	1.00	0.92	OVMAAB042112
CNPV*3617A**	0.98	0.94	OVMAAB042112
CNPV*3717A**	1.01	0.94	OVMAAB042112
CSPH*3012A**	0.99	0.95	OVMAAB042112
CSPH*3612A**	1.00	0.92	OVMAAB042112

See notes on pg. 61

DETAILED COOLING CAPACITIES# CONTINUED

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
CFM	EWB ° F (° C)	75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)			125 (51.7)		
		Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**	Capacity MBtuh		Total Sys. KW**
		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†	
1050	72 (22.2)	41.79	21.33	2.30	39.58	20.21	2.55	37.29	19.10	2.83	34.92	17.98	3.14	32.46	16.86	3.51	29.88	15.74	3.93
	67 (19.4)	37.98	26.27	2.28	35.95	25.04	2.53	33.86	23.81	2.81	31.68	22.58	3.12	29.42	21.34	3.49	27.06	20.10	3.92
	63 (17.2)††	35.23	25.25	2.27	33.34	24.04	2.52	31.38	22.83	2.79	29.34	21.61	3.11	27.22	20.39	3.48	25.00	19.15	3.91
	62 (16.7)	34.66	31.16	2.26	32.83	29.80	2.51	30.98	28.42	2.79	29.22	29.22	3.11	27.47	27.47	3.48	25.61	25.61	3.91
	57 (13.9)	33.97	33.97	2.26	32.44	32.44	2.51	30.85	30.85	2.79	29.18	29.18	3.11	27.42	27.42	3.48	25.57	25.57	3.91
	72 (22.2)	42.51	22.47	2.36	40.20	21.32	2.61	37.84	20.17	2.89	35.39	19.02	3.20	32.84	17.87	3.57	30.20	16.71	3.99
1200	67 (19.4)	38.68	28.11	2.34	36.57	26.83	2.59	34.40	25.54	2.87	32.16	24.26	3.18	29.82	22.96	3.55	27.40	21.67	3.97
	63 (17.2)††	35.91	26.96	2.33	33.94	25.70	2.58	31.91	24.44	2.85	29.80	23.17	3.17	27.61	21.89	3.54	25.35	20.60	3.97
	62 (16.7)	35.54	35.26	2.32	33.84	33.84	2.58	32.14	32.14	2.85	30.35	30.35	3.17	28.49	28.49	3.54	26.52	26.52	3.97
	57 (13.9)	35.43	35.43	2.32	33.79	33.79	2.58	32.09	32.09	2.85	30.31	30.31	3.17	28.45	28.45	3.54	26.48	26.48	3.97
	72 (22.2)	43.03	23.57	2.42	40.66	22.38	2.67	38.23	21.20	2.95	35.70	20.02	3.26	33.10	18.84	3.63	30.39	17.65	4.04
	67 (19.4)	39.19	29.87	2.40	37.03	28.54	2.65	34.81	27.21	2.93	32.50	25.87	3.24	30.12	24.52	3.61	27.67	23.16	4.03
1350	63 (17.2)††	36.41	28.60	2.39	34.39	27.29	2.64	32.31	25.98	2.91	30.15	24.66	3.23	27.92	23.33	3.60	25.62	21.97	4.03
	62 (16.7)	36.68	36.68	2.39	34.95	34.95	2.64	33.16	33.16	2.92	31.28	31.28	3.24	29.32	29.32	3.60	27.25	27.25	4.03
	57 (13.9)	36.63	36.63	2.39	34.90	34.90	2.64	33.11	33.11	2.92	31.23	31.23	3.24	29.28	29.28	3.60	27.21	27.21	4.03

COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL		COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL		COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL	
*CNPV*3717A**		1.00	1.00			FV4GN(B,F)005		0.99	0.92			CAP**3621A**		0.96	0.92	58CV(A)110-20	
CAP**3614A**		0.95	0.99			FV4GNB006		1.01	0.89			CAP**4221A**		0.97	0.93	58CV(A)110-20	
CAP**3617A**		0.96	1.00			FV4GNF002		0.96	0.96			CAP**4224A**		0.97	0.93	58CV(A)110-20	
CAP**3619A**		0.96	1.00			FX4DN(B,F)037		0.99	0.99			CAP**4821A**		0.98	0.90	58CV(A)110-20	
CAP**3621A**		0.96	1.00			FX4DN(B,F)043		0.99	0.92			CAP**4824A**		0.98	0.90	58CV(A)110-20	
CAP**4221A**		0.97	1.01			FX4DN(B,F)049		1.01	0.93			CNPV*3617A**		0.95	0.92	58CV(A)110-20	
CAP**4224A**		0.97	1.01			FY5BNF036		0.97	0.97			CNPV*4221A**		0.97	0.93	58CV(A)110-20	
CAP**4817A**		0.99	1.03			FY5BNF042		0.98	0.98			CNPV*4821A**		0.99	0.92	58CV(A)110-20	
CAP**4821A**		0.98	1.03			CAP**3614A**		0.95	0.95			CNPV*4824A**		0.98	0.91	58CV(A)110-20	
CAP**4823A**		0.98	1.03			CAP**3617A**		0.95	0.95			CNPV*4827A**		0.97	0.92	58CV(A)110-20	
CAP**4824A**		0.98	1.03			CAP**4817A**		0.98	0.94			CNPV*4831A**		0.96	0.93	58CV(A)110-20	
CNPV*3618A**		0.96	1.05			CNPV*3617A**		0.95	0.95			CNPV*4834A**		0.99	0.92	58CV(A)110-20	
CNPV*4818A**		0.98	1.03			CNPV*4221A**		0.96	0.96			CNPV*4837A**		0.98	0.91	58CV(A)110-20	
CNPV*3617A**		0.96	1.00			CNPV*4321A**		0.99	0.91			CNPV*4841A**		0.98	0.91	58CV(A)110-20	
CNPV*4221A**		0.97	1.01			CNPV*4821A**		0.98	0.94			CSPH*3612A**		0.98	0.90	58CV(A)110-20	
CNPV*4321A**		1.00	1.04			CNPV*3617A**		0.95	0.95			CSPH*4212A**		0.98	0.91	58CV(A)110-20	
CNPV*4821A**		0.99	1.03			CNPV*3717A**		0.99	0.95			CSPH*4812A**		0.99	0.91	58CV(A)110-20	
CNPV*6024A**		0.99	0.99			CNPV*4217A**		0.97	0.93			CAP**4224A**		0.97	0.89	58CV(A)135-22	
CNPV*3617A**		0.96	1.00			CSPH*3612A**		0.97	0.93			CAP**4824A**		0.98	0.90	58CV(A)135-22	
CNPV*3621A**		0.96	1.00			CSPH*4212A**		0.98	0.94			CNPV*3617A**		0.95	0.92	58CV(A)135-22	
CNPV*4221A**		0.97	1.03			CSPH*4812A**		0.98	0.94			CNPV*4221A**		0.97	0.93	58CV(A)135-22	
CNPV*4324A**		1.00	1.01			CAP**3617A**		0.96	0.92			CNPV*4821A**		0.98	0.92	58CV(A)135-22	
CNPV*4821A**		0.99	1.03			CAP**3621A**		0.96	0.92			CNPV*4824A**		0.98	0.91	58CV(A)135-22	
CNPV*4824A**		0.99	1.03			CAP**4221A**		0.97	0.93			CNPV*4324A**		0.99	0.92	58CV(A)135-22	
CNPV*4827A**		0.99	1.03			CAP**4817A**		0.98	0.91			CNPV*4834A**		0.98	0.91	58CV(A)135-22	
CSPH*3612A**		0.98	1.03			CAP**4821A**		0.98	0.90			CSPH*3612A**		0.98	0.90	58CV(A)135-22	
CSPH*4212A**		0.99	1.03			CNPV*3617A**		0.95	0.92			CSPH*4212A**		0.98	0.91	58CV(A)135-22	
CSPH*4812A**		0.99	1.04			CNPV*4221A**		0.97	0.93			CSPH*4812A**		0.99	0.91	58CV(A)135-22	
FB4CNF036		0.96	0.96			CNPV*4321A**		0.99	0.91			CAP**4224A**		0.97	0.90	58CV(A)155-22	
FB4CNF042		0.99	0.95			CNPV*4821A**		0.98	0.90			CAP**4824A**		0.98	0.91	58CV(A)155-22	
FB4CNF048		0.99	0.95			CNPV*4824A**		0.95	0.95			CNPV*3617A**		0.96	0.92	58CV(A)155-22	
FE4AN(B,F)003		0.97	0.89			CNPV*3621A**		0.95	0.92			CNPV*4221A**		0.97	0.90	58CV(A)155-22	
FE4AN(B,F)005		0.99	0.92			CNPV*3717A**		0.99	0.91			CNPV*4821A**		0.99	0.92	58CV(A)155-22	
FE4ANB006		1.01	0.89			CNPV*4217A**		0.97	0.93			CNPV*4824A**		0.98	0.91	58CV(A)155-22	
FE4ANF002		0.96	0.96			CNPV*4221A**		0.97	0.93			CNPV*4324A**		0.99	0.92	58CV(A)155-22	
FE5ANB004		1.01	0.89			CNPV*4821A**		0.98	0.90			CNPV*4824A**		0.98	0.91	58CV(A)155-22	
FF1ENP036		0.96	1.05			CSPH*3612A**		0.98	0.90			CSPH*3612A**		0.98	0.91	58CV(A)155-22	
FF1ENP037		0.97	1.01			CSPH*4212A**		0.98	0.91			CSPH*4212A**		0.99	0.91	58CV(A)155-22	
FV4GN(B,F)003		0.97	0.89			CSPH*4812A**		0.98	0.91			CSPH*4812A**		0.99	0.91	58CV(A)155-22	

DETAILED COOLING CAPACITIES# CONTINUED

24ANB636A**30 Outdoor Section With CNPV*3717A**+TDR Indoor Section

COOLING INDOOR					FURNACE MODEL				
MODEL	CAPACITY	POWER	FURNACE MODEL						
CAP**3619A**	0.95	0.99	58HDV040--12						
CNP#*3617A**	0.96	0.99	58HDV040--12						
CNP#*4221A**	0.95	1.00	58HDV040--12						
CNP#*4321A**	0.99	0.99	58HDV040--12						
CNPV*3617A**	0.95	0.99	58HDV040--12						
CNPV*3621A**	0.95	0.99	58HDV040--12						
CNPV*3717A**	0.99	0.99	58HDV040--12						
CNPV*4217A**	0.97	0.97	58HDV040--12						
CSPH*3612A**	0.97	0.98	58HDV040--12						
CSPH*4212A**	0.98	0.98	58HDV040--12						
CAP**3619A**	0.96	0.96	58HDV060--12						
CAP**4823A**	0.98	0.99	58HDV060--12						
CNP#*3617A**	0.95	0.99	58HDV060--12						
CNP#*4221A**	0.97	0.97	58HDV060--12						
CNP#*4321A**	1.00	1.00	58HDV060--12						
CNPV*3617A**	0.95	0.95	58HDV060--12						
CNPV*3621A**	0.96	0.96	58HDV060--12						
CNPV*3717A**	0.99	0.99	58HDV060--12						
CNPV*4217A**	0.97	0.97	58HDV060--12						
CSPH*3612A**	0.98	0.98	58HDV060--12						
CSPH*4212A**	0.99	0.99	58HDV060--12						
CAP**4823A**	0.99	0.95	58HDV080--20						
CNP#*3617A**	0.97	0.97	58HDV080--20						
CNP#*4221A**	0.98	0.98	58HDV080--20						
CNP#*4321A**	1.01	1.01	58HDV080--20						
CNPV*3617A**	0.97	0.97	58HDV080--20						
CNPV*3621A**	0.98	0.98	58HDV080--20						
CNPV*4212A**	1.01	0.93	58HDV080--20						
CNPV*4324A**	1.01	0.93	58HDV080--20						
CSPH*3612A**	0.99	0.95	58HDV100--20						
CSPH*4212A**	0.99	0.92	58HDV100--20						
CAP**3617A**	0.97	0.93	58HDV100--20						
CAP**3621A**	0.97	0.93	58HDV100--20						
CAP**4221A**	0.97	0.93	58HDV100--20						
CAP**4821A**	0.99	0.91	58HDV100--20						
CAP**4824A**	0.98	0.91	58HDV100--20						
CNP#*3617A**	0.98	0.98	58HDV100--20						
CNP#*4221A**	1.01	0.93	58HDV100--20						
CNP#*4324A**	1.01	0.93	58HDV100--20						
CNPV*3617A**	0.99	0.95	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						
CNPV*3617A**	0.98	0.91	58HDV100--20						
CNPV*4212A**	0.99	0.92	58HDV100--20						
CNPV*4324A**	0.97	0.93	58HDV100--20						
CSPH*3612A**	0.98	0.91	58HDV100--20						
CSPH*4212A**	0.99	0.91	58HDV100--20						
CAP**4821A**	0.98	0.94	58HDV100--20						
CAP**4824A**	0.98	0.94	58HDV100--20						
CNP#*3617A**	0.99	0.93	58HDV100--20						
CNP#*4221A**	0.97	0.93	58HDV100--20						
CNP#*4321A**	0.99	0.91	58HDV100--20						

DETAILED COOLING CAPACITIES# CONTINUED

24ANB636A30 Outdoor Section With CNPV*3717A**+TDR Indoor Section**

[illegible]

COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL
COOLING INDOOR	CAP**4221A**	0.97	0.97	58PH*070-16
	CAP**4817A**	0.98	0.98	58PH*070-16
	CAP**4821A**	0.98	0.98	58PH*070-16
	CNPH*3617A**	0.95	0.95	58PH*070-16
	CNPH*4221A**	0.97	0.97	58PH*070-16
	CNPH*4321A**	0.99	0.95	58PH*070-16
	CNPH**4821A**	0.98	0.94	58PH*070-16
	CNPV*3617A**	0.95	0.95	58PH*070-16
	CNPV*3621A**	0.95	0.95	58PH*070-16
	CNPV*3717A**	0.99	0.95	58PH*070-16
	CNPV*4217A**	0.97	0.97	58PH*070-16
	CNPV*4221A**	0.97	0.97	58PH*070-16
	CNPH*4821A**	0.98	0.94	58PH*070-16
	CSPH*3612A**	0.98	0.98	58PH*070-16
	CSPH*4212A**	0.98	0.94	58PH*070-16
	CSPH*4812A**	0.99	0.95	58PH*070-16
	CAP**3621A**	0.97	0.93	58PH*090-16
	CAP**4221A**	0.97	0.90	58PH*090-16
	CAP**4224A**	0.98	0.90	58PH*090-16
	CAP**4821A**	0.99	0.91	58PH*090-16
	CAP**4824A**	0.99	0.91	58PH*090-16
	CNPH*3617A**	0.96	0.92	58PH*090-16
	CNPH*4221A**	0.97	0.93	58PH*090-16
	CNPH*4321A**	1.00	0.92	58PH*090-16
	CNPH*4821A**	0.99	0.91	58PH*090-16
	CNPH*6024A**	1.00	0.92	58PH*090-16
	CNPV*3621A**	0.96	0.92	58PH*090-16
	CNPV*4221A**	0.97	0.93	58PH*090-16
	CNPV*4324A**	1.01	0.93	58PH*090-16
	CNPV*4821A**	0.99	0.91	58PH*090-16
	CNPV*4824A**	0.99	0.91	58PH*090-16
	CSPH*3612A**	0.98	0.91	58PH*090-16
	CSPH*4212A**	0.99	0.91	58PH*090-16
	CSPH*4812A**	0.99	0.92	58PH*090-16
	CAP**3621A**	0.97	0.93	58PH*110-20
	CAP**4221A**	0.98	0.90	58PH*110-20
CAP**4224A**	0.98	0.90	58PH*110-20	
CAP**4821A**	0.99	0.91	58PH*110-20	
CAP**4824A**	0.99	0.92	58PH*110-20	
CNPH*3617A**	0.96	0.92	58PH*110-20	
CNPH*4221A**	0.98	0.90	58PH*110-20	
CNPH*4321A**	1.01	0.93	58PH*110-20	
CNPH*4821A**	0.99	0.92	58PH*110-20	
CNPH*4824A**	0.97	0.93	58PH*110-20	
CSPH*4212A**	0.99	0.92	58PH*110-20	
CSPH*4812A**	1.00	0.92	58PH*110-20	
CAP**3617A**	0.95	0.95	OVLAAB036098	
CNPH*3617A**	0.95	0.95	OVLAAB036098	
CNPH*4221A**	0.96	0.96	OVLAAB036098	
CNPH*4321A**	0.98	0.94	OVLAAB036098	
CNPV*3617A**	0.95	0.95	OVLAAB036098	
CNPV*3717A**	0.98	0.94	OVLAAB036098	
CSPH*3612A**	0.97	0.97	OVLAAB036098	
CSPH*4212A**	0.97	0.97	OVLAAB036098	

See notes on pg. 61

DETAILED COOLING CAPACITIES# CONTINUED

EVAPORATOR AIR				CONDENSER ENTERING AIR TEMPERATURES ° F (° C)															
CFM	EWB ° F (° C)	75 (23.9)		85 (29.4)		95 (35)				105 (40.6)				115 (46.1)				125 (51.7)	
		Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**				
1225	72 (22.2)	49.34	24.70	2.66	47.47	24.08	3.01	45.41	23.40	3.42	43.15	22.67	3.88	40.71	21.89	4.39	38.06	21.06	4.98
	67 (19.4)	44.95	30.44	2.64	43.25	29.86	2.99	41.39	29.23	3.38	39.33	28.54	3.84	37.11	27.79	4.36	34.71	26.99	4.94
	63 (17.2)††	41.76	29.29	2.63	40.20	28.71	2.97	38.47	28.07	3.36	36.56	27.37	3.82	34.50	26.62	4.33	32.25	25.80	4.91
	62 (16.7)	41.12	36.11	2.63	39.63	35.56	2.97	38.01	34.93	3.36	36.38	36.38	3.82	34.75	34.75	4.33	32.94	32.94	4.92
	57 (13.9)	40.25	40.25	2.62	39.10	39.10	2.96	37.79	37.79	3.36	36.33	36.33	3.82	34.70	34.70	4.33	32.90	32.90	4.92
	72 (22.2)	50.16	25.99	2.73	48.18	25.36	3.08	46.03	24.68	3.49	43.68	23.95	3.95	41.13	23.16	4.47	38.39	22.32	5.06
1400	67 (19.4)	45.74	32.51	2.71	43.96	31.94	3.06	42.00	31.30	3.46	39.87	30.61	3.92	37.56	29.85	4.43	35.08	29.04	5.02
	63 (17.2)††	42.55	31.23	2.70	40.90	30.64	3.04	39.08	30.00	3.44	37.10	29.29	3.89	34.95	28.52	4.41	32.65	27.69	4.99
	62 (16.7)	42.11	38.86	2.70	40.72	40.72	3.04	39.30	39.30	3.44	37.71	37.71	3.90	35.95	35.95	4.42	34.01	34.01	5.01
	57 (13.9)	41.92	41.92	2.70	40.66	40.66	3.04	39.24	39.24	3.44	37.65	37.65	3.90	35.90	35.90	4.42	33.97	33.97	5.01
	72 (22.2)	50.74	27.21	2.80	48.70	26.58	3.16	46.46	25.90	3.56	44.03	25.16	4.03	41.41	24.38	4.55	38.60	23.54	5.14
	67 (19.4)	46.32	34.50	2.78	44.48	33.92	3.13	42.46	33.29	3.53	40.26	32.59	3.99	37.89	31.82	4.51	35.38	30.98	5.10
1575	63 (17.2)††	43.12	33.07	2.77	41.42	32.49	3.11	39.54	31.84	3.51	37.50	31.12	3.97	35.30	30.34	4.48	32.96	29.47	5.07
	62 (16.7)	43.35	43.35	2.77	42.00	42.00	3.11	40.47	40.47	3.52	38.78	38.78	3.98	36.91	36.91	4.50	34.86	34.86	5.09
	57 (13.9)	43.29	43.29	2.77	41.94	41.94	3.11	40.42	40.42	3.52	38.73	38.73	3.98	36.87	36.87	4.50	34.82	34.82	5.09
			COOLING INDOOR MODEL		CAPACITY		POWER		FURNACE MODEL		COOLING INDOOR MODEL		CAPACITY		POWER		FURNACE MODEL		
	*CNPV*4324A**		1.00		1.00		CNPV*4221A**		0.95		0.91		58CV(A)X1070-12		0.91		58CV(A)X110-20		
	CAP**4221A**		0.96		1.01		CNPV*4321A**		0.98		0.94		58CV(A)X1070-12		0.96		58CV(A)X135-22		
CAP**4224A**		0.96		1.01		CNPV*4821A**		0.96		0.93		58CV(A)X1070-12		0.98		58CV(A)X135-22			
CAP**4817A**		0.99		0.98		CNPV*6024A**		0.98		0.90		58CV(A)X1070-12		0.99		58CV(A)X135-22			
CAP**4821A**		0.98		0.98		CNPV*4217A**		0.96		0.93		58CV(A)X1070-12		0.96		58CV(A)X135-22			
CAP**4823A**		0.98		0.98		CSPH*4212A**		0.98		0.94		58CV(A)X1070-12		0.91		58CV(A)X135-22			
CAP**4824A**		0.98		0.98		CSPH*4812A**		0.98		0.94		58CV(A)X1070-12		0.90		58CV(A)X135-22			
CAP**6021A**		1.00		1.00		CSPH*6012A**		0.99		0.91		58CV(A)X1070-12		0.99		58CV(A)X135-22			
CAP**6024A**		1.00		1.00		CAP**4221A**		0.95		0.91		58CV(A)X1090-16		0.99		58CV(A)X135-22			
CAP**6025A**		1.00		1.00		CAP**4817A**		0.98		0.90		58CV(A)X1090-16		0.99		58CV(A)X135-22			
CNPV*4818A**		0.98		0.98		CAP**4821A**		0.96		0.89		58CV(A)X1090-16		0.99		58CV(A)X135-22			
CNPV*4221A**		0.96		0.96		CAP**6021A**		0.99		0.91		58CV(A)X1090-16		0.98		58CV(A)X135-22			
CNPV*4321A**		1.00		1.00		CNPV*4221A**		0.95		0.91		58CV(A)X1090-16		0.99		58CV(A)X135-22			
CNPV*4821A**		0.98		0.98		CNPV*4321A**		0.99		0.91		58CV(A)X1090-16		0.99		58CV(A)X135-22			
CNPV*6024A**		0.99		0.99		CNPV*4821A**		0.98		0.90		58CV(A)X1090-16		0.98		58CV(A)X135-22			
CNPV*4217A**		0.98		0.98		CNPV*6024A**		0.99		0.91		58CV(A)X1090-16		0.95		58CV(A)X155-22			
CNPV*4221A**		0.96		0.96		CNPV*4217A**		0.96		0.93		58CV(A)X1090-16		0.99		58CV(A)X155-22			
CNPV*4821A**		0.98		0.98		CNPV*4821A**		0.95		0.91		58CV(A)X1090-16		0.98		58CV(A)X155-22			
CNPV*4824A**		0.98		0.98		CNPV*4321A**		0.98		0.90		58CV(A)X1090-16		0.99		58CV(A)X155-22			
CSPH*4212A**		0.99		0.99		CSPH*4212A**		0.98		0.90		58CV(A)X1090-16		0.99		58CV(A)X155-22			
CSPH*4812A**		0.99		0.99		CSPH*4812A**		0.98		0.90		58CV(A)X1090-16		0.99		58CV(A)X155-22			
CSPH*6012A**		1.00		1.00		CAP**4221A**		0.95		0.88		58CV(A)X110-20		0.98		58CV(A)X155-22			
F84CNF042		0.99		0.95		CAP**4224A**		0.95		0.88		58CV(A)X110-20		0.99		58CV(A)X155-22			
F84CNF048		0.99		0.91		CAP**4821A**		0.98		0.90		58CV(A)X110-20		0.99		58CV(A)X155-22			
F84CNF060		1.00		0.92		CAP**4824A**		0.98		0.90		58CV(A)X110-20		0.98		58CV(A)X155-22			
FE4AN(B,F)003		0.95		0.88		CAP**6021A**		0.99		0.91		58CV(A)X110-20		0.99		58CV(A)X155-22			
FE4AN(B,F)005		0.99		0.91		CAP**6024A**		0.99		0.91		58CV(A)X110-20		0.99		58CV(A)X155-22			
FE4AN(B,F)006		1.00		0.92		CAP**6024A**		0.99		0.91		58CV(A)X110-20		0.99		58CV(A)X155-22			
FE5ANB004		1.00		0.92		CNPV*4221A**		0.99		0.91		58CV(A)X110-20		0.98		58HDV060 -- 12			
FE5ANB004		1.00		0.92		CNPV*4321A**		0.99		0.91		58CV(A)X110-20		0.98		58HDV060 -- 12			
FV4CN(B,F)003		0.95		0.88		CNPV*4821A**		0.98		0.90		58CV(A)X110-20		0.96		58HDV060 -- 12			
FV4CN(B,F)005		0.99		0.91		CNPV*6024A**		0.99		0.91		58CV(A)X110-20		0.95		58HDV060 -- 12			
FV4CN(B,F)006		1.00		0.92		CNPV*4221A**		0.95		0.91		58CV(A)X110-20		0.98		58HDV060 -- 12			
FX4DN(B,F)043		0.99		0.95		CNPV*4324A**		0.99		0.91		58CV(A)X110-20		0.98		58HDV060 -- 12			
FX4DN(B,F)049		1.00		0.92		CNPV*4821A**		0.99		0.90		58CV(A)X110-20		0.98		58HDV060 -- 12			
FX4DN(B,F)061		1.00		0.89		CNPV*4824A**		0.98		0.90		58CV(A)X110-20		0.98		58HDV060 -- 12			
FV5BNF042		0.98		0.94		CNPV*6024A**		0.99		0.91		58CV(A)X110-20		1.00		58HDV060 -- 20			
FV5BNF048		1.00		0.96		CSPH*4212A**		0.98		0.90		58CV(A)X110-20		0.96		58HDV060 -- 20			
CAP**4817A**		0.98		0.94		CSPH*4812A**		0.98		0.90		58CV(A)X110-20		1.00		58HDV060 -- 20			

24ANB642A**30 Outdoor Section With CNPV*4324A** + TDR Indoor Section

COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL
CNPH*4821A**	0.99	0.95	58HVDV080 - 20	
CNPV*4221A**	0.96	0.93	58HVDV080 - 20	
CNPH*4324A**	1.00	0.92	58HVDV080 - 20	
CNPV*4821A**	0.99	0.91	58HVDV080 - 20	
CNPH*4824A**	0.99	0.91	58HVDV080 - 20	
CSPH*4212A**	0.99	0.95	58HVDV080 - 20	
CSPH*4812A**	0.99	0.95	58HVDV080 - 20	
CAP**4224A**	0.96	0.93	58HVDV100 - 20	
CAP**4824A**	0.98	0.94	58HVDV100 - 20	
CAP**6025A**	0.99	0.91	58HVDV100 - 20	
CNPH*4221A**	0.96	0.93	58HVDV100 - 20	
CNPH*4321A**	0.99	0.91	58HVDV100 - 20	
CNPH*4821A**	0.98	0.94	58HVDV100 - 20	
CNPV*4324A**	0.99	0.91	58HVDV100 - 20	
CNPV*4824A**	0.98	0.94	58HVDV100 - 20	
CNPV*4824A**	0.98	0.90	58HVDV100 - 20	
CSPH*4212A**	0.98	0.90	58HVDV100 - 20	
CSPH*4812A**	0.99	0.91	58HVDV100 - 20	
CAP**4221A**	0.96	0.93	58MEB040-12	
CAP**4817A**	0.99	0.91	58MEB040-12	
CAP**4821A**	0.98	0.94	58MEB040-12	
CAP**6021A**	1.00	0.92	58MEB040-12	
CNPH*4221A**	0.96	0.93	58MEB040-12	
CNPH*4321A**	1.00	0.92	58MEB040-12	
CNPH*4821A**	0.98	0.90	58MEB040-12	
CNPH*6024A**	1.00	0.92	58MEB040-12	
CNPV*4217A**	0.96	0.93	58MEB040-12	
CNPV*4221A**	0.96	0.93	58MEB040-12	
CNPV*4821A**	0.98	0.90	58MEB040-12	
CSPH*4212A**	0.99	0.91	58MEB040-12	
CSPH*4812A**	0.99	0.91	58MEB040-12	
CSPH*6012A**	1.00	0.92	58MEB040-12	
CAP**4221A**	0.96	0.93	58MEC060-12	
CAP**4817A**	0.99	0.95	58MEC060-12	
CAP**4821A**	0.98	0.94	58MEC060-12	
CAP**6021A**	0.99	0.91	58MEC060-12	
CNPH*4221A**	0.96	0.93	58MEC060-12	
CNPH*4321A**	0.99	0.91	58MEC060-12	
CNPH*4821A**	0.98	0.94	58MEC060-12	
CNPH*6024A**	1.00	0.92	58MEC060-12	
CNPV*4217A**	0.96	0.93	58MEC060-12	
CNPV*4221A**	0.96	0.93	58MEC060-12	
CNPV*4821A**	0.98	0.90	58MEC060-12	
CSPH*4212A**	0.99	0.91	58MEC060-12	

[illegible]

COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL
Furnace Model	CSPH*4812A**	0.99	0.91	58MV/B.C)060 - 14
	CSPH*6012A**	1.00	0.92	58MV/B.C)060 - 14
	CAP**4221A**	0.95	0.91	58MV/B.C)080 - 14
	CAP**4224A**	0.95	0.91	58MV/B.C)080 - 14
	CAP**4821A**	0.96	0.93	58MV/B.C)080 - 14
	CAP**4824A**	0.96	0.93	58MV/B.C)080 - 14
	CAP**6021A**	0.98	0.94	58MV/B.C)080 - 14
	CAP**6024A**	0.99	0.95	58MV/B.C)080 - 14
	CNPH*4221A**	0.95	0.95	58MV/B.C)080 - 14
	CNPH*4321A**	0.99	0.95	58MV/B.C)080 - 14
	CNPH*4821A**	0.98	0.94	58MV/B.C)080 - 14
	CNPH*6024A**	0.99	0.91	58MV/B.C)080 - 14
	CNPV*4221A**	0.95	0.95	58MV/B.C)080 - 14
	CNPV*4324A**	0.99	0.91	58MV/B.C)080 - 14
	CNPV*4821A**	0.98	0.94	58MV/B.C)080 - 14
	CNPV*4824A**	0.98	0.94	58MV/B.C)080 - 14
	CNPV*6024A**	0.99	0.91	58MV/B.C)080 - 14
	CSPH*4212A**	0.98	0.94	58MV/B.C)080 - 14
	CSPH*4812A**	0.98	0.94	58MV/B.C)080 - 14
	CAP**4221A**	0.95	0.91	58MV/B.C)080 - 14
	CAP**4224A**	0.95	0.91	58MV/B.C)080 - 20
	CAP**4821A**	0.96	0.93	58MV/B.C)080 - 20
	CAP**4824A**	0.96	0.93	58MV/B.C)080 - 20
	CAP**6021A**	0.98	0.91	58MV/B.C)080 - 20
CAP**6024A**	0.99	0.91	58MV/B.C)080 - 20	
CNPH*4221A**	0.95	0.91	58MV/B.C)080 - 20	
CNPV*4324A**	0.99	0.91	58MV/B.C)080 - 20	
CNPV*4821A**	0.98	0.94	58MV/B.C)080 - 20	
CNPV*4824A**	0.98	0.94	58MV/B.C)080 - 20	
CNPV*6024A**	0.99	0.91	58MV/B.C)080 - 20	
CSPH*4212A**	0.98	0.94	58MV/B.C)080 - 20	
CSPH*4812A**	0.98	0.94	58MV/B.C)080 - 20	
CSPH*6012A**	0.99	0.91	58MV/B.C)080 - 20	
CAP**4221A**	0.95	0.91	58MV/B.C)100 - 20	
CAP**4224A**	0.95	0.91	58MV/B.C)100 - 20	
CAP**4821A**	0.96	0.93	58MV/B.C)100 - 20	
CAP**4824A**	0.96	0.93	58MV/B.C)100 - 20	
CAP**6021A**	0.98	0.90	58MV/B.C)100 - 20	
CAP**6024A**	0.98	0.90	58MV/B.C)100 - 20	
CNPH*4221A**	0.95	0.91	58MV/B.C)100 - 20	
CNPH*4324A**	0.99	0.90	58MV/B.C)100 - 20	
CNPV*4821A**	0.98	0.89	58MV/B.C)100 - 20	
CNPV*4824A**	0.98	0.89	58MV/B.C)100 - 20	
CNPV*6024A**	0.99	0.88	58MV/B.C)100 - 20	
CSPH*4212A**	0.98	0.91	58MV/B.C)100 - 20	
CSPH*4824A**	0.98	0.91	58MV/B.C)100 - 20	
CNPV*6024A**	0.99	0.88	58MV/B.C)120 - 20	
CSPH*4212A**	0.98	0.91	58MV/B.C)120 - 20	
CSPH*4824A**	0.98	0.91	58MV/B.C)120 - 20	
CNPV*6024A**	0.99	0.91	58MV/B.C)120 - 20	

24ANB642A**30 Outdoor Section With CNPV*4324A** + TDR Indoor Section

COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL
A	CNPH*4221A**	0.95	0.91	58MV(B,C)120-20
	CNPH*4321A**	0.99	0.91	58MV(B,C)120-20
	CNPH*4821A**	0.98	0.90	58MV(B,C)120-20
	CNPH*6024A**	0.99	0.91	58MV(B,C)120-20
	CNPV*4324A**	0.99	0.91	58MV(B,C)120-20
	CNPV*4824A**	0.98	0.90	58MV(B,C)120-20
	CNPV*6024A**	0.99	0.91	58MV(B,C)120-20
	CSPH*4812A**	0.98	0.90	58MV(B,C)120-20
	CSPH*4812A**	0.98	0.90	58MV(B,C)120-20
	CSPH*6012A**	0.99	0.91	58MV(B,C)120-20
B	CAP**4224A**	0.95	0.91	58WB/B040-14
	CAP**4824A**	0.96	0.93	58WB/B040-14
	CAP**6024A**	0.98	0.90	58WB/B040-14
	CNPH*4221A**	0.95	0.91	58WB/B040-14
	CNPH*4321A**	0.98	0.94	58WB/B040-14
	CNPH*4821A**	0.96	0.93	58WB/B040-14
	CNPH*6024A**	0.98	0.90	58WB/B040-14
	CNPV*4324A**	0.98	0.90	58WB/B040-14
	CNPV*4824A**	0.96	0.93	58WB/B040-14
	CNPV*6024A**	0.98	0.90	58WB/B040-14
C	CAP**4221A**	0.95	0.95	58PH*070-16
	CAP**4817A**	0.98	0.98	58PH*070-16
	CAP**4821A**	0.96	0.98	58PH*070-16
	CAP**6021A**	0.99	0.95	58PH*070-16
	CNPH*4221A**	0.95	0.95	58PH*070-16
	CNPH*4321A**	0.99	0.95	58PH*070-16
	CNPH*4821A**	0.98	0.98	58PH*070-16
	CNPH*6024A**	0.99	0.95	58PH*070-16
	CNPV*4217A**	0.96	0.96	58PH*070-16
	CNPV*4821A**	0.95	0.95	58PH*070-16
D	CNPV*4821A**	0.98	0.98	58PH*070-16
	CSPH*4212A**	0.98	0.98	58PH*070-16
	CSPH*4812A**	0.98	0.94	58PH*070-16
	CSPH*6012A**	0.99	0.95	58PH*070-16
	CAP**4221A**	0.96	0.89	58PH*090-16
	CAP**4224A**	0.96	0.89	58PH*090-16
	CAP**4821A**	0.98	0.90	58PH*090-16
	CAP**4824A**	0.98	0.90	58PH*090-16
	CAP**6021A**	0.99	0.91	58PH*090-16
	CAP**6024A**	0.99	0.91	58PH*090-16
E	CNPH*4221A**	0.96	0.93	58PH*090-16
	CNPH*4321A**	0.99	0.91	58PH*090-16
	CNPH*4821A**	0.98	0.90	58PH*090-16
	CNPH*6024A**	0.99	0.91	58PH*090-16
	CSPH*4212A**	0.98	0.90	58PH*090-16
	CSPH*4812A**	0.99	0.91	58PH*090-16
	CSPH*6012A**	1.00	0.92	58PH*090-16
	CSPH*6012A**	0.96	0.89	58PH*110-20
	CAP**4221A**	0.96	0.89	58PH*110-20
	CAP**4224A**	0.98	0.90	58PH*110-20

COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL
CAP**6021A**	0.99	0.91	58PH*110-20	
CAP**6024A**	0.99	0.91	58PH*110-20	
CNPV*4221A**	0.96	0.89	58PH*110-20	
CNPV*4321A**	0.99	0.91	58PH*110-20	
CNPV*4821A**	0.98	0.90	58PH*110-20	
CNPV*6024A**	1.00	0.92	58PH*110-20	
CNPV*4221A**	0.96	0.89	58PH*110-20	
CNPV*4324A**	1.00	0.92	58PH*110-20	
CNPV*4824A**	0.98	0.90	58PH*110-20	
CSPH*4812A**	1.00	0.91	58PH*110-20	
CSPH*6012A**	1.00	0.92	58PH*110-20	
CAP**4224A**	0.96	0.89	58PH*135-20	
CAP**4824A**	0.98	0.90	58PH*135-20	
CAP**6024A**	0.99	0.91	58PH*135-20	
CNPV*4221A**	0.95	0.91	58PH*135-20	
CNPV*4321A**	0.99	0.91	58PH*135-20	
CNPV*4821A**	0.98	0.90	58PH*135-20	
CNPV*6024A**	1.00	0.92	58PH*135-20	
CNPV*4324A**	1.00	0.92	58PH*135-20	
CNPV*4824A**	0.98	0.90	58PH*135-20	
CNPV*6024A**	1.00	0.92	58PH*135-20	
CSPH*4212A**	0.98	0.90	58PH*135-20	
CSPH*4812A**	0.99	0.91	58PH*135-20	
CSPH*6012A**	1.00	0.92	58PH*135-20	
CAP**4221A**	0.95	0.95	OVLAB048112	
CAP**4821A**	0.96	0.96	OVLAB048112	
CNPV*4221A**	0.99	0.95	OVLAB048112	
CNPV*4321A**	0.99	0.95	OVLAB048112	
CNPV*4821A**	0.98	0.94	OVLAB048112	
CNPV*4221A**	0.96	0.96	OVLAB048112	
CNPV*4821A**	0.98	0.94	OVLAB048112	
CSPH*4212A**	0.98	0.94	OVLAB048112	
CSPH*4812A**	0.99	0.95	OVLAB060154	
CNPV*4321A**	1.00	0.92	OVLAB060154	
CNPV*4821A**	1.00	0.92	OVLAB060154	
CSPH*4212A**	1.00	0.92	OVLAB060154	
CSPH*4812A**	1.00	0.92	OVLAB060154	
CAP**4817A**	0.98	0.94	OVMAA042112	
CNPV*4221A**	0.95	0.91	OVMAA042112	
CNPV*4321A**	0.99	0.91	OVMAA042112	
CNPV*4821A**	0.98	0.94	OVMAA042112	
CNPV*4217A**	0.96	0.93	OVMAA042112	
CSPH*4212A**	0.98	0.94	OVMAA042112	
CSPH*4812A**	0.98	0.94	OVMAA042112	

See notes on pg. 61

DETAILED COOLING CAPACITIES# CONTINUED

EVAPORATOR AIR			CONDENSER ENTERING AIR TEMPERATURES °F (°C)																
CFM	EWB °F (°C)	75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)			125 (51.7)		
		Capacity MBTuh		Total Sys. KW**	Capacity MBTuh		Total Sys. KW**	Capacity MBTuh		Total Sys. KW**	Capacity MBTuh		Total Sys. KW**	Capacity MBTuh		Total Sys. KW**	Capacity MBTuh		Total Sys. KW**
		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†	
1400	72 (22.2)	56.26	27.99	2.63	53.43	27.01	3.06	50.50	26.01	47.48	24.98	3.94	44.30	23.92	4.41	40.93	22.81	4.90	
	67 (19.4)	50.89	34.43	2.79	48.38	33.47	3.18	45.78	32.48	43.08	31.47	4.00	40.25	30.42	4.44	37.23	29.31	4.92	
	63 (17.2)††	47.07	33.02	2.89	44.78	32.08	3.26	42.40	31.11	39.93	30.12	4.03	37.32	29.07	4.46	34.55	27.98	4.92	
	62 (16.7)	46.35	40.80	2.90	44.17	39.83	3.27	41.98	41.83	39.98	39.98	4.03	37.84	37.84	4.45	35.52	35.52	4.92	
	57 (13.9)	45.55	45.55	2.92	43.76	43.76	3.27	41.89	41.89	39.91	39.91	4.03	37.78	37.78	4.45	35.47	35.47	4.92	
	72 (22.2)	57.28	29.51	2.66	54.30	28.50	3.10	51.24	27.48	48.08	26.43	4.00	44.78	25.35	4.47	41.29	24.22	4.97	
1600	67 (19.4)	51.86	36.85	2.83	49.21	35.85	3.23	46.50	34.85	43.69	33.81	4.06	40.75	32.72	4.51	37.85	31.58	4.99	
	63 (17.2)††	47.99	35.27	2.94	45.57	34.29	3.31	43.10	33.30	40.52	32.28	4.10	37.82	31.20	4.53	34.97	30.07	5.00	
	62 (16.7)	47.61	47.41	2.94	45.63	45.63	3.31	43.61	43.61	41.47	41.47	4.09	39.16	39.16	4.52	36.67	36.67	5.00	
	57 (13.9)	47.50	47.50	2.94	45.56	45.56	3.31	43.54	43.54	41.41	41.41	4.09	39.11	39.11	4.52	36.63	36.63	5.00	
	72 (22.2)	58.02	30.95	2.70	54.93	29.93	3.15	51.76	28.88	48.49	27.82	4.06	45.10	26.72	4.54	41.51	25.58	5.05	
	67 (19.4)	52.58	39.16	2.87	49.84	38.15	3.28	47.04	37.11	44.14	36.04	4.13	41.13	34.92	4.58	37.98	33.72	5.07	
1800	63 (17.2)††	48.67	37.42	2.99	46.18	36.42	3.37	43.62	35.40	40.96	34.34	4.17	38.21	33.22	4.60	35.32	31.99	5.08	
	62 (16.7)	49.21	49.21	2.96	47.13	47.13	3.35	44.96	44.96	42.67	42.67	4.15	40.23	40.23	4.59	37.59	37.59	5.07	
	57 (13.9)	49.14	49.14	2.97	47.06	47.06	3.35	44.90	44.90	42.61	42.61	4.15	40.18	40.18	4.59	37.55	37.55	5.07	
	72 (22.2)	56.26	27.99	2.63	53.43	27.01	3.06	50.50	26.01	47.48	24.98	3.94	44.30	23.92	4.41	40.93	22.81	4.90	
	67 (19.4)	50.89	34.43	2.79	48.38	33.47	3.18	45.78	32.48	43.08	31.47	4.00	40.25	30.42	4.44	37.23	29.31	4.92	
	63 (17.2)††	47.07	33.02	2.89	44.78	32.08	3.26	42.40	31.11	39.93	30.12	4.03	37.32	29.07	4.46	34.55	27.98	4.92	

COOLING INDOOR MODEL				FURNACE MODEL			
COOLING INDOOR MODEL	CAPACITY	POWER	FURNACE MODEL	COOLING INDOOR MODEL	CAPACITY	POWER	FURNACE MODEL
*CNPV*6124A**	1.00	1.00		CAP**6024A**	0.98	0.94	58CV(A,X)1110--20
CAP**4817A**	0.97	1.01		CNPV*4821A**	0.97	0.93	58CV(A,X)1110--20
CAP**4821A**	0.97	1.01		CNPV*6024A**	0.98	0.94	58CV(A,X)1110--20
CAP**4823A**	0.97	1.01		CNPV*6124A**	0.98	0.94	58CV(A,X)1110--20
CAP**4824A**	0.97	1.01		CNPV*4821A**	0.97	0.93	58CV(A,X)1110--20
CAP**6021A**	0.99	0.99		CNPV*4824A**	0.97	0.93	58CV(A,X)1110--20
CAP**6024A**	0.99	0.99		CNPV*6024A**	0.98	0.94	58CV(A,X)1110--20
CAP**6025A**	0.99	0.99		CNPV*6124A**	0.99	0.92	58CV(A,X)1110--20
CNPV*4821A**	0.98	1.02		CSPH*4812A**	0.97	0.93	58CV(A,X)1110--20
CNPV*6024A**	0.99	0.99		CSPH*6012A**	0.99	0.95	58CV(A,X)1110--20
CNPV*6124A**	0.99	0.99		CAP**4824A**	0.97	0.93	58CV(A,X)135--22
CSPH*4812A**	0.99	1.03		CAP**6024A**	0.98	0.94	58CV(A,X)135--22
CSPH*6012A**	1.00	1.00		CNPV*4821A**	0.97	0.93	58CV(A,X)135--22
FB4CNF048	0.97	0.97		CNPV*6024A**	0.98	0.94	58CV(A,X)135--22
FB4CNF080	0.99	0.95		CNPV*6124A**	0.99	0.95	58CV(A,X)135--22
FE4AN(B,F)005	0.99	0.92		CSPH*4812A**	0.98	0.94	58CV(A,X)135--22
FE4ANB006	1.00	0.93		CSPH*6012A**	0.99	0.95	58CV(A,X)135--22
FV4CN(B,F)005	0.99	0.92		CAP**4824A**	0.97	0.93	58CV(A,X)155--22
FV4CNB006	1.00	0.93		CAP**6024A**	0.99	0.95	58CV(A,X)155--22
FX4DN(B,F)049	1.00	0.96		CNPV*4821A**	0.97	0.93	58CV(A,X)155--22
FX4DN(B,F)061	1.01	0.94		CNPV*6024A**	0.99	0.95	58CV(A,X)155--22
FV5BNB060	0.99	1.03		CNPV*6124A**	0.99	0.95	58CV(A,X)155--22
FV5BNF048	0.99	0.99		CNPV*4824A**	0.97	0.93	58CV(A,X)155--22
CAP**4817A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58CV(A,X)155--22
CAP**4821A**	0.96	0.96		CNPV*6124A**	1.00	0.96	58CV(A,X)155--22
CAP**6021A**	0.98	0.94		CSPH*4812A**	0.98	0.94	58CV(A,X)155--22
CNPV*6024A**	0.98	0.97		CSPH*6012A**	0.99	0.95	58CV(A,X)155--22
CNPV*6124A**	0.98	0.94		CAP**4823A**	0.97	0.97	58HDV080--20
CNPV*4821A**	0.97	0.97		CAP**4824A**	0.97	0.97	58HDV080--20
CSPH*4812A**	0.98	0.94		CAP**6024A**	0.99	0.95	58HDV080--20
CSPH*4812A**	0.97	0.97		CAP**6025A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.98	0.94		CNPV*4821A**	0.97	0.97	58HDV080--20
CAP**4821A**	0.96	0.96		CNPV*4824A**	0.97	0.97	58HDV080--20
CAP**4824A**	0.96	0.96		CNPV*6024A**	0.99	0.95	58HDV080--20
CAP**6021A**	0.98	0.94		CNPV*6124A**	0.97	0.93	58HDV080--20
CAP**6024A**	0.98	0.94		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**6025A**	0.98	0.94		CNPV*6024A**	0.99	0.95	58HDV080--20
CNPV*4821A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CNPV*6024A**	0.99	0.95		CNPV*4821A**	0.97	0.93	58HDV080--20
CNPV*6124A**	1.00	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CSPH*4812A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.99	0.95		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**4817A**	0.97	0.97		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**4821A**	0.96	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CAP**4824A**	0.96	0.96		CNPV*6024A**	0.99	0.95	58HDV080--20
CAP**6021A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**6024A**	0.98	0.94		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**6025A**	0.98	0.94		CNPV*6024A**	0.99	0.95	58HDV080--20
CNPV*4821A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CNPV*6024A**	0.99	0.95		CNPV*4821A**	0.97	0.93	58HDV080--20
CNPV*6124A**	1.00	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CSPH*4812A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.99	0.95		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**4817A**	0.97	0.97		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**4821A**	0.96	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CAP**4824A**	0.96	0.96		CNPV*6024A**	0.99	0.95	58HDV080--20
CAP**6021A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**6024A**	0.98	0.94		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**6025A**	0.98	0.94		CNPV*6024A**	0.99	0.95	58HDV080--20
CNPV*4821A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CNPV*6024A**	0.99	0.95		CNPV*4821A**	0.97	0.93	58HDV080--20
CNPV*6124A**	1.00	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CSPH*4812A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.99	0.95		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**4817A**	0.97	0.97		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**4821A**	0.96	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CAP**4824A**	0.96	0.96		CNPV*6024A**	0.99	0.95	58HDV080--20
CAP**6021A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**6024A**	0.98	0.94		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**6025A**	0.98	0.94		CNPV*6024A**	0.99	0.95	58HDV080--20
CNPV*4821A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CNPV*6024A**	0.99	0.95		CNPV*4821A**	0.97	0.93	58HDV080--20
CNPV*6124A**	1.00	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CSPH*4812A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.99	0.95		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**4817A**	0.97	0.97		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**4821A**	0.96	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CAP**4824A**	0.96	0.96		CNPV*6024A**	0.99	0.95	58HDV080--20
CAP**6021A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**6024A**	0.98	0.94		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**6025A**	0.98	0.94		CNPV*6024A**	0.99	0.95	58HDV080--20
CNPV*4821A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CNPV*6024A**	0.99	0.95		CNPV*4821A**	0.97	0.93	58HDV080--20
CNPV*6124A**	1.00	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CSPH*4812A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.99	0.95		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**4817A**	0.97	0.97		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**4821A**	0.96	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CAP**4824A**	0.96	0.96		CNPV*6024A**	0.99	0.95	58HDV080--20
CAP**6021A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**6024A**	0.98	0.94		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**6025A**	0.98	0.94		CNPV*6024A**	0.99	0.95	58HDV080--20
CNPV*4821A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CNPV*6024A**	0.99	0.95		CNPV*4821A**	0.97	0.93	58HDV080--20
CNPV*6124A**	1.00	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CSPH*4812A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.99	0.95		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**4817A**	0.97	0.97		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**4821A**	0.96	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CAP**4824A**	0.96	0.96		CNPV*6024A**	0.99	0.95	58HDV080--20
CAP**6021A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**6024A**	0.98	0.94		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**6025A**	0.98	0.94		CNPV*6024A**	0.99	0.95	58HDV080--20
CNPV*4821A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CNPV*6024A**	0.99	0.95		CNPV*4821A**	0.97	0.93	58HDV080--20
CNPV*6124A**	1.00	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CSPH*4812A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.99	0.95		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**4817A**	0.97	0.97		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**4821A**	0.96	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CAP**4824A**	0.96	0.96		CNPV*6024A**	0.99	0.95	58HDV080--20
CAP**6021A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**6024A**	0.98	0.94		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**6025A**	0.98	0.94		CNPV*6024A**	0.99	0.95	58HDV080--20
CNPV*4821A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CNPV*6024A**	0.99	0.95		CNPV*4821A**	0.97	0.93	58HDV080--20
CNPV*6124A**	1.00	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CSPH*4812A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.99	0.95		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**4817A**	0.97	0.97		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**4821A**	0.96	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CAP**4824A**	0.96	0.96		CNPV*6024A**	0.99	0.95	58HDV080--20
CAP**6021A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**6024A**	0.98	0.94		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**6025A**	0.98	0.94		CNPV*6024A**	0.99	0.95	58HDV080--20
CNPV*4821A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CNPV*6024A**	0.99	0.95		CNPV*4821A**	0.97	0.93	58HDV080--20
CNPV*6124A**	1.00	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CSPH*4812A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.99	0.95		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**4817A**	0.97	0.97		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**4821A**	0.96	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CAP**4824A**	0.96	0.96		CNPV*6024A**	0.99	0.95	58HDV080--20
CAP**6021A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**6024A**	0.98	0.94		CNPV*4821A**	0.97	0.93	58HDV080--20
CAP**6025A**	0.98	0.94		CNPV*6024A**	0.99	0.95	58HDV080--20
CNPV*4821A**	0.98	0.94		CNPV*6124A**	0.99	0.95	58HDV080--20
CNPV*6024A**	0.99	0.95		CNPV*4821A**	0.97	0.93	58HDV080--20
CNPV*6124A**	1.00	0.96		CNPV*4824A**	0.97	0.93	58HDV080--20
CSPH*4812A**	0.97	0.97		CNPV*6024A**	0.99	0.95	58HDV080--20
CSPH*6012A**	0.99	0.95		CNPV*6124A**	0.99	0.95	58HDV080--20
CAP**4817A**	0.97	0.97		C			

DETAILED COOLING CAPACITIES# CONTINUED

24ANB648A**30 Outdoor Section With CNPV*6124A** + TDR Indoor Section

COOLING INDOOR MODEL	CAPACITY	POWER	FURNACE MODEL
CNPV*4824A**	0.97	0.93	58MEC100-20
CNPV*6024A**	0.99	0.95	58MEC100-20
CNPV*6124A**	1.00	0.93	58MEC100-20
CSPH*4812A**	0.98	0.94	58MEC100-20
CSPH*6012A**	0.99	0.95	58MEC100-20
CAP**4824A**	0.97	0.93	58MEC120-20
CAP**6024A**	0.99	0.95	58MEC120-20
CNPV*4821A**	0.98	0.94	58MEC120-20
CNPV*6024A**	0.99	0.95	58MEC120-20
CNPV*6124A**	0.99	0.95	58MEC120-20
CSPH*4812A**	0.98	0.94	58MEC120-20
CSPH*6012A**	1.00	0.96	58MEC120-20
CAP**4821A**	0.96	0.96	58MV(B,C)080-20
CAP**6021A**	0.97	0.93	58MV(B,C)080-20
CNPV*4824A**	0.97	0.93	58MV(B,C)080-20
CNPV*4821A**	0.96	0.96	58MV(B,C)080-20
CNPV*6024A**	0.97	0.93	58MV(B,C)080-20
CNPV*6124A**	0.98	0.94	58MV(B,C)080-20
CSPH*4821A**	0.96	0.96	58MV(B,C)080-20
CNPV*4824A**	0.96	0.96	58MV(B,C)080-20
CNPV*6024A**	0.97	0.93	58MV(B,C)080-20
CNPV*6124A**	0.99	0.95	58MV(B,C)080-20
CSPH*4812A**	0.97	0.97	58MV(B,C)080-20
CSPH*6012A**	0.98	0.94	58MV(B,C)080-20
CAP**4821A**	0.96	0.96	58MV(B,C)100-20
CAP**4821A**	0.96	0.96	58MV(B,C)100-20
CAP**4824A**	0.96	0.96	58MV(B,C)100-20
CAP**6021A**	0.98	0.98	58MV(B,C)100-20
CAP**6024A**	0.98	0.94	58MV(B,C)100-20
CNPV*4821A**	0.97	0.97	58MV(B,C)100-20
CNPV*4824A**	0.98	0.94	58MV(B,C)100-20
CNPV*6124A**	0.98	0.94	58MV(B,C)100-20
CNPV*4821A**	0.97	0.97	58MV(B,C)100-20
CNPV*4824A**	0.97	0.97	58MV(B,C)100-20
CNPV*6024A**	0.98	0.94	58MV(B,C)120-20
CNPV*6124A**	0.99	0.95	58MV(B,C)120-20
CSPH*4812A**	0.97	0.97	58MV(B,C)120-20
CSPH*6012A**	0.99	0.95	58MV(B,C)120-20
CAP**4824A**	0.96	0.96	58MV(B,C)120-20
CAP**6024A**	0.98	0.94	58MV(B,C)120-20
CNPV*4821A**	0.97	0.93	58MV(B,C)120-20
CNPV*6024A**	0.98	0.94	58MV(B,C)120-20
CNPV*6124A**	0.99	0.95	58MV(B,C)120-20
CSPH*4812A**	0.97	0.93	58MV(B,C)120-20
CSPH*6012A**	0.99	0.95	58MV(B,C)120-20
CAP**4821A**	0.97	0.97	58PH*090-16
CAP**4824A**	0.97	0.97	58PH*090-16
CAP**6021A**	0.99	0.95	58PH*090-16
CAP**6024A**	0.99	0.95	58PH*090-16
CNPV*4821A**	0.97	0.93	58PH*090-16
CNPV*6024A**	0.99	0.95	58PH*090-16
CNPV*6124A**	0.99	0.95	58PH*090-16

COOLING INDOOR MODEL	CAPACITY	POWER	FURNACE MODEL
CNPV*4821A**	0.97	0.93	58PH*090-16
CNPV*4824A**	0.97	0.93	58PH*090-16
CNPV*6024A**	0.99	0.95	58PH*090-16
CNPV*6124A**	1.00	0.96	58PH*090-16
CSPH*4812A**	0.98	0.94	58PH*090-16
CSPH*6012A**	0.99	0.95	58PH*090-16
CAP**4821A**	0.97	0.93	58PH*110-20
CAP**4824A**	0.97	0.93	58PH*110-20
CAP**6021A**	0.98	0.94	58PH*110-20
CAP**6024A**	0.99	0.95	58PH*110-20
CNPV*4821A**	0.97	0.93	58PH*110-20
CNPV*4824A**	0.97	0.93	58PH*110-20
CNPV*6024A**	0.99	0.95	58PH*110-20
CNPV*6124A**	1.00	0.96	58PH*110-20
CSPH*4812A**	0.98	0.94	58PH*110-20
CSPH*6012A**	0.99	0.95	58PH*110-20
CAP**4821A**	0.97	0.93	58PH*135-20
CAP**4824A**	0.97	0.93	58PH*135-20
CAP**6021A**	0.99	0.95	58PH*135-20
CAP**6024A**	0.99	0.95	58PH*135-20
CNPV*4821A**	0.97	0.93	58PH*135-20
CNPV*4824A**	0.97	0.93	58PH*135-20
CNPV*6024A**	0.99	0.95	58PH*135-20
CNPV*6124A**	1.00	0.96	58PH*135-20
CSPH*4812A**	0.98	0.94	58PH*135-20
CSPH*6012A**	0.99	0.95	58PH*135-20
CAP**4821A**	0.96	1.00	OVLAA048112
CAP**4824A**	0.98	1.01	OVLAA048112
CAP**6021A**	0.97	1.01	OVLAA048112
CAP**6024A**	0.98	0.98	OVLAA048112
CNPV*4821A**	0.97	1.01	OVLAA048112
CNPV*4824A**	0.97	1.01	OVLAA048112
CNPV*6024A**	0.99	0.99	OVLAA060154
CNPV*6124A**	1.00	0.96	OVLAA060154
CSPH*4812A**	0.99	0.99	OVLAA060154
CSPH*6012A**	1.01	0.97	OVLAA060154

See notes on pg. 61

DETAILED COOLING CAPACITIES# CONTINUED

EVAPORATOR AIR			CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
CFM	EWB ° F (° C)	75 (23.9)		85 (29.4)		95 (35)		105 (40.6)		115 (46.1)		125 (51.7)		Total Sys. KW**						
		Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**	Capacity MBtuh	Total Sys. KW**							
1750	72 (22.2)	66.03	33.71	3.54	62.86	32.49	3.92	4.33	59.49	31.24	4.33	55.92	29.95	47.8	52.09	28.60	5.29	47.94	27.18	5.86
	67 (19.4)	60.16	42.01	3.52	57.34	40.81	3.90	4.30	39.55	4.75	47.67	38.25	4.75	47.67	36.88	5.26	43.93	35.42	5.83	
	63 (17.2)††	55.92	40.36	3.52	53.34	39.17	3.88	4.28	47.64	36.64	4.73	44.45	36.64	4.73	44.45	35.28	5.23	41.00	33.82	5.81
	62 (16.7)	55.30	50.14	3.52	52.96	52.74	3.88	4.28	48.29	48.29	4.73	45.62	48.29	4.73	45.62	45.62	5.24	42.65	42.65	5.83
	57 (13.9)	54.87	54.87	3.51	52.85	52.85	3.88	4.28	48.23	48.23	4.73	45.56	48.23	4.73	45.56	45.56	5.24	42.60	42.60	5.83
	72 (22.2)	66.94	35.49	3.63	63.63	34.26	4.01	4.43	56.41	31.66	4.88	52.46	30.30	5.39	48.19	28.86	5.39	48.19	28.86	5.96
2000	67 (19.4)	61.07	44.91	3.62	58.11	43.67	3.99	4.40	51.67	41.04	4.85	48.13	39.62	5.36	44.32	38.08	5.36	44.32	38.08	5.93
	63 (17.2)††	56.81	43.05	3.61	54.12	41.83	3.98	4.38	48.20	39.22	4.83	44.93	37.80	5.34	41.42	36.25	5.34	41.42	36.25	5.91
	62 (16.7)	57.02	57.02	3.61	54.82	54.82	3.98	4.39	49.82	49.82	4.84	46.96	46.96	4.84	46.96	46.96	5.35	43.79	43.79	5.93
	57 (13.9)	56.95	56.95	3.61	54.75	54.75	3.98	4.39	49.76	49.76	4.84	46.90	46.90	4.84	46.90	46.90	5.35	43.74	43.74	5.93
	72 (22.2)	67.58	37.19	3.73	64.15	35.93	4.11	4.53	56.72	33.31	4.98	52.67	31.92	5.49	48.30	30.47	5.49	48.30	30.47	6.06
	67 (19.4)	61.73	47.68	3.71	58.69	46.41	4.09	4.50	52.08	43.68	4.95	48.50	42.18	5.46	44.73	44.73	5.46	44.73	44.73	6.03
2250	63 (17.2)††	57.47	45.62	3.71	54.69	44.36	4.08	4.48	48.64	41.65	4.93	45.33	40.11	5.43	41.94	41.94	5.43	41.94	41.94	6.01
	62 (16.7)	58.71	58.71	3.71	56.35	56.35	4.08	4.49	51.03	51.03	4.94	48.01	48.01	5.45	44.66	44.66	5.45	44.66	44.66	6.03
	57 (13.9)	58.64	58.64	3.71	56.29	56.29	4.08	4.49	50.98	50.98	4.94	47.96	47.96	5.45	44.62	44.62	5.45	44.62	44.62	6.03

COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL		CAPACITY	POWER	COOLING INDOOR MODEL		CAPACITY	POWER	FURNACE MODEL	
*CNPV*6124A**		1.00	1.00					CAP**6024A**		0.98	0.94	58CV(A.X)155--22	
CAP**6021A**		0.97	0.97	CNPV*6024A**		0.98	0.94	CNPV*6024A**		0.98	0.94	58CV(A.X)155--22	
CAP**6024A**		0.99	0.99	CNPV*6124A**		0.98	0.94	CNPV*6124A**		0.98	0.94	58MEC120--20	
CAP**6025A**		0.99	0.99	CNPV*6024A**		0.98	0.94	CNPV*6024A**		0.98	0.94	58MEC120--20	
CNPV*6024A**		0.99	0.99	CNPV*6124A**		0.99	0.95	CNPV*6124A**		0.99	0.95	58MV(B.C)120--20	
CNPV*6124A**		0.98	0.98	CSPH*6012A**		0.98	0.94	CSPH*6012A**		0.97	0.94	58MV(B.C)120--20	
CNPV*6024A**		0.99	0.99	CNPV*6024A**		0.97	0.94	CAP**6021A**		0.97	0.94	58PH*110--20	
CSPH*6012A**		0.99	0.99	CNPV*6124A**		0.98	1.01	CAP**6024A**		0.97	0.94	58PH*110--20	
FB4CNF060		0.98	0.98	CNPV*6024A**		0.97	1.02	CNPV*6024A**		0.98	0.94	58PH*110--20	
FE4ANB006		0.99	0.92	CNPV*6124A**		0.99	0.99	CNPV*6024A**		0.98	0.94	58PH*110--20	
FV4CNB006		0.99	0.92	CNPV*6024A**		0.97	0.97	CNPV*6124A**		0.99	0.95	58PH*110--20	
FV5BNB060		1.00	0.96	CNPV*6124A**		0.98	0.98	CSPH*6012A**		0.98	0.94	58PH*110--20	
CAP**6021A**		0.97	0.97	CNPV*6024A**		0.97	0.97	CNPV*6024A**		0.97	0.94	58PH*135--20	
CAP**6024A**		0.97	0.94	58CV(A.X)110--20		0.99	0.99	CNPV*6124A**		0.99	0.94	58PH*135--20	
CNPV*6024A**		0.97	0.94	58CV(A.X)110--20		0.99	0.96	CNPV*6024A**		0.96	0.94	58PH*135--20	
CNPV*6124A**		0.98	0.94	58CV(A.X)110--20		0.97	0.94	CSPH*6012A**		0.97	0.94	58PH*135--20	
CNPV*6024A**		0.97	0.97	58CV(A.X)110--20		0.97	0.94	CAP**6021A**		0.97	0.94	58PH*135--20	
CSPH*6012A**		0.99	0.95	58CV(A.X)110--20		0.97	0.94	CAP**6024A**		0.97	0.94	58PH*135--20	
FE4ANB006		0.99	0.92	58CV(A.X)110--20		0.99	0.99	CNPV*6024A**		0.98	0.94	58PH*135--20	
FV4CNB006		0.99	0.92	58CV(A.X)135--22		0.97	0.94	CNPV*6124A**		0.98	1.04	58PH*135--20	
FV5BNB060		1.00	0.96	58CV(A.X)135--22		0.97	0.94	CNPV*6024A**		0.98	1.04	58PH*135--20	
CAP**6021A**		0.97	0.97	58CV(A.X)135--22		0.97	0.94	CNPV*6024A**		0.97	1.03	58PH*135--20	
CAP**6024A**		0.97	0.94	58CV(A.X)135--22		0.97	0.94	CNPV*6124A**		0.97	1.02	58PH*135--20	
CNPV*6024A**		0.97	0.94	58CV(A.X)135--22		0.97	0.94	CSPH*6012A**		0.98	1.02	58PH*135--20	
CNPV*6124A**		0.98	0.94	58CV(A.X)135--22		0.97	0.94	CNPV*6024A**		0.98	1.03	58PH*135--20	
CSPH*6012A**		0.99	0.95	58CV(A.X)135--22		0.97	0.94	CSPH*6012A**		0.98	1.02	58PH*135--20	

* Tested combination.
† Total and sensible capacities are net capacities. Blower motor heat has been subtracted.
‡ Sensible capacities shown are based on 80° F (27°C) entering air at the indoor coil. For sensible capacities at other than 80° F (27°C), deduct 835 Btuh (245 kW) per 1000 CFM (480 L/S) of indoor coil air for each degree below 80° F (27°C), or add 835 Btuh (245 kW) per degree above 80° F (27°C).
Detailed cooling capacities are based on indoor and outdoor unit at the same elevation per AHRI standard 210/240--2008. If additional tubing length and/or indoor unit is located above outdoor unit, a slight variation in capacity may occur.
** System kw is total of indoor and outdoor unit kilowatts.
†† At TVA rating indoor condition (75° F edb/63° F ewb). All other indoor air temperatures are at 80° F edb.
NOTE: When the required data falls between the published data, interpolation may be performed. Extrapolation is not an acceptable practice.
EWB — Entering Wet Bulb

CONDENSER ONLY RATINGS*

SST ° F (° C)		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)							
		55 (12.78)	65 (18.33)	75 (23.89)	85 (29.44)	95 (35.0)	105 (40.56)	115 (46.11)	125 (51.67)
24ANB618A**30									
30 (-1.11)	TCG	14.00	13.50	13.00	12.40	11.80	11.00	10.20	9.30
	SDT	65.20	74.80	84.40	94.00	103.60	113.10	122.60	132.00
	KW	0.66	0.78	0.91	1.04	1.20	1.37	1.58	1.83
35 (1.67)	TCG	15.60	15.00	14.50	13.80	13.10	12.30	11.40	10.40
	SDT	66.30	75.90	85.40	94.90	104.40	113.80	123.20	132.70
	KW	0.65	0.77	0.90	1.04	1.20	1.38	1.58	1.83
40 (4.44)	TCG	17.30	16.70	16.10	15.30	14.60	13.70	12.70	11.70
	SDT	67.50	76.90	86.40	95.80	105.20	114.60	124.00	133.30
	KW	0.64	0.77	0.90	1.05	1.20	1.38	1.59	1.83
45 (7.22)	TCG	19.10	18.50	17.70	17.00	16.10	15.20	14.20	13.00
	SDT	68.70	78.00	87.40	96.70	106.10	115.40	124.80	134.10
	KW	0.63	0.77	0.90	1.05	1.21	1.39	1.59	1.83
50 (10.0)	TCG	21.10	20.30	19.50	18.70	17.80	16.70	15.70	14.50
	SDT	69.90	79.20	88.40	97.70	107.00	116.30	125.60	134.80
	KW	0.63	0.76	0.90	1.05	1.21	1.39	1.60	1.84
55 (12.78)	TCG	23.10	22.30	21.50	20.50	19.50	18.40	17.20	15.90
	SDT	71.20	80.40	89.60	98.80	108.00	117.20	126.50	135.60
	KW	0.62	0.76	0.91	1.06	1.22	1.40	1.61	1.85
24ANB624A**30									
30 (-1.11)	TCG	20.10	19.40	18.50	17.60	16.70	15.60	14.40	13.10
	SDT	66.10	75.80	85.30	94.90	104.40	114.00	123.40	132.80
	KW	0.97	1.13	1.29	1.46	1.65	1.87	2.13	2.42
35 (1.67)	TCG	22.30	21.40	20.50	19.50	18.50	17.30	16.00	14.70
	SDT	67.20	76.80	86.30	95.80	105.30	114.70	124.10	133.50
	KW	0.96	1.12	1.29	1.46	1.66	1.87	2.13	2.42
40 (4.44)	TCG	24.60	23.70	22.70	21.60	20.40	19.10	17.80	16.30
	SDT	68.40	77.90	87.30	96.70	106.10	115.50	124.80	134.10
	KW	0.95	1.12	1.29	1.46	1.66	1.88	2.13	2.42
45 (7.22)	TCG	27.10	26.00	24.90	23.70	22.40	21.10	19.60	18.00
	SDT	69.60	79.00	88.30	97.60	107.00	116.30	125.60	134.90
	KW	0.94	1.11	1.29	1.47	1.67	1.89	2.14	2.43
50 (10.0)	TCG	29.70	28.60	27.30	26.00	24.60	23.10	21.50	19.80
	SDT	70.80	80.10	89.40	98.70	107.90	117.20	126.40	135.60
	KW	0.93	1.11	1.29	1.47	1.67	1.90	2.15	2.43
55 (12.78)	TCG	32.50	31.20	29.90	28.40	26.90	25.30	23.50	21.70
	SDT	72.10	81.30	90.50	99.70	108.90	118.10	127.30	136.40
	KW	0.93	1.11	1.29	1.48	1.69	1.91	2.16	2.45
24ANB630A**30									
30 (-1.11)	TCG	23.80	22.90	21.90	20.90	19.80	18.50	17.00	15.30
	SDT	68.10	77.50	87.00	96.40	105.80	115.10	124.40	133.60
	KW	1.14	1.32	1.52	1.74	1.99	2.29	2.63	3.02
35 (1.67)	TCG	26.30	25.30	24.30	23.10	21.90	20.50	19.00	17.20
	SDT	69.40	78.70	88.10	97.40	106.70	116.00	125.30	134.40
	KW	1.15	1.33	1.52	1.75	2.00	2.30	2.64	3.03
40 (4.44)	TCG	29.00	27.90	26.80	25.50	24.20	22.80	21.10	19.20
	SDT	70.70	79.90	89.20	98.50	107.70	117.00	126.20	135.30
	KW	1.16	1.33	1.53	1.75	2.01	2.31	2.65	3.05
45 (7.22)	TCG	31.90	30.70	29.40	28.10	26.70	25.10	23.40	21.40
	SDT	72.00	81.20	90.40	99.60	108.80	118.00	127.20	136.30
	KW	1.16	1.33	1.53	1.76	2.01	2.31	2.66	3.06
50 (10.0)	TCG	35.00	33.60	32.30	30.80	29.30	27.60	25.70	23.60
	SDT	73.50	82.50	91.60	100.80	110.00	119.20	128.20	137.20
	KW	1.16	1.33	1.53	1.76	2.02	2.32	2.67	3.07
55 (12.78)	TCG	38.30	36.80	35.30	33.70	32.00	30.20	28.20	26.00
	SDT	75.00	84.00	93.00	102.10	111.20	120.30	129.30	138.20
	KW	1.15	1.33	1.53	1.76	2.02	2.32	2.67	3.08

See notes on page 64

CONDENSER ONLY RATINGS* CONTINUED

SST ° F (° C)		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)							
		55 (12.78)	65 (18.33)	75 (23.89)	85 (29.44)	95 (35.0)	105 (40.56)	115 (46.11)	125 (51.67)
24ANB636A**30									
30 (-1.11)	TCG	30.50	29.20	27.80	26.30	24.70	23.00	21.20	19.20
	SDT	69.50	78.70	87.90	97.20	106.60	115.90	125.20	134.50
	KW	1.41	1.62	1.85	2.10	2.37	2.69	3.07	3.51
35 (1.67)	TCG	33.70	32.20	30.70	29.10	27.40	25.50	23.60	21.50
	SDT	70.70	79.90	89.10	98.30	107.50	116.80	126.10	135.40
	KW	1.41	1.63	1.86	2.11	2.38	2.70	3.07	3.51
40 (4.44)	TCG	37.10	35.50	33.80	32.10	30.20	28.20	26.10	23.90
	SDT	72.10	81.20	90.30	99.50	108.60	117.80	127.10	136.30
	KW	1.42	1.64	1.87	2.12	2.40	2.71	3.08	3.52
45 (7.22)	TCG	40.80	39.00	37.20	35.30	33.20	31.10	28.80	26.40
	SDT	73.70	82.60	91.60	100.70	109.80	118.90	128.10	137.20
	KW	1.43	1.65	1.88	2.13	2.41	2.73	3.10	3.53
50 (10.0)	TCG	44.80	42.80	40.80	38.70	36.50	34.10	31.70	29.00
	SDT	75.30	84.10	93.10	102.00	111.00	120.10	129.10	138.10
	KW	1.45	1.67	1.90	2.15	2.43	2.75	3.12	3.54
55 (12.78)	TCG	48.90	46.80	44.60	42.30	39.90	37.40	34.70	31.80
	SDT	77.00	85.70	94.60	103.40	112.30	121.30	130.20	139.10
	KW	1.47	1.70	1.93	2.18	2.46	2.77	3.14	3.56
24ANB642A**30									
30 (-1.11)	TCG	33.00	32.30	31.40	30.30	28.90	27.40	25.60	23.70
	SDT	69.80	79.20	88.70	98.10	107.40	116.70	125.90	135.10
	KW	1.61	1.84	2.12	2.45	2.84	3.29	3.81	4.40
35 (1.67)	TCG	36.40	35.70	34.70	33.40	32.00	30.30	28.40	26.30
	SDT	71.20	80.60	89.90	99.20	108.40	117.70	126.80	136.00
	KW	1.62	1.86	2.14	2.47	2.86	3.31	3.83	4.42
40 (4.44)	TCG	40.10	39.30	38.20	36.80	35.20	33.40	31.40	29.10
	SDT	72.70	81.90	91.20	100.40	109.60	118.70	127.80	136.90
	KW	1.63	1.87	2.15	2.49	2.88	3.33	3.85	4.45
45 (7.22)	TCG	44.10	43.10	41.90	40.40	38.60	36.70	34.50	32.00
	SDT	74.20	83.30	92.50	101.60	110.80	119.90	128.90	137.90
	KW	1.64	1.88	2.17	2.51	2.91	3.36	3.88	4.48
50 (10.0)	TCG	48.30	47.20	45.80	44.20	42.30	40.10	37.70	35.00
	SDT	75.80	84.80	93.90	103.00	112.00	121.00	130.00	138.90
	KW	1.65	1.90	2.19	2.54	2.94	3.39	3.92	4.51
55 (12.78)	TCG	52.80	51.50	50.00	48.10	46.00	43.70	41.10	38.20
	SDT	77.40	86.40	95.40	104.40	113.40	122.30	131.20	140.00
	KW	1.67	1.92	2.22	2.57	2.97	3.43	3.96	4.55
24ANB648A**30									
30 (-1.11)	TCG	40.10	38.00	35.90	33.80	31.50	29.20	26.70	24.20
	SDT	67.60	77.00	86.40	95.80	105.10	114.50	123.80	133.10
	KW	1.97	2.26	2.54	2.83	3.13	3.46	3.84	4.29
35 (1.67)	TCG	44.40	42.00	39.70	37.30	34.80	32.30	29.60	26.80
	SDT	68.90	78.20	87.50	96.80	106.10	115.30	124.60	133.80
	KW	1.90	2.22	2.53	2.83	3.14	3.48	3.87	4.30
40 (4.44)	TCG	49.10	46.40	43.80	41.10	38.40	35.60	32.70	29.60
	SDT	70.30	79.40	88.60	97.80	107.00	116.30	125.40	134.60
	KW	1.80	2.15	2.49	2.81	3.14	3.50	3.89	4.32
45 (7.22)	TCG	54.20	51.20	48.20	45.20	42.20	39.20	36.00	32.60
	SDT	71.70	80.70	89.80	99.00	108.10	117.30	126.40	135.40
	KW	1.66	2.05	2.41	2.77	3.13	3.50	3.90	4.34
50 (10.0)	TCG	59.80	56.40	53.00	49.70	46.40	43.00	39.40	35.70
	SDT	73.20	82.10	91.20	100.20	109.30	118.30	127.30	136.30
	KW	1.47	1.90	2.31	2.70	3.09	3.48	3.90	4.35
55 (12.78)	TCG	65.80	62.00	58.30	54.50	50.80	47.00	43.10	39.00
	SDT	74.80	83.60	92.60	101.50	110.50	119.40	128.40	137.30
	KW	1.24	1.72	2.17	2.60	3.02	3.44	3.88	4.35

See notes on page 64

24ANB6

CONDENSER ONLY RATINGS* CONTINUED

SST ° F (° C)		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)							
		55 (12.78)	65 (18.33)	75 (23.89)	85 (29.44)	95 (35.0)	105 (40.56)	115 (46.11)	125 (51.67)
24ANB660A**30									
30 (-1.11)	TCG	45.10	43.80	42.30	40.50	38.50	36.20	33.50	30.50
	SDT	69.00	78.40	87.70	97.10	106.40	115.60	124.80	134.00
	KW	2.22	2.52	2.83	3.17	3.56	4.00	4.53	5.15
35 (1.67)	TCG	50.00	48.40	46.70	44.70	42.50	40.00	37.10	33.80
	SDT	70.40	79.70	89.00	98.20	107.40	116.60	125.80	134.90
	KW	2.21	2.52	2.85	3.19	3.58	4.03	4.55	5.16
40 (4.44)	TCG	55.10	53.40	51.40	49.20	46.70	44.00	40.80	37.30
	SDT	71.90	81.10	90.20	99.40	108.50	117.60	126.70	135.70
	KW	2.21	2.53	2.86	3.21	3.61	4.05	4.57	5.18
45 (7.22)	TCG	60.70	58.60	56.40	54.00	51.20	48.20	44.80	41.00
	SDT	73.50	82.50	91.60	100.70	109.70	118.70	127.70	136.70
	KW	2.20	2.53	2.87	3.23	3.63	4.08	4.60	5.20
50 (10.0)	TCG	66.50	64.20	61.70	59.00	56.00	52.60	48.90	44.70
	SDT	75.10	84.00	93.00	102.00	111.00	119.90	128.80	137.60
	KW	2.19	2.53	2.89	3.26	3.66	4.11	4.63	5.22
55 (12.78)	TCG	72.80	70.10	67.30	64.20	60.90	57.20	53.10	48.60
	SDT	76.80	85.70	94.50	103.40	112.30	121.10	129.90	138.60
	KW	2.18	2.54	2.90	3.28	3.69	4.15	4.66	5.25

* AHRI listing applies only to systems shown in Combination Ratings table.

KW – Outdoor Unit Kilowatts Only.

SDT – Saturated Temperature Leaving Compressor (° F/° C)

SST – Saturated Temperature Entering Compressor (° F)

TCG – Gross Cooling Capacity (1000 Btuh)

24ANB6

GUIDE SPECIFICATIONS

GENERAL

System Description

Outdoor-mounted, air-cooled, split-system air conditioner unit suitable for ground or rooftop installation. Unit consists of a hermetic compressor, an air-cooled coil, propeller-type condenser fan, and a control box. Unit will discharge supply air upward as shown on contract drawings. Unit will be used in a refrigeration circuit to match up to a packaged fan coil or coil unit.

Quality Assurance

- Unit will be rated in accordance with the latest edition of AHRI Standard 210.
- Unit will be certified for capacity and efficiency, and listed in the latest AHRI directory.
- Unit construction will comply with latest edition of ANSI/ASHRAE and with NEC.
- Unit will be constructed in accordance with UL standards and will carry the UL label of approval. Unit will have c-UL approval.
- Unit cabinet will be capable of withstanding Federal Test Method Standard No. 141 (Method 6061) 500-hr salt spray test.
- Air-cooled condenser coils will be leak tested and pressure tested.
- Unit constructed in ISO9001 approved facility.

Delivery, Storage, and Handling

- Unit will be shipped as single package only and is stored and handled per unit manufacturer's recommendations.

Warranty (for inclusion by specifying engineer)

- U.S. and Canada only.

PRODUCTS

Equipment

- Factory assembled, single piece, air-cooled air conditioner unit. Contained within the unit enclosure is all factory wiring, piping, controls, compressor, refrigerant charge Puron® (R-410A), and special features required prior to field start-up.

Unit Cabinet

- Unit cabinet, including louvered coil guard, will be constructed of galvanized steel, bonderized, and coated with a powder coat paint.

Fans

- Condenser fan will be direct-drive forward-swept propeller type, discharging air upward.

AIR-COOLED, SPLIT-SYSTEM AIR CONDITIONER

24ANB6

1-1/2 TO 5 NOMINAL TONS

- Condenser fan motors will be totally enclosed, 1-phase type with class B insulation and permanently lubricated bearings. Shafts will be corrosion resistant.
- Fan blades will be statically and dynamically balanced.
- Condenser fan openings will be equipped with coated steel wire safety guards.

Compressor

- Compressor will be hermetically sealed.
- Compressor will be mounted on rubber split-post vibration isolators.
- Compressor will be covered with a sound absorbing blanket.

Condenser Coil

- Condenser coil will be air cooled.
- Coil will be constructed of aluminum fins mechanically bonded to copper tubes which are then cleaned, dehydrated, and sealed.

Refrigeration Components

- Refrigeration circuit components will include liquid-line back-seating shutoff valve with sweat connections, vapor-line back-seating shutoff valve with sweat connections, system charge of Puron® (R-410A) refrigerant, and compressor oil.
- Unit will be equipped with high-pressure switch, low pressure switch and filter drier for Puron refrigerant.

Operating Characteristics

- The capacity of the unit will meet or exceed _____ Btuh at a suction temperature of _____ °F/°C. The power consumption at full load will not exceed _____ kW.
- Combination of the unit and the evaporator or fan coil unit will have a total net cooling capacity of _____ Btuh or greater at conditions of _____ CFM entering air temperature at the evaporator at _____ °F/°C wet bulb and _____ °F/°C dry bulb, and air entering the unit at _____ °F/°C.
- The system will have a SEER of _____ Btuh/watt or greater at DOE conditions.

Electrical Requirements

- Nominal unit electrical characteristics will be _____ v, single phase, 60 hz. The unit will be capable of satisfactory operation within voltage limits of _____ v to _____ v.
- Unit electrical power will be single point connection.
- Control circuit will be 24v.

Special Features

- Refer to section of this literature identifying accessories and descriptions for specific features and available enhancements.

24ANB6

SYSTEM DESIGN SUMMARY

1. Intended for outdoor installation with free air inlet and outlet. Outdoor fan external static pressure available is less than 0.01-in. wc.
2. Minimum outdoor operating air temperature without low-ambient operation accessory is 55°F (12.8°C).
3. Maximum outdoor operating air temperature is 125°F (51.7°C).
4. For reliable operation, unit should be level in all horizontal planes.
5. For interconnecting refrigerant tube lengths greater than 80 ft (23.4 m) and/or 35 ft (10.7 m) vertical differential, consult Residential Piping and Longline Guideline and Service Manual available from equipment distributor.
6. If any refrigerant tubing is buried, provide a 6 in. (152.4 mm) vertical rise to the valve connections at the unit. Refrigerant tubing lengths up to 36 in. (914.4 mm) may be buried without further consideration. Do not bury refrigerant lines longer than 36 in. (914.4 mm).
7. Use only copper wire for electric connection at unit. Aluminum and clad aluminum are not acceptable for the type of connector provided.
8. Do not apply capillary tube indoor coils to these units.
9. Factory-supplied filter drier must be installed.