

PERFORMANCE™ SERIES
38MBRC OUTDOOR UNIT



36K



48K/58K

An Efficient Outdoor Unit with Easy Maintenance

FEATURES OUTDOOR

- Variable speed compressor
- High efficiency ECM fan motor
- Factory installed base pan heater
- Factory installed crankcase heater
- Low voltage controls
- Auto-restart function
- Condenser high temp protection
- Quiet operation
- Anti-corrosive fin coating

COMPATIBLE WITH:

- 40MBAB Air Handler
- 40MBCAQ Cassette
- 40MBFQ Floor Console
- 40MBDQ Ducted

Performance
SERIES

Outdoor Heat Pump Unit

Inverter Compressor

Sizes: 36 / 48 / 58

KEY FEATURES

Premium Efficiency

Enjoy increased energy savings with a unit equipped with inverter technology that delivers first-rate comfort and efficiency.

Simple Maintenance

With convenient access to the control compartment through both top and side panels, this outdoor unit makes servicing and maintenance a breeze.



Air Handler
Size 36 / 48



Cassette



Ducted



Floor Console



SPECIFICATIONS:

38MBRC Outdoor Unit				
Heat Pump System				
Size		36K	48K	58K
Outdoor Model		38MBRCQ36AA3	38MBRCQ48AA3	38MBRCQ58AA3
Electrical				
Voltage-Phase-Cycle		V-Ph-Hz	208/230-1-60	208/230-1-60
MCA		A.	30	35
MOCP - Fuse Rating		A.	50	50
Operating Range				
Cooling Outdoor DB Min - Max		° F (° C)	-22~130 (-30~55)	-22~130 (-30~55)
Heating Outdoor DB Min - Max		° F (° C)	-22~86 (-30~30)	-22~86 (-30~30)
Piping				
Total Piping Length		ft (m)	213 (65)	213 (65)
Piping Lift*		ft (m)	98 (30)	98 (30)
Pipe Connection Size - Liquid		in (mm)	3/8 (9.52)	3/8 (9.52)
Pipe Connection Size - Suction		in (mm)	5/8 (16)	7/8 (22)
Refrigerant				
Type			R410A	R410A
Charge		lbs (kg)	6.72 (3.05)	9.26 (4.2)
				10.58 (4.8)
Compressor				
Type			Rotary Inverter	Rotary Inverter
				Rotary Inverter
Dimensions				
Unit Width		in (mm)	37.24 (946)	37.48 (952)
Unit Height		in (mm)	31.89 (810)	52.48 (1333)
Unit Depth		in (mm)	16.14 (410)	16.34 (415)
Net Weight		lbs (kg)	148.59 (67.4)	219.14 (99.4)
Airflow		CFM	2,130	4,500
Sound Pressure		dB(A)	63	62.5
				61.2

*Condensing unit above or below indoor unit.

COMPATIBILITY:

Indoor Unit		Outdoor Unit		
		38MBRCQ36AA3	38MBRCQ48AA3	38MBRCQ58AA3
Air Handler	40MBABQ36XA3	•		
	40MBABQ48XA3		•	
	40MBABQ60XA3			•
Cassette	40MBCAQ36XA3	•		
	40MBCAQ48XA3		•	
Floor Console	40MBFQ36---3	•		
	40MBFQ48---3		•	
	40MBFQ58---3			•
Ducted	40MBDQ36---3	•		
	40MBDQ48---3		•	
	40MBDQ58---3			•

PERFORMANCE™ SERIES
38MBRC OUTDOOR UNIT

PERFORMANCE:

40MBAB Air Handler				
Size		36K	48K	60K
Indoor Model		40MBABQ36XA3	40MBABQ48XA3	40MBABQ60XA3
Cooling System Tons		3.0	4.0	4.8
Cooling Rated Capacity	Btu/h	36,000	48,000	57,000
Cooling Cap. Range Min - Max	Btu/h	11,600-41,000	11,800~51,900	11,000~60,000
SEER		17.0	16.2	17.0
EER		8.8	8.6	10.0
Heating Rated Capacity (47° F)	Btu/h	38,000	55,000	60,000
Heating Rated Capacity (17° F)	Btu/h	25,600	37,500	34,000
Heating Maximum Capacity (17° F)	Btu/h	27,000	37,500	34,600
Heating Maximum Capacity (5° F)	Btu/h	22,000	31,000	33,000
Heating Cap. Range Min - Max	Btu/h	9,200-43,000	11,900~58,000	12,000~60,400
HSPF		11.3	10.8	10.4
COP (47° F)	W/W	3.35	3.03	3.2
COP (17° F)	W/W	2.61	2.46	2.52
COP (5° F)	W/W	1.9	1.75	1.81

PERFORMANCE:

40MBCA Cassette			
Size		36K	48K
Indoor Model		40MBCAQ36XA3	40MBCAQ48XA3
Cooling System Tons		3.0	4.0
Cooling Rated Capacity	Btu/h	36,000	48,000
Cooling Cap. Range Min - Max	Btu/h	12,400~36,000	16,600~48,000
SEER		18.2	17.8
EER		9.0	9.5
Heating Rated Capacity (47° F)	Btu/h	38,000	50,000
Heating Rated Capacity (17° F)	Btu/h	23,000	28,000
Heating Maximum Capacity (17° F)	Btu/h	25,300	37,900
Heating Maximum Capacity (5° F)	Btu/h	22,300	30,200
Heating Cap. Range Min - Max	Btu/h	11,200~38,000	11,850~52,000
HSPF		10.6	11.5
COP (47° F)	W/W	3.01	3.1
COP (17° F)	W/W	1.9	1.8
COP (5° F)	W/W	2.02	1.92

PERFORMANCE:

40MBF Floor Console				
Size		36K	48K	58K
Indoor Model		40MBFQ36---3	40MBFQ48---3	40MBFQ58---3
Cooling System Tons		3.0	4.0	4.5
Cooling Rated Capacity	Btu/h	36,000	48,000	54,000
Cooling Cap. Range Min - Max	Btu/h	11,400~36,000	15,800~48,000	15,000~54,000
SEER		17.0	18.0	18.0
EER		8.0	9.3	9.8
Heating Rated Capacity (47° F)	Btu/h	38,000	50,000	60,000
Heating Rated Capacity (17° F)	Btu/h	23,000	29,000	35,000
Heating Maximum Capacity (17° F)	Btu/h	23,000	29,000	35,000
Heating Maximum Capacity (5° F)	Btu/h	22,000	28,000	30,000
Heating Cap. Range Min - Max	Btu/h	11,400~38,000	12,000~50,000	17,000~62,000
HSPF		10.0	11.0	10.0
COP (47° F)	W/W	2.8	2.5	3
COP (17° F)	W/W	2.34	2.52	2.49
COP (5° F)	W/W	1.8	1.95	1.9

PERFORMANCE:

40MBD Ducted				
Size		36K	48K	58K
Indoor Model		40MBDQ36---3	40MBDQ48---3	40MBDQ58---3
Cooling System Tons		3.0	4.0	4.8
Cooling Rated Capacity	Btu/h	36,000	48,000	57,000
Cooling Cap. Range Min - Max	Btu/h	5,900~36,000	12,000~48,000	13,000~59,000
SEER		16.7	17.4	18.0
EER		9.0	9.2	10.0
Heating Rated Capacity (47° F)	Btu/h	40,000	50,000	60,000
Heating Rated Capacity (17° F)	Btu/h	27,000	29,000	35,400
Heating Maximum Capacity (17° F)	Btu/h	25,000	29,000	35,400
Heating Maximum Capacity (5° F)	Btu/h	22,000	32,000	35,000
Heating Cap. Range Min - Max	Btu/h	12,700~40,000	11,600~50,000	12,000~61,000
HSPF		11.5	10.3	10.0
COP (47° F)	W/W	3.37	3	3.5
COP (17° F)	W/W	2.63	2.57	2.5
COP (5° F)	W/W	1.9	1.95	2.01

Visit our website at carrierductless.com

