



STANDARD FEATURES

- Modes: Cool, Heat, Dry, Fan, Auto, Turbo
- Louver control (fixed or swing)
- Outside air intake
- Built-in condensate lift pump
- Follow Me (senses temperature at handheld remote)
- Heating setback (46° F Heating Mode)
- Quiet indoor operation
- Anti-corrosive fin coating

COMPATIBLE WITH:

- DLCSR Outdoor Unit
- DLCLRB Outdoor Unit
- DLCLRC Outdoor Unit
- DLCMRB Outdoor Unit
- DLCMHB Outdoor Unit

AN ERGONOMIC DESIGN FOR IMPROVED SERVICE & AIRFLOW

Sizes: 24 / 36 / 48

Select sizes are ENERGY STAR® certified based on indoor pairings



KEY FEATURES

Easier Service & Installation

A relocated condensate pump allows for easy replacement and increased spacing between lines.

Seamless Connection

Optimized Wi-Fi® connectivity means fewer installation steps for faster, more seamless connections.

Enhanced Design

A new, ergonomic design and larger vents for improved airflow means greater comfort from an unobtrusive indoor unit.

CONTROLS

Wireless Remote Controller included with indoor unit

Optional Wired Remote Controller KSACN0101AAA (timer function)


Optional Wired Remote Controller KSACN0701AAA (7 day programmable)



Wireless Remote Controller



Wired Controller (7-Day Programmable) KSACN0701AAA



SPECIFICATIONS:

DLFSCB Cassette				
Heat Pump				
System				
Size		24	36	48
Indoor Model		DLFSCBH24XAK	DLFLCBH36XAK	DLFLCBH48XAK
Electrical				
Voltage-Phase-Cycle	V-Ph-Hz	208/230-1-60	208/230-1-60	208/230-1-60
Power Supply		Indoor Unit Powered From Outdoor Unit		
MCA	A.	1.0	1.0	1.5
Controls				
Wireless Remote Controller (° F / ° C Convertible)		Standard	Standard	Standard
Wired Remote Controller (° F / ° C Convertible)		Optional	Optional	Optional
Operating Range				
Cooling Indoor DB Min - Max	° F (° C)	60.8~90 (16~32)	60.8~90 (16~32)	60.8~90 (16~32)
Heating Indoor DB Min - Max	° F (° C)	32~86 (0~30)	32~86 (0~30)	32~86 (0~30)
Piping				
Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)
Pipe Connection Size - Suction	in (mm)	5/8 (15.9)	5/8 (15.9)	5/8 (15.9)
Indoor				
Body Unit Width	in (mm)	32.68 (830)	32.68 (830)	32.68 (830)
Body Unit Height	in (mm)	8.07 (205)	9.65 (245)	11.3 (287)
Body Unit Depth	in (mm)	32.68 (830)	32.68 (830)	32.68 (830)
Body Net Weight	lbs (kg)	47.18 (21.4)	59.97 (27.2)	64.59 (29.3)
Panel Unit Width	in (mm)	37.4 (950)	37.4 (950)	37.4 (950)
Panel Unit Height	in (mm)	2.17 (55)	2.17 (55)	2.17 (55)
Panel Unit Depth	in (mm)	37.4 (950)	37.4 (950)	37.4 (950)
Panel Net Weight	lbs (kg)	11.02 (5)	11.02 (5)	11.02 (5)
Number of Fan Speeds		4	4	4
Airflow (Low to Turbo)	CFM	547/635/706/764	753/853/947/1041	935/1059/1171/1288
Sound Pressure (lowest to highest)	dB(A)	42/44/47/49	46/49/51/53	49/52/54/56
Air Throw Data	ft (m)	14.7 (4.5)	16.4 (5)	16.4 (5)
Moisture Removal	Pint/h (L/h)	5.6 (2.6)	8.5 (4.0)	12.3 (5.8)
Field Drain Pipe Size O.D.	in (mm)	1 (25.4)	1 (25.4)	1 (25.4)

COMPATIBILITY:

Indoor Unit	DLFSCBH24XAK	DLFLCBH36XAK	DLFLCBH48XAK
Outdoor Unit Single Zone*	DLCSR BH24AAK	DLCLR BH36AAK	DLCLR BH48AAK
		DLCLR CH36AAK	DLCLR CH48AAK
Outdoor Unit Multi-Zone*	DLCMRAH36DAK		
	DLCMRAH48EAK		
	DLCMRBH30DAK		
	DLCMRBH36DAK		
	DLCMH BH36DAK		
	DLCMRBH48EAK		
	DLCMH BH48EAK		

*Performance may vary based on the compatible outdoor units. See respective pages for performance data.

Manufacturer reserves the right to discontinue, or change at any time, specification or designs without notice or incurring obligations.

A Proud Member of the Carrier Family

DayandNightComfort.com | PO Box 128 Lewisburg, TN 37091 | ©2022 Carrier. All Rights Reserved.
Midea is a registered trademark owned by Midea Group Co., Ltd. Wi-Fi® is a registered trademark of Wi-Fi Alliance.
ENERGY STAR® is a registered trademark of the U.S. EPA. | Part No. DLS-002-DN-00

