



HEAT PUMP/HEAT COOL

83 SERIES AIR CONDITIONERS/HEAT PUMPS



PTACs deliver greater comfort, greater value.

Choose **fast** PTACs for reliability and performance.

EAST Packaged Terminal Air Conditioners and Heat Pumps are loaded with the features most important to you:

- The right size for retrofit (42" x 16")
- Appealing design
- Remote control
- Easy operation
- Solid state control
- Switch for fan cycle
- Protection against room freeze-ups
- Adjustable discharge louver (two-way)
- Filters positioned in front for easy cleaning
- Fresh air vent
- Superior corrosion protection
- Controllable from front desk (standard)
- Temperature limiting
- Load shedding control capability
- Random restart after power outage
- Internal self diagnostics and protection

Additional Heat Pump only features:

- Two-stage thermostat
- Low-ambient heat pump operation (to 25° F)
- Emergency heat



1621 Heil-Quaker Boulevard
LaVergne, TN 37086
Phone 615-248-8300
Fax 1-800-431-9752
www.icpusa.com

SPECIFICATIONS


HEAT/COOL												
CATALOG NUMBER	COOLING Btu/hr	EER	ELECTRIC HEAT (Btu/hr)	EVAP FAN CFM HI SPEED	APPROX. SHIP WEIGHT	1-Ph 60Hz VOLTAGE	CURRENT AMPS		POWER WATTS		BRANCH CIRCUIT FUSE AMPS	RECEPTACLE TYPE
							COOLING	ELEC. HT.	COOLING	ELEC. HT.		
830N063	6300/6100	10.0	11700/9600	210/180	132	230/208	2.9/3.1	15.0/13.6	630/610	3450/2820	20	2
830N093	9100/8900	9.8	11700/9600	290/250	132	230/208	4.2/4.6	15.0/13.6	930/910	3450/2820	20	2
830D093	9100	9.8	13600	290	132	265	3.7	15.1	930	3950	20	HW
830N123	12200/12000	9.2	11700/9600	360/330	141	230/208	6.0/6.6	15.0/13.6	1330/1310	3450/2820	20	2
830D123	12200	9.2	13600	360	141	265	5.2	15.1	1330	3950	20	HW
830N155	14100/13800	9.1	17000/13900	360/330	141	230/208	7.1/7.7	21.7/19.7	1550/1520	5000/4090	30	3

HEAT PUMP														
CATALOG NUMBER	COOLING Btu/hr	EER	REVERSE CYCLE	COP	ELECTRIC HEAT (Btu/hr)	EVAP FAN CFM HI SPEED	APPROX. SHIP WEIGHT	1-Ph 60Hz VOLTAGE	CURRENT AMPS		POWER WATTS		BRANCH CIRCUIT FUSE AMPS	RECEPTACLE TYPE
									COOLING	ELEC. HT.	COOLING	ELEC. HT.		
831N063	6100/6000	10.0/10.0	5500/5300	3.0	11700/9600	210/180	137	230/208	2.8/3.0	15.0/13.6	610/600	3450/2820	20	2
831N093	8900/8800	9.5/9.7	8500/8200	3.1	11700/9600	290/250	137	230/208	4.2/4.6	15.0/13.6	940/910	3450/2820	20	2
831N123	12100/11900	9.1/9.1	11700/11500	2.8	11700/9600	360/330	148	230/208	6.0/6.6	15.0/13.6	1330/1310	3450/2820	20	2

LEGEND: COP – Coefficient of Performance EER – Energy Efficiency Ratio HW – Hard Wire only. Junction Box Connection included with unit

AVAILABLE ACCESSORIES

- Junction Box Kit
- Polymer Wall Sleeve
- Wall Sleeve Insulation Kit
- Condensate Drain Kit
- Sub-base
- Polymer Architectural Grille (Beige or Brown)
- Aluminum Architectural Grille (Beige, Brown, White, Bronze or Unpainted)



PTAC THERMOSTATS OPTIONS

- Heat/Cool - Part No. 1170702
- Heat Pump - Part No. 1170703
- Height 3-1/2"
- Width 5-3/4"
- Depth 1-3/8"
- Single Speed
- Auto Changeover
- LCD Readout
- Clean Filter Feature
- Non-programable Thermostats
- Checks Outdoor Temperature



Manufacturer reserves the right to discontinue, or change, at any time, specifications or designs without notice and without incurring obligations.