



AIRFLOW TECHNICAL EVALUATION FORM

Distributor: _____
 Dealer: _____
 Technician's Name: _____

Job Site Reference: _____
 Installation Date: _____
 Fail Date: _____


MODEL INFO	Model #	Serial #	ELECTRICAL INFO
Outdoor/Package Unit:			Control Voltage: _____ Vac
Indoor Unit:			Supply Voltage: _____ Vac Φ _____
Air Cleaner:			3 Phase (Φ) Voltages: T1→T2 _____ Vac
Thermostat:			T1→T3 _____ Vac T2→T3 _____ Vac
Electronic Air Cleaner:			
Humidifier:			


DUCT SIZE	SQUARE DUCT	ROUND DUCT
	Area = h x w Height (h): _____ in Width (w): _____ in Cross Section Area of Square Duct: h x w = _____ in²	Area = $\pi \left(\frac{d}{2}\right)^2$ Diameter (d) = _____ in $\pi = 3.14$ Cross Sectional Area of Round Duct: $\pi \left(\frac{d}{2}\right)^2 = \text{_____ in}^2$
		

***Traversing The Duct** **NOTE: If using a Hot Wire or a Vane Anemometer, skip to filling out table in step 3.**

Pressure Method "Pitot Tube"

1. Divide your duct into equal sections taking your measurements approximately every two inches. Refer to duct diagrams to the right for examples. Take pressure measurements at letter designations.





2. Using your pitot tube and the equation to the right find the Velocity Pressure at each point and record them below.

Velocity Pressure = Total Pressure - Static Pressure

A = _____ w.c.	D = _____ w.c.	G = _____ w.c.	J = _____ w.c.	M = _____ w.c.
B = _____ w.c.	E = _____ w.c.	H = _____ w.c.	K = _____ w.c.	N = _____ w.c.
C = _____ w.c.	F = _____ w.c.	I = _____ w.c.	L = _____ w.c.	O = _____ w.c.

3. Convert your recorded Velocity Pressures above into Velocity by using the equation to the right and recording in the table below.

Velocity = 4,005 $\sqrt{\text{Velocity Pressure}}$

A = _____ ft/min.	D = _____ ft/min.	G = _____ ft/min.	J = _____ ft/min.	M = _____ ft/min.
B = _____ ft/min.	E = _____ ft/min.	H = _____ ft/min.	K = _____ ft/min.	N = _____ ft/min.
C = _____ ft/min.	F = _____ ft/min.	I = _____ ft/min.	L = _____ ft/min.	O = _____ ft/min.

4. Add all the Velocities together and divide by the number of measurements to get an Average Velocity. (Use calculated Velocities from the table in step 3.)

Average Velocity = _____ ft/min.

5. Multiply your Average Velocity by your Cross Sectional Duct Area to get your Airflow in cfm.

CFM = $\frac{\text{Cross Sectional Area (in}^2\text{)} \times \text{Average Velocity (ft/min)}}{144}$

cfm = _____ ft³/min

† Temperature rise is equal to the supply air temp. minus the return air temp. at steady state operation. The supply air temp. should be measured away from the line of sight of the heat exchanger.

*In small ducts or where traverse operations are otherwise impossible, an accuracy of ±5% can frequently be achieved by placing Pitot tube or Anemometer in center of duct. Determine velocity from the reading, then multiply by 0.9 for an approximate average velocity.

AIRFLOW TECHNICAL EVALUATION FORM

ELECTRIC HEAT TEMP RISE METHOD

1 PHASE

$$CFM = \frac{(Volts)(Amps)(3.413)}{1.08(\Delta T)}$$

Volts = _____ Amps = _____
 †Sup. Air Temp. _____°F - Ret. Air Temp. _____°F = ΔT

cfm = _____ ft³/min

3 PHASE

$$CFM = \frac{(Volts)(Amps)(5.91)}{1.08(\Delta T)}$$

Volts = _____ Amps = _____
 †Sup. Air Temp. _____°F - Ret. Air Temp. _____°F = ΔT

cfm = _____ ft³/min

TEMPERATURE VS. ENTHALPY

Wet-Bulb (F)	Btu/LB	Wet-Bulb (F)	Btu/LB	Wet-Bulb (F)	Btu/LB	Wet-Bulb (F)	Btu/LB	Wet-Bulb (F)	Btu/LB	Wet-Bulb (F)	Btu/LB
40	15.23	48	19.21	56	23.84	64	29.31	72	35.83	80	43.69
41	15.7	49	19.75	57	24.48	65	30.06	73	36.74	81	44.78
42	16.17	50	20.3	58	25.12	66	30.83	74	37.66	82	45.9
43	16.66	51	20.86	59	25.78	67	31.62	75	38.61	83	47.04
44	17.15	52	21.44	60	26.46	68	32.42	76	39.57	84	48.22
45	17.65	53	22.02	61	27.15	69	33.25	77	40.57	85	49.43
46	18.16	54	22.62	62	27.85	70	34.09	78	41.58		
47	18.68	55	23.22	63	28.57	71	34.95	79	42.62		

INDOOR COIL (EVAPORATOR)

OUTDOOR COIL (CONDENSOR)

ENTERING	LEAVING	DIFFERENCE	ENTERING	LEAVING	DIFFERENCE
W.B.			(Air) D.B.		ΔT = _____°F
Enthalpy		Δh = _____ Btu/LB	CONDENSOR CAPACITY		
EVAPORATOR CAPACITY			BTUH = 1.10 x COND. Cfm x ΔT		
BTUH = 4.5 x cfm x Δh					

Due to varying field conditions, a tolerance of 10% must be expected when comparing test data to actual performance.

OTHER METHODS TO CHECK AIRFLOW

Belt Driven Blowers

Blower Speed = _____ rpm
 Diameter of Pulley = _____ in
 # Of Turns = _____ Open
 Static Pressure = _____ w.c.
 Refer to Product Data Sheets for rpm vs static
 Pressure airflow charts.

Total External Method

Ret. Static + Sup. Static = Total External Static

Use the Total External Static in conjunction with the "Blower Performance" data in the Product Specification Sheets or the unit's "Tech Label".

NOTE: 350-400 CFM PER TON

NOTES

Furnace

$$cfm = \frac{btu\ output}{1.08(\Delta T)}$$

INDOOR DRY BULB ADJUSTMENT

Use equations below in conjunction with unit's "Tech Label" information for total and sensible capacities @ indoor dry bulbs other than 80°F entering coil.

$$\text{Sensible Capacity at Indoor db LOWER than } 80^{\circ}\text{F} = \frac{(MBh \times S/T) - (80 - \text{Indoor db}) \times 835 \times \text{Indoor cfm}}{1000}$$

$$\text{Sensible Capacity at Indoor db HIGHER than } 80^{\circ}\text{F} = \frac{(MBh \times S/T) + (\text{Indoor db} - 80) \times 835 \times \text{Indoor cfm}}{1000}$$

† Temperature rise is equal to the supply air temp. minus the return air temp. at steady state operation. The supply air temp. should be measured away from the line of sight of the heat exchanger.

*In small ducts or where traverse operations are otherwise impossible, an accuracy of ±5% can frequently be achieved by placing Pitot tube or Anemometer in center of duct. Determine velocity from the reading, then multiply by 0.9 for an approximate average velocity.