


DUCTLESS SYSTEMS

CONSTANT COMFORT™ DELUXE SERIES

DLFPHA HIGH WALL UNIT



INDOOR FEATURES

- Available in 208/230V
- Relative Humidity Sensor
- Occupancy Sensor
- Modes: Cool, Heat, Dry, Fan, Auto
- Turbo Mode
- Fully modulating fan speeds
- Sleep Mode
- Up-down / right-left louver control (fixed or swing)
- ECO Mode
- Carbon filter
- Follow Me (senses temperature at handheld remote)
- Heating Setback (46° F Heating Mode)
- Quiet indoor operation, as low as 29 dB(A)
- Aluminum Golden Hydrophilic pre-coated fins
- Up to 40.0 SEER and 14.5 HSPF when paired with DLCPRA outdoor unit

COMPATIBLE WITH:

- DLCPRA Outdoor Unit Single Zone
- DLCMRA Outdoor Unit Multi-Zone



Superior Comfort from a Single Energy Efficient Unit

Sizes: 09 / 12

All Systems are ENERGY STAR® certified based on outdoor unit pairing



KEY FEATURES

Relative Humidity Sensor

Increase comfort by setting the desired relative humidity in 5% increments in a range of 35% ~ 85%.

Occupancy Sensor

Detects activity in the room and adjusts the horizontal angle of airflow to blow away from people or follow people.

Wi-Fi®

Wi-Fi® connectivity is available (see below.)

CONTROLS

Wireless Remote Controller included with indoor unit

Optional Wired Remote Controller KSACN0401AAA (7-Day programmable)

Wi-Fi® connectivity is available through an accessory kit.



Wireless Remote Controller



Wired Remote Controller

ACCESSORIES

Wi-Fi® Kit KSAIF0601AAA



DUCTLESS SYSTEMS

CONSTANT COMFORT™ DELUXE SERIES

DLFPHA HIGH WALL UNIT

SPECIFICATIONS:

DLFPHA High Wall			
Heat Pump System			
Size		9	12
Indoor Model		DLFPHAH09XAK	DLFPHAH12XAK
Electrical			
Voltage-Phase-Cycle		V-Ph-Hz 208/230-1-60	208/230-1-60
Power Supply		Indoor unit powered from outdoor unit	
MCA	A.	0.3	0.3
Operating Range			
Cooling Indoor DB Min - Max		° F (° C) 62~90 (17~32)	62~90 (17~32)
Heating Indoor DB Min - Max		° F (° C) 32~86 (0~30)	32~86 (0~30)
Piping			
Pipe Connection Size - Liquid		in (mm) 1/4 (6.35)	1/4 (6.35)
Pipe Connection Size - Suction		in (mm) 3/8 (9.52)	1/2 (12.7)
Indoor			
Unit Width		in (mm) 35.2 (895)	35.2 (895)
Unit Height		in (mm) 11.7 (298)	11.7 (298)
Unit Depth		in (mm) 9.8 (248)	9.8 (248)
Net Weight		lbs (kg) 37.48 (17)	37.48 (17)
Number of Fan Speeds		4	4
Airflow (lowest to highest)		CFM 144/245/295/345	168/252/306/357
Sound Pressure (lowest to highest)		dB(A) 29/35.5/41.5/45.6	29/35.5/41.5/46.8
Air Throw Data		ft (m) 21.98 (6.7)	22.97 (7)
Moisture Removal		Pint/h (L/h) 2.11 (1.0)	2.53 (1.2)
Field Drain Pipe Size O.D.		in (mm) 1 (25.4)	1 (25.4)

COMPATIBILITY:

Indoor Unit	DLFPHAH09XAK	DLFPHAH12XAK
Outdoor Unit Single Zone*	DLCPPRAH09AAK	DLCPPRAH12AAK
Outdoor Unit Multi-Zone*	DLCMRAH18BAK DLCMRAH27CAK DLCMRAH36DAK DLCMRAH48EAK	

*Performance may vary based on the compatible outdoor units. See respective pages for performance data.

Manufacturer reserves the right to discontinue, or change at any time, specification or designs without notice or incurring obligations.