

Tulip Switchable



Benefits at a glance



- Enhanced merchandising opportunities
- Panorama sidewalls for customer attention
- Two-in-one solution for optimized merchandising flexibility
- Illuminated display header for additional promotions

Tulip Switchable

Plug-in switchable island for promotional sales

Standard configuration

- Internal and external panels galvanized steel withhard-wearing NCS 0501-B58G white powder-coated finish
- Temperature assured air-forced cooling
- Automatic defrost with drip water
- evaporation
- Analog thermometer
- Electronic controller
- Illuminated display header
- Castors







TS17


TS33

Basic models









		Natural	Standard
	Units	TS17	TS33
Temperature	[°C]	+4+6 -1518	+4+6 -1518
Refrigerant		R290	R404a
Width	[mm]	775	925
Depth	[mm]	850	1510
Height	[mm]	1080	1075
Volume	[1]	125	310
Power consumption ref. Freezer mode Chiller mode	[W]	431 500	1050
Power consumption def. Freezer mode Chiller mode	[W]	735	2400
Energy consumption* Freezer mode Chiller mode	[kWh/d]	9.5 4.8	22.5 2.5
Heat dispatch* Freezer mode Chiller mode	[W]	396 200	937 104
Application			

^{*} at Climate Class 3 according to ISO 23953



Carrier Commercial Refrigeration is a leading supplier of high-efficiency turnkey refrigeration systems and services in the food retail industry.

