



SUPRA®



Superior refrigeration  
performance for trucks  
with longer boxes



YOU CARRY  
WE CARE

Developed for distribution environments with multiple door openings, the robust design of the SUPRA® truck refrigeration unit delivers high performance for longer box sizes. Aesthetic front grill design and higher capacity make the SUPRA unit very suitable for high ambient applications for box sizes up to 55m³.



The Supra range benefits from the Easy COLD microprocessor.

## Example of Configurations Supra MT



## SUPERIOR AIR MANAGEMENT

The new electric fans increase airflow by 24% and work independent of engine speed. Constant airflow helps maintain accurate temperature control through proper air management.

## HIGH CAPACITY

Extended with two high capacity models, the SUPRA range is available up to 12000 Watts. High airflow provide quick temperature recovery and makes it suitable for large sized reefer boxes.

## ACCURATE TEMPERATURE CONTROL

The SUPRA range achieves superior pulldown and precise temperature control at all set points. Available as a multi-temperature system, the SUPRA unit offers enhanced load protection for all truck applications.

## EFFICIENT AND POWERFUL

With the introduction of 7 mm condenser tubes, the SUPRA unit's innovative design increases capacity with reduced refrigerant charge.

## ROBUST DESIGN

Building on hundreds of thousands of operating hours, the SUPRA unit demonstrates a robust design both for aesthetics (strong composite material) and components (easy start) to extend the unit lifetime and reduce downtime. Maintenance time is also optimised thanks to easy accessibility.

### ■ Mono temperature configurations

	■ Refrigeration capacity (Watts)*				■ Airflow (m³/h)	■ Weight
	Road		Standby			incl. Evaporator (kg)
	0°C	-20°C	0°C	-20°C		S
SUPRA 550	5455	3165	4670	2770	2150	391
SUPRA 750	6780	3750	5920	3120	2140	429
SUPRA 850	7800	4900	6450	4240	2500	461
SUPRA 1050	9100	5600	7800	5000	3350	617
SUPRA 1150	10500	6350	8900	5400	3350	626
SUPRA 1250	12050	6990	9100	6300	3350	636

### Multi temperature configurations

	Refrigeration capacity (Watts)*				Airflow (m³/h)	Weight condenser Section only (kg)
	Road		Standby			
	0°C	-20°C	0°C	-20°C		
SUPRA 750 MT	6140	3810	5560	3840	Up to 2500**	411*
SUPRA 850 MT	6300	4490	5000	3750	Up to 2500**	443*
SUPRA 1150 MT	11150	6450	9150	5600	Up to 3600**	576*

\* Ambient temperature at + 30°C (per A.T.P. procedure) \*\*According to evaporator type

## Carrier Airconditioning and Refrigeration Limited.

Bangalore : 080 - 43442000  
Kolkata : 033 - 40593000  
Mumbai : 022 - 61700700  
Gurgaon : 0124 - 4707311

E-mail : [transportservice@carrier.com](mailto:transportservice@carrier.com)  
[www.carriertranscoldindia.com](http://www.carriertranscoldindia.com)



For further information, please scan this code