

# Areor® ST



### Benefits at a glance



- Actively chilled bottom deck
- Extended product presentation on 3 levels
- Block grouping possibilities



## Areor® ST

#### Plug-in Counter-Island in modern design


#### Standard configuration

- Stepped superstructure with two acrylic sidewalls and adjustable glass shelves
- Temperature-assured forced-air cooling with air outlet
- Plinth of galvanized steel with powdercoated finish, sidewalls and front air deflectors of PVC, outside and inside color black (RAL 9005)
- Energy saving condenser fan
- Electronic controller
- Factory installed castors
- Digital thermometer (solar)
- Air cooled bottom shelf (ST 1240)
- Natural refrigerant R290



Areor ST 1230/1240

#### Basic models





		Natural	
	Units	1230	1240
Temperature	[°C]	+2+4	0+2
Refrigerant		R290	
Width (with / without bumper)	[mm]	1290 / 1410	
Depth (with / without bumper)	[mm]	1080 / 1150	
Height	[mm]	1280	
Volume	[1]	269	132.50
Shelf area (bottom / middle / upper shelf)	[m <sup>2</sup> ]	1.03 / 0.49 / 0.31	1.03 / 0.49 / 0.31
Power cons. ref.	[W]	770	770
Power cons. def.	[W]	29	29
Energy consumption*	[kWh/d]	12.3	10.5
Heat dispatch*	[W]	57	57
Application			

<sup>\*</sup> at Climate Class 3 according to ISO 23953



Carrier Commercial Refrigeration is a leading supplier of high-efficiency turnkey refrigeration systems and services in the food retail industry.

