1		
	CTD PART NO	STATUS
	98-60608-00	VOID
	98-60608-01	VOID
	98-60608-02	ACTIVE

A | INITIAL RELEASE VERSION -01


UPDATED SHEET INDEX. SEE SHEET 2.

PRELIMINARY RELEASE OF -01. VOIDED -00. UPDATED NOTE & CHARTS.

REVISION RECORD

NEOS 100S/HE 100S/HE 200S

UNIT MODEL	E V A P O R A T O R MODE L	REFRIGERANT CHARGE	CPR SETTING	GAS
NEOS 100S	MNS 600	1.0 kg±0.1 [2.2 lb]	0.7 bar±0.1 [10.3 psi]	R - 134A
NEOS HE 100S	MNS 600	1.0 kg±0.1 [2.2 lb]	FROZEN 0.9 bar±0.1 [13.1 psi] FRESH 1.6 bar±0.1 [23.2 psi]	R - 134A
NEOS HE 200S	MNS 850	1.5 kg±0.1 [3.3 lb]	2.9 bar±0.1 [42.0 psi]	R - 452A



18-JAN-21

18 FEB 2020

C.S.

LT-AB

ENGR.

М.Е.

71E0080P19

71E0080P1

NPCA NO.

THIRD ANGLE

PROJECTION





READ ALL NOTES PRIOR TO INSTALLATION

NOTES:

- 1 TRUCK BODY
 - 1.1- THE TRUCK STRUCTURE MUST BE EVALUATED BY THE TRUCK MANUFACTURER TO DETERMINE ITS ABILITY TO WITHSTAND THE LOADS IMPOSED BY THE UNIT OVER ITS SERVICE LIFE. CARRIER TRANSICOLD DOES NOT CONVEY ANY ENDORSEMENT OR WARRANTY FOR THE TRUCK'S STRUCTURAL INTEGRITY.
 - 1.2 -UNIT MOUNTING SURFACES OF THE TRUCK THAT CONTACT THE UNIT MOUNTING PADS MUST BE UNI-PLANAR TO WITHIN 3 mm [0.12] TO PREVENT DISTORTION OF THE UNIT AND/OR TRUCK.
- 2 INSTALLATION
 - 2.1- THIS REFRIGERATION UNIT HAS BEEN DESIGNED WITH THE SAFETY OF THE MECANICIAN IN MIND. DURING NORMAL OPERATION, ALL MOVING PARTS ARE FULLY ENCLOSED TO PREVENTINJURY. DURING ALL PRE-TRIP INSPECTIONS, DAILY INSPECTIONS AND PROBLEM TROUBLESHOOTING, YOU MAY BE EXPOSED TO MOVING PARTS.WE ADVISE YOU TO TAKE ALL REQUIRED PRECAUTIONS GENERAL AND TO WEAR ADEQUATE PROTECTIVE EQUIPMENT (SAFETY GLASSES, GLOVES, SAFETY SHOES) DURING INSTALLATION AND ALL REPAIRS AND MAINTENANCE SERVICES ON THE UNIT.
 - 2.2- TAKE EVERY SAFETY MEASURE WHEN ACCESING THE UNIT, USE STANDARDS LADDERS, WORKING PLATEFORM WITH RAILING, SAVETY BELT.
 - 2.3- UNITS ARE DELIVERED UNDER PRESSURE WITH NITROGEN. PLEASE BE SURE THAT THE CIRCUIT IS STILL UNDER PRESSURE (IT MEANS THAT THERE IS NO LEAK).
 - 2.4- INSTALLATION AND COMMISSIONING PROCEDURE WILL DESCRIBED ON ELECTRONIC TECHNICAL MANUAL "MODULE INSTALLATION" AVAILABLE FROM WEBSITES.

3- SERVICE

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS SHOWN ARE IN MILLIMETERS, WITH IMPERIAL CONVERSIONS IN [INCHES]

- 3.1- IT IS IMPORTANT FOR THE SAFETY AND UPKEEP OF THE REFRIGERATION UNIT THAT SERVICING IS PERIODICALLY PERFORMED ACCORDING TO THE FREQUENCY INDICATED BY THE MANUFACTURED (SEE SERVICE MANUAL), SERVICE OPERATIONS AND REPAIRSMUST BE CARRIED OUT BY APPROVED CARRIER SERVICE STATION.
- 3.2-[ETO ONLY]
 GOLDEN COLD SERVICE CONTRACTS: THE PROOF OF OUR COMMITMENT TO YOUR PROFITABILITY
 WITH A CHOISE OF CONTRACTS: FULL SERVICE / ROUTINE MAINTENANCE / EXTENDED WARRANTY.
- 4- UNIT MODIFICATION

NO MODIFICATION ON THE UNIT CAN BE REALIZED WITHOUT THE PRIOR WRITTEN CONSENT FROM CARRIER TRANSICOLD INDUSTRIES (ELECTRICAL, MECHANICAL . . . NON EXHAUSTIVE LIST.

SHEET	REV	D	D	В
INDEX	SHEET	1	2	3

INSTRUCTION D'INSTALLATION NEOS S [INSTALLATION INSTRUCTIONS NEOS S]

DRAWING NO. 98-60608

SHEET 1 OF 3

SUPERSEDES: PART CLASSIFICATION: US

CLASSIFICATION:

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS SHOWN ARE IN MILLIMETERS, WITH IMPERIAL CONVERSIONS IN [INCHES]

THIRD ANGLE PROJECTION

NPCA NO.


ENGR.

М.Е.

ВҮ

Carrier Transicold Division Carrier Corporation P.O. Box 4805 Syracuse, New York 13221


THIS DOCUMENT AND THE INFORMATION CONTAINED THEREIN IS PROPRIETARY TO CARRIER CORPORATION AND SHALL NOT BE USED OR DISCLOSED TO OTHERS, IN WHOLE OR IN PART, WITHOUT THE WRITTEN AUTHORIZATION OF CARRIER CORPORATION. SUBMISSION OF THESE DRAWINGS OR DOCUMENTS DOES NOT CONSTITUTE PART PERFORMANCE OR ACCEPTANCE OF CONTRACT



DATE

INITIAL RELEASE.


REVISION RECORD



VUE SUIVANT A FIXATION DU CONDENSEUR PAR LE DESSOUS

AVANT DE PERCER S'ASSURER QUE LES TROUS SERONT REALISES DANS LE BON SENS POUR CELA UTILISER LES FLECHES D'ORIENTATION DE VUES A ET B ET LES VUE S ASSOCIEES POUR SE REPERER [BEFORE DRILLING MAKE SURE HOLES WILL BE REALIZED IN THE GOOD SIDE, FOR THIS USED ARROWS A AND B AND VIEWS ASSOCIATED FOR ORIENTATION]

VUE SUIVANT B FIXATION DU CONDENSEUR PAR L'ARRIERE [VIEW FOLLOWING B CONDENSER FIXATION BY THE REARSIDE]



KIT	WEIGHT Kg [1b]				
1/ 1 1	NEOS 100S	NEOS HE 100S	NEOS 200S		
CONDENSER UNIT	48 [106]	48 [106]	48 [106]		
EVAPORATOR	15 [33]	17 [37]	19 [42]		

DRAWING NO.


98-60608

SHEET 2 OF

SUPERSEDES: PART CLASSIFICATION: US

INSTRUCTION D'INSTALLATION NEOS S

[INSTALLATION INSTRUCTIONS NEOS S]



HOT GAS LINE

В	ADDED THIS SHT. & VIEWS.	30 - JUN - 2021	LT-RR			1136092
SYM	REVISION RECORD	DATE	ВҮ	ENGR.	М.Е.	NPCA NO

EVAPORATOR MNS 600

583 [23.0]

405.0 [15.94]

548

[21.6]

607.0 — [23.90]

165 [6.5]

THIRD ANGLE PROJECTION	→	UN DIMEN WITH

UNLESS OTHERWISE SPECIFIED ALL MENSIONS SHOWN ARE IN MILLIMETERS, H IMPERIAL CONVERSIONS IN [INCHES]	TITLE [

.E	
	INSTRUCTION D'INSTALLATION NEOS S
	[INSTALLATION INSTRUCTIONS NEOS S]

PART	CLASSIFICATION:	US

SUPERSEDES:

98-60608