





Built upon the proven X2™ platform, the X4TM unit sets the bar even higher as the new industry standard for refrigeration performance and control.



SMARTER PERFORMANCE

Featuring microchannel heat exchanger coils, Carrier's X4™ platform boosts the performance-to-power ratio. By introducing enhanced power-management algorithms to communicate with a smarter engine, capacity is increased by 3% up to 6%* to 20 200 Watts.

Fleets can expect higher performance, lower maintenance costs, and lighter weight, all engineered into a straightforward, practical design.

Operating 18% slower in high-speed* and with 18% lower-required engine power*, the X4™ system smartly delivers fast pull down (up to 20% faster*) and peace of mind for the most demanding applications.

SMARTER CONTROL

X4[™] - model 7300 establishes the benchmark for intelligent refrigeration control. Integrated via the powerful APX™ Control System, components communicate, working in harmony instead of isolation.

The modular APX system combines remarkable control intelligence, temperature control and system reliability with amazingly simple operation.

DESIGNED FOR EXTREME OPERATIONS

Durable, rugged construction includes a proven engine, compressor and components that hold up to the rigors of distribution and long-haul operations while presenting a modern aerodynamic design that features damage and dirtresistant doors. Lower noise levels and better sound quality are acoustically engineered into the design

STANDARD EQUIPMENT:

- Road only operation
- APX Microprocessor
- Automatic Start/Stop
- 05G-41CFM Compressor
- CT4-134 DI Engine

ACCESSORIES & OPTIONS

- Fuel tank 200 L
- Led light bar
- Dual-view temperature display
- Door switch
- Control panel & cable extension
- DataCOLD range
- Electronic fuel sensor

TECHNICAL DETAILS FOR X4TM - 7300 MODEL

CONDENSER DIMENSIONS (mm)		1.940 x 2.176 x 579
APPROXIMATE WEIGHT (kg)		730
DIESEL HIGH SPEED CAPACITY (Watts)	0°C/+30°C	20 200
	-20°C/+30°C	10 600
AIRFLOW (m³/h)		5 200
HEATING CAPACITY (Watts)		9 900
R404A REFRIGERANT (kg)		6.8

EVERYTHING YOU NEED, WHERE YOU CAN SEE IT.



Setpoint change keys

Message center and menu options

ATM-Style menu buttons

9 On/Off switch

Backlit graphical display

*Performance data compared to the Carrier Transicold models they replace and dependent on a range of operational settings, environmental conditions, and model type.

USB Port with protective cap





Carrier Transicold Europe S.C.S. L'Européen Bâtiment D 4 rue Joseph Monier F-92500 Rueil-Malmaison Phone: +33 (0)1 41 42 28 00

Fax: +33 (0)1 41 42 28 28 www.carriertransicold.eu