


07-JAN-2002 : 16:28:01 : ctct04e


OPTION KITS			PART NO.
CENTER WALL DIVIDE BULKHEAD			76-00527-00
DOOR SWITCH SHUTDOWN			76-00703-01
REMOTE CONTROL/INDICATOR PANEL	SURFACE	2 COMP.	76-60796-01
	FLUSH	2 COMP.	76-60796-02


CONTENTS		SHEET
GENERAL INFORMATION		1,2
TRAILER PREPARATION/REFRIGERANT LINE ROUTING		2,3,4
ELECTRICAL DIAGRAM	MTD EVAP’S w/DEUTSCH CONNECTOR	5
	MTS EVAP’S w/DEUTSCH CONNECTOR	6
EVAPORATOR INFORMATION		7,8
SYSTEM’S A & B CONFIGURATION & PIPING SCHEMATIC		9

SHEET	REV	B	A	B	B	B	B	A	A	A
INDEX	SHEET	1	2	3	4	5	6	7	8	9

B	ADDED SAFETY NOTES A & B; UPDATED SHT’s 3, 4, 5 & 6	28 AUG 18	MGC			71N0251P18
A	INITIAL RELEASE PER PCA71N232GP09	8 SEPT 09	MGC			71N232GP09
SYM	REVISION RECORD	DATE	BY	ENGR.	M.E.	NPCA NO.



		Carrier Transicold Division Carrier Corporation P.O. Box 4805 Syracuse, New York 13221	THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER CORPORATION’S WRITTEN CONSENT.	SUBMISSION OF THESE DRAWINGS OR DOCUMENTS DOES NOT CONSTITUTE PART PERFORMANCE OR ACCEPTANCE OF CONTRACT
CTD PART NO.	U.S. ECCN	SYSTEM	MODEL DESCRIPTION	
98-03300-01	EAR99	A	2 COMPARTMENT W/ 2 MTS 1100 EVAPORATORS	
		B	2 COMPARTMENT W/ 1 MTS 1100 & 1 MTD 1100 EVAP’S.	



WARNING

READ ALL INSTRUCTIONS PRIOR TO INSTALLATION

IMPORTANT: INSTALLATION OF THIS REFRIGERATION SYSTEM MUST BE PERFORMED BY A QUALIFIED TECHNICIAN.

SAFETY:

A) PERSONAL PROTECTIVE EQUIPMENT (PPE):
DURING THE INSTALLATION OF THIS PRODUCT, ALWAYS WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT AND USE CORRECT TOOLS THAT ARE IN GOOD WORKING CONDITION.

B) RISKS:
BE AWARE OF YOUR ENVIRONMENT AND SURROUNDINGS. FOLLOW ALL LOCK OUT / TAG OUT PROCEDURES ON ALL EQUIPMENT INVOLVED IN THE INSTALLATION INCLUDING THE UNIT ITSELF. MAKE CERTAIN ALL TOOLS AND EQUIPMENT ARE APPROPRIATE FOR THE JOB BEING COMPLETED, AND ARE IN GOOD WORKING CONDITION.

MULTI-TEMP REMOTE EVAP. INSTALLATION PROCEDURE

1. SELECT LOCATION FOR REMOTE EVAPORATOR WHICH OPTIMIZES AIR CIRCULATION.

CAUTION: TRUCK BODY MFR TO DETERMINE IF ADJUSTMENT IN CORNER MOULDING IS NECESSARY TO AVOID INTERFERENCE WITH EVAPORATOR MOUNTING.

2. THE TRUCK BODY MANUFACTURER TO PROVIDE SMOOTH FLAT SURFACE IN SAME PLANE TO ACCEPT MOUNTING OF EVAPORATOR. INSTALL REMOTE EVAPORATOR. SEE BODY PREPARATION, SHEET 2.

3. CEILING MOUNTING STUDS SHOULD BE LOCATED BY THE BODY BUILDER PER EVAPORATOR DRAWING LOCATIONS. EVAPORATORS ARE DELIVERED WITH 16mm(5/8 in) CLEARANCE HOLES TO ACCOMODATE MOUNTING STUD SIZE: 1/2-13UNC. ON AN 1100 EVAPORATOR, SHIMS(1T.90) ARE TO BE INSTALLED BETWEEN THE CEILING AND EVAPORATOR TO PROVIDE A SUFFICIENT DRAINAGE SLOPE. TWO(2) SHIMS ARE TO BE INSTALLED ON EACH MOUNTING STUD CLOSEST TO THE EVAPORATOR DRAIN AND ONE(1) SHIM INSTALLED ON THE CENTER MOUNTING STUDS. AN ADDITIONAL TWO(2) SHIMS ARE PROVIDED FOR SPECIAL MOUNTING APPLICATIONS(i.e.: MOUNTING AN EVAPORATOR GUARD). NO SHIMS ARE REQUIRED ON THE STUDS LOCATED FARTHEST FROM THE DRAIN SIDE OF THE EVAPORATOR.

3.1 FOR 1100 EVAPORATORS ONLY, THE TWO CENTER MOUNTING STUDS ARE NOT REQUIRED WHEN 1/2-13 UNC STUDS ARE USED ON THE FOUR CORNER MOUNTING LOCATIONS.

4. AFTER MAIN UNIT IS MOUNTED, ROUTE REFRIGERANT LINES FROM MAIN UNIT TO REMOTE EVAPORATOR. APPLY A LIGHT COAT OF CLEAR REFRIGERANT OIL TO O-RINGS AT MAIN UNIT AND REMOTE EVAPORATOR(S) BEFORE ASSEMBLY.

5. TROUGH LOCATIONS:
5.1 WHEN USING A WALL TROUGH FOR TUBING AND ELECTRICAL WIRING, THE TROUGH SHOULD BEGIN AT A POINT 1-1/2 INCHES DOWN FROM THE CEILING. THIS WILL ALLOW THE TUBING FROM EVAPORATOR TO DIRECTLY ENTER THE TROUGH BEFORE MAKING THE FIRST BEND TOWARDS THE HOST UNIT.
5.2 IF A WALL TROUGH IS USED, THE TROUGH SHOULD CONTINUE TO A POINT 6 INCHES PAST THE SIDE TUBING CONNECTIONS OF A DUAL DISCHARGE EVAPORATOR.
5.3 IF A CEILING TROUGH IS USED, THE TROUGH SHOULD CONTINUE TO WITHIN 6 INCHES FROM THE REAR OF A SINGLE DISCHARGE EVAPORATOR.

- CONTINUED ON SHEET 2 -

SEE SEPARATE PARTS LIST

TITLE		INSTALLATION INSTRUCTIONS MTD/MTS REMOTE EVAPORATORS			DRAWING NO. 98-03300 SHT. 1 OF 9	REV B
-------	--	---	--	--	--	----------



Carrier Transicold Division
Carrier Corporation
P.O. Box 4805
Syracuse, New York 13221

THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION
AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE
CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER
CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS
DOES NOT CONSTITUTE PART PERFORMANCE OR
ACCEPTANCE OF CONTRACT

6. REFRIGERANT LINE SIZES:

- 6.1 THE HOST UNIT HAS A 1-1/8 INCH SUCTION LINE CONNECTION. THE REMOTE EVAPORATORS HAVE A 7/8 INCH SUCTION LINE CONNECTION.
- 6.2 WHEN CONNECTING THE REMOTE EVAPORATORS, STEP UP THE SUCTION LINE SIZE NEAR THE EVAPORATOR AND RUN THE ENTIRE LENGTH WITH 1-1/8 INCH PIPE.
- 6.4 THE SUCTION & HOT GAS LINES MUST BE INSULATED. IT IS NOT NECESSARY TO INSULATE THE LIQUID LINE.

7. REFRIGERANTS:

- 7.1 IF R-404A REFRIGERANT IS TO BE USED, IT IS MANDATORY THAT NITROGEN FLUSHING BRAZE TECHNIQUES ARE USED ON EVERY SOLDER TUBING JOINT. IT IS RECOMMENDED THAT THIS SAME PROCEDURE BE USED ON R-22 REFRIGERANT UNIT BUT IS NOT MANDATORY. THIS TECHNIQUE ELIMINATES OXIDATION WHICH WILL REDUCE SYSTEM RELIABILITY.
- 7.2 LEAK TEST AND THEN EVACUATE THE SYSTEM THROUGH RECEIVER PORT AND SUCTION PORT. SEE SERVICE MANUAL FOR PROPER PROCEDURE.

CAUTION: DISCONNECT ALL BATTERIES BEFORE WORKING ON ELECTRICAL SYSTEM.

8. ELECTRICAL CONNECTIONS:

- 8.1 THE WIRING HARNESS FOR THE REMOTE EVAPORATOR SHOULD BE RUN ALONG WITH THE SUCTION, HOT GAS AND LIQUID LINE TO THE HOST UNIT.
- 8.2 AFTER ROUTING THE WIRING HARNESS(S) AND INSTALLING THE REMOTE EVAPORATOR(S), DETERMINE REQUIRED HARNESS LENGTH(S) AND CUT HARNESS AT THE REMOTE EVAPORATOR END.

CAUTION: USE EXTREME CAUTION TO AVOID CUTTING THE INSULATION ON WIRES WHEN CUTTING WIRE HARNESS SLEEVE.

- 8.3 USE THE PRE-INSULATED TERMINALS SUPPLIED (IT.2) AND PROPER CRIMPING TOOL (AMP #59824-1) TO MAKE ELECTRICAL CONNECTIONS.
- 8.4 COMPLETE ALL ELECTRICAL CONNECTIONS ON THE MAIN UNIT AND ON THE REMOTE EVAPORATOR PER WIRING INSTRUCTIONS ON SHEET'S 5 & 6.
- 8.5 IF A REAR MOUNTED REMOTE CONTROL/INDICATOR PANEL IS USED, THE CONTROL CABLE MAY BE RUN WITH THE SUCTION, HOT GAS, LIQUID LINE AND THE EVAPORATOR WIRE HARNESS TO THE HOST UNIT OR UNDERNEATH THE TRUCK BODY TO THE HOST UNIT.

9. DRAIN TUBE CONNECTIONS:

- 9.1 DEFROST DRAIN TUBES PROVIDED BY THE TRUCK MANUFACTURER SHOULD BE CENTERED ON THE EVAPORATOR AND PLACED 10 TO 11 INCHES FROM THE CEILING. A 7/8 INCH I.D./ 15/16 INCH O.D. DRAIN TUBE IS SUPPLIED FOR CONNECTION OF THE REMOTE EVAPORATOR DRAIN OUTLET WHICH IS TO BE INSTALLED INTO THE TRAILER OEM SUPPLIED WALL DRAIN. THE DRAIN TUBE SUPPLIED BY CARRIER IS DESIGNED TO GO INSIDE THE WALL DRAIN PIPE SUPPLIED BY THE BODYBUILDER OEM. THE WALL DRAIN MUST BE CPVC SCHEDULE 40 RATED AT 200°F[93°C] OR EQUIVALENT.
- 9.2 THE 1100 EVAPORATOR USES ONLY ONE OF THE TWO DEFROST DRAINS. THE UNUSED DRAIN IS PLUGGED WITH PLUG PROVIDED WITH THE EVAPORATOR.
- 9.3 THE 2200 WIDTH EVAPORATOR USES BOTH DEFROST DRAINS UNLESS IN 96" WIDE APPLICATIONS.


10. CONSULT APPLICATION ENGINEERING FOR PROPER INSTALLATION OF FEATURES NOT SUPPLIED BY CARRIER.

INSTALLATION TIPS

- (A) USE FLAT FLOORING IN THE FLOOR SECTION UNDER THE BULKHEAD.
- (B) PROVIDE A THERMAL BREAK IN THE FLOOR UNDER THE BULKHEAD. FOR MOVABLE LOCATION BULKHEADS, USE RUBBERIZED HARDWOOD FLOORS.
- (C) COVER REFRIGERANT LINES TO AVOID IMPACT DAMAGE.
- (D) INSTALL A GUARD AROUND THE EVAP. TO PREVENT IMPACT DAMAGE.

CONVERSION CHART

DECIMAL INCHES	FRACTIONAL INCHES
1.50	1-1/2
5.83	5-27/32



TRUCK BODY PREPERATION FOR EVAPORATOR

A	INITIAL RELEASE PER PCA71N232GP09	8 SEPT 09	MGC			71N232GP09	THIRD ANGLE PROJECTION	TITLE	INSTALLATION INSTRUCTIONS MTD/MTS REMOTE EVAPORATORS	DRAWING NO. 98-03300 SHT. 2 OF	REV A
SYM	REVISION RECORD	DATE	BY	ENGR.	M.E.	NPCA NO.					

SUPERSEDES _____

PART CLASSIFICATION US SEE CHART



DRAWING CLASSIFICATION: US EAR99




Carrier Transicold Division
Carrier Corporation
P.O. Box 4805
Syracuse, New York 13221

THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION
AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE
CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER
CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS
DOES NOT CONSTITUTE PART PERFORMANCE OR
ACCEPTANCE OF CONTRACT



SYSTEM A - 2 MTS-1100's



NOTE: THE EVAP'S CAN BE
INSTALLED IN EITHER
COMPARTMENT AS LONG
AS THE DIMENSIONAL
REQUIREMENTS ARE MET.

SYSTEM B - 1 MTS-1100 AND 1 MTD-1100

TUBING INSTRUCTIONS


CAUTION: HOST UNIT IS SHIPPED FULLY CHARGED FROM FACTORY.

- 1.0 PUMP DOWN REFRIGERATION SYSTEM AND REMOVE CAPS FROM EVAPORATOR CONNECTIONS.
- 2.0 ROUTE TUBING TO REAR EVAPORATORS TO MINIMIZE EXPOSURE TO DAMAGE.
- 3.0 FOR COPPER TO COPPER BRAZING IT IS RECOMMENDED THAT A BRAZING MATERIAL OF 15% SILVER, 5% PHOSPHOROUS BE USED (FLUX IS NOT REQUIRED FOR COPPER TO COPPER JOINTS). "SOFT SOLDER" BRAZING MATERIAL IS NOT RECOMMENDED.
- 4.0 CLOSED CELL FOAM INSULATION IS RECOMMENDED TO COVER THE ENTIRE SUCTION & HOT GAS LINE LENGTH.

IMPORTANT: USE ONLY NEW O-RINGS SUPPLIED IN KIT WHEN
INSTALLING UNIT. DISCARD FACTORY INSTALLED O-RINGS TO
INSURE PROPERLY SEALED CONNECTIONS.

CAUTION: MAKE SURE ALL BRAZING IS COMPLETE AND HAS
COOLED COMPLETELY BEFORE INSTALLING O-RINGS; OTHERWISE
O-RING DAMAGE WILL OCCUR.

B	MOVED VIEW F-F TO SHT.4; ADDED SYSTEM B VIEW & DIM'S.	5 SEPT 18	MGC			71N0251P18
A	INITIAL RELEASE PER PCA71N232GP09	8 SEPT 09	MGC			71N232GP09
SYM	REVISION RECORD	DATE	BY	ENGR.	M.E.	NPCA NO.



TITLE

INSTALLATION INSTRUCTIONS
MTD/MTS REMOTE EVAPORATORS


DRAWING NO.
98-03300
SHT. 3 OF 3

REV
B

SUPERSEDES _____

PART CLASSIFICATION US SEE CHART





DRAWING CLASSIFICATION: US EAR99



Carrier Transicold Division
Carrier Corporation
P.O. Box 4805
Syracuse, New York 13221


THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION
AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE
CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER
CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS
DOES NOT CONSTITUTE PART PERFORMANCE OR
ACCEPTANCE OF CONTRACT




DETAIL "H"

CLAMP TUBES & CABLE SECURELY TO
CEILING OR WALL AS REQUIRED TO
PREVENT DAMAGE FROM VIBRATION
SCALE: 0.38



CEILING ROUTING




OPTION A

OPTION B

WALL ROUTING

B	ADDED VIEW F-F; WAS SHOWN ON SHT.3	5 SEPT 18	MGC			71N0251P18
A	INITIAL RELEASE PER PCA71N232GP09	8 SEPT 09	MGC			71N232GP09
SYM	REVISION RECORD	DATE	BY	ENGR.	M.E.	NPCA NO.

THIRD ANGLE
PROJECTION



TITLE

INSTALLATION INSTRUCTIONS
MTD/MTS REMOTE EVAPORATORS

DRAWING NO.
98-03300
SHT. 4 OF

REV
B

SUPERSEDES

PART CLASSIFICATION US SEE CHART

DRAWING CLASSIFICATION: US EAR99

30-JUL-98 : 11:29:07 : ctc03w




Carrier Transicold Division
Carrier Corporation
P.O. Box 4805
Syracuse, New York 13221

THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION
AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE
CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER
CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS
DOES NOT CONSTITUTE PART PERFORMANCE OR
ACCEPTANCE OF CONTRACT

ELECTRICAL CONNECTIONS(SEE SHT 1)

1.0 CONNECT THE WIRE COLORS IN ACCORDANCE TO
THE FOLLOWING CHARTS.



MAIN CONTROL BOX

1CP....COMPARTMENT 1
2CP....COMPARTMENT 2

FIELD INSTALLED CONNECTOR

CONNECTOR PIN NO.	WIRE COLOR	TERMINAL
1	YELLOW1	0460-202-16141
2	YELLOW2	0460-202-16141
3	BLACK1	0460-202-16141
4	BLACK2	0460-202-16141
5	ORANGE1	0460-202-16141
6	ORANGE2	0460-202-16141
7	GRAY	0460-202-16141
* 8	RED1	0460-204-12141
9	WHITE	0460-215-16141
* 10	RED2	0460-204-12141
11	PURPLE	0460-202-16141
* 12	RED3	0460-204-12141
13	DK BLUE	0460-202-16141
* 14	SEAL PLUG	SEAL PLUG
15	GREEN	0460-202-16141
* 16	SEAL PLUG	SEAL PLUG
17	BLUE	0460-202-16141
* 18	SEAL PLUG	SEAL PLUG
19	BROWN	0460-202-16141


CONNECTOR INSIDE EVAP (REF)

CONNECTOR PIN NO.	WIRE LABEL
1	C1-1/DTSB
2	C1-2/D TSA
3	C1-3/RASB
4	C1-4/RASA
5	SP1/C1-5
6	SP3/C1-6
7	C1-7/C1-13
* 8	SP5/C1-8
9	C1-9/SP9
* 10	SP12/C1-10
11	SP11/C1-11
* 12	SP6/C1-12
13	C1-13/C1-7
* 14	SEAL PLUG
15	C1-15/GRD
* 16	SEAL PLUG
17	SP4/C1-17
* 18	SEAL PLUG
19	C1-19/SP100

* INDICATES A LARGE CAVITY.

HEATERS


△ DELTA CONFIGURATION (REF)



- ⊗ INDICATES A COMPONENT
SPLICE POINT (EXTERNAL
OF HARNESS)
- ⊙ INDICATES A SPLICE
POINT (INTERNAL TO
TO THE HARNESS)
- LSVA MULTIPLE PLUG
CONNECTION NUMBER

SERVICE PARTS LIST

CTD P/N	TERMINAL	DESCRIPTION
22-50078-77C	0460-204-12141	LARGE
22-50078-78A	0460-215-16141	SMALL W/GRN STRIPE
22-01613-14	0460-202-16141	SMALL
22-01660-08	114017	SEAL PLUG



THIRD ANGLE
PROJECTION

TITLE

INSTALLATION INSTRUCTIONS
MTD REMOTE EVAPORATORS

DRAWING NO.
98-03300
SHT. 5 OF

REV
B

DRAWING CLASSIFICATION: US EAR99

SUPERSEDES

PART CLASSIFICATION US SEE CHART




Carrier Transicold Division
Carrier Corporation
P.O. Box 4805
Syracuse, New York 13221

THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION
AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE
CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER
CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS
DOES NOT CONSTITUTE PART PERFORMANCE OR
ACCEPTANCE OF CONTRACT

ELECTRICAL CONNECTIONS(SEE SHT 1)


1.0 CONNECT THE WIRE COLORS IN ACCORDANCE TO
THE FOLLOWING CHARTS.



FIELD INSTALLED CONNECTOR		
CONNECTOR PIN NO.	WIRE COLOR	TERMINAL
1	YELLOW1	0460-202-16141
2	YELLOW2	0460-202-16141
3	BLACK1	0460-202-16141
4	BLACK2	0460-202-16141
5	ORANGE1	0460-202-16141
6	ORANGE2	0460-202-16141
7	GRAY	0460-202-16141
* 8	RED1	0460-204-12141
9	WHITE	0460-215-16141
* 10	RED2	0460-204-12141
11	PURPLE	0460-202-16141
* 12	RED3	0460-204-12141
13	DK BLUE	0460-202-16141
* 14	SEAL PLUG	SEAL PLUG
15	GREEN	0460-202-16141
* 16	SEAL PLUG	SEAL PLUG
17	BLUE	0460-202-16141
* 18	SEAL PLUG	SEAL PLUG
19	BROWN	0460-202-16141

CONNECTOR INSIDE EVAP (REF)	
CONNECTOR PIN NO.	WIRE LABEL
1	C1-1/DTSB
2	C1-2/DTSA
3	C1-3/RASB
4	C1-4/RASA
5	SP1/C1-5
6	SP3/C1-6
7	C1-7/C1-13
* 8	SP5/C1-8
9	C1-9/SP9
* 10	SP12/C1-10
11	SP11/C1-11
* 12	SP6/C1-12
13	C1-13/C1-7
* 14	SEAL PLUG
15	C1-15/GRD
* 16	SEAL PLUG
17	SP4/C1-17
* 18	SEAL PLUG
19	C1-19/SP100


* INDICATES A LARGE CAVITY.



SERVICE PARTS LIST		
CTD P/N	TERMINAL	DESCRIPTION
22-50078-77C	0460-204-12141	LARGE
22-50078-78A	0460-215-16141	SMALL W/GRN STRIPE
22-01613-14	0460-202-16141	SMALL
22-01660-08	114017	SEAL PLUG

HEATERS

△ DELTA CONFIGURATION (REF)




- ⊗ INDICATES A COMPONENT
SPLICE POINT (EXTERNAL
OF HARNESS)
- ⊙ INDICATES A SPLICE
POINT (INTERNAL TO
TO THE HARNESS)
- LSVA MULTIPLE PLUG
CONNECTION NUMBER

MAIN CONTROL BOX

1CP....COMPARTMENT 1
2CP....COMPARTMENT 2

B	UPDATED SCHEMATIC ACCORDING TO LATEST HARNESS CHANGES	28 AUG 18	MGC			71N0251P18
A	INITIAL RELEASE PER PCA71N232GP09	8 SEPT 09	MGC			71N232GP09
SYM	REVISION RECORD	DATE	BY	ENGR.	M.E.	NPCA NO.



TITLE

INSTALLATION INSTRUCTIONS
MTS REMOTE EVAPORATORS

DRAWING NO.
98-03300
SHT. 6 OF 6

REV
B

SUPSEDES

PART CLASSIFICATION US SEE CHART



Carrier Transicold Division
Carrier Corporation
P.O. Box 4805
Syracuse, New York 13221





THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION
AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE
CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER
CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS
DOES NOT CONSTITUTE PART PERFORMANCE OR
ACCEPTANCE OF CONTRACT

CONVERSION CHART


DECIMAL INCHES	FRACTIONAL INCHES
0.83	27/32
1.77	1-25/32
2.44	2-7/16
2.83	2-27/32
2.87	2-7/8
3.21	3-7/32
3.54	3-17/32
3.58	3-19/32
4.17	4-3/16
4.76	4-3/4
7.76	7-3/4
10.85	10-27/32
11.02	11-1/32
16.30	16-5/16
17.72	17-23/32
23.62	23-5/8
41.10	41-3/32

EVAPORATOR WEIGHT
MTS-1100 106lbs[48.1 Kg]



MTS-1100-2

A	INITIAL RELEASE PER PCA71N232GP09	8 SEPT 09	MGC			71N232GP09
SYM	REVISION RECORD	DATE	BY	ENGR.	M.E.	NPCA NO.



TITLE

INSTALLATION INSTRUCTIONS
MTD/MTS REMOTE EVAPORATORS

DRAWING NO.
98-03300
SHT. 7 OF

REV
A

SUPERSEDES

PART CLASSIFICATION US SEE CHART

DRAWING CLASSIFICATION: US EAR99

15-JUL-1999 : 07:20:53 : ctct03w



Carrier Transicold Division
Carrier Corporation
P.O. Box 4805
Syracuse, New York 13221




THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION
AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE
CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER
CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS
DOES NOT CONSTITUTE PART PERFORMANCE OR
ACCEPTANCE OF CONTRACT

CONVERSION CHART

DECIMAL INCHES	FRACTIONAL INCHES
1.61	1-5/8
1.75	1-3/4
1.77	1-25/32
2.17	2-3/16
2.68	2-25/32
2.69	2-25/32
2.83	2-27/32
3.09	3-3/32
3.13	3-1/8
3.46	3-15/32
4.26	4-1/4
5.43	5-7/16
5.45	5-7/16
5.83	5-13/16
7.03	7-1/32
10.85	10-27/32
15.72	15-23/32
17.72	17-23/32
31.42	31-13/32
34.65	34-21/32
41.10	41-3/32

EVAPORATOR WEIGHT
MTD-1100 117lbs [53.1 Kg]



MTD-1100-2

A	INITIAL RELEASE PER PCA71N232GP09	8 SEPT 09	MGC			71N232GP09	THIRD ANGLE PROJECTION	TITLE	INSTALLATION INSTRUCTIONS MTD/MTS REMOTE EVAPORATORS	DRAWING NO. 98-03300 SHT. 8 OF	REV A
SYM	REVISION RECORD	DATE	BY	ENGR.	M.E.	NPCA NO.					

SUPERSEDES _____

PART CLASSIFICATION US SEE CHART


DRAWING CLASSIFICATION: US EAR99



Carrier Transicold Division
Carrier Corporation
P.O. Box 4805
Syracuse, New York 13221

THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION
AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE
CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER
CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS
DOES NOT CONSTITUTE PART PERFORMANCE OR
ACCEPTANCE OF CONTRACT




PIPING SCHEMATIC

SCHEMATIC FOR INFORMATION ONLY


EXACT PIPING TO BE DETERMINED BY REMOTE
EVAPORATOR STYLE, APPLICATION AND LOCATION.

2 COMPARTMENT SYSTEMS WITH TWO 1100 SIZE REMOTE EVAPORATORS



SYSTEM A

2 MTS 1100-2 SINGLE DISCHARGE EVAP'S




SYSTEM B

1 MTS 1100-2 SINGLE DISCHARGE EVAP AND
1 MTD 1100-2 DUAL DISCHARGE EVAP

A	INITIAL RELEASE PER PCA71N232GP09	8 SEPT 09	MGC			71N232GP09
SYM	REVISION RECORD	DATE	BY	ENGR.	M.E.	NPCA NO.

THIRD ANGLE
PROJECTION



TITLE

INSTALLATION INSTRUCTIONS
MTD/MTS REMOTE EVAPORATORS

DRAWING NO.
98-03300
SHT. 9 OF

REV
A

SUPERSEDES

PART CLASSIFICATION US SEE CHART

DRAWING CLASSIFICATION: US EAR99