



# PowerLINE®

## RG15/UG15 Series 24

Lifetime CARB Compliance

**RG15 Clip**  
69RG15-120W-24



**UG15 Undermount**  
69UG15-068S-24



**FuelWise**

Simply innovative

# PowerLINE Series 24

## With the new PowerLINE generator sets, lifetime CARB compliance is surprisingly simple.

Carrier Transicold's newest Series 24 PowerLINE generator sets build on our rugged and robust high-efficiency platform with an innovative new design.

### Includes key features of our well-accepted platform



- Ultra-high-efficiency generator enables full power for ISO reefers
- FuelWise™ two-speed functionality for up to 34% fuel savings relative to prior models without FuelWise

### Introduces a lower emission engine that allows use in California indefinitely\*

- No limitations on California Air Resources Board (CARB) life and no aftertreatment or emissions upgrades required for extension
- Engine's common-rail fuel injection is supported by an enhanced fuel filtration system and diesel oxidation catalyst
- Combined, these clean engine technologies push particulate, hydrocarbon and NOx emissions to new lows, helping customers achieve their sustainability goals
- The engine does not require complex exhaust gas recirculation (EGR) to achieve emissions targets

### Reduced fuel consumption extends range of distances traveled and reduces carbon footprint

**Simply put, PowerLINE generator sets offer efficient, environmentally responsible and compliant innovations, punctuated by a proven design.**



### More Sustainable



A **96% reduction** in particulate emissions makes the PowerLINE Series 24 unit the greenest in the PowerLINE series.

### Enhanced Regulatory Compliance



PowerLINE Series 24 unit is EPA Tier 4 compliant and provides **lifetime compliance** with current CARB requirements without the need for future engine emissions systems.

## Building on our high-efficiency, service-friendly design...



### **~ 94% efficient**

custom-designed permanent magnet generator



### **2-speed controller**

for automatic voltage and FuelWise control, no user interaction required

## ...with innovation at every turn

- 1 NEW: 2-Speed Kubota 2.4 liter Engine** compliant with EPA Tier 4 regulation for engines less than 25 HP (19 KW) and CARB's 2022 amendments to the Airborne Toxic Control Measure for Transport Refrigeration Units.
- 2 NEW: Common-Rail Fuel Injection** that reduces particulate matter emissions and lowers fuel consumption.

- 3 NEW: Maintenance-Free Diesel Oxidation Catalyst** that reduces hydrocarbon and other emissions.
- 4 NEW: Enhanced Fuel Filtration** that supports common-rail fuel injection.

## Fuel Efficiency Advantage Continues

Our PowerLINE Series 24 is built on the ultra-high-efficiency generator and two-speed FuelWise platform in PowerLINE Series 22 units.



PowerLINE Series 24 models continue to deliver **up to 34% fuel savings** vs. previous models without FuelWise.

## Safe and Secure Mounting (RG15 Clip and UG15 Undermount)



### **Header pin (RG)**

For clip mounting, our pin-mounting bracket design saves time.



### **Standard clamp (UG)**

The undermount has a standard four-point mounting that is easy to install.

# Performance Specifications: PowerLINE Series 24

## RG15 Clip 69RG15-120W-24



Specifications are subject to change without notice.

## UG15 Undermount 69UG15-068S-24



Specifications are subject to change without notice.

### Fuel tank lengths:

50 gal (189 L) = 1,413 mm (45.0 in)  
68 gal (257.5 L) = 1,485 mm (58.5 in)  
80 gal (303 L) = 1,632 mm (64.3 in)

### RG and UG Warranty:

Within two years after the date of shipment from the manufacturer's plant or 27 months from the manufactured date, whichever comes first, Carrier Transicold Division, through designated Container Service Centers, will, at Carrier Transicold's option, repair or replace, with a new or remanufactured part, any parts or components of the products identified above which UNDER NORMAL USE AND SERVICE malfunction as a result of defects in material or workmanship. The warranty terms and limitations are listed in Form 62-10185. Consult your Carrier Transicold representative for complete warranty details.

## Ready to put increased performance, efficiency and sustainability to work?

Connect with a Carrier Transicold representative in your region.

### Standard Features:

V2403-CR-E4B, 4-cylinder, water-cooled, 2.4-liter, Common rail injection diesel engine  
Nominal 15 kW high-efficiency permanent magnet generator  
Controller with enhanced FuelWise functionality  
120-gallon fuel tank  
Pin-mount system  
High-efficiency dry element air cleaner  
Full-flow spin-on oil filter with internal bypass  
Integral fuel filter with water separator  
Fuel heater  
Stainless steel exhaust  
Stainless steel hardware  
Low-mounted controls  
Large aluminum service access door  
Enclosed forklift pockets  
12V DC maintenance-free battery  
Safety stop controls for low oil pressure, high water temperature  
Frame and sheet metal components powder-coated for durability  
Patented E-coat tube and fin radiator

Large oil pan capacity extends running hours between oil changes  
Fuel gauge, color-coded for easy level identification from a distance  
Oil pressure and water temperature gauges  
DC ammeter  
Shipping bumpers  
Power output circuit breaker  
Start/Run, Preheat/Off switch  
Coolant overflow bottle  
Engine Hourmeter  
Solid-state battery charger  
Operating instruction labels (English and Spanish)  
Maintenance and schematic labels  
460V receptacle with spring-loaded cap

### Accessories and Options:

Clamp-mount system

### Approximate Weight:

1974 lb/895 kg, less fuel

### Standard Features:

V2403-CR-E4B, 4-cylinder, water-cooled, 2.4-liter, Common rail injection diesel engine  
Nominal 15 kW high-efficiency permanent magnet generator  
Controller with enhanced FuelWise functionality  
All-steel fabricated frame construction with four-point PlateMount system  
High-efficiency dry element air cleaner  
Full-flow spin-on oil filter with internal bypass  
Integral fuel filter with water separator  
Fuel heater  
Stainless steel exhaust  
Stainless steel hardware  
Driver-side controls  
Large aluminum service access door  
Battery access door  
Forklift pockets allow mounting from either side  
12V DC maintenance-free battery  
Safety stop controls for low oil pressure, high water temperature  
Frame and sheet metal components powder-coated for durability  
Patented E-coat tube and fin radiator

Large oil pan capacity extends running hours between oil changes  
Fuel gauge, color-coded for easy level identification from a distance  
DC ammeter  
Power output circuit breaker  
Start/Run, Preheat/Off switch  
Coolant overflow bottle  
Engine hourmeter  
68-gallon integral fuel tank  
Operating instruction labels (English and Spanish)  
Maintenance and schematic labels  
Oil pressure and water temperature gauges  
Solid-state battery charger

### Accessories and Options:

50-gallon steel tank  
50-gallon aluminum tank  
80-gallon aluminum tank

### Approximate Weight:

1664 lb/755 kg with 68 gallon integral steel tank, less fuel

### The Americas

Carrier Transicold  
Container Products Group  
TR-20 Carrier Parkway  
East Syracuse, NY 13057 USA

### Europe/Middle East/Africa

Carrier Transicold Limited  
Waalhaven Oostzijde 85  
3087 BM  
Rotterdam  
The Netherlands  
Tel: +31-10-2380100  
Fax: +31-10-2380142

### Asia/Pacific

Carrier Transicold Pte. Ltd.  
251 Jalan Ahmad Ibrahim  
Singapore 629146  
Tel: +65-6213-6388  
Fax: +65-6862-5309

### Hong Kong

Carrier Transicold  
Container Products Ltd.  
Unit 01, 16/F, Global Gateway (HK)  
168 Yeung Uk Road  
Tsuen Wan, N.T.  
Hong Kong  
Tel: +852-288-00389  
Fax: +852-288-00314

### Japan

Carrier Transicold  
Container Products Ltd.  
6-18-1201, Roppongi 7-chome  
Minato-ku Tokyo 106-0032  
Japan  
Tel: +81-3-5772-3668  
Fax: +81-3-5772-3669

### Carrier Transicold

Container Products Group  
P.O. Box 4805  
Syracuse, NY 13221 USA  
[carrier.com/container](http://carrier.com/container)