

## Contactors

### Overview

All purpose electric door switch. Knockouts on top, bottom and rear.

### Applications

Closet lights, dark rooms, walk-in refrigerators. For sliding or hinged doors.

### Ordering Information

Cat. No.	Description	Contact Ratings		Dimensions		
		Volts	AC Amps	H	W	D
502A	Depress plunger to open circuit	125	6	4 (102)	1-1/2 (38)	1-3/4 (44)
503A	Depress plunger to close circuit	125	6	4 (102)	1-1/2 (38)	1-3/4 (44)

Switch faceplate has mounting holes on 3-1/4" centres.



## Door Light Switch

502A, 503A

### Overview

Non-insulated, external mounting. Makes and breaks as door opens. Zinc plated.

### Applications

Signals entry into stores, offices, etc.

### Ordering Information

Cat. No.	Dimensions		
	L	W	D
236	1-1/4" (32mm)	1-5/16" (33mm)	3-1/4" (82mm)



## Door Trip

236

### Overview

Wide range of low voltage applications. Insulated, construction for long service life. Easily operated from pressure in any direction. Fast installation.

### Applications

Doors, windows, transoms, burglar alarms, machinery.

### Ordering Information

Cat. No.	Description	Contact Ratings			Hole	Depth Overall
		Volts	AC Amps	DC Amps		
44	Push to open contacts					
45	Push to close contacts	12	2	2	13/16 (20)	1-1/8 (28)
		24	2	1		
46E	Push to make then break and repeat on return	48	1	.5		



## Rolling Ball Contactor

44, 45, 46E