

### **Model P4010ACS-WF**



### **Features & Benefits**

- Remote notification and status with Kidde HomeSafe: Use the Kidde app to receive notifications if hazards are detected, know when the device needs to be replaced and test alarms.\* Mobile alerts allow you to notify friends and family of potential danger. Plus, you can Smart Hush™ false alarms when you are home.\*
- One battery for 10 years: Alarms are powered by 120V AC with a sealed long-life lithium backup battery that lasts for 10 years\*\* the entire life of the device.
- Simplify setup: Just scan the QR code on the back of the product in the Kidde app. No additional hub is needed to set up your Kidde smart devices.
- Whole-home alarm activation: Interconnected alarms activate together\*\*\* when one alarm sounds, they all sound, and an alert is sent to your phone.
- Compatible with Google Home and Amazon Alexa: Use voice commands to check alarm status and connection.<sup>†</sup>
- UL Listed: Comprehensively tested and designed to the exacting standards set by UL – a global safety science leader – for the latest in safety and reliability.











- \*This feature is only available on the Kidde HomeSafe alarm, not other interconnected alarms, when you are connected to the same Wi-Fi network as the alarm. Wi-Fi and app notifications do not function without AC Power.
- \*\*10-year limited warranty on alarm. Not a battery performance claim.
- \*\*\*Alarms only connect with other Kidde alarms that have hardwired AC interconnect capability.
- † Amazon, Alexa and all related marks are trademarks of Amazon.com, Inc. or its affiliates. Google and Google Home are trademarks of Google LLC.

#### Remote alarm notifications:

Real-time mobile alerts through the Kidde app.

#### One battery for 10 years:

Powered by 120V AC, with a backup battery that lasts 10 years.

#### Smart Detection featuring Kidde HomeSafe™:

This alarm is part of a comprehensive suite of home safety devices that help protect against smoke, carbon monoxide, indoor air quality issues, leaks and freezes.

## Description

From the #1 most installed fire safety brand in North America® comes Kidde's Smoke Alarm with smart features, giving you the functionality and capabilities you need to manage your home safety systems with confidence. Equipped with Kidde HomeSafe, it connects this Wi-Fi-enabled device to the Kidde app to place status updates and alerts at your fingertips. It's also designed to work together with existing Kidde hardwired interconnected alarms to provide whole-home alarm activation – when one alarm sounds, they all sound, and an alert is sent to your phone.\* It's a new level of control – and it's all from a trusted leader in fire safety for more than 100 years.

Glowing LED Status Ring allows easy identification of current state of alarm.



WARNING: Mobile alert services are ancillary to the product and for informational purposes only. They are not intended or suitable for life safety or critical purposes nor do these services take the place of third-party life safety monitoring services. This product's smartphone and tablet notifications require a stable Wi-Fi connection, and are only as reliable as your home Wi-Fi network. Images are representative only. Actual product may vary slightly.



## **Architectural and Engineering Specs**

See User Guide for complete instructions.

AC/DC Hardwire Specifications								
Installation	Fits most standard electrical box openings							
Electrical Connection	Plug-in connector							
Interconnect	Up to 24 Kidde devices							
Interconnect	(limited by NFPA 72, see user guide) <sup>△</sup>							
Sounds and Warnings								
Smoke Alarm	3 long beeps, voice "Fire," 3 long beeps							
	After 10 years of operation, chirps							
End of Unit Life	and voice "Replace alarm, press button							
	to temporarily silence"							
	Technical Specifications							
Power Source	120VAC 60Hz, 53mA max							
1 ower source	3V sealed lithium battery backup							
Sensor	Smoke: Photoelectric							
Audio Alarm	85dB at 10ft							
Temperature Range	40°F (4.4°C) to 100°F (37.8°C)							
Humidity Bango	Up to 95% relative humidity (RH),							
Humidity Range	non-condensing							
Wi-Fi	802.11b/g/n (2.4GHz) Wi-Fi (Wi-Fi features only							
VVI-FI	work with AC power connected)							
Weight	0.7 lb							
	UL 217							
Regulatory	NFPA 72							
Agency Compliance	NFPA 101 (One- and two-family dwellings)							
(at date of	Federal Housing Authority (FHA)							
manufacture)	Housing and Urban Development (HUD)							
	California State Fire Marshal (CSFM)							


 $\Delta$  This alarm is not designed to be interconnected with other manufacturer's products, unless otherwise specified.


# **Important Information**

Industry experts recommend specific locations for smoke alarms, such as every level and sleeping area of the dwelling. See user guide for more location information.

Leading authorities recommend that both ionization and photoelectric smoke alarms be installed to help ensure optimal detection of the various types of fires that can occur within the home. Ionization sensing alarms may detect invisible fire particles (associated with fast flaming fires) sooner than photoelectric alarms. Photoelectric sensing alarms may detect visible fire particles (associated with slow smoldering fires) sooner than ionization alarms.

## Installation





# Ordering Information (Not for sale by individual unit)

Ordering No.	UPC	i 2 of 5	Packaging	Master Pack Qty	Dimensions (w" x d" x h")	Weight	Pallet Qty
21032064	047871320646	10047871320643	Вох	2	7.05" x 7.6" x 8.4"	3.22 lbs	240





Distributed by:

A Carrier Company ©2022 Carrier. All Rights Reserved.

All trademarks and service marks referred herein are property of their respective owners.