



## For combustible metal fires

Badger's Class D Dry Powder Fire Extinguisher is ideal for addressing combustible metal fires involving metals like magnesium, sodium, potassium and sodium-potassium alloys.

Badger model WB570 contains a special blend of sodium chloride based dry powder extinguishing agent. When applied onto the high heat generated by combustible metal fires the agent crusts and effectively accomplishes extinguishment through a smothering action.

The extended soft flow applicator wand can be quickly detached to provide operators with longer discharge ranges when needed.

### Features:

- Heavy-duty plated brass valves
- Stainless steel handles and levers
- Extended Soft Flow applicator wand
- Factory Mutual (FM) Approved
- Six year warranty



## Technical Data:

# BADGER *Class D Dry Powder Stored Pressure Extinguisher*

| <b>MODEL</b>               | <b>WB570</b>     |
|----------------------------|------------------|
| PART NUMBER                | 24123            |
| CAPACITY (lb.)             | 30               |
| CAPACITY (kg)              | 13.6             |
| UL FIRE RATING             | FM Approved      |
| AGENT TYPE                 | Sodium Chloride  |
| CYLINDER MATERIAL          | Steel            |
| VALVE MATERIAL             | Plated Brass     |
| HANDLE/LEVER MATERIAL      | Stainless Steel  |
| EXPELLANT                  | Argon            |
| Operating Pressure @ 70° F | 195              |
| TEMPERATURE RANGE (° F)    | -40 to 120       |
| TEMPERATURE RANGE (° C)    | -40.0 to 48.9    |
| AGENT FLOW RATE (lb/sec)   | n/a              |
| AGENT FLOW RATE (kg/sec)   | n/a              |
| NOM. DISCHARGE TIME (sec)  | 13 to 24         |
| DISCHARGE RANGE (ft.)      | 3.0 to 10.0      |
| DISCHARGE RANGE (m)        | 0.9 to 3.0       |
| UNIT HEIGHT (in.)          | 32               |
| UNIT HEIGHT (cm)           | 81.3             |
| UNIT WIDTH (in.)           | 13               |
| UNIT WIDTH (cm)            | 33.0             |
| UNIT DEPTH (in.)           | 8                |
| UNIT DEPTH (cm)            | 20.3             |
| SHIPPING WEIGHT (lb.)      | 53               |
| SHIPPING WEIGHT (kg)       | 24.0             |
| USCG APPROVAL              | n/a              |
| BRACKET                    | Wall<br>Included |

This information is subject to change without notice. Kidde Canada Inc. disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Kidde Canada Inc. for your local distributor for assistance.

Distributed by:



A UTC Fire & Security Company