# Pro Plus 5 MP Fire Extinguisher

Part number 468001 Multipurpose use

# Rechargeable

# UL Rated 3-A:40-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro Plus 5 MP is fitted with a pressure gauge that provides at-a-glance status, is manufactured from impact resistant steel cylinder & sturdy aluminum valve assembly.

Includes metal strap bracket (24530).

#### At a Glance

- Model ProPlus 5 MP
- Multipurpose Dry Chemical
- Rechargeable
- UL listed
- UL rated 3-A:40-B:C
- USCG, DOT approved
- Supplied with USCG approved retention bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

# Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection

Pt # 468001- 1 pack UPC: 0-47871-68001-6 I2F: 20047871680010

# **Product Specification**

G · ELECTRICAL EQUIPMENT

For use on the following

в

types of fire:

Net agent weight (Average)	5 lb.	
Unit weight (Average)	8.63 lb.	
Diameter	4.25 inches	
Height	15.0 inches	MASTER PACK
Discharge time	12-14 seconds	
Discharge range	12-18 feet	
Operating pressure	195 psi	
Cylinder	Steel	
Valve, handle, lever	Metal	
Strap Bracket	U.S.C.G approved	





36