

# Mariner 5 Fire Extinguisher

Part number 466179N

Regular use

Disposable

## UL Rated 5-B:C



## Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Mariner 5 unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Features bilingual nameplate and carton.



Includes plastic strap bracket (322057)

## At a Glance

- Model Mariner 5
- Regular Dry Chemical
- UL listed
- UL rated 5-B:C
- U.S.C.G, DOT approved
- Supplied with retention strap bracket
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on liquid & energized electrical fires

For use on the following types of fire:



## Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection



Pt # 466179N - 6 pack  
 UPC: 0-47871-00179-8  
 I2F - 10047871001795

## Product Specification

Net agent weight (Average)	2 lb.
Unit weight (Average)	2.85 lb.
Diameter	3.25 inches
Height	11.65 inches
Discharge time	8-12 seconds
Discharge range	4-6 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

## Packaging Options



Packaging dimensions (inches)

	Depth	Width	Height
Carton	3.25	4.25	11.25
Master Pack	9.1	11.75	10.0