

Fire Extinguisher (Basic)

Part number 21005944N

Regular use

Disposable

UL Rated 5-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Includes plastic strap bracket (322057).



At a Glance

- Model FA5B
- Regular Dry Chemical
- UL listed
- UL rated 5-B:C
- Supplied with retention strap bracket
- Sodium Bicarbonate
- 5 year limited warranty
- Suitable for use on liquid & energized electrical fires

For use on the following types of fire:



Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 5 year limited warranty
- UL approved strap retention bracket
- Powder coated cylinder for corrosion protection



UPC: 0-47871-15944-4
I2F: 1004787159441

Product Specification

Net agent weight (Average)	1.5 lb.
Unit weight (Average)	2.35 lb.
Diameter	3.25 inches
Height	11.65 inches
Discharge time	8-12 seconds
Discharge range	4-6 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon

Packaging Options

Master Pack (6)	21005944N
Grainger (6)	21007077N



MASTER PACK

Packaging dimensions (inches)

	Depth	Width	Height
Carton	3.25	4.25	11.25
Master Pack	9.25	11.5	10.75



Kidde Fire Safety

1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788

www.Kidde.com