



Portable Air Cooled Air Conditioners

Classic Plus 26

Cooling Capacity	Btu/hr. @ 95°	
	At 60% Relative Humidity	24,000
Dimensions	Width (Inches)	19
	Depth (Inches)	29
	Height (Inches)	47
	Weight (Pounds)	235
	Shipping Weight	265
Electrical Characteristics	Power Supply (Volts)	208-230 1phase
	Power Consumption (Kilowatts)	2.4
	Current Consumption (Amperes)	11.8/10.8
	Fuse Size (Amperes)	20
	NEMA Plug Configuration	6-20
	Min-max Voltage	198-250 Volt
	Power Cord Gauge	12AWG (3 Core)
	Power Cord Length (Feet)	6
Compressor Characteristics	Compressor Type	Hermetic Scroll
	Refrigerant	R-410A
	Operating Conditions: Min-max °F	70°-113°F, 50% RH
Fan Characteristics	<i>Evaporator:</i>	
	Fan Type	Centrifugal
	Air Flow (CFM) High/Low	708/600
	Max. External Static Pressure (Inches Of Water Gauge)	0.54
	<i>Condenser:</i>	
	Fan Type	Centrifugal
	Air Flow (CFM) High/Low	1680/1460
Max. External Static Pressure (Inches Of Water Gauge)	0.25	
Safety Devices	Compressor Overload Relay	Yes
	Fan Motor Protection	Yes
	Anti-freeze Thermostat	Yes
	Automatic Tank Shut-off	Yes
	Condensate Tank Capacity (Gallons)	5
	High-pressure Switch	Yes
	Compressor Short-cycle Protection	Yes
	Fan Mode Switch	Yes
	Automatic Restart	Yes
	Thermostat	Yes
Control Panel	Programmable	
Miscellaneous Features	Operating Cost	\$0.223
	Humidity Removed @ 60% RH	1.38
	Accommodates Condensate Pump	Yes
	Sound Level (Db) High/Low	66/64
	Max Evaporator Ducting Length*(Ft.)	60
	Max Condenser Ducting Length*(Ft.)	45
	<i>*subtract 10 Ft. For Every 90° Bend</i>	



Portable Air Cooled Air Conditioners

Classic Plus 26

Power Supply 208-230 volts 60 hertz 1 phase 11.8/10.8 amperes

Width 19 inches

Depth 29 inches

Height 47 inches

Weight (net/shipping) lbs 235/265

All models are backed by a 12-month warranty with 36 months for the compressor.
All coils are treated with an acrylic resin coating for extended life and corrosion resistance.

