



Portable Water Cooled Air Conditioners

OWC 1211

Cooling Capacity	@ARI 80°F-67°F at 52% Relative Humidity	1 Ton - 12,000
Dimensions	Width (Inches)	20.125
	Depth (Inches)	13.125
	Height (Inches)	31.5
	Weight (Pounds)	110
	Shipping Weight	130
	Shipping Volume (cubic feet)	9
Electrical Characteristics	Power Supply (Volts)	115/1
	Current Consumption	8.1
	Cooling Watts	930
	In rush current (Amps)	70
	NEMA Plug Configuration	5 -15p
	EER	12.9
	Min-max Voltage	105-125
	Power Cord Gauge	14/3
	Power Cord Length (Feet)	10
Compressor Characteristics	Compressor HP	1
	Compressor RLA	9.5
	Compressor LRA	50
Evaporator	Evap (CFM)	400
	Evap Motor HP	1/8
	Evap Motor Watts	200
Water Connection Characteristics	Cond Water Flow (GPM) at 60°F inlet	0.75
	Cond Water Flow (GPM) at 85°F inlet	3.0
	Cond Coil Pressure Drop PSI	0.4
	Water Valve Pressure Drop PSI	2.0
	Water Valve Connection	3/8 MF
	Drain (Return) Connection	3/8 MF
Miscellaneous Features	Condensate Pump Lift	20 Ft.
	Sound Level	52
	R-410A Charge Oz.	14



Portable Water Cooled Air Conditioners

OWC 1211

Power Supply 115 volts 60 hertz 1 phase 8.1 amperes

Width 20.125 inches

Depth 13.125 inches

Height 31.5 inches

Weight (net/shipping) lbs 110/130

All models are backed by a 12-month warranty with 60 months for the compressor.

