



## Portable Air Cooled Air Conditioners

# Classic 10

<b>Cooling Capacity</b>	Btu/hr. @ 95°	
	At 60% Relative Humidity	10,000
<b>Dimensions</b>	Width (Inches)	19
	Depth (Inches)	26
	Height (Inches)	41
	Weight (Pounds)	145
	Shipping Weight	183
<b>Electrical Characteristics</b>	Power Supply (Volts)	115 1phase
	Power Consumption (Kilowatts)	1.1
	Current Consumption (Amperes)	10
	Fuse Size (Amperes)	15
	NEMA Plug Configuration	5-15
	Min-max Voltage	105-125 Volt
	Power Cord Gauge	14AWG (3 Core)
	Power Cord Length (Feet)	6
<b>Compressor Characteristics</b>	Compressor Type	Hermetic Rotary
	Refrigerant	R-410A
	Operating Conditions: Min-max °F	70°-105°F, 50% RH
<b>Fan Characteristics</b>	<i>Evaporator:</i>	
	Fan Type	Centrifugal
	Air Flow (CFM) High/Low	265
	Max. External Static Pressure (Inches Of Water Gauge)	0.33
	<i>Condenser:</i>	
	Fan Type	Centrifugal
	Air Flow (CFM) High/Low	740
Max. External Static Pressure (Inches Of Water Gauge)	0.13	
<b>Safety Devices</b>	Compressor Overload Relay	Yes
	Fan Motor Protection	Yes
	Anti-freeze Thermostat	Yes
	Automatic Tank Shut-off	Yes
	Condensate Tank Capacity (Gallons)	5
	High-pressure Switch	N/A
	Compressor Short-cycle Protection	Yes
	Fan Mode Switch	Yes
	Automatic Restart	Yes
	Thermostat	Yes
Control Panel	Digital	
<b>Miscellaneous Features</b>	Operating Cost	\$0.223
	Humidity Removed @ 60% RH	0.63
	Accommodates Condensate Pump	Yes
	Sound Level (Db) High/Low	55
	Max Evaporator Ducting Length*(Ft.)	40
	Max Condenser Ducting Length*(Ft.)	60
	<i>*subtract 10 Ft. For Every 90° Bend</i>	



## Portable Air Cooled Air Conditioners

# Classic 10

**Power Supply** 115 volts 60 hertz 1 phase 10.0 amperes

**Width** 19 inches

**Depth** 26 inches

**Height** 41 inches

**Weight** (net/shipping) lbs 145/183

All models are backed by a 12-month warranty with 36 months for the compressor.  
All coils are treated with an acrylic resin coating for extended life and corrosion resistance.

